

CS5760: Cryptanalysis of DES and DES-like Iterated Cryptosystems

Gautam Singh

Indian Institute of Technology Hyderabad

February 3, 2025

- ① Introduction
- ② Probability Analysis of S Boxes
- ③ Characteristic
- ④ Signal to Noise Ratio
- ⑤ Structures
- ⑥ Differential Cryptanalysis of DES Variants
DES Reduced to Four Rounds

Differential Cryptanalysis

- 1 Chosen plaintext attack.
- 2 Exploit XOR between plaintext pairs to find key bits.

Differential Cryptanalysis

- 1 Chosen plaintext attack.
- 2 Exploit XOR between plaintext pairs to find key bits.
- 3 Per DES round, XOR of respective inputs is:
 - *Linear* in expansion E to get S_E .
 - *Invariant* in key mixing with subkey S_K to get $S_I = S_E \oplus S_K$.
 - *Linear* in permutation P on S_O after S boxes.
 - *Invariant* in XOR operation connecting rounds.




Figure 1: F function of DES.

Differential Cryptanalysis

- 1 Chosen plaintext attack.
- 2 Exploit XOR between plaintext pairs to find key bits.
- 3 Per DES round, XOR of respective inputs is:
 - *Linear* in expansion E to get S_E .
 - *Invariant* in key mixing with subkey S_K to get $S_I = S_E \oplus S_K$.
 - *Linear* in permutation P on S_O after S boxes.
 - *Invariant* in XOR operation connecting rounds.
- 4 S boxes are *nonlinear*. Probability analysis performed between input and output XOR.




Figure 1: F function of DES.

Probability Analysis of S Boxes

- 1 Suppose $Si'_I = Si_I \oplus Si_I^*$ is the input XOR to the i^{th} S box, and Si'_O is the output XOR ($1 \leq i \leq 8$).

Probability Analysis of S Boxes

- ① Suppose $Si'_I = Si_I \oplus Si_I^*$ is the input XOR to the i^{th} S box, and Si'_O is the output XOR ($1 \leq i \leq 8$).
- ② We create a *pairs XOR distribution table* for each S box.
 - Each entry (Si'_I, Si'_O) equals the number of 6-bit key blocks Si_K for which $Si'_I \rightarrow Si'_O$.
 - 64-by-16 joint probability mass function.

Probability Analysis of S Boxes

- ① Suppose $Si'_I = Si_I \oplus Si_I^*$ is the input XOR to the i^{th} S box, and Si'_O is the output XOR ($1 \leq i \leq 8$).
- ② We create a *pairs XOR distribution table* for each S box.
 - Each entry (Si'_I, Si'_O) equals the number of 6-bit key blocks Si_K for which $Si'_I \rightarrow Si'_O$.
 - 64-by-16 joint probability mass function.
- ③ This joint PMF can reduce the number of possible (sub)keys. Used to drive choice for the plaintext XOR.
 - $\approx 80\%$ entries are non-zero/possible for each S box (some have lesser percentages).
 - Given Si'_I and Si'_O , we can narrow down Si_K to a few possibilities.

Probability Analysis of S Boxes

- ① Suppose $Si'_I = Si_I \oplus Si_i^*$ is the input XOR to the i^{th} S box, and Si'_O is the output XOR ($1 \leq i \leq 8$).
- ② We create a *pairs XOR distribution table* for each S box.
 - Each entry (Si'_I, Si'_O) equals the number of 6-bit key blocks Si_K for which $Si'_I \rightarrow Si'_O$.
 - 64-by-16 joint probability mass function.
- ③ This joint PMF can reduce the number of possible (sub)keys. Used to drive choice for the plaintext XOR.
 - $\approx 80\%$ entries are non-zero/possible for each S box (some have lesser percentages).
 - Given Si'_I and Si'_O , we can narrow down Si_K to a few possibilities.
- ④ i^{th} S box contributes probability p_i for $Si'_I \rightarrow Si'_O$.
 - For $X \rightarrow Y$ over a round, $P = \prod_i p_i$.
 - Over n rounds, $P = \prod_{i=1}^n P_i$.

Probability Analysis of S Boxes

- ① Suppose $Si'_I = Si_I \oplus Si_I^*$ is the input XOR to the i^{th} S box, and Si'_O is the output XOR ($1 \leq i \leq 8$).
- ② We create a *pairs XOR distribution table* for each S box.
 - Each entry (Si'_I, Si'_O) equals the number of 6-bit key blocks Si_K for which $Si'_I \rightarrow Si'_O$.
 - 64-by-16 joint probability mass function.
- ③ This joint PMF can reduce the number of possible (sub)keys. Used to drive choice for the plaintext XOR.
 - $\approx 80\%$ entries are non-zero/possible for each S box (some have lesser percentages).
 - Given Si'_I and Si'_O , we can narrow down Si_K to a few possibilities.
- ④ i^{th} S box contributes probability p_i for $Si'_I \rightarrow Si'_O$.
 - For $X \rightarrow Y$ over a round, $P = \prod_i p_i$.
 - Over n rounds, $P = \prod_{i=1}^n P_i$.

Desirable for cryptanalysis: high P with large n .

Characteristic

Formalizes notion of high-probability plaintext XORs.

Definition 1 (Characteristic)

An n -round *characteristic* is a tuple $\Omega = (\Omega_P, \Omega_\Lambda, \Omega_T)$ where $\Omega_P = (L', R')$ and $\Omega_T = (l', r')$ are m bit numbers, $\Omega_\Lambda = (\Lambda_1, \dots, \Lambda_n)$, $\Lambda_i = (\lambda_I^i, \lambda_O^i)$ and $\lambda_I^i, \lambda_O^i, L', R', l', r'$ are $\frac{m}{2}$ bit numbers and m is the block size of the cryptosystem satisfying

$$\lambda_I^1 = R' \quad (1)$$

$$\lambda_I^2 = L' \oplus \lambda_O^1 \quad (2)$$

$$\lambda_I^n = r' \quad (3)$$

$$\lambda_I^{n-1} = l' \oplus \lambda_O^n \quad (4)$$

$$\forall 1 < i < n, \lambda_O^i = \lambda_I^{i-1} \oplus \lambda_I^{i+1} \quad (5)$$

Characteristic

Definition 2 (Right Pair)

A *right pair* with respect to an n -round characteristic $\Omega = (\Omega_P, \Omega_\Lambda, \Omega_T)$ and an independent key K is a pair for which $P' = \Omega_P$ and for each round i of the first n rounds of the encryption of the pair using K the input XOR of the i^{th} round equals λ_i^i and the output XOR of the F function equals λ_O^i . Pairs that do not satisfy these conditions are called *wrong pairs*.

Characteristic

Definition 2 (Right Pair)

A *right pair* with respect to an n -round characteristic $\Omega = (\Omega_P, \Omega_\Lambda, \Omega_T)$ and an independent key K is a pair for which $P' = \Omega_P$ and for each round i of the first n rounds of the encryption of the pair using K the input XOR of the i^{th} round equals λ_i^i and the output XOR of the F function equals λ_{iO}^i . Pairs that do not satisfy these conditions are called *wrong pairs*.

Definition 3 (Probability of a Round of a Characteristic)

Round i of an n -round characteristic Ω has probability p_i^Ω if $\lambda_i^i \rightarrow \lambda_{iO}^i$ with probability p_i^Ω by the F function.

Probability of a Characteristic

Definition 4 (Probability of a Characteristic)

An n -round characteristic Ω has probability p^Ω given by

$$p^\Omega = \prod_{i=1}^n p_i^\Omega \quad (6)$$

Probability of a Characteristic

Definition 4 (Probability of a Characteristic)

An n -round characteristic Ω has probability p^Ω given by

$$p^\Omega = \prod_{i=1}^n p_i^\Omega \quad (6)$$

Theorem 5 (Probability of a Characteristic and Right Pairs)

The formally defined probability of a characteristic $\Omega = (\Omega_P, \Omega_\Lambda, \Omega_T)$ is the probability that any fixed plaintext pair satisfying $P' = \Omega_P$ is a right pair when random independent keys are used.

Probability of a Characteristic

Definition 4 (Probability of a Characteristic)

An n -round characteristic Ω has probability p^Ω given by

$$p^\Omega = \prod_{i=1}^n p_i^\Omega \quad (6)$$

Theorem 5 (Probability of a Characteristic and Right Pairs)

The formally defined probability of a characteristic $\Omega = (\Omega_P, \Omega_\Lambda, \Omega_T)$ is the probability that any fixed plaintext pair satisfying $P' = \Omega_P$ is a right pair when random independent keys are used.

Proof Idea.

Keys *randomize* the inputs to the S boxes in each round. □

Example of a Characteristic




Figure 2: Example of a two-round characteristic with probability $\frac{14}{64}$.

Signal to Noise Ratio

- 1 Right pairs will always suggest the right key value. But right pairs occur with probability p^Ω .

Signal to Noise Ratio

- 1 Right pairs will always suggest the right key value. But right pairs occur with probability p^Ω .
- 2 On the other hand, wrong pairs suggest a randomly chosen key (not necessarily the right key in the worst case).

Signal to Noise Ratio

- 1 Right pairs will always suggest the right key value. But right pairs occur with probability p^Ω .
- 2 On the other hand, wrong pairs suggest a randomly chosen key (not necessarily the right key in the worst case).
- 3 Suitable counting approach on the key values will “spike” at the right key and have smaller but approximately equal counts at other keys.

Signal to Noise Ratio

- 1 Right pairs will always suggest the right key value. But right pairs occur with probability p^Ω .
- 2 On the other hand, wrong pairs suggest a randomly chosen key (not necessarily the right key in the worst case).
- 3 Suitable counting approach on the key values will “spike” at the right key and have smaller but approximately equal counts at other keys.
- 4 The key with the largest count is likely the actual key.

Signal to Noise Ratio

- 1 Right pairs will always suggest the right key value. But right pairs occur with probability p^Ω .
- 2 On the other hand, wrong pairs suggest a randomly chosen key (not necessarily the right key in the worst case).
- 3 Suitable counting approach on the key values will “spike” at the right key and have smaller but approximately equal counts at other keys.
- 4 The key with the largest count is likely the actual key.

Definition 6 (Signal-to-Noise Ratio)

The ratio between the number of right pairs and the average count of incorrect subkeys in a counting scheme is called the *signal to noise ratio of the counting scheme* and is denoted by S/N .

Computing the SNR

Consider the variables shown in Table 1.

Variable	Definition
p	Probability of the characteristic
m	Number of created pairs
α	Average count per analyzed pair
β	Fraction of analyzed pairs
k	Number of key bits counted on

Table 1: Table of variables to compute the SNR.

Computing the SNR

Consider the variables shown in Table 1.

Variable	Definition
p	Probability of the characteristic
m	Number of created pairs
α	Average count per analyzed pair
β	Fraction of analyzed pairs
k	Number of key bits counted on

Table 1: Table of variables to compute the SNR.

Then,

$$S/N = \frac{m \cdot p}{\frac{m \cdot \beta \cdot \alpha}{2^k}} = \frac{2^k \cdot p}{\alpha \cdot \beta} \quad (7)$$

Structures

- 1 Many attacks on DES use more than one characteristic.

Structures

- 1 Many attacks on DES use more than one characteristic.
- 2 Requirement to minimize the amount of plaintexts generated.

Structures

- 1 Many attacks on DES use more than one characteristic.
- 2 Requirement to minimize the amount of plaintexts generated.

Definition 7 (Quartet and Octet)

A *quartet* is a structure of four ciphertexts that simultaneously contains two ciphertext pairs of one characteristic and two ciphertext pairs of a second characteristic. An *octet* is a structure of eight ciphertexts that simultaneously contains four ciphertext pairs of each of three characteristics.

- 3 As an example, $(P, P \oplus \Omega_P^1, P \oplus \Omega_P^2, P \oplus \Omega_P^1 \oplus \Omega_P^2)$ is a quartet.

Structures

- 1 Many attacks on DES use more than one characteristic.
- 2 Requirement to minimize the amount of plaintexts generated.

Definition 7 (Quartet and Octet)

A *quartet* is a structure of four ciphertexts that simultaneously contains two ciphertext pairs of one characteristic and two ciphertext pairs of a second characteristic. An *octet* is a structure of eight ciphertexts that simultaneously contains four ciphertext pairs of each of three characteristics.

- 3 As an example, $(P, P \oplus \Omega_P^1, P \oplus \Omega_P^2, P \oplus \Omega_P^1 \oplus \Omega_P^2)$ is a quartet.
- 4 Quartets save $\frac{1}{2}$ of the data and octets save $\frac{2}{3}$ of the data.

DES Reduced to Four Rounds

- 1 Use two one-round characteristics, as shown in Figure 3.

DES Reduced to Four Rounds

- 1 Use two one-round characteristics, as shown in Figure 3.
- 2 Both characteristics have probability 1.




Figure 3: Characteristics used for cryptanalysis of DES reduced to four rounds.

DES Reduced to Four Rounds

- 1 Use two one-round characteristics, as shown in Figure 3.
- 2 Both characteristics have probability 1.
- 3 Example of a *3R-attack*. There are *three* extra rounds after the characteristic is applied.




Figure 3: Characteristics used for cryptanalysis of DES reduced to four rounds.

DES Reduced to Four Rounds




Figure 4: DES reduced to four rounds.

DES Reduced to Four Rounds

① Using Ω^1 , we have

$$c' = D' \oplus l' = a' \oplus B' \implies D' = B' \oplus l' \quad (8)$$




Figure 4: DES reduced to four rounds.

DES Reduced to Four Rounds

- ① Using Ω^1 , we have

$$c' = D' \oplus l' = a' \oplus B' \implies D' = B' \oplus l' \quad (8)$$

- ② We have $a' = 0_x \implies A' = 0_x$ and $b' = A' \oplus L' = L'$.




Figure 4: DES reduced to four rounds.

DES Reduced to Four Rounds

① Using Ω^1 , we have

$$c' = D' \oplus l' = a' \oplus B' \implies D' = B' \oplus l' \quad (8)$$

② We have $a' = 0_x \implies A' = 0_x$ and $b' = A' \oplus L' = L'$.

- In the second round S2, ..., S8 receive zero XOR input.




Figure 4: DES reduced to four rounds.

DES Reduced to Four Rounds

① Using Ω^1 , we have

$$c' = D' \oplus l' = a' \oplus B' \implies D' = B' \oplus l' \quad (8)$$

② We have $a' = 0_x \implies A' = 0_x$ and $b' = A' \oplus L' = L'$.

- In the second round S2, ..., S8 receive zero XOR input.
- 28 bits of B' are zero and hence we can find 28 bits of D' .




Figure 4: DES reduced to four rounds.

DES Reduced to Four Rounds

① Using Ω^1 , we have

$$c' = D' \oplus l' = a' \oplus B' \implies D' = B' \oplus l' \quad (8)$$

② We have $a' = 0_x \implies A' = 0_x$ and $b' = A' \oplus L' = L'$.

- In the second round S2, ..., S8 receive zero XOR input.
- 28 bits of B' are zero and hence we can find 28 bits of D' .
- We already know $d' = r'$. So, we employ a counting approach to get $K4$.




Figure 4: DES reduced to four rounds.

DES Reduced to Four Rounds

- 1 To get Si_{Kd} for $2 \leq i \leq 8$, we verify (9).

$$S(S_{Ed} \oplus S_{Kd}) \oplus S(S_{Ed}^* \oplus S_{Kd}) = S'_{Od} \quad (9)$$

- 2 Only *one* plaintext pair is needed since characteristic probability is 1.
- 3 We recover $7 \times 6 = 42$ key bits of K_4 , which correspond to 42 bits of the master key.
- 4 Exhaustively search the other 14 key bits to get the entire master key.
- 5 We have used the key schedule to our advantage here? *What if all the keys were independent?*

DES Reduced to Four Rounds: Independent Subkeys

- 1 We now use Ω^2 to get the remaining 6 subkey bits of K_4 , as the input to S_1 in the second round is now zero.

DES Reduced to Four Rounds: Independent Subkeys

- 1 We now use Ω^2 to get the remaining 6 subkey bits of K_4 , as the input to S_1 in the second round is now zero.
- 2 We have $C' = b' \oplus d'$. Peeling off/decrypting one round will give us c' completely.

DES Reduced to Four Rounds: Independent Subkeys

- ① We now use Ω^2 to get the remaining 6 subkey bits of $K4$, as the input to $S1$ in the second round is now zero.
- ② We have $C' = b' \oplus d'$. Peeling off/decrypting one round will give us c' completely.
 - Since c' and C' are both completely known, $K3$ can be completely found using a similar counting argument.

DES Reduced to Four Rounds: Independent Subkeys

- ① We now use Ω^2 to get the remaining 6 subkey bits of $K4$, as the input to $S1$ in the second round is now zero.
- ② We have $C' = b' \oplus d'$. Peeling off/decrypting one round will give us c' completely.
 - Since c' and C' are both completely known, $K3$ can be completely found using a similar counting argument.
- ③ Since $a' = A' = 0_x$, all keys are equally likely. Other characteristics Ω^3 and Ω^4 are chosen such that
 - $S'_{Ea} \neq 0_x$ for all S boxes for both characteristics.
 - For every S box, the S'_{Ea} values differ between the characteristics.
 - Similar counting methods used to get $K1$ and $K2$.

DES Reduced to Four Rounds: Independent Subkeys

- 1 We now use Ω^2 to get the remaining 6 subkey bits of $K4$, as the input to $S1$ in the second round is now zero.
- 2 We have $C' = b' \oplus d'$. Peeling off/decrypting one round will give us c' completely.
 - Since c' and C' are both completely known, $K3$ can be completely found using a similar counting argument.
- 3 Since $a' = A' = 0_x$, all keys are equally likely. Other characteristics Ω^3 and Ω^4 are chosen such that
 - $S'_{Ea} \neq 0_x$ for all S boxes for both characteristics.
 - For every S box, the S'_{Ea} values differ between the characteristics.
 - Similar counting methods used to get $K1$ and $K2$.
- 4 16 chosen plaintexts are needed for this attack.
 - 8 pairs of Ω^1 and Ω^2 each.
 - 4 pairs of Ω^3 and Ω^4 each.

To reduce the data needed, two octets are used.

title