

The Retracing Boomerang Attack

Orr Dunkelman, Nathan Keller, Eyal Ronen, and Adi Shamir
EUROCRYPT 2020

Gautam Singh

Indian Institute of Technology Hyderabad

July 21, 2025

① Introduction

② Preliminaries

③ The Retracing Boomerang Attack

④ Retracing Boomerang Attack on Five Round AES

Introduction

- 1 Broke the record for 5-round AES when it was published.

Introduction

- 1 Broke the record for 5-round AES when it was published.
- 2 Brings the attack complexity down to $2^{16.5}$ encryptions.

Introduction

- 1 Broke the record for 5-round AES when it was published.
- 2 Brings the attack complexity down to $2^{16.5}$ encryptions.
- 3 Uncovers a hidden relationship between boomerang attacks and two other cryptanalysis techniques: yoyo game and mixture differentials.

The Boomerang Attack

- 1 Typically split the encryption function as $E = E_1 \circ E_0$, with differential trails for each sub-cipher.




Figure 1: The boomerang attack.

The Boomerang Attack

- 1 Typically split the encryption function as $E = E_1 \circ E_0$, with differential trails for each sub-cipher.
- 2 We can build a distinguisher that can distinguish E from a truly random permutation in $\mathcal{O}((pq)^{-2})$ plaintext pairs.




Figure 1: The boomerang attack.

The Boomerang Distinguisher

Algorithm 1 The Boomerang Attack Distinguisher

- 1: Generate $(pq)^{-2}$ plaintext pairs (P_1, P_2) such that $P_1 \oplus P_2 = \alpha$.
 - 2: **for all** pairs (P_1, P_2) **do**
 - 3: Ask for the encryption of (P_1, P_2) to (C_1, C_2) .
 - 4: Compute $C_3 = C_1 \oplus \delta$ and $C_4 = C_2 \oplus \delta$. $\triangleright \delta$ -shift
 - 5: Ask for the decryption of (C_3, C_4) to (P_3, P_4) .
 - 6: **if** $P_3 \oplus P_4 = \alpha$ **then**
 - 7: **return** This is the cipher E
 - 8: **return** This is a random permutation
-

The Yoyo Game

- 1 Similar to boomerang, starts by encrypting (P_1, P_2) to (C_1, C_2) , then modifying them to (C_3, C_4) and decrypting them.

The Yoyo Game

- 1 Similar to boomerang, starts by encrypting (P_1, P_2) to (C_1, C_2) , then modifying them to (C_3, C_4) and decrypting them.
- 2 Unlike the boomerang attack, this *continues* in the yoyo game.

The Yoyo Game

- 1 Similar to boomerang, starts by encrypting (P_1, P_2) to (C_1, C_2) , then modifying them to (C_3, C_4) and decrypting them.
- 2 Unlike the boomerang attack, this *continues* in the yoyo game.
- 3 All pairs of intermediate values (X_{2l+1}, X_{2l+2}) satisfy some property (such as zero difference in some part).

The Yoyo Game

- 1 Similar to boomerang, starts by encrypting (P_1, P_2) to (C_1, C_2) , then modifying them to (C_3, C_4) and decrypting them.
- 2 Unlike the boomerang attack, this *continues* in the yoyo game.
- 3 All pairs of intermediate values (X_{2l+1}, X_{2l+2}) satisfy some property (such as zero difference in some part).
- 4 Probabilities are low with large l . Still, the yoyo technique has been used to attack AES reduced to 5 rounds.

Mixture

Definition 1 (Mixture)

Suppose $P_i \triangleq (\rho_1^i, \rho_2^i, \dots, \rho_t^i)$. Given a plaintext pair (P_1, P_2) , we say (P_3, P_4) is a *mixture counterpart* of (P_1, P_2) if for each $1 \leq j \leq t$, the quartet $(\rho_j^1, \rho_j^2, \rho_j^3, \rho_j^4)$ consists of two pairs of equal values or of four equal values. The quartet (P_1, P_2, P_3, P_4) is called a *mixture*.

Mixture

Definition 1 (Mixture)

Suppose $P_i \triangleq (\rho_1^i, \rho_2^i, \dots, \rho_t^i)$. Given a plaintext pair (P_1, P_2) , we say (P_3, P_4) is a *mixture counterpart* of (P_1, P_2) if for each $1 \leq j \leq t$, the quartet $(\rho_j^1, \rho_j^2, \rho_j^3, \rho_j^4)$ consists of two pairs of equal values or of four equal values. The quartet (P_1, P_2, P_3, P_4) is called a *mixture*.

- 1 If (P_1, P_2, P_3, P_4) is a mixture, then XOR of the intermediate values (X_1, X_2, X_3, X_4) is zero.

Mixture

Definition 1 (Mixture)

Suppose $P_i \triangleq (\rho_1^i, \rho_2^i, \dots, \rho_t^i)$. Given a plaintext pair (P_1, P_2) , we say (P_3, P_4) is a *mixture counterpart* of (P_1, P_2) if for each $1 \leq j \leq t$, the quartet $(\rho_j^1, \rho_j^2, \rho_j^3, \rho_j^4)$ consists of two pairs of equal values or of four equal values. The quartet (P_1, P_2, P_3, P_4) is called a *mixture*.

- 1 If (P_1, P_2, P_3, P_4) is a mixture, then XOR of the intermediate values (X_1, X_2, X_3, X_4) is zero.
- 2 $X_1 \oplus X_3 = \gamma \implies X_2 \oplus X_4 = \gamma$. Hence, for $\gamma \xrightarrow{q} \delta$ in E_1 , $C_1 \oplus C_3 = C_2 \oplus C_4 = \delta$ with probability q^2 .

The SimpleSWAP Algorithm

Algorithm 2 is a simple method to generate mixture counterparts.

Algorithm 2 Swaps the first word where texts are different and returns one word.

```

1: function SIMPLESWAP( $x^0, x^1$ )  $\triangleright x^0 \neq x^1$ 
2:    $x'^0, x'^1 \leftarrow x^0, x^1$ 
3:   for  $i$  from 0 to 3 do
4:     if  $x_i^0 \neq x_i^1$  then
5:        $x_i'^0, x_i'^1 \leftarrow x_i^1, x_i^0$ 
6:   return  $x'^0, x'^1$ 

```

The Retracing Boomerang Framework




Figure 2: The retracing boomerang attack.

The Retracing Boomerang Attack

- 1 The *retracing boomerang* framework consists of a *shifting* type and a *mixing* type.

The Retracing Boomerang Attack

- 1 The *retracing boomerang* framework consists of a *shifting* type and a *mixing* type.
- 2 Both attacks use the setup shown in Figure 2.

The Retracing Boomerang Attack

- 1 The *retracing boomerang* framework consists of a *shifting* type and a *mixing* type.
- 2 Both attacks use the setup shown in Figure 2.
- 3 Although the additional split looks restrictive, it applies for a wide class of block ciphers such as SASAS constructions.

The Retracing Boomerang Attack

- 1 The *retracing boomerang* framework consists of a *shifting* type and a *mixing* type.
- 2 Both attacks use the setup shown in Figure 2.
- 3 Although the additional split looks restrictive, it applies for a wide class of block ciphers such as SASAS constructions.
- 4 It is assumed that E_{12} can be split into two parts of size b and $n - b$ bits, call these functions E_{12}^L and E_{12}^R , with characteristic probabilities q_2^L and q_2^R respectively.

The Shifting Retracing Boomerang Attack

- 1 Check if $C_1^L \oplus C_2^L = 0$ or δ_L . *Discard all pairs not satisfying this relation.* This is a $(b - 1)$ -bit filtering.

The Shifting Retracing Boomerang Attack

- ① Check if $C_1^L \oplus C_2^L = 0$ or δ_L . *Discard all pairs not satisfying this relation.* This is a $(b - 1)$ -bit filtering.
- ② δ -shift is performed on the filtered ciphertext pairs to get (C_3, C_4) . This ensures $\{C_1, C_3\} = \{C_2, C_4\}$.

The Shifting Retracing Boomerang Attack

- 1 Check if $C_1^L \oplus C_2^L = 0$ or δ_L . *Discard all pairs not satisfying this relation.* This is a $(b - 1)$ -bit filtering.
- 2 δ -shift is performed on the filtered ciphertext pairs to get (C_3, C_4) . This ensures $\{C_1, C_3\} = \{C_2, C_4\}$.
- 3 *If one of these pairs satisfies $\delta_L \xrightarrow{q_2^L} \mu_L$, the other pair will too!*
Increases the probability of the boomerang distinguisher by $(q_2^L)^{-1}$.

The Shifting Retracing Boomerang Attack

- ① Check if $C_1^L \oplus C_2^L = 0$ or δ_L . *Discard all pairs not satisfying this relation.* This is a $(b-1)$ -bit filtering.
- ② δ -shift is performed on the filtered ciphertext pairs to get (C_3, C_4) . This ensures $\{C_1, C_3\} = \{C_2, C_4\}$.
- ③ *If one of these pairs satisfies $\delta_L \xrightarrow{q_2^L} \mu_L$, the other pair will too!*
Increases the probability of the boomerang distinguisher by $(q_2^L)^{-1}$.
- ④ Any possible characteristic of E_{12}^L has probability at least 2^{-b+1} , thus overall probability increases by a factor of at most 2^{b-1} . On the other hand, filtering only leaves 2^{-b+1} of the pairs, so *no apparent gain?*

The Shifting Retracing Attack

The Shifting Retracing Boomerang Attack




Figure 3: A shifted quartet (dashed lines indicate equality).

The Mixing Retracing Boomerang Attack

- 1 In shifting attack, $\{C_1^L, C_2^L\} = \{C_3^L, C_4^L\}$ forced using a δ -shift.

The Mixing Retracing Boomerang Attack

- ① In shifting attack, $\{C_1^L, C_2^L\} = \{C_3^L, C_4^L\}$ forced using a δ -shift.
- ② Each ciphertext shifted by $(C_1^L \oplus C_2^L, 0)$, thus

$$C_3 = (C_3^L, C_3^R) = (C_1^L \oplus (C_1^L \oplus C_2^L), C_1^R) = (C_2^L, C_1^R), \quad (1)$$

$$C_4 = (C_4^L, C_4^R) = (C_2^L \oplus (C_1^L \oplus C_2^L), C_2^R) = (C_1^L, C_2^R). \quad (2)$$

Here, $\{C_1^L, C_2^L\} = \{C_3^L, C_4^L\}$.

The Mixing Retracing Boomerang Attack

- 1 In shifting attack, $\{C_1^L, C_2^L\} = \{C_3^L, C_4^L\}$ forced using a δ -shift.
- 2 Each ciphertext shifted by $(C_1^L \oplus C_2^L, 0)$, thus

$$C_3 = (C_3^L, C_3^R) = (C_1^L \oplus (C_1^L \oplus C_2^L), C_1^R) = (C_2^L, C_1^R), \quad (1)$$

$$C_4 = (C_4^L, C_4^R) = (C_2^L \oplus (C_1^L \oplus C_2^L), C_2^R) = (C_1^L, C_2^R). \quad (2)$$

Here, $\{C_1^L, C_2^L\} = \{C_3^L, C_4^L\}$.

- 3 Further, $C_1^R = C_3^R$ and $C_2^R = C_4^R$. *Additional gain of $(q_2^R)^{-2}$ for total probability $(pq_1)^2 q_2^L$, better than shifting!*

The Mixing Retracing Boomerang Attack

- 1 In shifting attack, $\{C_1^L, C_2^L\} = \{C_3^L, C_4^L\}$ forced using a δ -shift.
- 2 Each ciphertext shifted by $(C_1^L \oplus C_2^L, 0)$, thus

$$C_3 = (C_3^L, C_3^R) = (C_1^L \oplus (C_1^L \oplus C_2^L), C_1^R) = (C_2^L, C_1^R), \quad (1)$$

$$C_4 = (C_4^L, C_4^R) = (C_2^L \oplus (C_1^L \oplus C_2^L), C_2^R) = (C_1^L, C_2^R). \quad (2)$$

Here, $\{C_1^L, C_2^L\} = \{C_3^L, C_4^L\}$.

- 3 Further, $C_1^R = C_3^R$ and $C_2^R = C_4^R$. *Additional gain of $(q_2^R)^{-2}$ for total probability $(pq_1)^2 q_2^L$, better than shifting!*
- 4 Similar to the core step used in the yoyo attack on AES.

The Mixing Retracing Boomerang Attack




Figure 4: A mixture quartet of ciphertexts (dashed lines indicate equality).

Advantages of Shifting Retracing Attack

① Using structures

Advantages of Shifting Retracing Attack

① Using structures

- Shifting applies the same δ -shift to all pairs of ciphertexts.

Advantages of Shifting Retracing Attack

① Using structures

- Shifting applies the same δ -shift to all pairs of ciphertexts.
- Filtering applied first reduces the data complexity. No filtering in mixing since shift is based on ciphertexts.

Advantages of Shifting Retracing Attack

① Using structures

- Shifting applies the same δ -shift to all pairs of ciphertexts.
- Filtering applied first reduces the data complexity. No filtering in mixing since shift is based on ciphertexts.
- With shifting, one can obtain all ciphertexts, shift them by δ and then decrypt, simultaneously checking for the filter and condition between P_3 and P_4 using a hash table.

Advantages of Shifting Retracing Attack

① Using structures

- Shifting applies the same δ -shift to all pairs of ciphertexts.
- Filtering applied first reduces the data complexity. No filtering in mixing since shift is based on ciphertexts.
- With shifting, one can obtain all ciphertexts, shift them by δ and then decrypt, simultaneously checking for the filter and condition between P_3 and P_4 using a hash table.

② Combination with E_{11}

Advantages of Shifting Retracing Attack

① Using structures

- Shifting applies the same δ -shift to all pairs of ciphertexts.
- Filtering applied first reduces the data complexity. No filtering in mixing since shift is based on ciphertexts.
- With shifting, one can obtain all ciphertexts, shift them by δ and then decrypt, simultaneously checking for the filter and condition between P_3 and P_4 using a hash table.

② Combination with E_{11}

- In mixing, the output difference of E_{12}^L is arbitrary.

Advantages of Shifting Retracing Attack

① Using structures

- Shifting applies the same δ -shift to all pairs of ciphertexts.
- Filtering applied first reduces the data complexity. No filtering in mixing since shift is based on ciphertexts.
- With shifting, one can obtain all ciphertexts, shift them by δ and then decrypt, simultaneously checking for the filter and condition between P_3 and P_4 using a hash table.

② Combination with E_{11}

- In mixing, the output difference of E_{12}^L is arbitrary.
- Usually no good combination between characteristics of $(E_{12}^L)^{-1}$ and $(E_{11})^{-1}$. For instance, in the yoyo attack, E_{11} is empty.

Advantages of Shifting Retracing Attack

① Using structures

- Shifting applies the same δ -shift to all pairs of ciphertexts.
- Filtering applied first reduces the data complexity. No filtering in mixing since shift is based on ciphertexts.
- With shifting, one can obtain all ciphertexts, shift them by δ and then decrypt, simultaneously checking for the filter and condition between P_3 and P_4 using a hash table.

② Combination with E_{11}

- In mixing, the output difference of E_{12}^L is arbitrary.
- Usually no good combination between characteristics of $(E_{12}^L)^{-1}$ and $(E_{11})^{-1}$. For instance, in the yoyo attack, E_{11} is empty.

③ Construction of ‘friend pairs’

Advantages of Shifting Retracing Attack

① Using structures

- Shifting applies the same δ -shift to all pairs of ciphertexts.
- Filtering applied first reduces the data complexity. No filtering in mixing since shift is based on ciphertexts.
- With shifting, one can obtain all ciphertexts, shift them by δ and then decrypt, simultaneously checking for the filter and condition between P_3 and P_4 using a hash table.

② Combination with E_{11}

- In mixing, the output difference of E_{12}^L is arbitrary.
- Usually no good combination between characteristics of $(E_{12}^L)^{-1}$ and $(E_{11})^{-1}$. For instance, in the yoyo attack, E_{11} is empty.

③ Construction of ‘friend pairs’

- ‘Friend pairs’ are pairs which satisfy a common property.

Advantages of Shifting Retracing Attack

① Using structures

- Shifting applies the same δ -shift to all pairs of ciphertexts.
- Filtering applied first reduces the data complexity. No filtering in mixing since shift is based on ciphertexts.
- With shifting, one can obtain all ciphertexts, shift them by δ and then decrypt, simultaneously checking for the filter and condition between P_3 and P_4 using a hash table.

② Combination with E_{11}

- In mixing, the output difference of E_{12}^L is arbitrary.
- Usually no good combination between characteristics of $(E_{12}^L)^{-1}$ and $(E_{11})^{-1}$. For instance, in the yoyo attack, E_{11} is empty.

③ Construction of ‘friend pairs’

- ‘Friend pairs’ are pairs which satisfy a common property.
- More ‘friend pairs’ can be constructed in the shifting variant.

Description of AES

- 1 Byte ordering shown after *SB* in Figure 5 (column major).




Figure 5: An AES round.

Description of AES

- 1 Byte ordering shown after *SB* in Figure 5 (column major).
- 2 j -th byte of a state X_i is denoted as $X_{i,j}$ or $(X_i)_j$.




Figure 5: An AES round.

Description of AES

- 1 Byte ordering shown after *SB* in Figure 5 (column major).
- 2 j -th byte of a state X_i is denoted as $X_{i,j}$ or $(X_i)_j$.
- 3 Denote by W, Z and X the states before *MC* in round 0, at the input to round 1 and before *MC* in round 2 respectively.




Figure 5: An AES round.

Description of AES

- 1 Byte ordering shown after SB in Figure 5 (column major).
- 2 j -th byte of a state X_i is denoted as $X_{i,j}$ or $(X_i)_j$.
- 3 Denote by W, Z and X the states before MC in round 0, at the input to round 1 and before MC in round 2 respectively.
- 4 The l -th shifted column (resp. l -th inverse shifted column) refers to application of SR (resp. SR^{-1}) to the l -th column.




Figure 5: An AES round.

Description of AES

- 1 Byte ordering shown after SB in Figure 5 (column major).
- 2 j -th byte of a state X_i is denoted as $X_{i,j}$ or $(X_i)_j$.
- 3 Denote by W, Z and X the states before MC in round 0, at the input to round 1 and before MC in round 2 respectively.
- 4 The l -th shifted column (resp. l -th inverse shifted column) refers to application of SR (resp. SR^{-1}) to the l -th column.
- 5 Round subkeys are k_{-1}, k_0, \dots




Figure 5: An AES round.

Summary of Yoyo Attack on Five Round AES

- 1 Decomposes AES as $E = E_{12} \circ E_{11} \circ E_0$ where E_0 is the first 2.5 rounds, E_{11} is the MC of round 2 and E_{12} is the last 2 rounds.

Summary of Yoyo Attack on Five Round AES

- ① Decomposes AES as $E = E_{12} \circ E_{11} \circ E_0$ where E_0 is the first 2.5 rounds, E_{11} is the MC of round 2 and E_{12} is the last 2 rounds.
- ② Truncated differential characteristic for E_0 : zero input difference in three inverse shifted columns and zero output difference in a single shifted column with probability $4 \cdot 2^{-8} = 2^{-6}$.



Summary of Yoyo Attack on Five Round AES

- 1 Decomposes AES as $E = E_{12} \circ E_{11} \circ E_0$ where E_0 is the first 2.5 rounds, E_{11} is the MC of round 2 and E_{12} is the last 2 rounds.
- 2 Truncated differential characteristic for E_0 : zero input difference in three inverse shifted columns and zero output difference in a single shifted column with probability $4 \cdot 2^{-8} = 2^{-6}$.
- 3 For E_{12} , 1.5 rounds of AES can be taken as four 32-bit super S-boxes.



Summary of Yoyo Attack on Five Round AES

- ① Decomposes AES as $E = E_{12} \circ E_{11} \circ E_0$ where E_0 is the first 2.5 rounds, E_{11} is the MC of round 2 and E_{12} is the last 2 rounds.
- ② Truncated differential characteristic for E_0 : zero input difference in three inverse shifted columns and zero output difference in a single shifted column with probability $4 \cdot 2^{-8} = 2^{-6}$.
- ③ For E_{12} , 1.5 rounds of AES can be taken as four 32-bit super S-boxes.
- ④ Attack inverse shifted columns of k_{-1} . Friend pairs used to get more information.

Meet in the Middle Improvement on Yoyo Attack

- 1 Denote the value of byte m before MC operation of round 0 by W_m , and WLOG let $l = 0$. Then,

$$Z_0 = 02_x \cdot W_0 \oplus 03_x \cdot W_1 \oplus 01_x \cdot W_2 \oplus 01_x \cdot W_3. \quad (3)$$

Meet in the Middle Improvement on Yoyo Attack

- 1 Denote the value of byte m before MC operation of round 0 by W_m , and WLOG let $l = 0$. Then,

$$Z_0 = 02_x \cdot W_0 \oplus 03_x \cdot W_1 \oplus 01_x \cdot W_2 \oplus 01_x \cdot W_3. \quad (3)$$

- 2 Adversary guesses $k_{-1, \{0,5\}}$ by computing the following for $j = 1, 2, 3$ and storing the concatenated 24-bit value in a hash table.

$$02_x \cdot ((W_3^j)_0 \oplus (W_4^j)_0) \oplus 03_x \cdot ((W_3^j)_1 \oplus (W_4^j)_1) \quad (4)$$

Meet in the Middle Improvement on Yoyo Attack

- 1 Denote the value of byte m before MC operation of round 0 by W_m , and WLOG let $l = 0$. Then,

$$Z_0 = 02_x \cdot W_0 \oplus 03_x \cdot W_1 \oplus 01_x \cdot W_2 \oplus 01_x \cdot W_3. \quad (3)$$

- 2 Adversary guesses $k_{-1, \{0,5\}}$ by computing the following for $j = 1, 2, 3$ and storing the concatenated 24-bit value in a hash table.

$$02_x \cdot ((W_3^j)_0 \oplus (W_4^j)_0) \oplus 03_x \cdot ((W_3^j)_1 \oplus (W_4^j)_1) \quad (4)$$

- 3 We need $Z_0 = 0$ to satisfy the truncated differential characteristic. Meet in the Middle (MITM) methods are used to narrow down candidates for k_{-1} .

Meet in the Middle Improvement on Yoyo Attack

- 1 Denote the value of byte m before MC operation of round 0 by W_m , and WLOG let $l = 0$. Then,

$$Z_0 = 02_x \cdot W_0 \oplus 03_x \cdot W_1 \oplus 01_x \cdot W_2 \oplus 01_x \cdot W_3. \quad (3)$$

- 2 Adversary guesses $k_{-1, \{0,5\}}$ by computing the following for $j = 1, 2, 3$ and storing the concatenated 24-bit value in a hash table.

$$02_x \cdot ((W_3^j)_0 \oplus (W_4^j)_0) \oplus 03_x \cdot ((W_3^j)_1 \oplus (W_4^j)_1) \quad (4)$$

- 3 We need $Z_0 = 0$ to satisfy the truncated differential characteristic. Meet in the Middle (MITM) methods are used to narrow down candidates for k_{-1} .
 - Specific choice of plaintexts based on DDT of AES S-boxes.

Meet in the Middle Improvement on Yoyo Attack

- 1 Denote the value of byte m before MC operation of round 0 by W_m , and WLOG let $l = 0$. Then,

$$Z_0 = 02_x \cdot W_0 \oplus 03_x \cdot W_1 \oplus 01_x \cdot W_2 \oplus 01_x \cdot W_3. \quad (3)$$

- 2 Adversary guesses $k_{-1, \{0,5\}}$ by computing the following for $j = 1, 2, 3$ and storing the concatenated 24-bit value in a hash table.

$$02_x \cdot ((W_3^j)_0 \oplus (W_4^j)_0) \oplus 03_x \cdot ((W_3^j)_1 \oplus (W_4^j)_1) \quad (4)$$

- 3 We need $Z_0 = 0$ to satisfy the truncated differential characteristic. Meet in the Middle (MITM) methods are used to narrow down candidates for k_{-1} .
 - Specific choice of plaintexts based on DDT of AES S-boxes.
 - Eliminating key bytes using friend pairs.

Specific Choice of Plaintexts

- 1 Choose plaintexts with non-zero difference *only in bytes 0 and 5*.
Here, $(Z_1)_0 = (Z_2)_0$ leaves 2^8 candidates for $k_{-1,\{0,5\}}$, given by

$$02_x \cdot ((W_1)_0 \oplus (W_2)_0) \oplus 03_x \cdot ((W_1)_1 \oplus (W_2)_1) = 0. \quad (5)$$

Specific Choice of Plaintexts

- 1 Choose plaintexts with non-zero difference *only in bytes 0 and 5*.
Here, $(Z_1)_0 = (Z_2)_0$ leaves 2^8 candidates for $k_{-1,\{0,5\}}$, given by

$$02_x \cdot ((W_1)_0 \oplus (W_2)_0) \oplus 03_x \cdot ((W_1)_1 \oplus (W_2)_1) = 0. \quad (5)$$

- 2 Constrain $(P_1)_5 \oplus (P_2)_5 = 01_x$ to detect right key bytes efficiently.

Specific Choice of Plaintexts

- 1 Choose plaintexts with non-zero difference *only in bytes 0 and 5*. Here, $(Z_1)_0 = (Z_2)_0$ leaves 2^8 candidates for $k_{-1,\{0,5\}}$, given by

$$02_x \cdot ((W_1)_0 \oplus (W_2)_0) \oplus 03_x \cdot ((W_1)_1 \oplus (W_2)_1) = 0. \quad (5)$$

- 2 Constrain $(P_1)_5 \oplus (P_2)_5 = 01_x$ to detect right key bytes efficiently.
- 3 DDT row of AES S-box for input difference 01_x along with input pair(s) for each output difference computed and stored in memory.

Specific Choice of Plaintexts

- 1 Choose plaintexts with non-zero difference *only in bytes 0 and 5*. Here, $(Z_1)_0 = (Z_2)_0$ leaves 2^8 candidates for $k_{-1,\{0,5\}}$, given by

$$02_x \cdot ((W_1)_0 \oplus (W_2)_0) \oplus 03_x \cdot ((W_1)_1 \oplus (W_2)_1) = 0. \quad (5)$$

- 2 Constrain $(P_1)_5 \oplus (P_2)_5 = 01_x$ to detect right key bytes efficiently.
- 3 DDT row of AES S-box for input difference 01_x along with input pair(s) for each output difference computed and stored in memory.
- 4 For each (P_1, P_2) and for each guess of $k_{-1,0}$, use (5) to compute the output difference of the SB operation in byte 5.

Specific Choice of Plaintexts

- 1 Choose plaintexts with non-zero difference *only in bytes 0 and 5*. Here, $(Z_1)_0 = (Z_2)_0$ leaves 2^8 candidates for $k_{-1,\{0,5\}}$, given by

$$02_x \cdot ((W_1)_0 \oplus (W_2)_0) \oplus 03_x \cdot ((W_1)_1 \oplus (W_2)_1) = 0. \quad (5)$$

- 2 Constrain $(P_1)_5 \oplus (P_2)_5 = 01_x$ to detect right key bytes efficiently.
- 3 DDT row of AES S-box for input difference 01_x along with input pair(s) for each output difference computed and stored in memory.
- 4 For each (P_1, P_2) and for each guess of $k_{-1,0}$, use (5) to compute the output difference of the SB operation in byte 5.
- 5 Lookup to find inputs that can lead to this difference and retrieve possible values of $k_{-1,5}$ corresponding to the guessed $k_{-1,0}$.

Specific Choice of Plaintexts

- 1 Choose plaintexts with non-zero difference *only in bytes 0 and 5*. Here, $(Z_1)_0 = (Z_2)_0$ leaves 2^8 candidates for $k_{-1,\{0,5\}}$, given by

$$02_x \cdot ((W_1)_0 \oplus (W_2)_0) \oplus 03_x \cdot ((W_1)_1 \oplus (W_2)_1) = 0. \quad (5)$$

- 2 Constrain $(P_1)_5 \oplus (P_2)_5 = 01_x$ to detect right key bytes efficiently.
- 3 DDT row of AES S-box for input difference 01_x along with input pair(s) for each output difference computed and stored in memory.
- 4 For each (P_1, P_2) and for each guess of $k_{-1,0}$, use (5) to compute the output difference of the SB operation in byte 5.
- 5 Lookup to find inputs that can lead to this difference and retrieve possible values of $k_{-1,5}$ corresponding to the guessed $k_{-1,0}$.
- 6 Obtain 2^8 candidates for $k_{-1,\{0,5\}}$ in about 2^8 operations per pair.

Eliminating Key Bytes Using Friend Pairs

- 1 To reduce the number of candidates for $k_{-1,\{10,15\}}$, the boomerang process is used to return multiple friend pairs (P_3^j, P_4^j) .

Eliminating Key Bytes Using Friend Pairs

- 1 To reduce the number of candidates for $k_{-1,\{10,15\}}$, the boomerang process is used to return multiple friend pairs (P_3^j, P_4^j) .
- 2 In particular, we choose one such pair for which

$$(P_3^j)_{10} \oplus (P_4^j)_{10} = 0 \quad \text{or} \quad (P_3^j)_{15} \oplus (P_4^j)_{15} = 0. \quad (6)$$

Eliminating Key Bytes Using Friend Pairs

- 1 To reduce the number of candidates for $k_{-1,\{10,15\}}$, the boomerang process is used to return multiple friend pairs (P_3^j, P_4^j) .
- 2 In particular, we choose one such pair for which

$$(P_3^j)_{10} \oplus (P_4^j)_{10} = 0 \quad \text{or} \quad (P_3^j)_{15} \oplus (P_4^j)_{15} = 0. \quad (6)$$

- 3 If equality holds in byte 10, then $k_{-1,15}$ is isolated for a fixed $k_{-1,\{0,5\}}$ and has only 2^8 possible values.

Eliminating Key Bytes Using Friend Pairs

- 1 To reduce the number of candidates for $k_{-1,\{10,15\}}$, the boomerang process is used to return multiple friend pairs (P_3^j, P_4^j) .
- 2 In particular, we choose one such pair for which

$$(P_3^j)_{10} \oplus (P_4^j)_{10} = 0 \quad \text{or} \quad (P_3^j)_{15} \oplus (P_4^j)_{15} = 0. \quad (6)$$

- 3 If equality holds in byte 10, then $k_{-1,15}$ is isolated for a fixed $k_{-1,\{0,5\}}$ and has only 2^8 possible values.
- 4 Requires 2^9 simple operations and leaves 2^8 candidates for $k_{-1,\{0,5,15\}}$.

Eliminating Key Bytes Using Friend Pairs

- 1 To reduce the number of candidates for $k_{-1,\{10,15\}}$, the boomerang process is used to return multiple friend pairs (P_3^j, P_4^j) .
- 2 In particular, we choose one such pair for which

$$(P_3^j)_{10} \oplus (P_4^j)_{10} = 0 \quad \text{or} \quad (P_3^j)_{15} \oplus (P_4^j)_{15} = 0. \quad (6)$$

- 3 If equality holds in byte 10, then $k_{-1,15}$ is isolated for a fixed $k_{-1,\{0,5\}}$ and has only 2^8 possible values.
- 4 Requires 2^9 simple operations and leaves 2^8 candidates for $k_{-1,\{0,5,15\}}$.
- 5 Similar MITM procedure followed with another friend pair to obtain the unique value of $k_{-1,\{0,5,10,15\}}$ by isolating $k_{-1,10}$.

Eliminating Key Bytes Using Friend Pairs

- 1 To reduce the number of candidates for $k_{-1,\{10,15\}}$, the boomerang process is used to return multiple friend pairs (P_3^j, P_4^j) .
- 2 In particular, we choose one such pair for which

$$(P_3^j)_{10} \oplus (P_4^j)_{10} = 0 \quad \text{or} \quad (P_3^j)_{15} \oplus (P_4^j)_{15} = 0. \quad (6)$$

- 3 If equality holds in byte 10, then $k_{-1,15}$ is isolated for a fixed $k_{-1,\{0,5\}}$ and has only 2^8 possible values.
- 4 Requires 2^9 simple operations and leaves 2^8 candidates for $k_{-1,\{0,5,15\}}$.
- 5 Similar MITM procedure followed with another friend pair to obtain the unique value of $k_{-1,\{0,5,10,15\}}$ by isolating $k_{-1,10}$.
- 6 Perform 2^8 operations for each pair (P_1, P_2) and for each value of l . Total time complexity of about 2^{16} operations.

Eliminating Key Bytes Using Friend Pairs

- 1 To reduce the number of candidates for $k_{-1,\{10,15\}}$, the boomerang process is used to return multiple friend pairs (P_3^j, P_4^j) .
- 2 In particular, we choose one such pair for which

$$(P_3^j)_{10} \oplus (P_4^j)_{10} = 0 \quad \text{or} \quad (P_3^j)_{15} \oplus (P_4^j)_{15} = 0. \quad (6)$$

- 3 If equality holds in byte 10, then $k_{-1,15}$ is isolated for a fixed $k_{-1,\{0,5\}}$ and has only 2^8 possible values.
- 4 Requires 2^9 simple operations and leaves 2^8 candidates for $k_{-1,\{0,5,15\}}$.
- 5 Similar MITM procedure followed with another friend pair to obtain the unique value of $k_{-1,\{0,5,10,15\}}$ by isolating $k_{-1,10}$.
- 6 Perform 2^8 operations for each pair (P_1, P_2) and for each value of l . Total time complexity of about 2^{16} operations.
- 7 Each pair requires 2^7 friend pairs to find one that satisfies (6) with high probability. Total data complexity is increased to about 2^{15} .

Attack Algorithm

- 1 **Precomputation:** Compute DDT row of AES S-box for input difference 01_x , along with actual inputs for each output difference.

Attack Algorithm

- 1 **Precomputation:** Compute DDT row of AES S-box for input difference 01_x , along with actual inputs for each output difference.
- 2 **Online Phase:** Take 64 pairs (P_1, P_2) with $(P_1)_5 = 00_x$, $(P_2)_5 = 01_x$, $(P_1)_0 \neq (P_2)_0$ and all other corresponding bytes equal.

Attack Algorithm

- 1 **Precomputation:** Compute DDT row of AES S-box for input difference 01_x , along with actual inputs for each output difference.
- 2 **Online Phase:** Take 64 pairs (P_1, P_2) with $(P_1)_5 = 00_x$, $(P_2)_5 = 01_x$, $(P_1)_0 \neq (P_2)_0$ and all other corresponding bytes equal.
- 3 For each plaintext pair, create 2^7 friend pairs (P_1^j, P_2^j) such that for each j , $P_1^j \oplus P_2^j = P_1 \oplus P_2$ and $(P_1^j)_{\{0,5,10,15\}} = (P_1)_{\{0,5,10,15\}}$.

Attack Algorithm

- 4 For each plaintext pair (P_1, P_2) and for each $l \in \{0, 1, 2, 3\}$, do the following. ($l = 0$ taken below)

Attack Algorithm

- 4 For each plaintext pair (P_1, P_2) and for each $l \in \{0, 1, 2, 3\}$, do the following. ($l = 0$ taken below)
 - 1 Use (5) to compute and store all 2^8 candidates for $k_{-1, \{0,5\}}$ in a table.

Attack Algorithm

- 4 For each plaintext pair (P_1, P_2) and for each $l \in \{0, 1, 2, 3\}$, do the following. ($l = 0$ taken below)
 - 1 Use (5) to compute and store all 2^8 candidates for $k_{-1, \{0,5\}}$ in a table.
 - 2 Use the boomerang process to obtain pairs (P_3, P_4) and (P_3^j, P_4^j) .

Attack Algorithm

- 4 For each plaintext pair (P_1, P_2) and for each $l \in \{0, 1, 2, 3\}$, do the following. ($l = 0$ taken below)
 - 1 Use (5) to compute and store all 2^8 candidates for $k_{-1, \{0,5\}}$ in a table.
 - 2 Use the boomerang process to obtain pairs (P_3, P_4) and (P_3^j, P_4^j) .
 - 3 Find a j for which (6) is satisfied. Perform an MITM attack on column 0 of round 0 using (P_3^j, P_4^j) to obtain 2^8 candidates for $k_{-1, \{0,5,15\}}$.

Attack Algorithm

- 4 For each plaintext pair (P_1, P_2) and for each $l \in \{0, 1, 2, 3\}$, do the following. ($l = 0$ taken below)
 - 1 Use (5) to compute and store all 2^8 candidates for $k_{-1, \{0,5\}}$ in a table.
 - 2 Use the boomerang process to obtain pairs (P_3, P_4) and (P_3^j, P_4^j) .
 - 3 Find a j for which (6) is satisfied. Perform an MITM attack on column 0 of round 0 using (P_3^j, P_4^j) to obtain 2^8 candidates for $k_{-1, \{0,5,15\}}$.
 - 4 Perform another MITM attack on column 0 of round 0 using two plaintext pairs $(P_3^{j'}, P_4^{j'})$. This gives a possible value for $k_{-1, \{0,5,10,15\}}$.

Attack Algorithm

- 4 For each plaintext pair (P_1, P_2) and for each $l \in \{0, 1, 2, 3\}$, do the following. ($l = 0$ taken below)
 - 1 Use (5) to compute and store all 2^8 candidates for $k_{-1, \{0,5\}}$ in a table.
 - 2 Use the boomerang process to obtain pairs (P_3, P_4) and (P_3^j, P_4^j) .
 - 3 Find a j for which (6) is satisfied. Perform an MITM attack on column 0 of round 0 using (P_3^j, P_4^j) to obtain 2^8 candidates for $k_{-1, \{0,5,15\}}$.
 - 4 Perform another MITM attack on column 0 of round 0 using two plaintext pairs $(P_3^{j'}, P_4^{j'})$. This gives a possible value for $k_{-1, \{0,5,10,15\}}$.
 - 5 If contradiction, go to the next value of l . If contradiction for all l , discard this pair and go to the next pair.

Attack Algorithm

- 4 For each plaintext pair (P_1, P_2) and for each $l \in \{0, 1, 2, 3\}$, do the following. ($l = 0$ taken below)
 - 1 Use (5) to compute and store all 2^8 candidates for $k_{-1, \{0,5\}}$ in a table.
 - 2 Use the boomerang process to obtain pairs (P_3, P_4) and (P_3^j, P_4^j) .
 - 3 Find a j for which (6) is satisfied. Perform an MITM attack on column 0 of round 0 using (P_3^j, P_4^j) to obtain 2^8 candidates for $k_{-1, \{0,5,15\}}$.
 - 4 Perform another MITM attack on column 0 of round 0 using two plaintext pairs (P_3^j, P_4^j) . This gives a possible value for $k_{-1, \{0,5,10,15\}}$.
 - 5 If contradiction, go to the next value of l . If contradiction for all l , discard this pair and go to the next pair.
- 5 Using a pair (P_1, P_2) for which no contradiction occurred, perform MITM attacks on columns 1, 2 and 3 of round 0 using the fact that $Z_3 \oplus Z_4$ equals 0 in the l -th inverse shifted column to recover k_{-1} .

Attack Analysis

- 1 Attack succeeds if data contains a pair that satisfies the truncated differential characteristic of E_0 and if a friend pair has zero difference in either byte 10 or 15.

Attack Analysis

- 1 Attack succeeds if data contains a pair that satisfies the truncated differential characteristic of E_0 and if a friend pair has zero difference in either byte 10 or 15.
- 2 Increasing the number of initial pairs and friend pairs per initial pair boosts success probability. With 64 pairs and 128 friend pairs per initial pair, the probability of success is $(1 - e^{-1})^2 \approx 0.4$

Attack Analysis

- 1 Attack succeeds if data contains a pair that satisfies the truncated differential characteristic of E_0 and if a friend pair has zero difference in either byte 10 or 15.
- 2 Increasing the number of initial pairs and friend pairs per initial pair boosts success probability. With 64 pairs and 128 friend pairs per initial pair, the probability of success is $(1 - e^{-1})^2 \approx 0.4$
- 3 Another way to boost success probability is to find other ways to cancel terms in (3). For instance, if there exist j, j' such that $\{(P_3^j)_{10}, (P_4^j)_{10}\} = \{(P_3^{j'})_{10}, (P_4^{j'})_{10}\}$, we can take the XOR of (3) to cancel the effect of $k_{-1,10}$, thus increasing the success probability even when there is no pair that satisfies (6).

Attack Analysis

- 4 Data complexity is $2 \cdot 2^6 \cdot 2^7 = 2^{14}$ chosen plaintexts and 2^{14} adaptively chosen ciphertexts.

Attack Analysis

- 4 Data complexity is $2 \cdot 2^6 \cdot 2^7 = 2^{14}$ chosen plaintexts and 2^{14} adaptively chosen ciphertexts.
- 5 Structures reduce the data complexity to slightly above 2^{14} adaptively chosen ciphertexts and plaintexts, but success probability slightly reduced due to additional dependencies between analyzed pairs.

Attack Analysis

- 4 Data complexity is $2 \cdot 2^6 \cdot 2^7 = 2^{14}$ chosen plaintexts and 2^{14} adaptively chosen ciphertexts.
- 5 Structures reduce the data complexity to slightly above 2^{14} adaptively chosen ciphertexts and plaintexts, but success probability slightly reduced due to additional dependencies between analyzed pairs.
- 6 Memory complexity of the attack remains at 2^9 , like yoyo attack.

Attack Analysis

- ④ Data complexity is $2 \cdot 2^6 \cdot 2^7 = 2^{14}$ chosen plaintexts and 2^{14} adaptively chosen ciphertexts.
- ⑤ Structures reduce the data complexity to slightly above 2^{14} adaptively chosen ciphertexts and plaintexts, but success probability slightly reduced due to additional dependencies between analyzed pairs.
- ⑥ Memory complexity of the attack remains at 2^9 , like yoyo attack.
- ⑦ Time complexity dominated by MITM attacks that take 2^{16} operations each. Taking one AES operation equivalent to 80 S-box lookups and adding it to the number of queries gives us a total of $2^{16.5}$ encryptions.