

# Anonymous Key Agreements for V2X Communication

Gautam Singh

Indian Institute of Technology Hyderabad

May 1, 2024

## 1 Introduction

## 2 Preliminaries

## 3 Our Proposition

## 4 Conclusion

# V2X Related Terminology




Figure 1: A breakdown of V2X.

- 1 Exchanged between vehicles to create awareness and support cooperative performance of vehicles in the road network.
- 2 Includes status information such as time, position, speed, active systems, vehicle dimensions, etc.
- 3 Broadcasted unencrypted in 5.9 GHz channel (ETSI ITS-G5).
- 4 **Huge privacy concerns and threats!**

<sup>2</sup>J2735\_202309: V2X Communications Message Set Dictionary - SAE International. URL: [https://www.sae.org/standards/content/j2735\\_202309/](https://www.sae.org/standards/content/j2735_202309/) (visited on 04/15/2024).

# Message Types in V2X

## ① **Cooperative Awareness Messages (CAMs)<sup>1</sup> and Basic Safety Messages (BSMs)<sup>2</sup>.**

- ① Exchanged between vehicles to create awareness and support cooperative performance of vehicles in the road network.
- ② Includes status information such as time, position, speed, active systems, vehicle dimensions, etc.
- ③ Broadcasted unencrypted in 5.9 GHz channel (ETSI ITS-G5).
- ④ **Huge privacy concerns and threats!**

## ② Other types of messages

- ① **Signal Phase and Timing (SPaT)**
- ② **Roadside Infrastructure Information (MAP)**

---

<sup>1</sup>European Telecommunications Standards Institute, "Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Part 2: Specification of Cooperative Awareness Basic Service".

<sup>2</sup>J2735\_202309.

# Motivation and Goals

- ① Do we *really* need to encrypt CAMs?
  - Google (Maps) may already be profiling us!
  - Focus on encrypting more sensitive messages and information sent less frequently.

# Motivation and Goals

- ① Do we *really* need to encrypt CAMs?
  - Google (Maps) may already be profiling us!
  - Focus on encrypting more sensitive messages and information sent less frequently.
- ② Unlimited privacy.

# Motivation and Goals

- ① Do we *really* need to encrypt CAMs?
  - Google (Maps) may already be profiling us!
  - Focus on encrypting more sensitive messages and information sent less frequently.
- ② Unlimited privacy.
- ③ Better security guarantees (privacy, authenticity, confidentiality).



# Pairings

## Definition 1

Pairing<sup>a</sup> Let  $\mathbb{G}_0 = \langle g_0 \rangle$ ,  $\mathbb{G}_1 = \langle g_1 \rangle$ ,  $\mathbb{G}_T$  be three cyclic groups of prime order  $q$ . A *pairing* is an efficiently computable function  $e : \mathbb{G}_0 \times \mathbb{G}_1 \rightarrow \mathbb{G}_T$  satisfying the following properties:

- ① *bilinear*: for all  $u, u' \in \mathbb{G}_0$  and  $v, v' \in \mathbb{G}_1$ , we have

$$e(uu', v) = e(u, v) e(u', v) \quad (1)$$

$$e(u, vv') = e(u, v) e(u, v') \quad (2)$$

- ② *non-degenerate*:  $g_T := e(g_0, g_1)$  is a generator of  $\mathbb{G}_T$ .

---

<sup>a</sup>A Graduate Course in Applied Cryptography. URL: <https://toc.cryptobook.us/> (visited on 04/30/2024).

# Pairings

## Definition 1

Pairing<sup>a</sup> Let  $\mathbb{G}_0 = \langle g_0 \rangle$ ,  $\mathbb{G}_1 = \langle g_1 \rangle$ ,  $\mathbb{G}_T$  be three cyclic groups of prime order  $q$ . A *pairing* is an efficiently computable function  $e : \mathbb{G}_0 \times \mathbb{G}_1 \rightarrow \mathbb{G}_T$  satisfying the following properties:

- ① *bilinear*: for all  $u, u' \in \mathbb{G}_0$  and  $v, v' \in \mathbb{G}_1$ , we have

$$e(uu', v) = e(u, v) e(u', v) \quad (1)$$

$$e(u, vv') = e(u, v) e(u, v') \quad (2)$$

- ② *non-degenerate*:  $g_T := e(g_0, g_1)$  is a generator of  $\mathbb{G}_T$ .

---

<sup>a</sup> A Graduate Course in Applied Cryptography.

- ① Here,  $\mathbb{G}_0$  and  $\mathbb{G}_1$  are called *source groups* and  $\mathbb{G}_T$  is called the *target group*.

# Pairings

## Definition 1

Pairing<sup>a</sup> Let  $\mathbb{G}_0 = \langle g_0 \rangle$ ,  $\mathbb{G}_1 = \langle g_1 \rangle$ ,  $\mathbb{G}_T$  be three cyclic groups of prime order  $q$ . A *pairing* is an efficiently computable function  $e : \mathbb{G}_0 \times \mathbb{G}_1 \rightarrow \mathbb{G}_T$  satisfying the following properties:

- ① *bilinear*: for all  $u, u' \in \mathbb{G}_0$  and  $v, v' \in \mathbb{G}_1$ , we have

$$e(uu', v) = e(u, v) e(u', v) \quad (1)$$

$$e(u, vv') = e(u, v) e(u, v') \quad (2)$$

- ② *non-degenerate*:  $g_T := e(g_0, g_1)$  is a generator of  $\mathbb{G}_T$ .

---

<sup>a</sup> A Graduate Course in Applied Cryptography.

- ① Here,  $\mathbb{G}_0$  and  $\mathbb{G}_1$  are called *source groups* and  $\mathbb{G}_T$  is called the *target group*.
- ② When  $\mathbb{G}_0 = \mathbb{G}_1$ , the pairing is said to be *symmetric*.

# Anonymous Key Agreement

- 1 A key agreement protocol where two parties agree on a shared secret key, without being able to determine the other party.

---

<sup>3</sup>Aniket Kate, Greg Zaverucha, and Ian Goldberg. "Pairing-Based Onion Routing". In: *Privacy Enhancing Technologies*. Ed. by Nikita Borisov and Philippe Golle. Vol. 4776. Berlin, Heidelberg: Springer Berlin Heidelberg, 2007, pp. 95–112. ISBN: 978-3-540-75550-0. DOI: 10.1007/978-3-540-75551-7\_7. URL: [http://link.springer.com/10.1007/978-3-540-75551-7\\_7](http://link.springer.com/10.1007/978-3-540-75551-7_7) (visited on 04/04/2024).

# Anonymous Key Agreement

- 1 A key agreement protocol where two parties agree on a shared secret key, without being able to determine the other party.
- 2 Pairing-based anonymous key agreement for V2X.

---

<sup>3</sup>Kate, Zaverucha, and Goldberg, "Pairing-Based Onion Routing".

# Anonymous Key Agreement

- ① A key agreement protocol where two parties agree on a shared secret key, without being able to determine the other party.
- ② Pairing-based anonymous key agreement for V2X.
- ③ We use a pairing-based anonymous key agreement involving a private key generator (PKG)<sup>3</sup>.
  - ① PKG has its own master private and public key.
  - ② PKG uses master secret key to generate secret keys for clients.
  - ③ Clients use this secret key to establish the shared secret key.

---

<sup>3</sup>Kate, Zaverucha, and Goldberg, "Pairing-Based Onion Routing".

# Anonymous Key Agreement

- ① A key agreement protocol where two parties agree on a shared secret key, without being able to determine the other party.
- ② Pairing-based anonymous key agreement for V2X.
- ③ We use a pairing-based anonymous key agreement involving a private key generator (PKG)<sup>3</sup>.
  - ① PKG has its own master private and public key.
  - ② PKG uses master secret key to generate secret keys for clients.
  - ③ Clients use this secret key to establish the shared secret key.
- ④ Clients can now create **pseudonyms** or fake identities  
 $id \rightarrow (\mathcal{H}(id))^r, \mathcal{H} : \mathcal{ID} \rightarrow \mathcal{G}, r \in \mathbb{Z}_q.$

<sup>3</sup>Kate, Zaverucha, and Goldberg, "Pairing-Based Onion Routing".

# Attributes, Credentials, Anonymous Credentials

- 1 **Attributes:** Labels associated with a user that describe them fully, such as role of a user.

---

<sup>4</sup>Jan Camenisch et al. *Zone Encryption with Anonymous Authentication for V2V Communication*. 2020. URL: <https://eprint.iacr.org/2020/043> (visited on 02/04/2024). preprint.



# Attributes, Credentials, Anonymous Credentials

- ① **Attributes:** Labels associated with a user that describe them fully, such as role of a user.
- ② **Credential:** Data possessed by a user that demonstrates their attributes.

---

<sup>4</sup>Camenisch et al., *Zone Encryption with Anonymous Authentication for V2V Communication*.

# Attributes, Credentials, Anonymous Credentials

- ① **Attributes:** Labels associated with a user that describe them fully, such as role of a user.
- ② **Credential:** Data possessed by a user that demonstrates their attributes.
- ③ **Anonymous Credential:** Data possessed by a user that demonstrates their attributes, *without revealing any additional information* about their identity.

---

<sup>4</sup>Camenisch et al., *Zone Encryption with Anonymous Authentication for V2V Communication*.[▶](#)

# Attributes, Credentials, Anonymous Credentials

- ① **Attributes:** Labels associated with a user that describe them fully, such as role of a user.
- ② **Credential:** Data possessed by a user that demonstrates their attributes.
- ③ **Anonymous Credential:** Data possessed by a user that demonstrates their attributes, *without revealing any additional information* about their identity.
- ④ For V2X
  - Anonymous credentials issued to vehicles regularly.
  - We use DGSA (Digital Group Signatures with Attributes)<sup>4</sup>, which gives us a **randomizable** group element as the credential  $\sigma \rightarrow \sigma^r, r \in \mathbb{Z}_q$ .

---

<sup>4</sup>Camenisch et al., *Zone Encryption with Anonymous Authentication for V2V Communication*.

# Proposed Message Flow Diagram




Figure 2: Message flow of the proposed scheme.

# Proposed Message Flow

- ① Enrollment authority issues certificate to vehicle.
  - Certificate is a long-term credential that can be used to revoke the holder in case of misbehaviour.

# Proposed Message Flow

- ① Enrollment authority issues certificate to vehicle.
  - Certificate is a long-term credential that can be used to revoke the holder in case of misbehaviour.
- ② Issuer issues DGSA credentials and secret key after verifying certificate.
  - This secret key is different from secret key associated with certificate.
  - DGSA credentials guarantee authenticity.
  - Anonymous key agreement ensures that user identities remain anonymous throughout communication.
  - This is done periodically every *epoch*.

# Proposed Message Flow

- ① Enrollment authority issues certificate to vehicle.
  - Certificate is a long-term credential that can be used to revoke the holder in case of misbehaviour.
- ② Issuer issues DGSA credentials and secret key after verifying certificate.
  - This secret key is different from secret key associated with certificate.
  - DGSA credentials guarantee authenticity.
  - Anonymous key agreement ensures that user identities remain anonymous throughout communication.
  - This is done periodically every *epoch*.
- ③ Vehicles exchange DGSA-signed randomized pseudonyms to generate shared key for further communication.
  - Used in verifying legitimacy of the other party.

# Analysis

## ① Advantages

- Fully anonymous communication, unlimited privacy between communicating parties.
- Third parties cannot identify who is communicating.
- Useful for sending extremely sensitive data.
- Malicious vehicles can be revoked.



# Analysis

## ① Advantages

- Fully anonymous communication, unlimited privacy between communicating parties.
- Third parties cannot identify who is communicating.
- Useful for sending extremely sensitive data.
- Malicious vehicles can be revoked.

## ② Disadvantages

- Lots of pairing computations, for DGSA and for anonymous key agreement. Incurs computational overheads.
- Works for single-hop connections only.
- May not be scalable to communicating with many vehicles simultaneously in terms of storage overhead.

# Future Work

- 1 Encrypt V2X messages like CAMs.

---

<sup>5</sup>Camenisch et al., *Zone Encryption with Anonymous Authentication for V2V Communication*.


<sup>6</sup>Xiaohan Yue et al. "A Practical Privacy-Preserving Communication Scheme for CAMs in C-ITS". In: *Journal of Information Security and Applications* 65 (Mar. 1, 2022), p. 103103. ISSN: 2214-2126. DOI: 10.1016/j.jisa.2021.103103. URL: <https://www.sciencedirect.com/science/article/pii/S2214212621002799> (visited on 04/29/2024).

# Future Work

- ① Encrypt V2X messages like CAMs.
- ② Improve efficiency of the present work.
  - Use one of DGSA or anonymous key agreement, but not both?

---

<sup>5</sup>Camenisch et al., *Zone Encryption with Anonymous Authentication for V2V Communication*.

<sup>6</sup>Yue et al., "A Practical Privacy-Preserving Communication Scheme for CAMs in C-ITS"          

# Future Work

- ① Encrypt V2X messages like CAMs.
- ② Improve efficiency of the present work.
  - Use one of DGSA or anonymous key agreement, but not both?
- ③ A new workflow for encryption using zones<sup>5</sup> and zone managers<sup>6</sup>

---

<sup>5</sup>Camenisch et al., *Zone Encryption with Anonymous Authentication for V2V Communication*.

<sup>6</sup>Yue et al., "A Practical Privacy-Preserving Communication Scheme for CAMs in C-ITS", 