

Anonymous Key Agreements for V2X Communication

Gautam Singh

Indian Institute of Technology Hyderabad

May 1, 2024

1 Introduction

2 Preliminaries

3 Conclusion

V2X Related Terminology




Figure 1: A breakdown of V2X.

- 1 Exchanged between vehicles to create awareness and support cooperative performance of vehicles in the road network.
- 2 Includes status information such as time, position, speed, active systems, vehicle dimensions, etc.
- 3 Broadcasted unencrypted in 5.9 GHz channel (ETSI ITS-G5).
- 4 **Huge privacy concerns and threats!**

²J2735_202309: V2X Communications Message Set Dictionary - SAE International. URL: https://www.sae.org/standards/content/j2735_202309/ (visited on 04/15/2024).

Message Types in V2X

① **Cooperative Awareness Messages (CAMs)¹ and Basic Safety Messages (BSMs)².**

- ① Exchanged between vehicles to create awareness and support cooperative performance of vehicles in the road network.
- ② Includes status information such as time, position, speed, active systems, vehicle dimensions, etc.
- ③ Broadcasted unencrypted in 5.9 GHz channel (ETSI ITS-G5).
- ④ **Huge privacy concerns and threats!**

② Other types of messages

- ① **Signal Phase and Timing (SPaT)**
- ② **Roadside Infrastructure Information (MAP)**

¹European Telecommunications Standards Institute, "Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Part 2: Specification of Cooperative Awareness Basic Service".

²J2735_202309.

Motivation and Goals

- ① Do we *really* need to encrypt CAMs?
 - Google (Maps) may already be profiling us!
 - Focus on encrypting more sensitive messages and information sent less frequently.

Motivation and Goals

- ① Do we *really* need to encrypt CAMs?
 - Google (Maps) may already be profiling us!
 - Focus on encrypting more sensitive messages and information sent less frequently.
- ② Unlimited privacy.

Motivation and Goals

- ① Do we *really* need to encrypt CAMs?
 - Google (Maps) may already be profiling us!
 - Focus on encrypting more sensitive messages and information sent less frequently.
- ② Unlimited privacy.
- ③ Better security guarantees (privacy, authenticity, confidentiality).

Pairings

Definition 1

Pairing^a Let $\mathbb{G}_0 = \langle g_0 \rangle$, $\mathbb{G}_1 = \langle g_1 \rangle$, \mathbb{G}_T be three cyclic groups of prime order q . A *pairing* is an efficiently computable function $e : \mathbb{G}_0 \times \mathbb{G}_1 \rightarrow \mathbb{G}_T$ satisfying the following properties:

- ① *bilinear*: for all $u, u' \in \mathbb{G}_0$ and $v, v' \in \mathbb{G}_1$, we have

$$e(uu', v) = e(u, v) e(u', v) \quad (1)$$

$$e(u, vv') = e(u, v) e(u, v') \quad (2)$$

- ② *non-degenerate*: $g_T := e(g_0, g_1)$ is a generator of \mathbb{G}_T .

^aA Graduate Course in Applied Cryptography. URL: <https://toc.cryptobook.us/> (visited on 04/30/2024).

Pairings

Definition 1

Pairing^a Let $\mathbb{G}_0 = \langle g_0 \rangle$, $\mathbb{G}_1 = \langle g_1 \rangle$, \mathbb{G}_T be three cyclic groups of prime order q . A *pairing* is an efficiently computable function $e : \mathbb{G}_0 \times \mathbb{G}_1 \rightarrow \mathbb{G}_T$ satisfying the following properties:

- ① *bilinear*: for all $u, u' \in \mathbb{G}_0$ and $v, v' \in \mathbb{G}_1$, we have

$$e(uu', v) = e(u, v) e(u', v) \quad (1)$$

$$e(u, vv') = e(u, v) e(u, v') \quad (2)$$

- ② *non-degenerate*: $g_T := e(g_0, g_1)$ is a generator of \mathbb{G}_T .

^a A Graduate Course in Applied Cryptography.

- ① Here, \mathbb{G}_0 and \mathbb{G}_1 are called *source groups* and \mathbb{G}_T is called the *target group*.

Pairings

Definition 1

Pairing^a Let $\mathbb{G}_0 = \langle g_0 \rangle$, $\mathbb{G}_1 = \langle g_1 \rangle$, \mathbb{G}_T be three cyclic groups of prime order q . A *pairing* is an efficiently computable function $e : \mathbb{G}_0 \times \mathbb{G}_1 \rightarrow \mathbb{G}_T$ satisfying the following properties:

- ① *bilinear*: for all $u, u' \in \mathbb{G}_0$ and $v, v' \in \mathbb{G}_1$, we have

$$e(uu', v) = e(u, v) e(u', v) \quad (1)$$

$$e(u, vv') = e(u, v) e(u, v') \quad (2)$$

- ② *non-degenerate*: $g_T := e(g_0, g_1)$ is a generator of \mathbb{G}_T .

^a A Graduate Course in Applied Cryptography.

- ① Here, \mathbb{G}_0 and \mathbb{G}_1 are called *source groups* and \mathbb{G}_T is called the *target group*.
- ② When $\mathbb{G}_0 = \mathbb{G}_1$, the pairing is said to be *symmetric*.

Anonymous Key Agreement

- 1 A key agreement protocol where two parties agree on a shared secret key, without being able to determine the other party.

³Aniket Kate, Greg Zaverucha, and Ian Goldberg. "Pairing-Based Onion Routing". In: *Privacy Enhancing Technologies*. Ed. by Nikita Borisov and Philippe Golle. Vol. 4776. Berlin, Heidelberg: Springer Berlin Heidelberg, 2007, pp. 95–112. ISBN: 978-3-540-75550-0. DOI: 10.1007/978-3-540-75551-7_7. URL: http://link.springer.com/10.1007/978-3-540-75551-7_7 (visited on 04/04/2024).

Anonymous Key Agreement

- ① A key agreement protocol where two parties agree on a shared secret key, without being able to determine the other party.
- ② Pairing-based anonymous key agreement for V2X
 - Clients should authenticate each other.
 - Clients should not be able to determine the identity of each other.

³Kate, Zaverucha, and Goldberg, "Pairing-Based Onion Routing".

Anonymous Key Agreement

- ① A key agreement protocol where two parties agree on a shared secret key, without being able to determine the other party.
- ② Pairing-based anonymous key agreement for V2X
 - Clients should authenticate each other.
 - Clients should not be able to determine the identity of each other.
- ③ We use a pairing-based anonymous key agreement involving a private key generator (PKG)³.
 - ① PKG has its own master private and public key.
 - ② PKG uses master secret key to generate secret keys for clients.
 - ③ Clients use this secret key to establish the shared secret key.

³Kate, Zaverucha, and Goldberg, "Pairing-Based Onion Routing".

Anonymous Key Agreement

- ① A key agreement protocol where two parties agree on a shared secret key, without being able to determine the other party.
- ② Pairing-based anonymous key agreement for V2X
 - Clients should authenticate each other.
 - Clients should not be able to determine the identity of each other.
- ③ We use a pairing-based anonymous key agreement involving a private key generator (PKG)³.
 - ① PKG has its own master private and public key.
 - ② PKG uses master secret key to generate secret keys for clients.
 - ③ Clients use this secret key to establish the shared secret key.
- ④ Clients can now create **pseudonyms** or fake identities
 $id \rightarrow (\mathcal{H}(id))^r, \mathcal{H} : \mathcal{ID} \rightarrow \mathcal{G}, r \in \mathbb{Z}_q.$

³Kate, Zaverucha, and Goldberg, "Pairing-Based Onion Routing".

Attributes, Credentials, Anonymous Credentials

- 1 **Attributes:** Labels associated with a user that describe them fully, such as role of a user.

⁴Jan Camenisch et al. *Zone Encryption with Anonymous Authentication for V2V Communication*. 2020. URL: <https://eprint.iacr.org/2020/043> (visited on 02/04/2024). preprint.

Attributes, Credentials, Anonymous Credentials

- ① **Attributes:** Labels associated with a user that describe them fully, such as role of a user.
- ② **Credential:** Data possessed by a user that demonstrates their attributes.

⁴Camenisch et al., *Zone Encryption with Anonymous Authentication for V2V Communication*.

Attributes, Credentials, Anonymous Credentials

- ① **Attributes:** Labels associated with a user that describe them fully, such as role of a user.
- ② **Credential:** Data possessed by a user that demonstrates their attributes.
- ③ **Anonymous Credential:** Data possessed by a user that demonstrates their attributes, *without revealing any additional information* about their identity.

⁴Camenisch et al., *Zone Encryption with Anonymous Authentication for V2V Communication*.

Attributes, Credentials, Anonymous Credentials

- ① **Attributes:** Labels associated with a user that describe them fully, such as role of a user.
- ② **Credential:** Data possessed by a user that demonstrates their attributes.
- ③ **Anonymous Credential:** Data possessed by a user that demonstrates their attributes, *without revealing any additional information* about their identity.
- ④ For V2X
 - Anonymous credentials issued to vehicles regularly.
 - We use DGSA (Digital Group Signatures with Attributes)⁴, which gives us a **randomizable** group element as the credential $\sigma \rightarrow \sigma^r, r \in \mathbb{Z}_q$.

⁴Camenisch et al., *Zone Encryption with Anonymous Authentication for V2V Communication*.

Proposed Message Flow Diagram




Figure 2: Message flow of the proposed scheme.

Proposed Message Flow

- ① Enrollment authority issues certificate to vehicle.
 - Certificate is a long-term credential that can be used to revoke the holder in case of misbehaviour.

Proposed Message Flow

- ① Enrollment authority issues certificate to vehicle.
 - Certificate is a long-term credential that can be used to revoke the holder in case of misbehaviour.
- ② Issuer issues DGSA credentials and secret key after verifying certificate.
 - This secret key is different from secret key associated with certificate.
 - DGSA credentials guarantee authenticity.
 - Anonymous key agreement ensures that user identities remain anonymous throughout communication.
 - This is done periodically every *epoch*.

Proposed Message Flow

- ① Enrollment authority issues certificate to vehicle.
 - Certificate is a long-term credential that can be used to revoke the holder in case of misbehaviour.
- ② Issuer issues DGSA credentials and secret key after verifying certificate.
 - This secret key is different from secret key associated with certificate.
 - DGSA credentials guarantee authenticity.
 - Anonymous key agreement ensures that user identities remain anonymous throughout communication.
 - This is done periodically every *epoch*.
- ③ Vehicles exchange DGSA-signed randomized pseudonyms to generate shared key for further communication.
 - Used in verifying legitimacy of the other party.

Analysis

① Advantages

- Fully anonymous communication, unlimited privacy between communicating parties.
- Third parties cannot identify who is communicating.
- Useful for sending extremely sensitive data.
- Malicious vehicles can be revoked.

Analysis

① Advantages

- Fully anonymous communication, unlimited privacy between communicating parties.
- Third parties cannot identify who is communicating.
- Useful for sending extremely sensitive data.
- Malicious vehicles can be revoked.

② Disadvantages

- Lots of pairing computations, for DGSA and for anonymous key agreement. Incurs computational overheads.
- Works for single-hop connections only.
- May not be scalable to communicating with many vehicles simultaneously in terms of storage overhead.

Future Work

- 1 Encrypt V2X messages like CAMs.

Future Work

- ① Encrypt V2X messages like CAMs.
- ② Improve efficiency of the present work.
 - Use one of DGSA or anonymous key agreement, but not both?

Future Work

- ① Encrypt V2X messages like CAMs.
- ② Improve efficiency of the present work.
 - Use one of DGSA or anonymous key agreement, but not both?
- ③ A new workflow for encryption using zones and zone managers.