Simple Weather Station Using ESP32

Gautam Singh

April 20, 2023

Outline

Aim

Use machine learning to build a simple weather station with a web interface using a PT-100 and ESP32.

Hardware

1. ESP32 microcontroller with Type-B USB cable
2. PT-100 RTD
3. Breadboard and Jumper Wires
4. Android phone
5. (Optional) USB 2.0/3.0 Hub

Software

Relevant platformio codes can be found here.

1. In this directory, type `pio run` to generate the firmware to flash to the ESP32.
2. Using ArduinoDroid, flash it to the ESP32 from your Android phone.
3. Run the server by typing `flask run --host=<YOUR HOST IP>`.

A more detailed manual is present here.

Setup for Experiment



Figure: Setup for Weather Station.

Underlying Principles

1. The PT-100 is a resistance temperature detector (RTD),

Underlying Principles

1. The PT-100 is a resistance temperature detector (RTD),
2. It is governed by the Callendar van Dusen Equation

$$V(T) = V(0)\left(1 + AT + BT^2\right) \tag{1}$$

$$= V(0)\begin{pmatrix}1 & A & B\end{pmatrix}\begin{pmatrix}1\\ T\\ T^2\end{pmatrix} \tag{2}$$

Underlying Principles

1. The PT-100 is a resistance temperature detector (RTD),
2. It is governed by the Callendar van Dusen Equation

$$V(T) = V(0)\left(1 + AT + BT^2\right) \tag{1}$$

$$= V(0)\begin{pmatrix}1 & A & B\end{pmatrix}\begin{pmatrix}1\\ T\\ T^2\end{pmatrix} \tag{2}$$

3. We can use the least squares method to find the coefficients.

In-Class Demonstration

Thank You!