Simple Weather Station Using ESP32

Gautam Singh

April 27, 2023

Outline

Aim

Use machine learning to build a simple weather station with a web interface using a PT-100 and ESP32.

Hardware

1. ESP32 microcontroller with Type-B USB cable
2. PT-100 RTD (Resistance Temperature Detector)
3. Breadboard and Jumper Wires
4. Digital LCD Display (JHD 162A)
5. Android phone
6. (Optional) USB 2.0/3.0 Hub

Software

Relevant codes can be found here.

1. In the `client` directory, type `pio run` to generate the firmware to flash to the ESP32.

2. Using ArduinoDroid, flash it to the ESP32 from your Android phone.

3. Run the server by typing `flask run --host=<YOUR HOST IP>` in the `server` directory.

Circuit Diagram

Figure: Setup for Weather Station.

Choice of Pull-up Resistance

Circuit is a pull-up resistor and PT-100 resistance in series across voltage supply V_0. Suppose we want V_T at temperature T across the PT-100 resistor $P_T = P_0 \left(1 + \alpha T \right)$. Then, using voltage division,

$$V_T = \frac{P_T V_0}{P_T + R} \tag{1}$$

$$\implies R \approx P_T \left(\frac{V_0}{V_T} - 1 \right) \tag{2}$$

For this experiment, the pull-up resistance $R = 100\Omega$.

Underlying Principles

1. The PT-100 is a resistance temperature detector (RTD),
2. It is governed by the Callendar van Dusen Equation

$$V(T) = V(0)\left(1 + AT + BT^2\right) \tag{3}$$

$$= V(0)\begin{pmatrix} 1 & A & B \end{pmatrix}\begin{pmatrix} 1 \\ T \\ T^2 \end{pmatrix} \tag{4}$$

$$= \mathbf{w}^\top \mathbf{x} \tag{5}$$

3. We can use the least mean squares method to find the coefficients.
4. The calculated coefficients are

$$\mathbf{w}^* = \begin{pmatrix} 1.568 \\ 2.894 \times 10^{-3} \\ -3.975 \times 10^{-6} \end{pmatrix} \tag{6}$$

In-Class Demonstration

Thank You!