

Lecture Notes on Numerical Weather Prediction

Harshit Prashant Dhanwalkar (SC21B164)^{1*}

Abstract

Notes of Lectures and additional information from books.

¹ *MTech, Earth System Sciences (ESS), 1st year, Department of Physics, Indian Institute Of Space Science and Technology (IIST)*

***email:** harshitpd1729@gamil.com

Contents

1	Lecture 1 06/01/2025	4
1.1	Introduction to Numerical Weather Prediction . .	4
2	Lecture 2 07/01/2025	5
3	Lecture 3 08/01/2025	6
3.1	Navier-Stokes Equation	6
4	Lecture 4 15/01/2025	8
4.1	Forward Difference	8
4.2	Backward Difference	8
4.3	Current Difference	8
5	Lecture 5 20/01/2025	10
5.1	Space Difference	10
5.2	Time Difference	10
5.3	Explicit Form Of Second Order PDE	10
5.4	Implicit Form Of Second Order PDE	10
6	Lecture 6 21/01/2025	12
6.1	1-D Linear Advection Equation	12
6.2	Triangular Property	12
7	Lecture 7 22/01/2025	13
8	Lecture 8 08/01/2025	14
8.1	Heat Equation	14
8.2	1-D Wave Equation	14
8.3	Laplace Equation	14
9	Lecture 9 28/01/2025	16
9.1	Wave Equation	16
9.2	Heat Transfer Equation	16
10	Lecture 10 29/01/2025	18
10.1	Lax Theorem	18
10.2	Van Neumann	18
11	Lecture 11 03/02/2025	19
11.1	Van Neumann Stability Analysis For 1-D Heat Con- ducting Equation For FTCS Scheme	19
12	Lecture 12 04/02/2025	20
12.1	BTCS Scheme	20
12.2	CTCS Scheme / Richardson Scheme	20
13	Lecture 13 06/02/2025	21
13.1	Crank Nicholson Scheme	21
13.2	Dufart Frankel Scheme	21
14	Lecture 14 10/02/2025	23
14.1	2-D Heat Conduction Equation	23
14.2	ADI Method	23
15	Lecture 15 11/02/2025	24
15.1	1-D Advection Equation	24
15.2	Method of separation of variables	24

16	Lecture 16 12/02/2025	25
16.1	1-D Advection Equation	25
17	Lecture 17 17/02/2025	26
17.1	1-D Advection Equation	26
18	Lecture 18 17/02/2025	27
18.1	1-D Advection Equation	27
18.2	Upwind/Upstream Scheme	27
19	Lecture 19 17/02/2025	28
19.1	1-D Advection Equation	28
19.2	Transportative Properties	28
20	Lecture 20 24/02/2025	30
20.1	Lax Wandroff Scheme	30
	References	31

List of Figures

1	Figure showing the grid	5
2	Path line or trajectory of fluid element	12
3	Triangular property distribution	12

1. Lecture 1 06/01/2025

1.1 Introduction to Numerical Weather Prediction

Numerical Weathering Problem (NWP) was first proposed by Bjerkvies around 1900. It is mathematical initial value problem (IVP).

Initial value Problem (IVP) → simple pendulum.

$$\ddot{\theta} + \omega^2 \theta = 0 \quad (1.1)$$

$$\frac{d^2 \theta}{dt^2} + \omega^2 \theta = 0 \quad (1.2)$$

$$\theta(t) = A \cos(\omega t) + B \sin(\omega t) \quad (1.3)$$

Eq.(1.1) and Eq.(1.2) are second order linear ordinary differential equation, whose solution. Eq.(1.3) has 2 constants of integration A and B . Here θ and t are the dependent and independent variable since Eq.(1.1) and Eq.(1.2) have only one independent variable.

Values of A and B will depend on initial condition.

Since ODE is second order, 2 initial condition are needed at initial time, say $t = 0$. Which are:

$$\left. \begin{array}{l} \theta(t=0) = 1 \\ \frac{\theta(t=0)}{dt} = 0 \end{array} \right\} \quad (1.4)$$

Eq.(1.2) and initial conditions Eq.(1.4) are together called **Mathematical IVP**. For any physical system the following two requirements are needed:

1. The equation (ODE or PDE) that governs the evolution of the above system.
2. The initial state of the system.

7 independent variables ($\mathbf{u}, \mathbf{v}, \mathbf{w}, \mathbf{T}, \rho, \mathbf{p}, \mathbf{q}$).

Surface area of Earth = $4\pi R^2 = 4\pi(6.37 \times 10^{12}) \approx 5.1 \times 10^{14} \text{ m}^2$

2. Lecture 2 07/01/2025

7 independent variables (u, v, w, T, ρ, p, q) therefore we need 7 Governing equations (system of 7 coupled non-linear partial differential equations):

1. Conservation of mass (continuity equation).
2. Conservation of momentum in rotating frame of reference (3 scalar equations, one each corresponding to scalar component of velocity).
3. Conservation of energy (Thermodynamic energy equation).
4. Conservation of moisture (moisture continuity equation).
5. Equation of state (Ideal gas equation).

Euler description of fluid motion is more convenient because of dependence on time and above 7 equations.

Total advective and convective time of lagrangian is given by:

$$\underbrace{\frac{DT}{Dt}}_{\text{Lagrangian Derivative}} = \underbrace{\frac{\partial T}{\partial t}}_{\text{Local derivative}} + \underbrace{\vec{V} \cdot \nabla T}_{\text{Advective Term}} \quad (2.1)$$

$$\frac{DT}{Dt} = \frac{\partial T}{\partial t} + u \frac{\partial T}{\partial x} + v \frac{\partial T}{\partial y} + w \frac{\partial T}{\partial z} \quad (2.2)$$

Using first law of Thermodynamics, Rate of heat is given by:

$$\begin{aligned} d\dot{q} &= d\dot{u} + d\dot{w} \\ \frac{DU}{Dt} &= \frac{Dq}{Dt} - \frac{Dw}{Dt} \\ C_v \frac{DT}{Dt} &= \frac{Dq}{Dt} - p \frac{D\alpha}{Dt} \end{aligned}$$

where $\frac{Dq}{Dt}$ is rate at which heating of air parcel due to non-adiabatic process, this change can happen via radiation, convection, conduction, latent heat while phase change.

$$\frac{DU}{Dt} = \vec{F}_{\text{net}} + \vec{F}_{\text{coriolis}} \quad (2.3)$$

This above Eq.(2.3) is convective derivative equation involving non-linear terms (i.e. $u \frac{\partial U}{\partial x}, v \frac{\partial U}{\partial y}, w \frac{\partial U}{\partial z}$).

Continuity equation:

$$\frac{1}{\rho} \frac{D\rho}{Dt} + \nabla \cdot \vec{V} = 0 \quad (2.4)$$

Consider grid on globe as shown in figure(1).

Let grid of following resolutions:

- $1^\circ \times 1^\circ \rightarrow 3 \times 10^6$ grid cells $\therefore$ no. of variables $\rightarrow 7 \times 3 \times 10^6$.
- $5^\circ \times 5^\circ \rightarrow 1.3 \times 10^5$ grid cells $\therefore$ no. of variables $\rightarrow 7 \times 1.3 \times 10^5$.
- $20^\circ \times 20^\circ \rightarrow 9 \times 10^3$ grid cells $\therefore$ no. of variables $\rightarrow 7 \times 9 \times 10^3$.

- $25^\circ \times 25^\circ \rightarrow 6 \times 10^3$ grid cells $\therefore$ no. of variables $\rightarrow 7 \times 6 \times 10^3$.

These are even larger than entire country, which means that we can't hope to find the change of variables with these grids. This we don't have a way to determine initial condition, if we try to use interpolation, it will cause errors which will grow with time since atmosphere is chaotic and dynamic system.




Figure 1. Figure showing the grid

3. Lecture 3 08/01/2025

$$u = \bar{u} + u' \quad (3.1)$$

Here, u is the velocity field, which is decomposed into a mean component $\bar{u}$ and a fluctuating component u' .

3.1 Navier-Stokes Equation

The general Navier-Stokes equation is given by:

$$\left. \begin{aligned} \frac{\partial u}{\partial t} + u \frac{\partial u}{\partial x} + v \frac{\partial u}{\partial y} + w \frac{\partial u}{\partial z} - f v &= \frac{1}{\rho} \frac{\partial \bar{P}}{\partial x} \\ &+ \gamma \left(\frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} + \frac{\partial^2 u}{\partial z^2} \right) \end{aligned} \right\} \quad (3.2)$$

Reynolds-Averaged Navier-Stokes (RANS) Equation

Applying Reynolds decomposition ($u = \bar{u} + u'$) and averaging leads to the RANS equation:

$$\begin{aligned} \underbrace{\frac{\partial \bar{u}}{\partial t}}_{\text{Local acceleration}} + \underbrace{\bar{u} \frac{\partial \bar{u}}{\partial x} + \bar{v} \frac{\partial \bar{u}}{\partial y} + \bar{w} \frac{\partial \bar{u}}{\partial z}}_{\text{Advection}} - \underbrace{f \bar{v}}_{\text{Coriolis force}} &= \underbrace{\frac{1}{\rho} \frac{\partial \bar{P}}{\partial x}}_{\text{Pressure gradient force}} \\ &+ \underbrace{\gamma \left(\frac{\partial^2 \bar{u}}{\partial x^2} + \frac{\partial^2 \bar{u}}{\partial y^2} + \frac{\partial^2 \bar{u}}{\partial z^2} \right)}_{\text{Viscous dissipation}} \\ &+ \underbrace{\frac{1}{\rho} \left(\frac{\partial (-\rho \overline{u'u'})}{\partial x} + \frac{\partial (-\rho \overline{u'v'})}{\partial y} + \frac{\partial (-\rho \overline{u'w'})}{\partial z} \right)}_{\text{Reynolds stress tensor}} \end{aligned} \quad (3.3)$$

The Reynolds stress tensor represents the transport of momentum due to turbulent fluctuations.

Nonlinear Term Expansion

Expanding the nonlinear term $u \frac{\partial u}{\partial x}$ using Reynolds decomposition:

$$\begin{aligned} u \frac{\partial u}{\partial x} &= (\bar{u} + u') \frac{\partial (\bar{u} + u')}{\partial x} \\ &= \bar{u} \frac{\partial \bar{u}}{\partial x} + u' \frac{\partial \bar{u}}{\partial x} + \bar{u} \frac{\partial u'}{\partial x} + u' \frac{\partial u'}{\partial x}. \end{aligned}$$

Applying Reynolds averaging rules:

$$\begin{aligned} \bar{u} &= \overline{\bar{u} + u'} \\ \bar{u} &= \bar{\bar{u}} + \bar{u'} \\ \bar{u} &= \bar{u} + \bar{u'} \Rightarrow \bar{u'} = 0. \end{aligned}$$

Thus, the fluctuating component u' averages out to zero over time, leaving only the mean component $\bar{u}$ in the averaged equations.

We have,

$$\frac{\partial \bar{u}}{\partial x} + \frac{\partial \bar{v}}{\partial y} + \frac{\partial \bar{w}}{\partial z} = 0 \quad (3.4)$$

Substituting u, v and w in above Eq.(3.4), we get:

$$\begin{aligned} \frac{\partial (\bar{u} + u')}{\partial x} + \frac{\partial (\bar{v} + v')}{\partial y} + \frac{\partial (\bar{w} + w')}{\partial z} &= 0 \\ \frac{\partial \bar{u}}{\partial x} + \frac{\partial \bar{v}}{\partial y} + \frac{\partial \bar{w}}{\partial z} &= 0 \end{aligned} \quad (3.5)$$

The term $\frac{\partial (\overline{u'u'})}{\partial t}$ represents the rate of change of kinetic energy per unit mass due to turbulent fluctuations. It can be expressed as:

$$\frac{\partial (\overline{u'u'})}{\partial t} = \frac{\partial (\rho \overline{u'v'})}{\partial y} + \dots$$

This term involves higher-order correlations between velocity fluctuations, which complicates the equation system.

The closure problem arises in the Reynolds-Averaged Navier-Stokes (RANS) equations because the number of dependent variables (unknowns) exceeds the number of equations available. For instance:

- $\bar{u}$ is an unknown.
- $\overline{u'v'}$ (a Reynolds stress term) introduces additional unknowns.

To resolve this, closure models are used, which provide approximations for higher-order terms based on known variables.

For example, consider the term $\overline{u'w'}$. Using a simple closure model:

$$\overline{u'w'} = -k \frac{\partial \bar{u}}{\partial x}$$

where k is a proportionality constant (often related to eddy viscosity). Here, $\bar{u}$ is already an unknown, so no additional variables are introduced, avoiding further complexity.

This is an example of first-order closure where higher-order terms are approximated using first-order variables.

Types of Closure Models

1. First-Order Closure:

- Simplifies higher-order terms using known variables and gradients (e.g., eddy viscosity models).
- Example: $\overline{u'w'} = -k \frac{\partial \bar{u}}{\partial x}$.
- Advantage: Computationally efficient but may lack accuracy in complex flows.

2. One-Point Closure:

- Approximates turbulence at a single point using local flow properties.
- Example: Mixing length models, where turbulent viscosity is proportional to local shear.

3. Second-Order Closure:

- Directly models second-order correlations like $\overline{u'u'}$ and $\overline{u'v'}$ by solving additional transport equations.
- Provides higher accuracy but increases computational cost.

- Example: Reynolds stress models (RSM), where additional equations are solved for Reynolds stresses.

4. Lecture 4 15/01/2025

$$\frac{d^2\theta}{dt^2} + \omega^2\theta = 0 \quad (4.1)$$

Initial conditions:

$$\theta(t = t_0) = \theta_0$$

$$\dot{\theta}(t = t_0) = \omega_0$$

We can rewrite this equation into two 1st-order ODEs,

Let $\frac{\theta}{dt} = p$, then

$$\frac{dp}{dt} + \omega^2\theta = 0 \quad (4.i)$$

$$\frac{d\theta}{dt} = p \quad (4.ii)$$

Initial conditions become:

$$\theta(t = t_0) = \theta_0$$

$$p(t = t_0) = \omega_0$$

4.1 Forward Difference

Invoking Taylor series expansion for $f(t + t_0)$:

$$\left. \begin{aligned} f(t + t_0) &= f(t_0) + (t + t_0) \frac{\partial f}{\partial t} \Big|_{t=t_0} \\ &\quad + \frac{(t+t_0)^2}{2!} \frac{\partial^2 f}{\partial t^2} \Big|_{t=t_0} + \dots \\ f(t + \Delta t) &= f(t_0) + \Delta t \frac{\partial f}{\partial t} \Big|_{t=t_0} \\ &\quad + \frac{(\Delta t)^2}{2!} \frac{\partial^2 f}{\partial t^2} \Big|_{t=t_0} + \dots \end{aligned} \right\} \quad (4.2)$$

we will get;

$$\begin{aligned} p(t + t_0) &\approx p(t_0) + \Delta t \frac{\partial p}{\partial t} \Big|_{t=t_0} \\ p(t + t_0) &\approx p(t_0) + (t - t_0) \frac{\partial p}{\partial t} \Big|_{t=t_0} \\ \frac{\partial p}{\partial t} \Big|_{t=t_0} &\approx \frac{p(t + t_0) - p(t_0)}{(t - t_0)} \\ \frac{\partial p}{\partial t} \Big|_{t=t_0} &\approx \frac{p(t_1) - p(t_0)}{\Delta t} \end{aligned} \quad (4.3)$$

Eq.(4.3) is called **Forward difference**.

Order of Forward difference is $O(\Delta t)$.

Similarly Forward difference for θ ,

$$\begin{aligned} \frac{\partial \theta}{\partial t} \Big|_{t=t_0} &\approx \frac{\theta(t + t_0) - \theta(t_0)}{(t - t_0)} \\ \frac{\partial \theta}{\partial t} \Big|_{t=t_0} &\approx \frac{\theta(t_1) - \theta(t_0)}{\Delta t} \end{aligned} \quad (4.4)$$

From Eq.(4.i) and Eq.(4.3):

$$\begin{aligned} \frac{p(t + t_0) - p(t_0)}{(t - t_0)} + \omega^2\theta(t_0) &= 0 \\ p(t + t_0) &= p(t_0) - (t - t_0)\omega^2\theta(t_0) \\ p(t_1) &= p(t_0) - \Delta t\omega^2\theta(t_0) \end{aligned} \quad (4.5)$$

From Eq.(4.ii) and Eq.(4.4):

$$\begin{aligned} \frac{\theta(t + t_0) - \theta(t_0)}{(t - t_0)} &= p(t_0) \\ \theta(t + t_0) &= \theta(t_0) - (t - t_0)p(t_0) \\ \theta(t_1) &= \theta(t_0) - \Delta t p(t_0) \end{aligned} \quad (4.6)$$

4.2 Backward Difference

Invoking Taylor series expansion for $f(t - t_0)$:

$$\left. \begin{aligned} f(t - t_0) &= f(t_0) - (t - t_0) \frac{\partial f}{\partial t} \Big|_{t=t_0} \\ &\quad + \frac{(t-t_0)^2}{2!} \frac{\partial^2 f}{\partial t^2} \Big|_{t=t_0} + \dots \\ f(t - \Delta t) &= f(t_0) - \Delta t \frac{\partial f}{\partial t} \Big|_{t=t_0} \\ &\quad + \frac{(\Delta t)^2}{2!} \frac{\partial^2 f}{\partial t^2} \Big|_{t=t_0} + \dots \end{aligned} \right\} \quad (4.7)$$

we will get;

$$\begin{aligned} p(t - t_0) &\approx p(t_0) - \Delta t \frac{\partial p}{\partial t} \Big|_{t=t_0} \\ p(t - t_0) &\approx p(t_0) - (t - t_0) \frac{\partial p}{\partial t} \Big|_{t=t_0} \\ \frac{\partial p}{\partial t} \Big|_{t=t_0} &\approx \frac{p(t_0) - p(t - t_0)}{(t - t_0)} \\ \frac{\partial p}{\partial t} \Big|_{t=t_0} &\approx \frac{p(t_0) - p(t_{-1})}{\Delta t} \end{aligned} \quad (4.8)$$

Eq.(4.8) is called **Backward difference**.

Order of Backward difference is $O(\Delta t)$.

Similarly Backward difference for θ ,

$$\begin{aligned} \frac{\partial \theta}{\partial t} \Big|_{t=t_0} &\approx \frac{\theta(t_0) - \theta(t - t_0)}{(t - t_0)} \\ \frac{\partial \theta}{\partial t} \Big|_{t=t_0} &\approx \frac{\theta(t_0) - \theta(t_{-1})}{\Delta t} \end{aligned} \quad (4.9)$$

From Eq.(4.i) and Eq.(4.8):

$$\begin{aligned} \frac{p(t + t_0) - p(t_0)}{(t - t_0)} + \omega^2\theta(t_0) &= 0 \\ p(t + t_0) &= p(t_0) - (t - t_0)\omega^2\theta(t_0) \\ p(t_1) &= p(t_0) - \Delta t\omega^2\theta(t_0) \end{aligned} \quad (4.10)$$

From Eq.(4.ii) and Eq.(4.9):

$$\begin{aligned} \frac{\theta(t + t_0) - \theta(t_0)}{(t - t_0)} &= p(t_0) \\ \theta(t + t_0) &= \theta(t_0) - (t - t_0)p(t_0) \\ \theta(t_1) &= \theta(t_0) - \Delta t p(t_0) \end{aligned} \quad (4.11)$$

4.3 Current Difference

The current difference method is a combination of the forward and backward difference methods, where we approximate the

values at the current time using both the forward and backward information.

Using forward difference:

$$\left. \frac{d\theta}{dt} \right|_{t=t_0} = p(t_0) = \text{known} = p(t_0) - \Delta t \omega^2 \theta(t_0) \quad (4.12)$$

Using backward difference:

$$\left. \frac{d\theta}{dt} \right|_{t=t_0} = \frac{\theta(t_1) - \theta(t - \Delta t)}{\Delta t} \quad (4.13)$$

From Eq.(4.12) and Eq.(4.13), we can combine both the equations to get:

$$\begin{aligned} \frac{\theta(t_1) - \theta(t - \Delta t)}{\Delta t} &= p(t_0) - \Delta t \omega^2 \theta(t_0) \\ \theta(t_1) &= \theta(t - \Delta t) + \Delta t [p(t_0) - \Delta t \omega^2 \theta(t_0)] \end{aligned} \quad (4.14)$$

In Eq.(4.14) all the terms on the RHS are known, allowing us to compute the value of θ at time (t_1) .

Thus, we obtain a method to compute the new value of θ based on the current and past time steps.

5. Lecture 5 20/01/2025

$$\left. \begin{aligned} f(x+\Delta x) &= f(x) + \Delta x \left. \frac{\partial f}{\partial x} \right|_{x=x_0} \\ &\quad + \frac{(\Delta x)^2}{2!} \left. \frac{\partial^2 f}{\partial x^2} \right|_{x=x_0} \\ &\quad + \frac{(\Delta x)^3}{3!} \left. \frac{\partial^3 f}{\partial x^3} \right|_{x=x_0} + \dots \end{aligned} \right\} \quad (5.1)$$

$$\left. \begin{aligned} f(x-\Delta x) &= f(x) - \Delta x \left. \frac{\partial f}{\partial x} \right|_{x=x_0} \\ &\quad + \frac{(\Delta x)^2}{2!} \left. \frac{\partial^2 f}{\partial x^2} \right|_{x=x_0} \\ &\quad - \frac{(\Delta x)^3}{3!} \left. \frac{\partial^3 f}{\partial x^3} \right|_{x=x_0} + \dots \end{aligned} \right\} \quad (5.2)$$

Using Eq.(5.1),

$$\left. \frac{df}{dx} \right|_{x=x_0} \simeq \left[\frac{f(x+\Delta x) - f(x)}{\Delta x} \right] + O(\Delta x) \quad (5.3)$$

Similarly, using Eq.(5.2), one obtain,

$$\left. \frac{df}{dx} \right|_{x=x_0} \simeq \left[\frac{f(x) - f(x-\Delta x)}{\Delta x} \right] + O(\Delta x) \quad (5.4)$$

Subtracting Eq.(5.2) from Eq.(5.1), we get,

$$\left. \frac{df}{dx} \right|_{x=x_0} \simeq \left[\frac{f(x+\Delta x) - f(x-\Delta x)}{2\Delta x} \right] + O(\Delta x^2) \quad (5.5)$$

Adding Eq.(5.1) and Eq.(5.2), we get,

$$\left. \frac{d^2 f}{dx^2} \right|_{x=x_0} \simeq \left[\frac{f(x+\Delta x) - 2f(x) + f(x-\Delta x)}{(\Delta x)^2} \right] + O(\Delta x^2) \quad (5.6)$$

$$\left. \begin{aligned} f(x+\Delta x, t) &= f(x, t) + \Delta x \left. \frac{\partial f(x, t)}{\partial x} \right|_{x=x_0} \\ &\quad + \frac{(\Delta x)^2}{2!} \left. \frac{\partial^2 f(x, t)}{\partial x^2} \right|_{x=x_0} \\ &\quad + \frac{(\Delta x)^3}{3!} \left. \frac{\partial^3 f(x, t)}{\partial x^3} \right|_{x=x_0} + \dots \end{aligned} \right\} \quad (5.7)$$

$$\left. \begin{aligned} f(x-\Delta x, t) &= f(x, t) - \Delta x \left. \frac{\partial f(x, t)}{\partial x} \right|_{x=x_0} \\ &\quad + \frac{(\Delta x)^2}{2!} \left. \frac{\partial^2 f(x, t)}{\partial x^2} \right|_{x=x_0} \\ &\quad - \frac{(\Delta x)^3}{3!} \left. \frac{\partial^3 f(x, t)}{\partial x^3} \right|_{x=x_0} + \dots \end{aligned} \right\} \quad (5.8)$$

5.1 Space Difference

From Eq.(5.7) and Eq.(5.8) respectively by difference equation w.r.t 1-direction, say x, we obtain **Space difference**:

$$\left. \frac{df}{dx} \right|_{x=x_0} \simeq \left[\frac{f(x+\Delta x, t) - f(x, t)}{\Delta x} \right] + O(\Delta x) \quad (5.9)$$

Subtracting Eq.(5.8) from Eq.(5.7), we get,

$$\left. \frac{df}{dx} \right|_{x=x_0} \simeq \left[\frac{f(x+\Delta x, t) - f(x-\Delta x, t)}{2\Delta x} \right] + O(\Delta x^2) \quad (5.12)$$

Adding Eq.(5.7) and Eq.(5.8), we get,

$$\left. \frac{d^2 f}{dx^2} \right|_{x=x_0} \simeq \left[\frac{f(x+\Delta x, t) - 2f(x, t) + f(x-\Delta x, t)}{(\Delta x)^2} \right] + O(\Delta x^2) \quad (5.13)$$

5.2 Time Difference

Similarly, From Eq.(5.7) and Eq.(5.8) respectively, difference equation w.r.t time (t), we obtain **Time difference**:

$$\left. \frac{df}{dt} \right|_{t=t_0} \simeq \left[\frac{f(x, t+\Delta t) - f(x, t)}{\Delta t} \right] + O(\Delta t) \quad (5.14)$$

$$\left. \frac{df}{dt} \right|_{t=t_0} \simeq \left[\frac{f(x, t+\Delta t) + f(x, t-\Delta t)}{2\Delta t} \right] + O(\Delta t^2) \quad (5.15)$$

$$\left. \frac{d^2 f}{dt^2} \right|_{t=t_0} \simeq \left[\frac{f(x, t+\Delta t) - 2f(x, t) + f(x, t-\Delta t)}{(\Delta t)^2} \right] + O(\Delta t^2) \quad (5.16)$$

5.3 Explicit Form Of Second Order PDE

$$A \frac{\partial^2 f}{\partial x^2} + B \frac{\partial^2 f}{\partial x \partial y} + C \frac{\partial^2 f}{\partial y^2} + D \frac{\partial f}{\partial x} + E \frac{\partial f}{\partial y} + F f = G \quad (5.17)$$

Cases:

1. If A, B, C, D, E, F and G are either constant or function of x and y, Eq.(5.17) is called **Linear PDE**.
2. If A, B and C are function of x, y and f, Eq.(5.17) is called **Quasi-linear PDE**.
3. If A, B and C are function of x and y only, Eq.(5.17) is called **Semi-linear PDE**.

Example: Momentum equation, which is,

$$\frac{\partial u}{\partial t} + u \frac{\partial u}{\partial x} + v \frac{\partial u}{\partial y} + w \frac{\partial u}{\partial z} - f v = -\frac{1}{\rho} \frac{\partial P}{\partial x}$$

is a quasi-linear PDE.

5.4 Implicit Form Of Second Order PDE

$$G\left(f, \frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial^2 f}{\partial x^2}, \frac{\partial^2 f}{\partial y^2}, \frac{\partial^2 f}{\partial x \partial y}\right) = 0 \quad (5.18)$$

Eq.(5.18) is Implicit form of PDE. Example: Continuity equation in 1-D, which is,

$$\frac{\partial \rho}{\partial t} + \frac{\partial}{\partial x}(\rho u) = 0$$

1-D linear advection equation:

$$\frac{\partial \rho}{\partial t} + u \frac{\partial \rho}{\partial x} = 0$$

in Euler description.

$$\frac{D\rho}{Dt} = 0$$

in Lagrangian description, represents change in density (ρ) following the motion.

6. Lecture 6 21/01/2025

6.1 1-D Linear Advection Equation

$$\frac{\partial f}{\partial t} + u \frac{\partial f}{\partial x} = 0 \quad (6.1)$$

where

f is fluid property

u is x-component of fluid velocity




Figure 2. Path line or trajectory of fluid element

$$\frac{dx}{dt} = u = \text{constant} \quad (6.2)$$

Eq.(6.2) is called **Characteristic equation**.

Integrating Eq.(6.2) w.r.t time, we get:

$$x = x_0 + \int_{t_0}^t u dt \quad (6.3)$$

Eq.(6.3) is called equation of pathline as shown in Fig2.

Substituting, $u = \frac{dx}{dt}$ in Eq.(6.1), we obtain:

$$\frac{\partial f}{\partial t} + \frac{dx}{dt} \frac{\partial f}{\partial x} = 0 \quad (6.4)$$

$$\frac{Df}{Dt} = 0 \quad (6.5)$$

Eq.(6.5) implies the property f is conserved following the motion of fluid element.

6.2 Triangular Property

1. **Hyperbolic:** 1st order partial equation → 1 family of characteristic equation in real domain.
2. **Hyperbolic:** 2nd order partial equation → 2 distinct and real set of characteristic equations.
3. **Parabolic:** 2nd order partial equation → 2 equal and real set of characteristic equations.
4. **Elliptical:** 2nd order partial equation → 2 distinct and complex set of characteristic equations.




Figure 3. Triangular property distribution

$$\frac{\partial f}{\partial t} + u \frac{\partial f}{\partial x} = 0 \quad \begin{cases} u = \text{constant} & \Rightarrow \text{linear PDE} , \\ u = u(x, t) & \Rightarrow \text{semi-linear PDE} , \\ u = u(x, t, f) & \Rightarrow \text{quasi-linear PDE} \end{cases}$$

$$a(x, t, f) \frac{\partial f}{\partial t} + b(x, t, f) \frac{\partial f}{\partial x} = 0 \quad (6.6)$$

Above Eq.(6.6) is quasi-linear PDE, having characteristic equation in real domain $\Rightarrow \frac{dx}{dt} = \frac{b}{a}$

$$a(x, t, f) \frac{\partial f}{\partial t} + b(x, t, f) \frac{\partial f}{\partial x} = c(x, t, f) \quad (6.7)$$

Above Eq.(6.7) is semi-linear PDE, having characteristic equation in real domain.

7. Lecture 7 22/01/2025

General quasi-linear 2^{nd} order PDE:

$$\frac{\partial^2 f}{\partial x^2} + B \frac{\partial^2 f}{\partial x \partial y} + C \frac{\partial^2 f}{\partial y^2} + D \frac{\partial f}{\partial x} + E \frac{\partial f}{\partial y} + Ff = G \quad (7.1)$$

i.e. A, B, C can be function of $x, y, f, \frac{\partial f}{\partial x}$ and $\frac{\partial f}{\partial y}$.

To find sign of discriminant $B^2 - 4AC$ tells the classification of equation:

$$B^2 - 4AC \begin{cases} > 0, & \text{Hyperbolic PDE} \\ = 0, & \text{Parabolic PDE} \\ < 0, & \text{Elliptical PDE} \end{cases}$$

This is analogous to general equation of conic-section curves. Which is represented by Eq.(7.2)

$$Ay^2 + Bxy + Cx^2 + Dx + Ey + F = 0 \quad (7.2)$$

$$B^2 - 4AC \begin{cases} > 0, & \text{Hyperbola} \\ = 0, & \text{Parabola} \\ < 0, & \text{Ellipse} \end{cases}$$

$$df = \frac{\partial f}{\partial x} dx + \frac{\partial f}{\partial y} dy \quad (7.3)$$

$$d\left(\frac{\partial f}{\partial x}\right) = \frac{\partial^2 f}{\partial x^2} dx + \frac{\partial^2 f}{\partial x \partial y} dy \quad (7.4)$$

$$d\left(\frac{\partial f}{\partial y}\right) = \frac{\partial^2 f}{\partial x \partial y} dx + \frac{\partial^2 f}{\partial y^2} dy \quad (7.5)$$

Unknown in Eq.(7.3), Eq.(7.4) and Eq.(7.5) are 2^{nd} order derivatives.

From Eq.(7.1),

$$A \frac{\partial^2 f}{\partial x^2} + B \frac{\partial^2 f}{\partial x \partial y} + C \frac{\partial^2 f}{\partial y^2} = -D \frac{\partial f}{\partial x} - E \frac{\partial f}{\partial y} - Ff + G \quad (7.6)$$

From Eq.(7.4),

$$\frac{\partial^2 f}{\partial x^2} dx + \frac{\partial^2 f}{\partial x \partial y} dy = d\left(\frac{\partial f}{\partial x}\right) \quad (7.7)$$

From Eq.(7.5),

$$\frac{\partial^2 f}{\partial x \partial y} dx + \frac{\partial^2 f}{\partial y^2} dy = d\left(\frac{\partial f}{\partial y}\right) \quad (7.8)$$

Matrix representation of Eq.(7.6), Eq.(7.7) and Eq.(7.8):

$$\underbrace{\begin{bmatrix} A & B & C \\ dx & dy & 0 \\ 0 & dx & dy \end{bmatrix}}_{\det(\mathbf{A})=0} \begin{bmatrix} \frac{\partial^2 f}{\partial x^2} \\ \frac{\partial^2 f}{\partial x \partial y} \\ \frac{\partial^2 f}{\partial y^2} \end{bmatrix} = \begin{bmatrix} -D \frac{\partial f}{\partial x} - E \frac{\partial f}{\partial y} - Ff + G \\ d\left(\frac{\partial f}{\partial x}\right) \\ d\left(\frac{\partial f}{\partial y}\right) \end{bmatrix}.$$

Determinant of $(\mathbf{A})$ should be equal to zero, i.e.,

$$\begin{aligned} \det(\mathbf{A}) &= 0 \\ A(dy)^2 - B(dxdy) + C(dx)^2 &= 0 \\ A\left(\frac{dy}{dx}\right)^2 - B\left(\frac{dy}{dx}\right) + C &= 0 \end{aligned} \quad (7.9)$$

Solution of above Eq.(7.9) are 2 characteristic equations:

$$\frac{dy}{dx} = \frac{B \pm \sqrt{B^2 - 4AC}}{2A}$$

if $B^2 - 4AC > 0 \Rightarrow 2$ distinct Real roots

Family of char. curve $\in \mathbb{R}$

Hyperbolic PDE

if $B^2 - 4AC = 0 \Rightarrow$ Real and equal roots

1 Family of char. curve $\in \mathbb{R}$


Parabolic PDE

if $B^2 - 4AC < 0 \Rightarrow$ Imaginary roots

Family of char. curves $\in \mathbb{C}$

Elliptic PDE

Examples:



8. Lecture 8 08/01/2025

8.1 Heat Equation

$$k \frac{\partial^2 T}{\partial x^2} - \frac{\partial T}{\partial t} = 0 \quad (8.1)$$

Eq.(8.1) can be decomposed into pair of PDEs:

$$\frac{\partial^2 T}{\partial x \partial t} dx + \frac{\partial^2 T}{\partial t^2} dt = d\left(\frac{\partial T}{\partial t}\right) \quad (8.2)$$

$$\frac{\partial^2 T}{\partial x^2} dx + \frac{\partial^2 T}{\partial x \partial t} dt = d\left(\frac{\partial T}{\partial x}\right) \quad (8.3)$$

Rewriting Eq.(8.1), Eq.(8.2) and Eq.(8.3) into matrix form:

$$\underbrace{\begin{bmatrix} k & 0 & 0 \\ 0 & dx & dt \\ dx & dt & 0 \end{bmatrix}}_A \begin{bmatrix} \frac{\partial^2 T}{\partial x^2} \\ \frac{\partial^2 T}{\partial x \partial t} \\ \frac{\partial^2 T}{\partial t^2} \end{bmatrix} = \begin{bmatrix} d\left(\frac{\partial T}{\partial t}\right) \\ d\left(\frac{\partial T}{\partial x}\right) \end{bmatrix}$$

$$\det(A) = 0$$

$$k(0 - (dt)^2) - 0(0 - dxdt) + 0(0 - (dx)^2) = 0$$

$$-k(dt)^2 = 0$$

$$\therefore dt = 0$$

$$t = \text{const.}$$

Therefore the equation represents Parabolic PDE (2ⁿ order quasi-linear PDE).

8.2 1-D Wave Equation

$$\frac{\partial^2 f}{\partial t^2} = c^2 \frac{\partial^2 f}{\partial x^2} \quad (8.4)$$

$$\underbrace{\left(\frac{\partial^2}{\partial t^2} - c^2 \frac{\partial^2}{\partial x^2}\right)}_{\text{Operator acting on } f} f = 0$$

$$\left[\left(\frac{\partial}{\partial t} - c \frac{\partial}{\partial x}\right)\left(\frac{\partial}{\partial t} + c \frac{\partial}{\partial x}\right)\right] f = 0 \quad (8.5)$$

Above Eq.(8.5) is pair two 1-D advection equations with constant speed c in **negative** x-direction and **positive** x-direction respectively.

Discriminant of Eq.(8.4), for A = 1, B=0, C=-1:

$$B^2 - 4AC$$


$$0^2 - 4c^2(-1)$$

$$4c^2 > 0$$

Therefore Eq.(8.4) represents Hyperbolic PDE.

$$\frac{\partial^2 f}{\partial x \partial t} dx + \frac{\partial^2 f}{\partial t^2} dt = d\left(\frac{\partial f}{\partial t}\right) \quad (8.6)$$

$$\frac{\partial^2 f}{\partial x^2} dx + \frac{\partial^2 f}{\partial x \partial t} dt = d\left(\frac{\partial f}{\partial x}\right) \quad (8.7)$$



Rewriting Eq.(8.4), Eq.(8.6) and Eq.(8.7) into matrix form:

$$\underbrace{\begin{bmatrix} c^2 & 0 & -1 \\ 0 & dx & dt \\ dx & dt & 0 \end{bmatrix}}_A \begin{bmatrix} \frac{\partial^2 f}{\partial x^2} \\ \frac{\partial^2 f}{\partial x \partial t} \\ \frac{\partial^2 f}{\partial t^2} \end{bmatrix} = \begin{bmatrix} d\left(\frac{\partial f}{\partial t}\right) \\ d\left(\frac{\partial f}{\partial x}\right) \end{bmatrix}$$

$$\det(A) = 0$$

$$c^2(0 - (dt)^2) - 0(0 - dxdt) + (-1)(0 - (dx)^2) = 0$$

$$-c^2(dt)^2 + (dx)^2 = 0$$

$$-c^2\left(\frac{dt}{dx}\right)^2 + 1 = 0$$

$$c^2\left(\frac{dt}{dx}\right)^2 - 1 = 0$$

Slope $\frac{dt}{dx}$ is equal to:

$$\frac{dt}{dx} = \frac{-0 \pm \sqrt{0^2 - 4 \cdot c^2 \cdot (-1)}}{2 \cdot c^2}$$

$$\frac{dt}{dx} = \pm \frac{1}{c}$$

8.3 Laplace Equation

$$\frac{\partial^2 f}{\partial x^2} + \frac{\partial^2 f}{\partial y^2} = 0 \quad (8.8)$$

$$\frac{\partial^2 f}{\partial x \partial y} dx + \frac{\partial^2 f}{\partial y^2} dy = d \left(\frac{\partial f}{\partial y} \right) \quad (8.9)$$

$$\frac{\partial^2 f}{\partial x^2} dx + \frac{\partial^2 f}{\partial x \partial y} dy = d \left(\frac{\partial f}{\partial x} \right) \quad (8.10)$$

Discriminant of Eq.(8.7), for A = 1, B=0, C=1:

$$\begin{aligned} B^2 - 4AC \\ 0^2 - 4(1)(1) \\ -4 < 0 \end{aligned}$$

Therefore Eq.(8.8) represents Elliptical PDE.

Rewriting Eq.(8.8), Eq.(8.9) and Eq.(8.10) into matrix form:

$$\underbrace{\begin{bmatrix} 1 & 0 & 1 \\ 0 & dx & dy \\ dx & dy & 0 \end{bmatrix}}_A \begin{bmatrix} \frac{\partial^2 f}{\partial x^2} \\ \frac{\partial^2 f}{\partial x \partial y} \\ \frac{\partial^2 f}{\partial y^2} \end{bmatrix} = \begin{bmatrix} 0 \\ d \left(\frac{\partial f}{\partial y} \right) \\ d \left(\frac{\partial f}{\partial x} \right) \end{bmatrix}$$

$$\det(A) = 0$$

$$1(0 - (dy)^2) - 0(0 - dx dy) + 1(0 - (dx)^2) = 0$$

$$-(dy)^2 - (dx)^2 = 0$$

$$\left(\frac{dy}{dx} \right)^2 + 1 = 0$$

$$\frac{dy}{dx} = \pm i$$

9. Lecture 9 28/01/2025

- Domain of dependence at a given point in the solution domain would corresponding to the region where solution will impact solution will be impacted by the solution at the above given point.
- Range of independence at a given point in the solution domain would corresponding to the region where solution will impact solution will be impacted by the solution at the above given point.

9.1 Wave Equation

Hyperbolic PDE:


$$\frac{\partial^2 f}{\partial t^2} = c^2 \frac{\partial^2 f}{\partial x^2} \quad (9.1)$$

Parabolic PDE:

$$\frac{\partial f}{\partial t} = c^2 \frac{\partial f}{\partial x} \quad (9.2)$$

Ellipse PDE:

$$\frac{\partial^2 f}{\partial t^2} + \frac{\partial^2 f}{\partial x^2} = 0 \quad (9.3)$$



$$a \frac{\partial f}{\partial x} + b \frac{\partial f}{\partial x} + c \frac{\partial g}{\partial t} + d \frac{\partial g}{\partial x} = e \quad (9.4)$$

$$A \frac{\partial f}{\partial x} + B \frac{\partial f}{\partial x} + C \frac{\partial g}{\partial t} + D \frac{\partial g}{\partial x} = E \quad (9.5)$$

Using chain rule;

$$\frac{\partial f}{\partial t} dt + \frac{\partial f}{\partial x} dx = df \quad (9.6)$$

$$\frac{\partial g}{\partial t} dt + \frac{\partial g}{\partial x} dx = dg \quad (9.7)$$

Rewriting Eq.(9.4), Eq.(9.5), Eq.(9.6) and Eq.(9.7) into matrix form:

$$\underbrace{\begin{bmatrix} a & b & c & d \\ A & B & C & D \\ dt & dx & 0 & 0 \\ 0 & 0 & dt & dx \end{bmatrix}}_A \begin{bmatrix} \frac{\partial f}{\partial t} \\ \frac{\partial f}{\partial x} \\ \frac{\partial g}{\partial t} \\ \frac{\partial g}{\partial x} \end{bmatrix} = \begin{bmatrix} e \\ E \\ df \\ dg \end{bmatrix}$$

$$\det(A) = 0$$

$$\left. \begin{aligned} (dx)^2 \underbrace{(aC - Ac)}_{\bar{A}} - (dx)(dt) \underbrace{(aD - Ad + bC - Bc)}_{\bar{B}} \\ + (dt)^2 \underbrace{(bD - Bd)}_{\bar{C}} = 0 \end{aligned} \right\} \quad (9.8)$$

Discriminant of Eq.(9.8), for $\bar{A} = (aC - Ac)$, $\bar{B} = (aD - Ad + bC - Bc)$, $\bar{C} = (bD - Bd)$:

$$\bar{B}^2 - 4\bar{A}\bar{C} \quad (aD - Ad + bC - Bc)^2 - 4(aC - Ac)(bD - Bd)$$

$$\frac{dx}{dt} = \frac{\bar{B} \pm \sqrt{\bar{B}^2 - 4\bar{A}\bar{C}}}{2\bar{A}} \quad (9.9)$$


Depending upon sign of $\bar{B}^2 - 4\bar{A}\bar{C}$ the following classification can be made:

- Positive $\rightarrow$ Hyperbolic
- Zero $\rightarrow$ Parabolic
- Negative $\rightarrow$ Elliptic

9.2 Heat Transfer Equation

$$\frac{\partial T}{\partial t} = k \frac{\partial^2 T}{\partial x^2} \quad (9.10)$$

where, k is coefficient of thermal expansion.



Applying FTCS (Forward Time and Central in Space) scheme,

$$\begin{aligned} t_n &= n\Delta t & , n = 0, 1, 2, \dots \\ x_m &= x_0 + m\Delta x & , m = 0, 1, 2, \dots, N \end{aligned}$$

Backward difference:

$$\left(\frac{\partial T}{\partial t} \right)_{x,t} = \frac{T_{m,n+1} - T_{m,n}}{\Delta t} \quad (9.11)$$

Central difference:


$$\left(\frac{\partial^2 T}{\partial t^2} \right)_{x,t} = \frac{T_{m+1,n} - 2 \cdot T_{m,n} + T_{m-1,n}}{\Delta t} \quad (9.12)$$

Substituting Eq.(9.11) and Eq.(9.12) into Eq.(9.10), we obtain,

$$\left(\frac{T_{m,n+1}-T_{m,n}}{\Delta t}\right)=k\left(\frac{T_{m+1,n}-2\cdot T_{m,n}+T_{m-1,n}}{\Delta t}\right)$$

$$T_{m,n+1}=T_{m,n}+\underbrace{\frac{k\Delta t}{(\Delta x)^2}}_{\lambda}(T_{m+1,n}-2T_{m,n}+T_{m-1,n})$$

$$T_{m,n+1}=(1-2\lambda)T_{m,n}+\lambda T_{m-1,n}+\lambda T_{m+1,n}$$



10. Lecture 10 29/01/2025

10.1 Lax Theorem

The **Lax Equivalence Theorem** is a fundamental result in numerical analysis that provides a necessary and sufficient condition for the convergence of finite difference schemes used to approximate solutions of partial differential equations (PDEs).

For a well-posed initial value problem, a consistent finite difference scheme is convergent if and only if it is stable.

Key Concepts:

- **Consistency:** A finite difference scheme is said to be *consistent* if the truncation error tends to zero as the grid spacing $(\Delta x, \Delta t)$ approaches zero.
- **Stability:** A scheme is *stable* if numerical errors do not grow uncontrollably as time progresses.
- **Convergence:** A numerical scheme is *convergent* if the solution obtained from the scheme approaches the exact solution as the grid is refined.

Let $u(x, t)$ be the exact solution of a PDE, and let u_j^n be the numerical solution at time level n and spatial index j . The numerical scheme can be written as:

$$u_j^{n+1} = F(u_{j-1}^n, u_j^n, u_{j+1}^n, \dots),$$

where F is the finite difference operator.

For the scheme to be **consistent**, the local truncation error must satisfy:

$$\lim_{\Delta x, \Delta t \rightarrow 0} (\text{Truncation Error}) = 0.$$

By **Lax's theorem**, if the scheme is consistent and stable, it is guaranteed to be convergent:

$$\lim_{\Delta x, \Delta t \rightarrow 0} \|u_j^n - u(x_j, t_n)\| = 0.$$

10.2 Van Neumann

Van Neumann stability analysis is a mathematical technique used to assess the stability of finite difference schemes for solving partial differential equations (PDEs). It is particularly useful in analyzing the behavior of numerical solutions over time.

Key Idea: The method is based on applying a Fourier mode decomposition to the numerical scheme. The numerical solution is expressed as a sum of Fourier modes, and the growth factor.

Stability Criterion: A finite difference scheme is **stable** if and only if the magnitude of the amplification factor satisfies Eq.(10.1):

$$|G(k)| \leq 1, \quad \forall k. \quad (10.1)$$

This ensures that numerical errors do not grow uncontrollably as time progresses.

1. **Express the numerical scheme** as a recurrence relation.

2. **Substitute a Fourier mode** of the form:

$$u_j^n = \hat{u}^n e^{ikj\Delta x},$$

where i is the imaginary unit, k is the wave number, and Δx is the spatial step size.

3. **Determine the amplification factor** $G(k)$ by solving for:

$$G(k) = \frac{\hat{u}^{n+1}}{\hat{u}^n}.$$

4. **Check the stability condition** $|G(k)| \leq 1$.

Application : Van Neumann analysis is commonly used for schemes solving hyperbolic PDEs, such as the **heat equation**, **wave equation**, and **advection equation**. It helps determine whether a numerical method will produce bounded solutions over time.

For **stability**, we often use techniques like the **Von Neumann stability analysis** to check that perturbations do not grow indefinitely using Eq.(10.1).

11. Lecture 11 03/02/2025

11.1 Van Neumann Stability Analysis For 1-D Heat Conducting Equation For FTCS Scheme

$$\frac{\partial T}{\partial t} = k \frac{\partial^2 T}{\partial x^2} \quad (11.1)$$

Applying FTCS scheme:

$$\frac{T_{m,n+1} - T_{m,n}}{\Delta t} = k \left[\frac{T_{m+1,n} - 2T_{m,n} + T_{m-1,n}}{(\Delta x)^2} \right] \quad (11.2)$$

Let $\lambda = k\Delta t / (\Delta x)^2$

Since error $\epsilon_{m,n}$ identically satisfies difference equations, we can write;

$$\begin{aligned} \epsilon_{m,n+1} &= \epsilon_{m,n} + \lambda (\epsilon_{m+1,n} + \epsilon_{m-1,n} - 2\epsilon_{m,n}) \\ \epsilon_{m,n+1} &= (1 - 2\lambda) \epsilon_{m,n} + \lambda (\epsilon_{m+1,n} + \epsilon_{m-1,n}) \end{aligned} \quad (11.3)$$

Let $\epsilon_{m,n} = e^{(at)} \cdot e^{(ikx)}$

Since, $t = n\Delta t$ and $x = m\Delta x$;

$$\epsilon_{m,n} = e^{(an\Delta t)} \cdot e^{(ikm\Delta x)} \quad (11.4)$$

Substituting Eq.(11.4) in Eq.(11.3), we obtain;

$$\begin{aligned} e^{(a(n+1)\Delta t)} \cdot e^{(ikm\Delta x)} &= (1 - 2\lambda) e^{(an\Delta t)} e^{(ikm\Delta x)} \\ &\quad + \lambda \left[e^{(ik(m+1)\Delta x)} + e^{(ik(m-1)\Delta x)} \right] e^{(an\Delta t)} \\ e^{(a\Delta t)} \cdot e^{(ikm\Delta x)} &= (1 - 2\lambda) e^{(ikm\Delta x)} \\ &\quad + \lambda \left[e^{(ik(m+1)\Delta x)} + e^{(ik(m-1)\Delta x)} \right] \end{aligned} \quad (11.5)$$

Divide both sides of Eq.(11.5) by $e^{(ikm\Delta x)}$

$$\begin{aligned} e^{(a\Delta t)} &= (1 - 2\lambda) + \lambda \underbrace{\left[e^{(ik\Delta x)} + e^{-(ik\Delta x)} \right]}_{2\cos(k\Delta x)} \\ e^{(a\Delta t)} &= (1 - 2\lambda) + 2\lambda \cos(k\Delta x) \\ e^{(a\Delta t)} &= 1 - 2\lambda [1 - \cos(k\Delta x)] \\ e^{(a\Delta t)} &= 1 - 4\lambda \left[\sin^2 \left(\frac{k\Delta x}{2} \right) \right] \end{aligned} \quad (11.6)$$

Amplification factor

$$\begin{aligned} G &= \left| \frac{\epsilon_{m,n+1}}{\epsilon_{m,n}} \right| \\ &= \left| \frac{e^{a(n+1)\Delta t} \cdot e^{ikm\Delta x}}{e^{an\Delta t} \cdot e^{ikm\Delta x}} \right| \\ &= \left| e^{a\Delta t} \right| \end{aligned} \quad (11.7)$$

FTCS scheme will be stable if

$$\left| e^{a\Delta t} \right| \leq 1 \Rightarrow \left| 1 - 4\lambda \left[\sin^2 \left(\frac{k\Delta x}{2} \right) \right] \right| \leq 1$$

The following 2 conditions has to be identically satisfied

$$1 - 4\lambda \left[\sin^2 \left(\frac{k\Delta x}{2} \right) \right] \leq 1 \quad (11.8.i)$$

$$1 - 4\lambda \left[\sin^2 \left(\frac{k\Delta x}{2} \right) \right] \geq -1 \quad (11.8.ii)$$

For Eq.(11.8.i);

$$\begin{aligned} 1 - 4\lambda \left[\sin^2 \left(\frac{k\Delta x}{2} \right) \right] &\leq 1 \\ -4\lambda \left[\sin^2 \left(\frac{k\Delta x}{2} \right) \right] &\leq 0 \end{aligned}$$

Therefore, it is always true.

For Eq.(11.8.ii);

$$\begin{aligned} 1 - 4\lambda \left[\sin^2 \left(\frac{k\Delta x}{2} \right) \right] &\geq -1 \\ 4\lambda \left[\sin^2 \left(\frac{k\Delta x}{2} \right) \right] &\leq 2 \end{aligned}$$

Maximum magnitude of $\sin^2(k\Delta x/2) = 1$

$$\begin{aligned} 4\lambda \cdot 1 &\leq 2 \\ \lambda &\leq \frac{1}{2} \\ \frac{k\Delta t}{(\Delta x)^2} &\leq \frac{1}{2} \\ \Delta t &\leq \frac{(\Delta x)^2}{2k} \end{aligned}$$

12. Lecture 12 04/02/2025

12.1 BTCS Scheme

$$\frac{\partial T}{\partial t} = k \frac{\partial^2 T}{\partial x^2} \quad (12.1)$$

$$\frac{T_{m,n} - T_{m,n-1}}{\Delta t} = k \left[\frac{T_{m+1,n} - 2 \cdot T_{m,n} + T_{m-1,n}}{(\Delta x)^2} \right] \quad (12.2)$$

Let $\lambda = k\Delta t / (\Delta x)^2$

$$(1 + 2\lambda)T_{m,n} - \lambda(T_{m+1,n} + T_{m-1,n}) = T_{m,n-1} \quad (12.3)$$

For stability;

$$(1 + 2\lambda)\epsilon_{m,n} - \lambda(\epsilon_{m+1,n} + \epsilon_{m-1,n}) = \epsilon_{m,n-1} \quad (12.4)$$

$$\epsilon_{m,n} = B^{\mu n \Delta t} \cdot e^{ikm\Delta x} \quad (12.5)$$

Substituting Eq.(12.5) in Eq.(12.4), we obtain;

$$\left. \begin{aligned} (1 + 2\lambda)B^{\mu n \Delta t} e^{ikm\Delta x} \\ - \lambda B^{\mu n \Delta t} (e^{ik(m+1)\Delta x} + e^{ik(m-1)\Delta x}) \\ = B^{\mu(n-1)\Delta t} e^{ikm\Delta x} \end{aligned} \right\} \quad (12.6)$$

Divide Eq.(12.6) throughout by $B^{\mu(n-1)\Delta t} \cdot e^{ikm\Delta x}$

$$\begin{aligned} (1 + 2\lambda)B^{\mu \Delta t} - \lambda B^{\mu \Delta t} (e^{ik\Delta x} + e^{-ik\Delta x}) &= 1 \\ (1 + 2\lambda)B^{\mu \Delta t} - 2\lambda B^{\mu \Delta t} \cos(k\Delta x) &= 1 \\ B^{\mu \Delta t} (1 + 2\lambda - 2\lambda \cos(k\Delta x)) &= 1 \\ B^{\mu \Delta t} (1 + 2\lambda [1 - \cos(k\Delta x)]) &= 1 \\ B^{\mu \Delta t} \left(1 + 4\lambda \sin^2 \left(\frac{k\Delta x}{2} \right) \right) &= 1 \\ B^{\mu \Delta t} &= \frac{1}{(1 + 4\lambda \sin^2 \left(\frac{k\Delta x}{2} \right))} \end{aligned} \quad (12.7)$$

Amplification factor

$$G = \left| \frac{\epsilon_{m,n+1}}{\epsilon_{m,n}} \right| = |B^{\mu \Delta t}| \leq 1 \quad (12.8)$$

Eq.(12.8) shows that BTCS scheme is unconditionally stable.

12.2 CTCS Scheme / Richardson Scheme

$$\frac{T_{m,n+1} - T_{m,n-1}}{2 \cdot \Delta t} = k \left[\frac{T_{m+1,n} - 2 \cdot T_{m,n} + T_{m-1,n}}{(\Delta x)^2} \right] \quad (12.9)$$

Let $\lambda = 2 \cdot k\Delta t / (\Delta x)^2$

$$T_{m,n+1} = T_{m,n-1} + \lambda(T_{m+1,n} - 2 \cdot T_{m,n} + T_{m-1,n}) \quad (12.10)$$

For stability;

$$\epsilon_{m,n+1} = \epsilon_{m,n-1} + \lambda(\epsilon_{m+1,n} - 2 \cdot \epsilon_{m,n} + \epsilon_{m-1,n}) \quad (12.11)$$

$$\epsilon_{m,n} = B^{\mu n \Delta t} \exp(ikm\Delta x) \quad (12.12)$$

$$\begin{aligned} \epsilon_{m,n} &= B^{\mu n \Delta t} e^{(ikm\Delta x)} \\ &= B^{\mu(n-1)\Delta t} e^{(ikm\Delta x)} \\ &\quad + \lambda B^{\mu n \Delta t} [e^{ik\Delta x} - e^{-ik\Delta x}] e^{ikm\Delta x} \end{aligned}$$

Divide throughout by $B^{\mu(n-1)\Delta t} e^{ikm\Delta x}$

$$B^{2 \cdot \mu(n-1)\Delta t} = 1 - 2\lambda \cdot B^{\mu \Delta t} (1 - \cos(k\Delta x))$$

$$B^{2 \cdot \mu(n-1)\Delta t} = 1 - 2\lambda \cdot B^{\mu \Delta t} (2 \cdot \sin^2(k\Delta x))$$

$$(B^{\mu(n-1)\Delta t})^2 + 4\lambda \cdot \sin^2(k\Delta x) B^{\mu \Delta t} - 1 = 0$$

$$G^2 + \beta G - 1 = 0 \quad (12.13)$$

Amplification factor

$$G = \left| \frac{\epsilon_{m,n+1}}{\epsilon_{m,n}} \right| = |B^{\mu \Delta t}| \leq 1 \quad (12.14)$$

$$G_{1,2} = \frac{-\beta \pm \sqrt{\beta^2 + 4}}{2} \quad (12.15)$$

Eq.(12.14) shows that CTCS scheme is stable.

To be checked

13. Lecture 13 06/02/2025

13.1 Crank Nicholson Scheme


$$\left(\frac{\partial T}{\partial t}\right)_{m,n+1/2} = \tilde{k} \left(\frac{\partial^2 T}{\partial x^2}\right)_{m,n+1/2} \quad (13.1)$$

$$\begin{aligned} \frac{T_{m,n} - T_{m,n-1}}{\Delta t} \\ = \tilde{k} \left[\frac{T_{m+1,n+1/2} - 2T_{m,n+1/2} + T_{m-1,n+1/2}}{(\Delta x)^2} \right] \end{aligned} \quad (13.2)$$

Let $\lambda = \tilde{k}\Delta t/2(\Delta x)^2$

Averaging between time n and $n+1$ and substituting in Eq.(13.2)

$$\begin{aligned} (1+2\lambda)T_{m,n+1} - \lambda T_{m,n-1} - \lambda T_{m+1,n+1} = \\ (1-2\lambda)T_{m,n} - \lambda T_{m,n} \end{aligned} \quad (13.3)$$



For stability;

$$\left. \begin{aligned} (1+2\lambda)\varepsilon_{m,n+1} - \lambda\varepsilon_{m+1,n+1} - \lambda\varepsilon_{m-1,n+1} = \\ (1-2\lambda)\varepsilon_{m,n} - \lambda\varepsilon_{m+1,n} + \lambda\varepsilon_{m-1,n} \end{aligned} \right\} \quad (13.4)$$

$$\varepsilon_{m,n} = B^{\mu n \Delta t} e^{ikm\Delta x} \quad (13.5)$$

Substituting Eq.(13.5) in Eq.(13.4), we obtain;

$$\left. \begin{aligned} (1+2\lambda)B^{\mu(n+1)\Delta t} e^{ikm\Delta x} \\ - \lambda B^{\mu(n+1)\Delta t} \left[e^{ik(m+1)\Delta x} + e^{-ik(m-1)\Delta x} \right] \\ = (1-2\lambda)B^{\mu n \Delta t} e^{ikm\Delta x} \\ + \lambda B^{\mu n \Delta t} \left[e^{ik(m+1)\Delta x} + e^{ik(m-1)\Delta x} \right] \end{aligned} \right\} \quad (13.6)$$

Divide throughout by $B^{\mu n \Delta t} e^{ikm\Delta x}$

$$\begin{aligned} (1+2\lambda)B^{\mu \Delta t} - 2\lambda B^{\mu \Delta t} [\cos(k\Delta x)] \\ = (1-2\lambda) + 2\lambda [\cos(k\Delta x)] \\ (1+2\lambda - 2\lambda \cos(k\Delta x))B^{\mu \Delta t} \\ = (1-2\lambda) + 2\lambda [\cos(k\Delta x)] \\ (1+2\lambda(1-\cos(k\Delta x)))B^{\mu \Delta t} \\ = 1 - 2\lambda(1-\cos(k\Delta x)) \\ B^{\mu \Delta t} = \frac{1-2\lambda(1-\cos(k\Delta x))}{1+2\lambda(1-\cos(k\Delta x))} \\ B^{\mu \Delta t} = \frac{1-4\lambda(\sin^2(k\Delta x/2))}{1+4\lambda(\sin^2(k\Delta x/2))} \end{aligned} \quad (13.7)$$

Let $4\lambda(\sin^2(k\Delta x/2)) = \beta$
Amplification factor

$$G = \left| \frac{\varepsilon_{m,n+1}}{\varepsilon_{m,n}} \right| = \left| \frac{1-\beta}{1+\beta} \right| = |B^{\mu \Delta t}| \leq 1 \quad (13.8)$$

13.2 Dufart Frankel Scheme

$$\left(\frac{\partial T}{\partial t}\right)_{m,n} = k \left(\frac{\partial^2 T}{\partial x^2}\right)_{m,n} \quad (13.9)$$

$$\frac{T_{m,n+1} - T_{m,n}}{2\Delta t} = k \left[\frac{T_{m+1,n} - 2T_{m,n} + T_{m-1,n}}{(\Delta x)^2} \right] \quad (13.10)$$

Let $\lambda = 2 \cdot k\Delta t/(\Delta x)^2$

Taking average $T_{m,n} = \frac{T_{m,n+1} + T_{m,n-1}}{2}$

$$\begin{aligned} T_{m,n+1} - T_{m,n} &= \lambda \left[\frac{T_{m+1,n} - 2\left(\frac{T_{m,n+1} + T_{m,n-1}}{2}\right) + T_{m-1,n}}{(\Delta x)^2} \right] \\ (1+\lambda)T_{m,n+1} &= \lambda T_{m+1,n} + (1-\lambda)T_{m,n-1} + \lambda T_{m-1,n} \end{aligned} \quad (13.11)$$

Errors should satisfy the same difference equation identically;

$$(1+\lambda)\varepsilon_{m,n+1} = \lambda\varepsilon_{m+1,n} + (1-\lambda)\varepsilon_{m,n-1} + \lambda\varepsilon_{m-1,n} \quad (13.12)$$

$$\varepsilon_{m,n} = B^{\mu n \Delta t} \exp(ikm\Delta x) \quad (13.13)$$

Substituting Eq.(13.12) in Eq.(13.11), we obtain;

$$\left. \begin{aligned} (1+\lambda)B^{\mu(n+1)\Delta t} \exp(ikm\Delta x) \\ = \lambda B^{\mu n \Delta t} \exp(ik(m+1)\Delta x) \\ + (1-\lambda)B^{\mu(n-1)\Delta t} \exp(ikm\Delta x) \\ + \lambda B^{\mu n \Delta t} \exp(ik(m-1)\Delta x) \end{aligned} \right\} \quad (13.14)$$

Divide throughout by $B^{\mu n \Delta t} e^{ikm\Delta x}$

$$\begin{aligned} (1+\lambda)(B^{\mu \Delta t})^2 &= \lambda B^{\mu \Delta t} (2\cos(k\Delta t)) + (1-\lambda) \\ (1+\lambda)G^2 &= \lambda (2\cos(k\Delta t)) G + (1-\lambda) \\ (1+\lambda)G^2 - \lambda (2\cos(k\Delta t)) G - (1-\lambda) &= 0 \end{aligned} \quad (13.15)$$

$$\begin{aligned} G_{1,2} &= \frac{2\lambda \cos(k\Delta x) \pm \sqrt{4\lambda^2 \cos^2(k\Delta x) + 4(1-\lambda^2)}}{2(1+\lambda)} \\ G_{1,2} &= \frac{\lambda \cos(k\Delta x) \pm \sqrt{\lambda^2 (\cos^2(k\Delta x) - 1) + 1}}{\lambda(1+\lambda)} \\ G_{1,2} &= \frac{\lambda \cos(k\Delta x) \pm \sqrt{1 - \lambda^2 \sin^2(k\Delta x)}}{(1+\lambda)} \end{aligned} \quad (13.16)$$

For Dufart Frankel Scheme to be stable G_1 & G_2 in Eq.(13.16) should both simultaneously less than 1.

Case i: Quantity under square root is real.
i.e., $1 - \lambda^2 \sin^2(k\Delta x) \geq 0$

$$\begin{aligned}
G &= \frac{\lambda \cos(k\Delta x) \pm \sqrt{1 - \lambda^2 \sin^2(k\Delta x)}}{(1 + \lambda)} \\
&\leq \frac{\lambda \cos(k\Delta x) + 1}{(1 + \lambda)} \\
&\leq \frac{\lambda + 1}{(1 + \lambda)} \\
&\leq 1
\end{aligned}$$

Case ii: Quantity under square root is imaginary.
i.e., $1 - \lambda^2 \sin^2(k\Delta x) \leq 0$

$$\begin{aligned}
G_{1,2} &= \frac{\lambda \cos(k\Delta x) \pm \sqrt{1 - \lambda^2 \sin^2(k\Delta x)}}{(1 + \lambda)} \\
&= \frac{\lambda \cos(k\Delta x) \pm i \sqrt{\lambda^2 \sin^2(k\Delta x) - 1}}{(1 + \lambda)} \\
|G_{1,2}^2| &= \frac{\lambda^2 \cos^2(k\Delta x) + \lambda^2 \sin^2(k\Delta x) - 1}{(1 + \lambda)^2} \\
&= \frac{(\lambda^2 - 1)}{(1 + \lambda)^2} \\
&= \frac{(\lambda - 1)(\lambda + 1)}{(1 + \lambda)^2} \\
&= \frac{(\lambda - 1)}{(1 + \lambda)} \\
&\leq 1
\end{aligned}$$

Therefore Dufart Frankel Scheme is unconditionally stable.

14. Lecture 14 10/02/2025

14.1 2-D Heat Conduction Equation

$$\left(\frac{\partial T}{\partial t}\right)_{m,n,p} = \tilde{k} \left[\left(\frac{\partial^2 T}{\partial x^2}\right)_{m,n,p} + \left(\frac{\partial^2 T}{\partial y^2}\right)_{m,n,p} \right] \quad (14.1)$$

Initial conditions: $T(x, y, t = 0)$

Boundary conditions: temperatures on 4 sides

$m \rightarrow l, n \rightarrow y$ and $p \rightarrow t$

Applying FTCS:

$$\left. \begin{aligned} \frac{T_{m,n,p+1} - T_{m,n,p}}{\Delta t} &= \tilde{k} \left[\frac{T_{m+1,n,p} - 2T_{m,n,p} + T_{m-1,n,p}}{(\Delta x)^2} \right] \\ &+ \tilde{k} \left[\frac{T_{m,n+1,p} - 2T_{m,n,p} + T_{m,n-1,p}}{(\Delta y)^2} \right] \end{aligned} \right\} \quad (14.2)$$

For stability;

$$\varepsilon_{m,n,p} = B^{\mu p \Delta t} e^{ikm\Delta x} e^{ikn\Delta y} \quad (14.3)$$

Amplification factor:

$$G = \left| \frac{\varepsilon_{m,n,p+1}}{\varepsilon_{m,n,p}} \right| = |B^{\mu \Delta t}| \leq 1 \quad (14.4)$$

$$\frac{2k\Delta t}{(\Delta x)^2} + \frac{2l\Delta t}{(\Delta y)^2} \leq 1$$

if $\Delta x = \Delta y = d, k = l$

$$\left. \begin{aligned} \frac{4k\Delta t}{(\Delta d)^2} &\leq 1 \\ \lambda = \frac{k\Delta t}{(\Delta d)^2} &\leq \frac{1}{4} \end{aligned} \right\} \quad (14.5)$$

Eq.(14.5) is stability condition for 2-D heat conduction equation.

Apply Crank Nicholson Scheme on 2-D heat conduction equation:

$$\left(\frac{\partial T}{\partial t}\right)_{m,n,p+1/2} = \tilde{k} \left[\left(\frac{\partial^2 T}{\partial x^2}\right)_{m,n,p+1/2} + \left(\frac{\partial^2 T}{\partial y^2}\right)_{m,n,p+1/2} \right] \quad (14.6)$$

$$\left. \begin{aligned} \frac{T_{m,n,p+1} - T_{m,n,p}}{\Delta t/2} &= \tilde{k} \left[\frac{T_{m+1,n,p+1/2} - 2T_{m,n,p+1/2} + T_{m-1,n,p+1/2}}{(\Delta x)^2} \right] \\ &+ \tilde{k} \left[\frac{T_{m,n+1,p+1/2} - 2T_{m,n,p+1/2} + T_{m,n-1,p+1/2}}{(\Delta y)^2} \right] \end{aligned} \right\} \quad (14.7)$$

Assuming average:

$$T_{m,n,p+1/2} = \left[\frac{T_{m,n+1,p+1} + T_{m+1,n,p-1}}{2} \right] \quad (14.8)$$

Substituting Eq.(14.8) in Eq.(14.6)

14.2 ADI Method

Alternate Directional Implicit method (ADE) take one direction as implicit (Unknown time) and another explicit (Known time)

$$\left. \begin{aligned} \frac{T_{m,n,p+1/2} - T_{m,n,p}}{\Delta t/2} &= \tilde{k} \left[\frac{T_{m+1,n,p+1/2} - 2T_{m,n,p+1/2} + T_{m-1,n,p+1/2}}{(\Delta x)^2} \right] \\ &+ \tilde{k} \left[\frac{T_{m,n+1,p} - 2T_{m,n,p} + T_{m,n-1,p}}{(\Delta y)^2} \right] \end{aligned} \right\} \quad (14.9)$$

$$\left. \begin{aligned} \frac{T_{m,n,p+1} - T_{m,n,p+1/2}}{\Delta t/2} &= \tilde{k} \left[\frac{T_{m+1,n,p+1/2} - 2T_{m,n,p+1/2} + T_{m-1,n,p+1/2}}{(\Delta x)^2} \right] \\ &+ \tilde{k} \left[\frac{T_{m,n+1,p+1} - 2T_{m,n,p+1} + T_{m,n-1,p+1}}{(\Delta y)^2} \right] \end{aligned} \right\} \quad (14.10)$$

15. Lecture 15 11/02/2025


15.1 1-D Advection Equation

$$\frac{\partial f}{\partial t} + c \frac{\partial f}{\partial x} = 0 \quad (15.1)$$

Solution of Eq.(15.1) is wave equation, for $c > 0$ wave propagate in positive x-direction with speed c .

$$\begin{aligned} f(x - c\Delta t, t) &= f(x, t + \Delta t) \\ f(x, t) + \Delta t \frac{\partial f}{\partial t} \Big|_x + \dots &= f(x, t) - c\Delta t \frac{\partial f}{\partial x} \Big|_t + \dots \\ \Delta t \frac{\partial f}{\partial t} \Big|_x &= -c\Delta t \frac{\partial f}{\partial x} \Big|_t \\ \frac{\partial f}{\partial t} \Big|_x + c \frac{\partial f}{\partial x} \Big|_t &= 0 \end{aligned}$$

Speed of propagation depends on wavelength of wave which means each wave in wave packet will vary with time called **dispersive wave** and which doesn't change with time is called **non-dispersive wave**.



Shallow water equation (assuming no coriolis force, i.e., without rotation) the gravitational wave equation ($c = \sqrt{gH}$) after applying finite wave approximation make wave dispersive.

Finite layer method always introduce dispersion while computing, all we can do is to think of scheme which will minimise this introduced dispersion.

15.2 Method of separation of variables

$$\begin{aligned} f(x, t) &= A \exp(i\mu(x - ct)) \\ f(x, t = 0) &= A \exp(i\mu x) \quad \text{I.C.} \end{aligned} \quad (15.2)$$

Using method of separation of variables

$$F(x, t) = a(x)H(t)$$

$$\begin{aligned} G \frac{dH}{dt} + cH \frac{dG}{dx} &= 0 \\ \Rightarrow \frac{1}{H} \frac{dH}{dt} &= -\frac{c}{G} \frac{dG}{dx} = -k \text{ (constant)} \\ \frac{1}{H} \frac{dH}{dt} &= -k, \quad -\frac{c}{G} \frac{dG}{dx} = -k \\ d(\ln H) &= -k dt, \quad d(\ln G) = \frac{k}{c} dx \\ H &= A_1 \exp(-kt), \quad G = A_2 \exp\left(\frac{k}{c} dx\right) \end{aligned}$$

Since $F = GH$

$$\begin{aligned} f(x, t) &= A_1 A_2 e^{-kt} e^{\frac{k}{c}x} \\ f(x, t) &= A e^{\frac{k}{c}(x - ct)} \end{aligned}$$

For applying CTCS scheme,
 $x \rightarrow m, t \rightarrow n$, Let $\lambda = c \frac{\Delta t}{\Delta x}$

Solve Eq.(15.1) using CTCS scheme;

$$\frac{f_{m,n+1} - f_{m,n-1}}{2 \cdot \Delta t} = -c \left[\frac{f_{m+1,n} - f_{m-1,n}}{2 \cdot \Delta x} \right] \quad (15.3)$$

$$f_{m,n+1} = f_{m,n-1} - \lambda [f_{m+1,n} - f_{m-1,n}] \quad (15.4)$$

$$f_{m,n} = A e^{ik(x - \Delta t)} \quad (15.4.i)$$

$$f_{m,0} = A e^{ikx} \quad (15.4.ii)$$

For stability analysis;

$$\epsilon_{m,n+1} = \epsilon_{m,n-1} - \lambda (\epsilon_{m+1,n} - \epsilon_{m-1,n}) \quad (15.5)$$

Let $\epsilon_{m,n} = B^{pn\Delta t} e^{ikm\Delta x}$ and Substitute in Eq.(15.4)

$$\left. \begin{aligned} B^{p(n+1)\Delta t} e^{ikm\Delta x} &= B^{p(n-1)\Delta t} e^{ikm\Delta x} \\ &\quad - \lambda \left[B^{p(n+1)\Delta t} e^{ik(m+1)\Delta x} \right. \\ &\quad \left. - B^{p(n+1)\Delta t} e^{ik(m-1)\Delta x} \right] \end{aligned} \right\} \quad (15.6)$$

Dividing Eq.(15.5) with $B^{p(n-1)\Delta t} e^{ikm\Delta x}$, we obtain,

$$\begin{aligned} (B^{pn\Delta t})^2 &= 1 - \lambda B^{p\Delta t} [e^{ik\Delta x} - e^{-ik\Delta x}] \\ (B^{pn\Delta t})^2 &= 1 - \lambda B^{p\Delta t} (2i \sin(k\Delta x)) \\ (B^{pn\Delta t})^2 + \lambda B^{p\Delta t} (2i \sin(k\Delta x)) - 1 &= 0 \end{aligned} \quad (15.7)$$

Amplification factor:

$$G = \left| \frac{\epsilon_{m,n+1}}{\epsilon_{m,n}} \right| = |B^{p\Delta t}| \leq 1 \quad (15.8)$$

Substituting Eq.(15.8) in Eq.(15.7), we get,

$$\begin{aligned} G^2 + 2i\lambda \sin(k\Delta x)G - 1 &= 0 \\ G_{1,2} &= \frac{-2i\lambda \sin(k\Delta x) \pm \sqrt{-4\lambda^2 \sin^2(k\Delta x) + 4}}{2} \\ G_{1,2} &= -i\lambda \sin(k\Delta x) \pm \sqrt{1 - \lambda^2 \sin^2(k\Delta x)} \end{aligned} \quad (15.9)$$

Continued in next lecture...

16. Lecture 16 12/02/2025

16.1 1-D Advection Equation

Continuing from last lecture.

We need to ensure $|G_{1,2}| = |B_{1,2}^{p\Delta t}| \leq 1$ for scheme to be stable.

Case 1: Quantity under the square root, i.e., $(1 - \lambda^2 \sin^2(k\Delta x))$ is positive.

$$1 - \lambda^2 \sin^2(k\Delta x) < 1$$

Let $\alpha = \sin^{-1}(\lambda \sin(k\Delta x))$ and substituting in Eq.(15.8)

$$\begin{aligned} G_{1,2} &= -i \sin(\alpha) \pm \sqrt{1 - \sin^2(\alpha)} \\ G_{1,2} &= \pm \cos(\alpha) - i \sin(\alpha) \end{aligned} \quad (16.1)$$

$$G_1 = \cos(\alpha) - i \sin(\alpha) = e^{i\alpha} \quad (16.2)$$

$$G_2 = -\cos(\alpha) - i \sin(\alpha) = -e^{i\alpha} = e^{i(\pi+\alpha)} \quad (16.3)$$

Therefore the solution of the Eq.(15.1) is

$$f_{m,n} = [M e^{-in\alpha} + E e^{i(\pi+\alpha)n}] \cdot e^{ikm\Delta x} \quad (16.4)$$

where M and E are arbitrary constants.

At initial time ($n = 0$):

$$f_{m,0} = [M + E] \cdot e^{ikm\Delta x} \quad (16.5)$$

Comparing Eq.(15.4.ii) and Eq.(16.5),

$$A = M + E \Rightarrow M = A - E$$

Substituting M in Eq.(16.4)

$$f_{m,n} = \underbrace{(A - E) e^{-i\alpha n} e^{ikm\Delta x}}_{\text{Physical Mode}} + \underbrace{(-1)^n E e^{i(\pi+\alpha)n} e^{ikm\Delta x}}_{\text{Computational Mode}} \quad (16.6)$$

$$f_{m,n} = (A - E) e^{-i\alpha n + ikm\Delta x} + (-1)^n E e^{i\alpha n + ikm\Delta x}$$

$$f_{m,n} = (A - E) e^{ik(-\frac{\alpha n}{k} + m\Delta x)} + (-1)^n E e^{ik(\frac{\alpha n}{k} + m\Delta x)} \quad (16.7)$$

$c = \alpha/(k\Delta t)$ is speed of a numerical wave.

Next lecture we will put cases over $\lambda < 1$, $= 1$ and > 1 .

17. Lecture 17 17/02/2025

17.1 1-D Advection Equation

Continuing from last lecture.

Case 1: For $\lambda < 1$

For $\lambda^2 \sin^2(k\Delta x) < 1$, λ should be < 1

Therefore the value under square root in Eq.(15.8) is greater than 0, hence Scheme is **stable**.

Characteristic	Physical Mode	Computational Mode	Analytical Solution
Amplitude	A - E	E	A
Phase speed	$\alpha/(k\Delta t)$	$-\alpha/(k\Delta t)$	c
Phase change	No change	180° every time step $(-1)^n$	No change

Table 1. Comparison of different modes and solutions for $\lambda < 1$

Case 2: For $\lambda = 1$

For $\lambda^2 \sin^2(k\Delta x) < 1$, $\lambda = 1 \Rightarrow \sin^2(k\Delta x) < 1$

Therefore the value under square root in Eq.(15.8) is greater than 0, hence Scheme is **stable**.

Characteristic	Physical Mode	Computational Mode	Analytical Solution
Amplitude	A - E	E	A
Phase speed	c	-c	c
Phase change	No change	180° every time step $(-1)^n$	No change

Table 2. Comparison of different modes and solutions for $\lambda = 1$

Case 3: For $\lambda > 1$

The quantity under square root in Eq.(15.8) becomes negative, i.e., $1 - \lambda^2 \sin^2(k\Delta x) < 0$, hence Scheme is **unstable**.

This scheme was proposed by 3 mathematicians, namely, Courant, Fridriks and Lenry in 1940. This scheme for $\lambda \leq 1$ is also called **CFL condition**.

$$\frac{f_{m,1} - f_{m,0}}{\Delta t} = -c \left[\frac{f_{m+1,0} - f_{m-1,0}}{2 \cdot \Delta x} \right] \quad (17.1)$$

$$f_{m,1} = f_{m,0} - \lambda [f_{m+1,0} - f_{m-1,0}] \quad (17.2)$$

Substitute $f_{m,0} = Ae^{ikm\Delta x}$

$$\begin{aligned} f_{m,1} &= Ae^{ikm\Delta x} - \frac{\lambda A}{2} [e^{ik(m+1)\Delta x} - e^{ik(m-1)\Delta x}] \\ f_{m,1} &= Ae^{ikm\Delta x} \left\{ 1 - \frac{\lambda}{2} [e^{ik(m+1)\Delta x} - e^{ik(m-1)\Delta x}] \right\} \\ f_{m,1} &= Ae^{ikm\Delta x} \{1 - i\lambda \sin(k\Delta x)\} \end{aligned} \quad (17.3)$$

Let $\alpha = \sin^{-1}(\lambda \sin(k\Delta x))$ and substitute in Eq.(17.3)

$$f_{m,1} = Ae^{ikm\Delta x} (1 - i \sin(\alpha)) \quad (17.5)$$

Also, we know that from Eq.(16.7)

$$f_{m,n} = (A - E)e^{ik(-\frac{\alpha n}{k} + m\Delta x)} + (-1)^n E e^{ik(\frac{\alpha n}{k} + m\Delta x)} \quad (17.6)$$

Equating RHS of Eq.(17.5) and Eq.(17.6);

$$Ae^{ikm\Delta x} (1 - i \sin(\alpha)) = (A - E)e^{ik(-\frac{\alpha n}{k} + m\Delta x)} + (-1)^n E e^{ik(\frac{\alpha n}{k} + m\Delta x)} \quad (17.7)$$

Divide Eq.(17.7) by $Ae^{ikm\Delta x}$ on both sides;

$$\begin{aligned} 1 - i \sin(\alpha) &= \left(1 - \frac{E}{A}\right) e^{-i\alpha} + (-1)^n \left(\frac{E}{A}\right) e^{i\alpha} \\ 1 - i \sin(\alpha) &= -\left(\frac{E}{A}\right) (e^{i\alpha} + e^{-i\alpha}) + e^{-i\alpha} \\ 1 - i \sin(\alpha) &= -\left(\frac{E}{A}\right) (2 \cos(\alpha)) + \cos(\alpha) - i \sin(\alpha) \\ 1 &= -\left(\frac{E}{A}\right) (2 \cos(\alpha)) + \cos(\alpha) \\ -\left(\frac{E}{A}\right) &= \left(\frac{1 - \cos(\alpha)}{2 \cos(\alpha)}\right) \end{aligned} \quad (17.8)$$

Substituting Eq.(17.8) in Eq.(17.6)

$$f_{m,n} = A \left(1 - \left(\frac{E}{A}\right)\right) e^{ik(-\frac{\alpha n}{k} + m\Delta x)} + (-1)^n A \left(\frac{E}{A}\right) e^{ik(\frac{\alpha n}{k} + m\Delta x)} \quad (17.9)$$

$$f_{m,n} = A \left(1 + \left(\frac{1 - \cos(\alpha)}{2 \cos(\alpha)}\right)\right) e^{ik(-\frac{\alpha n}{k} + m\Delta x)} - (-1)^n A \left(\frac{1 - \cos(\alpha)}{2 \cos(\alpha)}\right) e^{ik(\frac{\alpha n}{k} + m\Delta x)} \quad (17.10)$$

$$f_{m,n} = A \left[\underbrace{\left(\frac{1 + \cos(\alpha)}{2 \cos(\alpha)}\right) e^{ik(-\frac{\alpha n}{k} + m\Delta x)}}_{\text{Physical Mode}} - (-1)^n \underbrace{\left(\frac{1 - \cos(\alpha)}{2 \cos(\alpha)}\right) e^{ik(\frac{\alpha n}{k} + m\Delta x)}}_{\text{Computational Mode}} \right] \quad (17.11)$$

18. Lecture 18 17/02/2025

18.1 1-D Advection Equation

$$\frac{\partial f}{\partial t} + c \frac{\partial f}{\partial x} = 0 \quad (18.1)$$

For applying BTCS scheme,

$x \rightarrow m, t \rightarrow n$,

Solve Eq.(18.1) using BTCS scheme;

$$\frac{f_{m,n} - f_{m,n-1}}{\Delta t} = -c \left[\frac{f_{m+1,n} - f_{m-1,n}}{2 \cdot \Delta x} \right] \quad (18.2)$$

Let $\lambda = c \frac{\Delta t}{\Delta x}$

Implicit finite difference scheme

$$-\frac{\lambda}{2} f_{m-1,n} + f_{m,n} + \frac{\lambda}{2} f_{m+1,n} = f_{m,n-1}$$

For stability analysis;

$$-\frac{\lambda}{2} \varepsilon_{m-1,n} + \varepsilon_{m,n} + \frac{\lambda}{2} \varepsilon_{m+1,n} = \varepsilon_{m,n-1} \quad (18.3)$$

Amplification factor:

$$G = \left| \frac{\varepsilon_{m,n}}{\varepsilon_{m,n-1}} \right| = |B^{\mu \Delta t}| \leq 1 \quad (18.4)$$

Let $\varepsilon_{m,n} = B^{\mu n \Delta t} e^{ikm \Delta x}$

$$\left. \begin{aligned} B^{\mu n \Delta t} \left[-\frac{\lambda}{2} e^{ik(m-1)\Delta x} + e^{ikm\Delta x} + \frac{\lambda}{2} e^{ik(m+1)\Delta x} \right] \\ = B^{\mu n \Delta t} e^{ikm\Delta x} \end{aligned} \right\} \quad (18.5)$$

Dividing throughout Eq.(18.5) with $B^{\mu(n-1)\Delta t} e^{ikm\Delta x}$

$$\begin{aligned} B^{\mu \Delta t} \left[1 + \frac{\lambda}{2} \{ e^{ik\Delta x} - e^{-ik\Delta x} \} \right] &= 1 \\ B^{\mu \Delta t} [1 + i\lambda \sin(k\Delta x)] &= 1 \end{aligned}$$

$$\begin{aligned} B^{\mu \Delta t} &= \frac{1}{[1 + i\lambda \sin(k\Delta x)]} \\ |B^{\mu \Delta t}| &= \frac{[1 - i\lambda \sin(k\Delta x)]}{[1 + \lambda^2 \sin^2(k\Delta x)]} \\ |B^{\mu \Delta t}|^2 &= \frac{[1 + \lambda^2 \sin^2(k\Delta x)]}{[1 + \lambda^2 \sin^2(k\Delta x)]^2} \\ |B^{\mu \Delta t}|^2 &= \frac{1}{[1 + \lambda^2 \sin^2(k\Delta x)]} < 1 \end{aligned}$$

Therefore this scheme is **Stable**.

18.2 Upwind/Upstream Scheme

$$\frac{\partial f}{\partial t} + c \frac{\partial f}{\partial x} = 0 \quad (18.6)$$

Let $c > 0, x \rightarrow m, t \rightarrow n$,

Solve Eq.(18.6) using FTBS (Forward in Time, Backward in Space) scheme;

$$\frac{f_{m,n+1} - f_{m,n}}{\Delta t} = -c \left[\frac{f_{m,n} - f_{m-1,n}}{\Delta x} \right] \quad (18.7)$$

Let $\lambda = c \frac{\Delta t}{\Delta x}$;

Explicit finite difference scheme

$$f_{m,n+1} = (1 - \lambda) f_{m,n} + \lambda f_{m-1,n} \quad (18.8)$$

For stability analysis;

$$\varepsilon_{m,n+1} = (1 - \lambda) \varepsilon_{m,n} + \lambda \varepsilon_{m-1,n} \quad (18.9)$$

Let $\varepsilon_{m,n} = B^{\mu n \Delta t} e^{ikm \Delta x}$

$$\left. \begin{aligned} B^{\mu(n+1)\Delta t} e^{ikm\Delta x} &= (1 - \lambda) B^{\mu n \Delta t} e^{ikm\Delta x} \\ &+ \lambda B^{\mu(n+1)\Delta t} e^{ik(m-1)\Delta x} \end{aligned} \right\} \quad (18.10)$$

Dividing throughout Eq.(18.10) with $B^{\mu n \Delta t} e^{ikm\Delta x}$

$$\begin{aligned} B^{\mu \Delta t} &= (1 - \lambda) + \lambda e^{-ik\Delta x} \\ B^{\mu \Delta t} &= (1 - \lambda) + \lambda (\cos(k\Delta x) - i \sin(k\Delta x)) \\ B^{\mu \Delta t} &= [1 - \lambda(1 - \cos(k\Delta x))] - i\lambda \sin(k\Delta x) \\ |B^{\mu \Delta t}|^2 &= [1 - \lambda(1 - \cos(k\Delta x))]^2 + [\lambda \sin(k\Delta x)]^2 \\ |B^{\mu \Delta t}|^2 &= 1 + 2\lambda(\lambda - 1)(1 - \cos(k\Delta x)) \end{aligned} \quad (18.11)$$

Since, $-1 \leq \cos(k\Delta x) \leq 1$

For $\cos(k\Delta x) = 1$

$$|B^{\mu \Delta t}|^2 = 1 + 2\lambda(\lambda - 1)(1 - 1) = 1$$

For $\cos(k\Delta x) = -1$

$$|B^{\mu \Delta t}|^2 = 1 + 2\lambda(\lambda - 1)(1 + 1)$$

$$|B^{\mu \Delta t}|^2 = 1 + 4\lambda(\lambda - 1), \begin{cases} = 1, & \text{if } \lambda = 1, \\ > 1, & \text{if } \lambda > 1, \\ \in (0, 1), & \text{if } \lambda \in (0, 1) \end{cases}$$

Therefore this scheme is **Stable** only for λ from 0 to 1.

19. Lecture 19 17/02/2025

19.1 1-D Advection Equation

$$f(x) + A \sin\left(\frac{2\pi x}{L}\right) = 0 \quad (19.1)$$

$$\frac{\partial f}{\partial t} + \frac{2\pi}{L} A \cos\left(\frac{2\pi x}{L}\right) = 0 \quad (19.2)$$

Finite difference method for the first derivation using central differencing scheme

$$\begin{aligned} \frac{df}{dx} &= \frac{f(x+\Delta x) - f(x-\Delta x)}{2\Delta x} \\ \frac{df}{dx} &= \frac{A}{2\Delta x} \left[\sin\left(\frac{2\pi(x+\Delta x)}{L}\right) - \sin\left(\frac{2\pi(x-\Delta x)}{L}\right) \right] \\ \frac{df}{dx} &= \frac{A}{2\Delta x} \left[2 \cos\left(\frac{2\pi x}{L}\right) \sin\left(\frac{2\pi\Delta x}{L}\right) \right] \\ \frac{df}{dx} &= \frac{A}{\Delta x} \cos\left(\frac{2\pi x}{L}\right) \sin\left(\frac{2\pi\Delta x}{L}\right) \\ \frac{df}{dx} &= A \cos\left(\frac{2\pi x}{L}\right) \frac{\sin\left(\frac{2\pi\Delta x}{L}\right)}{\Delta x} \\ \frac{df}{dx} &= \underbrace{\frac{2\pi A}{L} \cos\left(\frac{2\pi x}{L}\right)}_{\text{constant (say } A')} \frac{\sin\left(\frac{2\pi\Delta x}{L}\right)}{\left(\frac{2\pi\Delta x}{L}\right)} \\ \frac{df}{dx} &= A' \frac{\sin\left(\frac{2\pi\Delta x}{L}\right)}{\left(\frac{2\pi\Delta x}{L}\right)} \end{aligned}$$

$$\frac{df}{dx} = \begin{cases} 1 \times \left(\frac{2\pi A}{L} \cos\left(\frac{2\pi x}{L}\right)\right) & , \text{ when } \Delta x \rightarrow 0 \\ 0 \times \left(\frac{2\pi A}{L} \cos\left(\frac{2\pi x}{L}\right)\right) & , \text{ when } \Delta x = 1/2 \end{cases}$$

If $c < 0$ space difference is forward.

$$c \left(\frac{\Delta t}{\Delta x} \right) \rightarrow \text{Courant No.}$$

When analytical solution coincide with numerical solution.

$$c \left(\frac{\Delta t}{\Delta x} \right) = 1$$

When numerical domain of dependence contains all analytical domain of dependence. **(Stable)**

$$c \left(\frac{\Delta t}{\Delta x} \right) < 1$$

When analytical domain of dependence contains all numerical domain of dependence. **(Unstable)**

$$c \left(\frac{\Delta t}{\Delta x} \right) > 1$$

Figures for these conditions

For stable solution

$$\text{Time step} \leftarrow \Delta t < \frac{\Delta x}{c} \rightarrow \text{Grid size} \rightarrow \text{Speed of analytical wave}$$

Δt choosen must be less than $\Delta x/c$ which is the time taken for wave to travel distance Δx .

19.2 Transportative Properties

Consider Advection equation:

$$\frac{\partial f}{\partial t} + c \frac{\partial f}{\partial x} = 0 \quad (19.3)$$

1. FTCS scheme, for $c > 0$

$$\frac{f_{m,n+1} - f_{m,n}}{\Delta t} = -c \left[\frac{f_{m+1,n} - f_{m-1,n}}{2\Delta x} \right]$$

Let us introduce disturbance (δ) at point x corresponding to index m at time index n .

- changing $m \rightarrow m+1$

$$\begin{aligned} \frac{f_{m+1,n+1} - f_{m+1,n}}{\Delta t} &= -c \left[\frac{f_{m+2,n} - f_{m,n}}{2\Delta x} \right] \\ \frac{f_{m+1,n+1} - f_{m+1,n}}{\Delta t} &= -\frac{c}{2\Delta x} [0 - \delta] \\ \frac{f_{m+1,n+1} - f_{m+1,n}}{\Delta t} &= \frac{c\Delta t}{2\Delta x} \delta \\ \frac{f_{m+1,n+1}}{\Delta t} &= \lambda \delta \end{aligned} \quad (19.4)$$

Disturbance propagated from m to $m+1$ with time from n to $n+1$.

- changing $m \rightarrow m-1$

$$\begin{aligned} \frac{f_{m-1,n+1} - f_{m-1,n}}{\Delta t} &= -c \left[\frac{f_{m,n} - f_{m-2,n}}{2\Delta x} \right] \\ \frac{f_{m-1,n+1}}{\Delta t} &= -\frac{c\Delta t}{2\Delta x} [\delta - 0] \\ \frac{f_{m-1,n+1}}{\Delta t} &= -\lambda \delta \end{aligned} \quad (19.5)$$

Disturbance propagated from m to $m-1$ with time from n to $n+1$.

Which is wrong. Since it is FTCS, disturbance should propagate only in forward direction. Therefore Scheme is **Unstable**.

2. Upwind scheme/ Upstream scheme, for $c > 0$

$$\frac{f_{m,n+1} - f_{m,n}}{\Delta t} = -c \left[\frac{f_{m,n} - f_{m-1,n}}{2\Delta x} \right]$$

Let us disturbance (δ) at x point corresponding to m index at time index n .

- changing $m \rightarrow m + 1$

$$\begin{aligned} \frac{f_{m+1,n+1} - f_{m+1,n}}{\Delta t} &= -c \left[\frac{f_{m+1,n} - f_{m,n}}{\Delta x} \right] \\ \frac{f_{m+1,n+1}}{\Delta t} &= -\frac{c}{\Delta x} [0 - \delta] \\ f_{m+1,n+1} &= \frac{c\Delta t}{\Delta x} \delta \\ f_{m+1,n+1} &= \lambda \delta \end{aligned} \quad (19.6)$$

Disturbance propagated from m to $m + 1$ with time from n to $n + 1$.

- changing $m \rightarrow m - 1$

$$\begin{aligned} \frac{f_{m-1,n+1} - f_{m-1,n}}{\Delta t} &= -c \left[\frac{f_{m-1,n} - f_{m-2,n}}{2\Delta x} \right] \\ f_{m-1,n+1} &= -\frac{c\Delta t}{2\Delta x} [0 - 0] \\ f_{m-1,n+1} &= 0 \end{aligned} \quad (19.7)$$

No disturbance propagated from m to $m - 1$ with time from n to $n + 1$.

Which is as expected. Therefore Scheme is **Stable**.

20. Lecture 20 24/02/2025

20.1 Lax Wandroff Scheme

Consider 1-D Advection equation,

$$\frac{\partial f}{\partial t} + c \frac{\partial f}{\partial x} = 0 \quad (20.1)$$

Differentiating Eq.(20.1) w.r.t time t,

$$\frac{\partial^2 f}{\partial t^2} + c \frac{\partial^2 f}{\partial x \partial t} = 0 \quad (20.2)$$

Substituting for $\frac{\partial f}{\partial t}$ from Eq.(20.1) in Eq.(20.2), we obtain;

$$\frac{\partial^2 f}{\partial t^2} - c^2 \frac{\partial^2 f}{\partial x^2} = 0 \quad (20.3)$$

On RHS replace time derivative with space derivative and apply CTCS scheme;

$$\begin{aligned} f(x, t + \Delta t) &= f(x, t) + \Delta t \left(-c \frac{\partial f}{\partial x} \right) \\ &\quad + \frac{(\Delta t)^2}{2!} \left(c^2 \frac{\partial^2 f}{\partial x^2} \right) + \dots \\ f(x, t + \Delta t)_{m,n} &= f(x, t)_{m,n} - c \Delta t \left(\frac{\partial f}{\partial x} \right)_{m,n} \\ &\quad + \frac{c^2 (\Delta t)^2}{2!} \left(\frac{\partial^2 f}{\partial x^2} \right)_{m,n} + \dots \\ f_{m,n+1} &= f_{m,n} - c \Delta t \left[\frac{f_{m+1,n} - f_{m-1,n}}{2\Delta x} \right] \\ &\quad + \frac{c^2 (\Delta t)^2}{2!} \left[\frac{f_{m+1,n} - 2f_{m,n} + f_{m-1,n}}{(\Delta x)^2} \right] \\ f_{m,n+1} &= \left[1 - \frac{c^2 (\Delta t)^2}{(\Delta x)^2} \right] f_{m,n} \\ &\quad - \frac{c (\Delta t)^2}{2\Delta x} \left[-1 + \frac{c \Delta t}{\Delta x} \right] f_{m+1,n} \\ &\quad + \frac{c (\Delta t)}{2\Delta x} \left[\frac{c \Delta t}{\Delta x} + 1 \right] f_{m-1,n} \end{aligned}$$

Let $\lambda = c \frac{\Delta t}{\Delta x}$;

$$\begin{aligned} f_{m,n+1} &= [1 - \lambda^2] f_{m,n} - \frac{\lambda}{2} [-1 + \lambda] f_{m+1,n} \\ &\quad + \frac{\lambda}{2} [\lambda + 1] f_{m-1,n} \\ f_{m,n+1} &= (1 - \lambda^2) f_{m,n} - \frac{(\lambda^2 - \lambda)}{2} f_{m+1,n} \\ &\quad + \frac{(\lambda^2 + \lambda)}{2} f_{m-1,n} \end{aligned}$$

For stability analysis;

$$\begin{aligned} \epsilon_{m,n+1} &= (1 - \lambda^2) \epsilon_{m,n} - \frac{(\lambda^2 - \lambda)}{2} \epsilon_{m+1,n} \\ &\quad + \frac{(\lambda^2 + \lambda)}{2} \epsilon_{m-1,n} \end{aligned}$$

fix this there should be + for 2nd term

Let $\epsilon_{m,n} = B^{\mu \Delta t} e^{ikm\Delta x}$

$$\begin{aligned} B^{\mu(n+1)\Delta t} e^{ikm\Delta x} &= (1 - \lambda^2) B^{\mu n \Delta t} e^{ikm\Delta x} \\ &\quad - \frac{(\lambda^2 - \lambda)}{2} B^{\mu n \Delta t} e^{ik(m+1)\Delta x} \\ &\quad + \frac{(\lambda^2 + \lambda)}{2} B^{\mu n \Delta t} e^{ik(m-1)\Delta x} \end{aligned}$$

Dividing throughout Eq.(0) with $B^{\mu n \Delta t} e^{ikm\Delta x}$

$$\begin{aligned} B^{\mu \Delta t} &= (1 - \lambda^2) - \frac{(\lambda^2 - \lambda)}{2} e^{ik\Delta x} \\ &\quad + \frac{(\lambda^2 + \lambda)}{2} e^{-ik\Delta x} \\ B^{\mu \Delta t} &= (1 - \lambda^2) - \frac{\lambda^2}{2} (2 \cos(k\Delta x)) \\ &\quad + \frac{\lambda}{2} (2i \sin(k\Delta x)) \\ B^{\mu \Delta t} &= (1 - \lambda^2) - \lambda^2 \cos(k\Delta x) + i\lambda \sin(k\Delta x) \\ |B^{\mu \Delta t}|^2 &= ((1 - \lambda^2) - \lambda^2 \cos(k\Delta x))^2 + (\lambda \sin(k\Delta x))^2 \\ |B^{\mu \Delta t}|^2 &= (1 - \lambda^2)^2 - \lambda^4 \cos^2(k\Delta x) + \lambda^2 \sin^2(k\Delta x) \\ &\quad + 2\lambda^2(1 - \lambda^2) \cos(k\Delta x) \end{aligned}$$

Amplification factor:

$$G = \left| \frac{\epsilon_{m,n}}{\epsilon_{m,n-1}} \right| = |B^{\mu \Delta t}| \begin{cases} > 1 & \text{for } \lambda > 0 \\ = 1 & \text{for } \lambda = 0 \\ < 1 & \text{for } \lambda < 0 \end{cases}$$

This scheme provide 2^{nd} order accuracy in time and as well as in space, i.e. from $\frac{\partial^2 f}{\partial x^2}$ term.

Limitations of Lax Wandroff scheme:

- This scheme is applicable only to **Linear PDE**.
- This scheme didn't account for **Boundary conditiions**.

References