

DELHI TECHNOLOGICAL UNIVERSITY



DATABASE MANAGEMENT SYSTEM

MC 209

THIRD SEMESTER (2024-2025)

Submitted to:

Prof. Brij Kishore Tyagi

&

Ms. Shweta Kalson

Submitted by:

Himanshu

23/MC/65

INDEX

S. No.	Experiment	Date	Signature
1	Synopsis of the Project, along with its E-R Diagram.	12-08-2024	
2	Implementation of the DDL statements : 1. Create 2. Create table with constraints 3. Alter Table a. Add column b. Drop column c. Add/Drop constraint d. Rename column 4. Drop Table	02-09-2024	
3	Implementation of the DML statements : 1. Insert 2. Update 3. Delete 4. Truncate	09-09-2024	
4	Implementation of the SELECT statements : 1. Simple SELECT statement 2. Where clause + IN/NOT IN 3. Aggregate functions 4. Group by + Having 5. Order by 6. Views 7. Inbuilt function	16-09-2024	
5	Implement and perform Nested Queries along with Joins .	30-09-2024	
6	Introduction to PL/SQL . Create a PL/SQL block and implement the following: 1. Variables 2. Packages 3. Procedures 4. Functions	07-10-2024	
7	Perform Exception handling in a PL/SQL block.	07-10-2024	
8	Project Report with Code and Screenshots.	14-09-2024	
9	Implement Triggers in SQL.	14-09-2024	
10	Implement the following transaction statements: 1. Commit 2. Rollback 3. Savepoint	21-10-2024	

DBMS PROJECT

ON

RAILWAY MANAGEMENT SYSTEM

Experiment 1

Aim: Synopsis of the Project, along with its E-R Diagram.

Project Title: Railway System Database Management

Project Synopsis:

The Railway System Database Management project is dedicated to developing a sophisticated database for managing India's extensive railway network. The primary goal is to create a structured, relational database that streamlines user management, passenger reservations, train schedules, ticketing, and more.

Objective:

To design and implement a relational database that supports efficient data storage, retrieval, and management for various aspects of the railway system. This project ensures data integrity, consistency, and security, providing a solid foundation for railway operations.

Scope:

The database encompasses tables for Users, Passengers, Trains, Stations, Tickets, and Train Status. Relationships between these entities are established to reflect real-world interactions, such as booking tickets, train schedules, and station stops.

Entities and Attributes:

1. **Users:** UserID, Password, FirstName, LastName, Gender, Age, Email, AadharNumber, MobileNumber, City, State, PinCode, SecurityQuestion, SecurityAnswer.
2. **Passengers:** PassengerID, Name, Gender, Age, PnrNumber, SeatNumber, BookedBy, ReservationStatus.

3. **Trains:** TrainNumber, TrainName, Source, Destination, ArrivalTime, DepartureTime, AvailabilityOfSeats, Date.
4. **Stations:** StationNumber, Name, TrainNumber, ArrivalTime, Hault.
5. **Tickets:** TicketID, TrainNumber, BookedUser, Status, NumberOfPassengers.
6. **Train Status:** TrainNumber, A_Seats1, A_Seats2, A_Seats3, B_Seats1, B_Seats2, B_Seats3, W_Seats1, W_Seats2, W_Seats3, Fare1, Fare2, Fare3.


Relationships:

1. **Cancel:** Between User (one) and Ticket (one).
2. **Books:** Between User (one), Passenger (many), and Ticket (many).
3. **Starts:** Between Train and Station.
4. **Stops At:** Between Train and Station.
5. **Reaches:** Between Train and Station.
6. **Source:** Between Ticket and Station.
7. **Destination:** Between Ticket and Station.

Conclusion:

This project delivers a robust and scalable database management system that enhances the efficiency of railway operations in India. By providing accurate data management and seamless integration of railway functions, it significantly contributes to the modernization and optimization of the Indian railway system.


E-R Diagram:



Experiment 2

Aim: Implementation of the DDL statements:

a) Create



The screenshot displays a SQL IDE interface. The top pane shows a SQL script for creating a table and inserting data. The bottom pane shows the result of a query, displaying 4 records from the 'trains' table.

SQL Script:

```
1 -- Question 2(a): Create Table
2
3 USE railway_management_system;
4
5 CREATE TABLE Trains (
6     TrainNumber INT PRIMARY KEY,
7     TrainName VARCHAR(100),
8     Source VARCHAR(100),
9     Destination VARCHAR(100),
10    ArrivalTime TIME,
11    DepartureTime TIME,
12    AvailabilityOfSeats INT,
13    Date DATE
14 );
```

Query Result:

TrainNumber	TrainName	Source	Destination	ArrivalTime	DepartureTime	AvailabilityOfSeats	Date
12011	Shatabdi Express	New Delhi	Kalka	11:40:00	07:40:00	500	2024-11-03
12050	Gatimaan Express	Hazrat Nizamuddin Delhi	Virangana Lakshmi Bai Jhansi Junction	08:10:00	12:45:00	715	2024-11-03
12301	Rajdhani Express	Howrah Jn	New Delhi	10:05:00	16:50:00	715	2024-11-03
22435	Vande Bharat	Varanasi Jn	New Delhi	14:30:00	15:00:00	1440	2024-11-03

b) Create table with constraints

```
1 -- Q2 (b) Create table with constraints (Not NULL, UNIQUE, DEFAULT, CHECK, PRIMARY KEY, FOREIGN KEY)
2
3 USE railway_management_system;
4
5 CREATE TABLE users (
6     UserID INT PRIMARY KEY,
7     Username VARCHAR(50) NOT NULL UNIQUE,
8     Password VARCHAR(255) NOT NULL,
9     Age INT DEFAULT 18,
10    Email VARCHAR(100),
11    CHECK (Age >= 18),
12    City VARCHAR(100),
13    State VARCHAR(100),
14    PinCode VARCHAR(6),
15    AadharNumber VARCHAR(12) UNIQUE,
16    FOREIGN KEY (City, State) REFERENCES Locations(City, State)
17 );
```

VsConnect: 4 records on 'users' table X

UserID	Password	FirstName	LastName	Gender	Age	Email	AadharNumber	MobileNumber
1123	Himanshu@123	Himanshu	Kumar	M	20	Himanshu@gmail.com	01123	9958
2123	Heemant@123	Heemant	Saini	M	20	Heemant@gmail.com	02123	8859
3123	Deepak@123	Deepak	Chaudhary	M	21	Deepak@gmail.com	03123	9087
4123	Himanshi@123	Himanshi	Sharma	F	19	Himashi@gmail.com	04123	8844

c) Alter table

1. Add column

MobileNumber	City	State	PinCode	SecurityQuestion	SecurityAnswer	DateOfBirth
9958	Uttam Nagar	New Delhi	110059	Who are you	Himanshu	NULL
8859	Pashcim Vihar	Delhi	110039	Who are you	Heemant	NULL
9087	Govindpuri	Delhi	110039	Who are you	Deepak	NULL
8844	Keshavpur	Delhi	110099	Who are you	Himanshi	NULL

2. Drop column

MobileNumber	City	State	PinCode	SecurityQuestion	SecurityAnswer
9958	Uttam Nagar	New Delhi	110059	Who are you	Himanshu
8859	Pashcim Vihar	Delhi	110039	Who are you	Heemant
9087	Govindpuri	Delhi	110039	Who are you	Deepak
8844	Keshavpur	Delhi	110099	Who are you	Himanshi

3. Add/Drop constraint

VsConnect: 4 records on 'users' table X

UserID	Password	FirstName	LastName	Gender	Age	Email	AadharNumber	MobileNumber
1123	Himanshu@123	Himanshu	Kumar	M	20	Himanshu@gmail.com	01123	9958
2123	Heemant@123	Heemant	Saini	M	20	Heemant@gmail.com	02123	8859
3123	Deepak@123	Deepak	Chaudhary	M	21	Deepak@gmail.com	03123	9087
4123	Himanshi@123	Himanshi	Sharma	F	19	Himashi@gmail.com	04123	8844

4. Rename column

VsConnect: 4 records on 'users' table X

UserID	Password	First_Name	LastName	Gender	Age	Email	AadharNumber	MobileNumber
1123	Himanshu@123	Himanshu	Kumar	M	20	Himanshu@gmail.com	01123	9958
2123	Heemant@123	Heemant	Saini	M	20	Heemant@gmail.com	02123	8859
3123	Deepak@123	Deepak	Chaudhary	M	21	Deepak@gmail.com	03123	9087
4123	Himanshi@123	Himanshi	Sharma	F	19	Himashi@gmail.com	04123	8844

Experiment 3

Aim: Implementation of the DML statements:

a) Insert

```
1  -- Question 3(a): Insert
2
3  INSERT INTO trains (
4      TrainNumber,
5      TrainName,
6      Source,
7      Destination,
8      ArrivalTime,
9      DepartureTime,
10     AvailabilityOfSeats,
11     Date
12 )
13 VALUES (
14     12301,
15     'Rajdhani Express',
16     'Howrah Jn',
17     'New Delhi',
18     '10:05',
19     '16:50',
20     715,
21     '2024-11-03'
22 );
23
24 INSERT INTO trains (
25     TrainNumber,
26     TrainName,
27     Source,
28     Destination,
29     ArrivalTime,
30     DepartureTime,
31     AvailabilityOfSeats,
32     Date
33 )
34 VALUES (
35     22435,
36     'Vande Bharat',
37     'Varanasi Jn',
38     'New Delhi',
39     '14L40',
40     '15:00',
41     1440,
42     '2024-11-03'
43 );
```


VsConnect: 4 records on 'trains' table X

TrainNumber	TrainName	Source	Destination	ArrivalTime	DepartureTime	AvailabilityOfSe...	Date
12011	Shatabdi Express	New Delhi	Kalka	11:40:00	07:40:00	500	2024-11-03
12050	Gatimaan Express	Hazrat Nizamuddin Delhi	Virangana Lakshmibai Jhasi Junction	08:10:00	12:45:00	715	2024-11-03
12301	Rajdhani Express	Howrah Jn	New Delhi	10:05:00	16:50:00	715	2024-11-03
22435	Vande Bharat	Varanasi Jn	New Delhi	14:30:00	15:00:00	1440	2024-11-03

b) Update

Project > Q3b.sql

Run on active connection | Select block

```

1  -- Question 3(b): Update
2
3  USE railway_management_system;
4
5  UPDATE trains
6  SET Destination = 'Sri Lanka'
7  WHERE TrainNumber = 12301

```

TrainNumber	TrainName	Source	Destination	ArrivalTime ↑	DepartureTime	AvailabilityOfSe...	Date
12011	Shatabdi Express	New Delhi	Kalka	11:40:00	07:40:00	500	2024-11-03
12050	Gatimaan Express	Hazrat Nizamuddin Delhi	Virangana Lakshmibai Jhasi Junction	08:10:00	12:45:00	715	2024-11-03
12301	Rajdhani Express	Howrah Jn	Sri Lanka	10:05:00	16:50:00	715	2024-11-03

c) Delete

Project > Q3c.sql

Run on active connection | Select block

```

1  -- Question 3(c): Delete
2
3  USE railway_management_system;
4
5  DELETE FROM trains WHERE TrainNumber = 22435;

```

TrainNumber	TrainName	Source	Destination	ArrivalTime	DepartureTime	AvailabilityOfSe...	Date
12011	Shatabdi Express	New Delhi	Kalka	11:40:00	07:40:00	500	2024-11-03
12050	Gatimaan Express	Hazrat Nizamuddin Delhi	Virangana Lakshmibai Jhasi Junction	08:10:00	12:45:00	715	2024-11-03
12301	Rajdhani Express	Howrah Jn	Sri Lanka	10:05:00	16:50:00	715	2024-11-03

d) Truncate

Q3d.sql ×

Project > Q3d.sql

Run on active connection | Select block

```
1  -- Question 3(d): Truncate
2
3  USE railway_management_system;
4
5  CREATE TABLE SampleTable2 (
6      ID INT,
7      Name VARCHAR(100)
8  );
9
10 INSERT INTO sampletable2 (ID, Name)
11 VALUES (1, 'Deepak');
12
13 INSERT INTO sampletable2 (ID, Name)
14 VALUES (2, 'Himanshu');
15
16 INSERT INTO sampletable2 (ID, Name)
17 VALUES (3, 'Heemant');
18
19 INSERT INTO sampletable2 (ID, Name)
20 VALUES (4, 'Devansh');
21
22 -- Query
23 TRUNCATE TABLE sampletable2;
```

VsConnect: 4 records on 'sampletable2' table ×

ID	Name
abc Filter...	abc Filter...
1	Deepak
2	Himanshu
3	Heemant
4	Devansh

VsConnect: 0 records on 'sampletable2' table ×

ID	Name
abc Filter...	abc Filter...
No data	

Experiment 4

Aim: Implementation of the SELECT statements:

a) Simple SELECT statement

Q4a.sql ×

Project > Q4a.sql

▶ Run on active connection | Select block

```
1 -- Question 4(a): Simple Select Statement
2
3 SELECT TrainNumber, TrainName FROM trains;
```

VsConnect: SELECT TrainNumb... ×

TrainNumber	TrainName
abc Filter...	abc Filter...
12011	Shatabdi Express
12050	Gatimaan Express
12301	Rajdhani Express

b) Where clause + IN/NOT IN

Q4b.sql ×

Project > Q4b.sql

▶ Run on active connection | Select block

```
1 -- Question 4(b): Where clause + in/not in statement
2
3 -- where clause + in statement
4 SELECT * FROM users
5 WHERE Gender IN('M');
6
7 -- where clause + not in statement
8 SELECT * FROM users
9 WHERE Gender NOT IN('M');
```

-- Question 4(b): Where clause + in/not in...

-- where clause + not in statement SELEC...

UserID	Password	First_Name	LastName	Gender	Age	Email	AadharNumber
abc Filter...	abc Filter...	abc Filter...	abc Filter...	abc Filter...	abc Filter...	abc Filter...	abc Filter...
4123	Himanshi@123	Himanshi	Sharma	F	19	Himashi@gmail.com	04123

-- Question 4(b): Where clause + in/not in...		-- where clause + not in statement SELEC...					
UserID	Password	First_Name	LastName	Gender	Age	Email	AadharNumber
1123	Himanshu@123	Himanshu	Kumar	M	20	Himanshu@gmail.com	01123
2123	Heemant@123	Heemant	Saini	M	20	Heemant@gmail.com	02123
3123	Deepak@123	Deepak	Chaudhary	M	21	Deepak@gmail.com	03123

c) Aggregate functions

```

Q4c.sql
Project > Q4c.sql
Run on active connection | Select block
1  -- Question 4(c): Aggregate functions
2
3  -- 1: Min
4  SELECT MIN(Age) AS YoungestUser FROM users;
5
6  -- 2: Max
7  SELECT MAX(Age) AS HighestAge FROM users;
8
9  -- 3: Count
10 SELECT COUNT(*) AS TotalUsers FROM users;
11
12 -- 4: Sum
13 SELECT SUM(Age) AS TotalAge FROM users;
14
15 -- 5: Average
16 SELECT AVG(Age) AS AverageAge FROM users;

```

VsConnect: multiple query results X	
-- Question 4(c): Aggregate functions -- 1: ...	
YoungestUser	
Filter...	
19	

VsConnect: multiple query results X	
-- Question 4(c): Aggregate functions -- 1: ...	
-- 2: Max SELECT MAX(Age) AS HighestAg...	
HighestAge	
Filter...	
21	

VsConnect: multiple query results X	
-- Question 4(c): Aggregate functions -- 1: ...	
-- 2: Max SELECT MAX(Age) AS HighestAg...	
-- 3: Count SELECT COUNT(*) AS TotalUse...	
TotalUsers	
Filter...	
4	

VsConnect: multiple query results X

-- Questin 4(c): Aggregate functions -- 1: ...

TotalAge
abc Filter...
80

VsConnect: multiple query results X

< I(c): Aggregate functions -- 1: ... --

AverageAge
abc Filter...
20.0000

d) Group by + Having

Q4d.sql X

Project > Q4d.sql

Run on active connection | Select block

```

1 -- Question 4(d): Group by + having statement
2
3 SELECT Department, sum(Salary) as Salary
4 FROM Employee
5 GROUP BY department
6 HAVING SUM(Salary) >= 50000;

```

VsConnect: -- Question 4(d)... X

Department	Salary
abc Filter...	abc Filter...
IT	95000
Sales	65000
Marketing	55000
Finance	75000

e) Order by

Q4e.sql X Q4f.sql Q4g.sql

Project > Q4e.sql

Run on active connection | Select block

```

1 -- Question 4(e): Order by
2
3 SELECT ArrivalTime, trainNumber, TrainName
4 FROM trains
5 ORDER BY TrainNumber

```

VsConnect: -- Question 4(e)... X

ArrivalTime	trainNumber	TrainName
Filter...	Filter...	Filter...
11:40:00	12011	Shatabdi Express
08:10:00	12050	Gatimaan Express
10:05:00	12301	Rajdhani Express

f) Views

```

1  -- Question 4(f): Views
2
3  CREATE TABLE Customers (
4      CustomerID INT PRIMARY KEY,
5      FirstName VARCHAR(100),
6      LastName VARCHAR(100),
7      Email VARCHAR(100)
8  );
9
10 CREATE TABLE Orders (
11     OrderID INT PRIMARY KEY,
12     CustomerID INT,
13     OrderDate DATE,
14     Amount DECIMAL(10, 2),
15     FOREIGN KEY (CustomerID) REFERENCES Customers(CustomerID)
16 );
17
18 INSERT INTO Customers (CustomerID, FirstName, LastName, Email) VALUES
19 (1, 'John', 'Doe', 'john.doe@example.com'),
20 (2, 'Jane', 'Smith', 'jane.smith@example.com');
21
22 INSERT INTO Orders (OrderID, CustomerID, OrderDate, Amount) VALUES
23 (101, 1, '2024-01-15', 250.50),
24 (102, 2, '2024-02-10', 150.75),
25 (103, 1, '2024-03-05', 300.00);
26
27 CREATE VIEW CustomerOrders AS
28 SELECT
29     Customers.CustomerID, Customers.FirstName, Customers.LastName, Customers.Email,
30     Orders.OrderID, Orders.OrderDate, Orders.Amount
31 FROM
32     Customers
33 JOIN
34     Orders ON Customers.CustomerID = Orders.CustomerID;
35
36 SELECT * FROM CustomerOrders;

```

VsConnect: SELECT * FROM Cu... X

CustomerID	FirstName	LastName	Email	OrderID	OrderDate	Amount
Filter...	Filter...	Filter...	Filter...	Filter...	Filter...	Filter...
1	John	Doe	john.doe@example.com	101	2024-01-15	250.50
1	John	Doe	john.doe@example.com	103	2024-03-05	300.00
2	Jane	Smith	jane.smith@example.com	102	2024-02-10	150.75

Experiment 5

Aim: Implement and perform Nested Queries along with Joins (Inner join, Outer join, Left join, Right join).

Nested Queries

Project > Q5.sql

Run on active connection | Select block

```
1 -- Question 5: Nested Queries along with Joins (Inner join, Outer join, Left join, Right join)
2
3 -- Nested Queries
4 SELECT CustomerID, FirstName, LastName, Email
5 FROM Customers
6 WHERE CustomerID IN (
7     SELECT CustomerID
8     FROM Orders
9     WHERE Amount > (
10         SELECT AVG(Amount)
11         FROM Orders
12     )
13 );
14
```

CustomerID	FirstName	LastName	Email
abc Filter...	abc Filter...	abc Filter...	abc Filter...
1	John	Doe	john.doe@example.com
2	Jane	Smith	jane.smith@example.com

Inner Join

Q5.sql X

Project > Q5.sql

Run on active connection | Select block

```
1 -- Question 5: Nested Queries along with Joins (Inner join, Outer join, Left join, Right join)
2
3 -- Inner Joins
4
5 SELECT
6     Customers.CustomerID, Customers.FirstName, Customers.LastName, Customers.Email,
7     Orders.OrderID, Orders.OrderDate, Orders.Amount
8 FROM
9     Customers
10 INNER JOIN
11     Orders ON Customers.CustomerID = Orders.CustomerID;
```


VsConnect: SELECT Cus... X						
CustomerID	FirstName	LastName	Email	OrderID	OrderDate	Amount
abc Filter...	abc Filter...	abc Filter...	abc Filter...	abc Filter...	abc Filter...	abc Filter...
1	John	Doe	john.doe@example.com	101	2024-01-15	250.50
1	John	Doe	john.doe@example.com	102	2024-02-10	150.75
2	Jane	Smith	jane.smith@example.com	103	2024-03-05	300.00
3	Bob	Brown	bob.brown@example.com	104	2024-03-15	120.00

Outer Join

```

Project > Q5.sql
  Run on active connection | Select block
1  -- Question 5: Nested Queries along with Joins (Inner join, Outer join, Left join, Right join)
2
3  -- Outer Joins
4
5  SELECT
6      Customers.CustomerID, Customers.FirstName, Customers.LastName, Customers.Email,
7      Orders.OrderID, Orders.OrderDate, Orders.Amount
8  FROM
9      Customers
10 LEFT JOIN
11     Orders ON Customers.CustomerID = Orders.CustomerID;

```

VsConnect: SELECT Cus... X						
CustomerID	FirstName	LastName	Email	OrderID	OrderDate	Amount
abc Filter...	abc Filter...	abc Filter...	abc Filter...	abc Filter...	abc Filter...	abc Filter...
1	John	Doe	john.doe@example.com	NULL	NULL	NULL
2	Jane	Smith	jane.smith@example.com	NULL	NULL	NULL

Left Join

```

Project > Q5.sql
  Run on active connection | Select block
1  -- Question 5: Nested Queries along with Joins (Inner join, Outer join, Left join, Right join)
2
3  -- Left Joins
4
5  SELECT
6      Customers.CustomerID, Customers.FirstName, Customers.LastName, Customers.Email,
7      Orders.OrderID, Orders.OrderDate, Orders.Amount
8  FROM
9      Customers
10 LEFT JOIN
11     Orders ON Customers.CustomerID = Orders.CustomerID;
12

```


VsConnect: SELECT Cus... X

CustomerID	FirstName	LastName	Email	OrderID	OrderDate	Amount
<div>abc Filter...</div>	<div>abc Filter...</div>	<div>abc Filter...</div>	<div>abc Filter...</div>	<div>abc Filter...</div>	<div>abc Filter...</div>	<div>abc Filter...</div>
1	John	Doe	john.doe@example.com	101	2024-01-15	250.50
1	John	Doe	john.doe@example.com	102	2024-02-10	150.75
2	Jane	Smith	jane.smith@example.com	NULL	NULL	NULL
3	Bob	Brown	bob.brown@example.com	103	2024-03-05	300.00

Right Join

Project > Q5.sql

Run on active connection | Select block

1

-- Question 5: Nested Queries along with Joins (Inner join, Outer join, Left join, Right join)

2

3

-- Right Joins

4

5

SELECT

6

Customers.CustomerID, Customers.FirstName, Customers.LastName, Customers.Email,

7

Orders.OrderID, Orders.OrderDate, Orders.Amount

8

FROM

9

Customers

10

RIGHT JOIN

11

Orders ON Customers.CustomerID = Orders.CustomerID;

CustomerID	FirstName	LastName	Email	OrderID	OrderDate	Amount
1	John	Doe	john.doe@example.com	101	2024-01-15	250.50
2	Jane	Smith	jane.smith@example.com	102	2024-02-10	150.75
NULL	NULL	NULL	NULL	103	2024-03-05	300.00

Experiment 6

Aim: Introduction to PL/SQL. Create a PL/SQL block and implement the following:

a) Variables

```
Project > Q6.sql
  ▶ Run on active connection | ≡ Select block
1  -- Question 6(a): Variables
2
3  DECLARE
4      -- Declaring variables
5      v_item_price NUMBER := 500;
6      v_tax_rate   NUMBER := 0.08; -- 8% tax rate
7      v_total_price NUMBER;
8  BEGIN
9      -- Calculating total price including tax
10     v_total_price := v_item_price + (v_item_price * v_tax_rate);
11
12     -- Output the result
13     DBMS_OUTPUT.PUT_LINE('Item Price: ' || v_item_price);
14     DBMS_OUTPUT.PUT_LINE('Tax Rate: ' || v_tax_rate * 100 || '%');
15     DBMS_OUTPUT.PUT_LINE('Total Price: ' || v_total_price);
16 END;
```

```
Item Price:      500
Tax Rate:        8%
Total Price:     540
```

b) Packages

```
1  -- Question 6(b): Packages
2
3  USE test1;
4
5  SET SERVEROUTPUT ON;
6
7  CREATE OR REPLACE PACKAGE math_operations AS
8      PROCEDURE add_numbers(x NUMBER, y NUMBER, result OUT NUMBER);
9
10     FUNCTION multiply_numbers(x NUMBER, y NUMBER) RETURN NUMBER;
11 END math_operations;
12 /
13
14 CREATE OR REPLACE PACKAGE BODY math_operations AS
15     PROCEDURE add_numbers(x NUMBER, y NUMBER, result OUT NUMBER) IS
16     BEGIN
17         result := x + y;
18     END add_numbers;
19
20     FUNCTION multiply_numbers(x NUMBER, y NUMBER) RETURN NUMBER IS
21     BEGIN
22         RETURN x * y;
23     END multiply_numbers;
24 END math_operations;
25 /
26
27 DECLARE
28     sum_result NUMBER;
29     product_result NUMBER;
30 BEGIN
31     math_operations.add_numbers(5, 7, sum_result);
32     DBMS_OUTPUT.PUT_LINE('Sum Result: ' || sum_result);
33
34     product_result := math_operations.multiply_numbers(3, 4);
35     DBMS_OUTPUT.PUT_LINE('Product Result: ' || product_result);
36 END;
37 /
```

Package created.

Package Body created.

Statement processed.

Sum Result: 12

Product Result: 12

c) Procedures

```
Project > Q6.sql
  Run on active connection | Select block
1  -- Question 6(c): procedures
2
3  CREATE PROCEDURE add_employee(
4      IN p_first_name VARCHAR(50),
5      IN p_last_name VARCHAR(50),
6      IN p_salary DECIMAL(10, 2),
7      IN p_department_id INT
8  )
9  BEGIN
10     INSERT INTO employees (first_name, last_name, salary, department_id)
11     VALUES (p_first_name, p_last_name, p_salary, p_department_id);
12 END;
13
14
15 CALL add_employee('Emily', 'Clark', 4800.00, 3);
```

employee_id	first_name	last_name	salary	department_id
1	John	Doe	5000.00	1
2	Jane	Smith	6000.00	2
3	Alice	Johnson	5500.00	1
4	Bob	Brown	4500.00	3
5	Charlie	Davis	7000.00	2
6	Emily	Clark	4800.00	3

d) Functions

```
Q6.sql X
Project > Q6.sql
  Run on active connection | Select block
1  -- Question 6(d): functions
2
3  CREATE FUNCTION calculate_annual_salary(employee_id INT)
4  RETURNS DECIMAL(10, 2)
5  AS
6  BEGIN
7      DECLARE annual_salary DECIMAL(10, 2);
8
9      SELECT salary * 12 INTO annual_salary
10     FROM employees
11     WHERE employee_id = employee_id;
12
13     RETURN annual_salary;
14 END;
15
16 SELECT calculate_annual_salary(1) AS annual_salary;
17 |
```

annual_salary

60000.00

Experiment 7

Aim: Perform Exception handling in a PL/SQL block.

```
▷ Run on active connection | ≡ Select block
1  -- Question 7: Exception Handling in PL/SQL block.
2
3  DECLARE
4      num1 NUMBER := 10;
5      num2 NUMBER := 0; -- This will cause a division by zero error
6      result NUMBER;
7  BEGIN
8      -- Attempt to perform the division
9      result := num1 / num2;
10     DBMS_OUTPUT.PUT_LINE('Result: ' || result);
11 EXCEPTION
12     WHEN ZERO_DIVIDE THEN
13         DBMS_OUTPUT.PUT_LINE('Error: Division by zero is not allowed.');
```

Error: Division by zero is not allowed.

Experiment 9

Aim: Implement Triggers in SQL.

```
1  -- Question 9: Implement triggers in sql.
2
3  CREATE TABLE Employees (
4      EmployeeID INT PRIMARY KEY,
5      FirstName VARCHAR(100),
6      LastName VARCHAR(100),
7      Salary NUMBER
8  );
9
10 CREATE TABLE SalaryChanges (
11     ChangeID INT PRIMARY KEY,
12     EmployeeID INT,
13     OldSalary NUMBER,
14     NewSalary NUMBER,
15     ChangeDate TIMESTAMP DEFAULT CURRENT_TIMESTAMP
16 );
17
18 CREATE OR REPLACE TRIGGER SalaryChangeTrigger
19 AFTER UPDATE OF Salary ON Employees
20 FOR EACH ROW
21 BEGIN
22     INSERT INTO SalaryChanges (ChangeID, EmployeeID, OldSalary, NewSalary)
23     VALUES (SEQ_SalaryChanges.NEXTVAL, :OLD.EmployeeID, :OLD.Salary, :NEW.Salary);
24 END;
25 /
26
27 INSERT INTO Employees (EmployeeID, FirstName, LastName, Salary)
28 VALUES (1, 'Alice', 'Johnson', 60000);
29
30 UPDATE Employees
31 SET Salary = 65000
32 WHERE EmployeeID = 1;
33
34 INSERT INTO Employees (EmployeeID, FirstName, LastName, Salary)
35 VALUES (1, 'Alice', 'Johnson', 60000);
36
37 UPDATE Employees
38 SET Salary = 65000
39 WHERE EmployeeID = 1;
40
41 SELECT * FROM SalaryChanges;
```

ChangeID	EmployeeID	OldSalary	NewSalary	ChangeDate
1	1	60000	65000	2024-03-10 12:34:56

Experiment 10

Aim: Implement the following transaction statements:

a) Commit

```
Project > Q10.sql
  ▶ Run on active connection | Select block
1  -- Question 10(a): Commit
2
3  CREATE TABLE Accounts (
4      AccountID INT PRIMARY KEY,
5      AccountHolder VARCHAR(100),
6      Balance DECIMAL(10, 2)
7  );
8
9  INSERT INTO Accounts (AccountID, AccountHolder, Balance) VALUES
10 (1, 'Alice', 1000.00),
11 (2, 'Bob', 500.00);
12
13 BEGIN;
14 -- Start the transaction
15
16 UPDATE Accounts
17 SET Balance = Balance - 200
18 WHERE AccountID = 1;
19
20 UPDATE Accounts
21 SET Balance = Balance + 200
22 WHERE AccountID = 2;
23
24 COMMIT;
```

AccountID	AccountHolder	Balance
1	Alice	1000.00
2	Bob	500.00

AccountID	AccountHolder	Balance
1	Alice	800.00
2	Bob	700.00

b) Rollback

Project > Q10.sql

Run on active connection | Select block

```
1  -- Question 10(b): Rollback
2
3  CREATE TABLE Accounts (
4      AccountID INT PRIMARY KEY,
5      AccountHolder VARCHAR(100),
6      Balance DECIMAL(10, 2)
7  );
8
9  INSERT INTO Accounts (AccountID, AccountHolder, Balance) VALUES
10 (1, 'Alice', 1000.00),
11 (2, 'Bob', 500.00);
12
13 BEGIN;
14
15 UPDATE Accounts
16 SET Balance = Balance - 200
17 WHERE AccountID = 1;
18
19 UPDATE Accounts
20 SET Balance = Balance + 200
21 WHERE AccountID = 3;
22
23 COMMIT;
24
25 EXCEPTION
26 WHEN OTHERS THEN
27     ROLLBACK;
28     DBMS_OUTPUT.PUT_LINE('Transaction failed. Changes have been rolled back.');
```

AccountID	AccountHolder	Balance
1	Alice	1000.00
2	Bob	500.00

c) Savepoint

```
1  -- Question 10(c): Savepoint
2
3  CREATE TABLE Accounts (
4      AccountID INT PRIMARY KEY,
5      AccountHolder VARCHAR(100),
6      Balance DECIMAL(10, 2)
7  );
8
9  INSERT INTO Accounts (AccountID, AccountHolder, Balance) VALUES
10 (1, 'Alice', 1000.00),
11 (2, 'Bob', 500.00);
12
13 BEGIN;
14 -- Start the transaction
15
16 -- Debit 200 from Alice's account
17 UPDATE Accounts
18 SET Balance = Balance - 200
19 WHERE AccountID = 1;
20
21 -- Create a savepoint after debiting Alice's account
22 SAVEPOINT DebitAlice;
23
24 -- Introduce an error to trigger rollback
25 -- This update will fail because AccountID 3 does not exist
26 UPDATE Accounts
27 SET Balance = Balance + 200
28 WHERE AccountID = 3;
29
30 -- Rollback to the savepoint if there is an error
31 ROLLBACK TO DebitAlice;
32
33 -- Commit the transaction
34 COMMIT;
35 END;
36 /
--
```

AccountID	AccountHolder	Balance
1	Alice	800.00
2	Bob	500.00

