

Q01: Qname

- prompt: **What is the difference between pseudo-polynomial and polynomial?**
- model_name: **ChatGPT**
- model_version: **ChatGPT-4o**
- response:

The main difference between **pseudo-polynomial time** and **polynomial time** lies in how the complexity depends on the size of the input:

1. Polynomial Time

If the time complexity of an algorithm can be expressed as a polynomial function of the size of the input (usually represented by $\log(n)$, the number of bits needed to represent the input), such as $O(\text{poly}(\log(n)))$, the algorithm is said to have polynomial time complexity. It depends on the length of the input, not the numerical value itself.

2. Pseudo-Polynomial Time

If the time complexity depends on the numerical value of the input (n) rather than the size of its representation $\log(n)$, it is called pseudo-polynomial. For example, an algorithm with a complexity of $O(n^k)$ is pseudo-polynomial because it depends on the value of n instead of $\log(n)$.

Key Difference:

- **Polynomial time** complexity grows as a polynomial of the input size, making it scalable.
- **Pseudo-polynomial time** complexity grows as a polynomial of the input value, which becomes inefficient as the input size increases.

Examples:

- Polynomial time: The time complexity of fast exponentiation is $O(\log(n))$, as it depends on the input's bit-length.
 - Pseudo-polynomial time: The time complexity of trial division is $O(\sqrt{n})$, as it depends on the numerical value of n .
-

Q02: Qname

- prompt: **How to determine whether the complexity of an algorithm is pseudo-polynomial?**
- model_name: **ChatGPT**
- model_version: **ChatGPT-4o**
- response:

To determine whether the complexity of an algorithm is pseudo-polynomial, consider the following aspects:

1. Representation of Input Size

First, check if the input size is represented in terms of the number of bits $\log(n)$. A pseudo-polynomial algorithm's complexity depends on the numerical value n of the input rather than its bit-length $\log(n)$.

2. Form of Time Complexity

If the algorithm's time complexity can be expressed as a polynomial function of the input value n , such as $O(n^k)$ (where n is the actual value of the input), rather than as a polynomial of $\log(n)$, such as $O((\log(n))^k)$, the algorithm is likely pseudo-polynomial.

3. Comparison of Input Size and Actual Complexity

As the input value increases, the complexity of a pseudo-polynomial algorithm grows much faster, but it may appear similar to polynomial algorithms for small input values. Analyzing the growth pattern helps distinguish pseudo-polynomial complexity from true polynomial complexity.

4. Specific Dependency on Input

Check if the algorithm depends on the numerical value of the input. For example, trial division has a complexity of $O(\sqrt{n})$, which depends on the numerical value, making it pseudo-polynomial. In contrast, fast exponentiation has a complexity of $O(\log(n))$, depending on the input bit-length, classifying it as polynomial time.

Q03: Qname

- prompt: **Is the 0-1 knapsack problem a P problem? Why?**
- model_name: **ChatGPT**

- model_version: **ChatGPT-4o**
- response:

The 0-1 knapsack problem is **not** a P problem because it belongs to the class of NP problems. Specifically, the 0-1 knapsack problem is a combinatorial optimization problem, and its complexity is NP-complete in general. This means that while a given solution can be verified in polynomial time, no algorithm has been found that can solve all instances of the problem in polynomial time. However, when treated as a weighted problem with integer weights and values, there are dynamic programming algorithms that solve it in pseudo-polynomial time, but this does not change its classification as an NP problem.

Q04: Qname

- prompt: **Primality Testing Problem: Given any positive integer n , check whether n has an integer factor greater than 1. Please provide an algorithm with pseudo-polynomial complexity for this problem and explain the reason behind its complexity.**
- model_name: **ChatGPT**
- model_version: **ChatGPT-4o**
- response:

The **primality testing problem** can be solved using trial division within pseudo-polynomial time. Below is the pseudo-polynomial algorithm and its explanation:

Pseudo-Polynomial Algorithm:

1. Given a positive integer n .
2. Check whether n is divisible by any integer in the range from 2 to \sqrt{n} :
 - If $n \% d == 0$ (where d is the divisor being tested), then n is not a prime.
 - If no divisor is found, n is a prime number.
3. Algorithm Complexity:
 - The range of testing is \sqrt{n} , and each division operation takes constant time. Thus, the time complexity is $O(\sqrt{n})$.

Reason for Pseudo-Polynomial Nature:

The definition of pseudo-polynomial time refers to algorithms whose complexity depends on the **numerical value of the problem** size rather than the number of digits (input size). In the case of trial division:

1. When a positive integer n is given as input, its input size is $\log(n)$, i.e., the number of bits required to represent n .
 2. The time complexity of trial division is $O(\sqrt{n})$, which depends on the actual numerical value of n , not its bit-length $\log(n)$.
 3. If the complexity were a polynomial function of $\log(n)$ (e.g., $O(\text{poly}(\log(n)))$), the algorithm would be in strictly polynomial time. However, in trial division, the dependence on \sqrt{n} leads to exponential growth relative to the input size.
 4. Thus, while trial division is efficient for small numerical values of n , its complexity scales exponentially with the input size $\log(n)$, categorizing it as pseudo-polynomial time.
-

Q05: Qname

- prompt: **What are the latest and most cutting-edge studies on whether P equals NP?**
- model_name: **ChatGPT**
- model_version: **ChatGPT-4o**
- response:

The P vs. NP problem remains a central unsolved question in computer science. In recent years, researchers have made significant progress in this area, focusing on the following aspects:

1. **Application of Large Language Models (LLMs):** In 2023, researchers from Microsoft Research Asia, Peking University, and Beihang University utilized the GPT-4 model in a "Socratic" reasoning approach. After 97 rounds of dialogue, they successfully concluded that $P \neq NP$. This study demonstrates the potential of LLMs in addressing complex mathematical problems.
2. **Development of Meta-Complexity Theory:** Meta-complexity examines the

complexity of computational problems themselves. In 2023, researchers achieved subtle yet significant advancements in this field, offering new perspectives on understanding the P vs. NP problem.

3. **Algorithm Optimization and Applications:** While the P vs. NP problem remains unsolved, researchers have made practical progress on specific NP-complete problems. For instance, more efficient approximation algorithms have been developed for the Traveling Salesman Problem, enhancing solution efficiency in real-world applications.

Although these studies have not definitively resolved the P vs. NP problem, they provide new insights and tools for understanding and addressing this fundamental question.
