

SS Lab Exam

Sahil Bondre: U18CO021

```
import sys
import re
from termcolor import colored
from tabulate import tabulate

if len(sys.argv) != 3:
    print("Usage: python index.py <file-name> <file-name>")
    exit(1)

file_name = sys.argv[1]
macro_file = sys.argv[2]

ssn_tab = []
evn_tab = []
pn_tab = []
mdt = [] # Label, opcode, operands

ssn_tab2 = []
evn_tab2 = []
pn_tab2 = []
mdt2 = [] # Label, opcode, operands

address = 200

with open(macro_file) as f:
    for num, line in enumerate(f, 1):
        tokens = line.split()
        is_label_def = not bool(re.match(r'\s', line))
        if num != 1 and num != 2 and is_label_def:
            label = tokens[0]
            if label[0] == '&' and label not in evn_tab:
                evn_tab.append(label)
            elif label[0] == '.' and label not in ssn_tab:
                ssn_tab.append(label)

with open(macro_file) as f:
    for num, line in enumerate(f, 1):
        address += 1
        tokens = line.split()
        is_label_def = not bool(re.match(r'\s', line))
        if num == 1:
```

```

        print(line)
    elif num == 2:
        pn_tab = [x.split(',')[0].split('=')[0] for x in tokens[1:]]
        print(line)
    else:
        # fill mdt:
        row = ['', '', '']
        if is_label_def:

            label = tokens[0]
            tokens = tokens[1:]
            if label in evn_tab:
                row[0] += f"(E, {evn_tab.index(label) + 1})"
            elif label in ssn_tab:
                row[0] += f"(S, {ssn_tab.index(label) + 1})"

        row[1] = tokens[0]
        tokens = tokens[1:]

        res = ''
        for token in tokens:
            temp = token.split(',')[0]
            has_comma = (temp != token)
            token = temp
            if token in evn_tab:
                res += f"(E, {evn_tab.index(token) + 1})"
            elif token in ssn_tab:
                res += f"(S, {ssn_tab.index(token) + 1})"
            elif token in pn_tab:
                res += f"(P, {pn_tab.index(token) + 1})"
            else:
                res += token

            if has_comma:
                res += ','

        row[2] = res
        row.insert(0, address)
        mdt2.append(row)

with open(file_name) as f:
    for num, line in enumerate(f, 1):
        tokens = line.split()
        is_label_def = not bool(re.match(r'\s', line))
        if num != 1 and num != 2 and is_label_def:
            label = tokens[0]
            if label[0] == '&' and label not in evn_tab:
                evn_tab.append(label)

```

```

        elif label[0] == '.' and label not in ssn_tab:
            ssn_tab.append(label)

with open(file_name) as f:
    for num, line in enumerate(f, 1):
        address += 1
        tokens = line.split()
        is_label_def = not bool(re.match(r'\s', line))
        if num == 1:
            print(line)
        elif num == 2:
            pn_tab = [x.split(',')[0].split('=')[0] for x in tokens[1:]]
            print(line)
        else:
            # fill mdt:
            row = ['', '', '']
            if is_label_def:

                label = tokens[0]
                tokens = tokens[1:]
                if label in evn_tab:
                    row[0] += f"(E, {evn_tab.index(label) + 1})"
                elif label in ssn_tab:
                    row[0] += f"(S, {ssn_tab.index(label) + 1})"

            row[1] = tokens[0]
            tokens = tokens[1:]

            res = ''
            for token in tokens:
                temp = token.split(',')[0]
                has_comma = (temp != token)
                token = temp
                if token in evn_tab:
                    res += f"(E, {evn_tab.index(token) + 1})"
                elif token in ssn_tab:
                    res += f"(S, {ssn_tab.index(token) + 1})"
                elif token in pn_tab:
                    res += f"(P, {pn_tab.index(token) + 1})"
                else:
                    res += token

            if has_comma:
                res += ','

            row[2] = res
            row.insert(0, address)
            mdt.append(row)

```

```

print(tabulate([[x] for x in pn_tab], headers=[
    colored("PN Table", color="yellow")], tablefmt="fancy_grid"))

print(tabulate([[x] for x in evn_tab], headers=[
    colored("EVN Table", color="yellow")], tablefmt="fancy_grid"))

print(tabulate([[x] for x in ssn_tab], headers=[
    colored("SSN Table", color="yellow")], tablefmt="fancy_grid"))

print()
print(colored("Macro Definition Table Initial", attrs=["bold"],
color="blue"))
print(tabulate(mdt, headers=[colored("Addr", color="yellow"),
    colored("Label", color="yellow"), colored("Opcode", color="yellow"),
    colored("Operands", color="yellow")], tablefmt="fancy_grid"))

print(colored("Macro Definition Table Nested", attrs=["bold"],
color="blue"))
print(tabulate(mdt2, headers=[colored("Addr", color="yellow"),
    colored("Label", color="yellow"), colored("Opcode", color="yellow"),
    colored("Operands", color="yellow")], tablefmt="fancy_grid"))

address = mdt[0][0]
for i in range(len(mdt)):
    x = i
    if(mdt[i][2] == "ADDNUM"):
        mdt.pop(i)
        for r in mdt2:
            mdt.insert(x, r)
            x += 1

address = mdt[0][0]
for i in range(len(mdt)):
    mdt[i][0] = address
    address += 1

print(colored("Macro Definition Table Combined", attrs=["bold"],
color="blue"))
print(tabulate(mdt, headers=[colored("Addr", color="yellow"),
    colored("Label", color="yellow"), colored("Opcode", color="yellow"),
    colored("Operands", color="yellow")], tablefmt="fancy_grid"))

```

file.asm

```
MACRO
  ADDTEN &X, &Y
  MOVER AREG, X
  MOVER BREG, Y
  LCL &M
&M  SET 0
  ADDNUM AREG, BREG
  INCR AREG
  INCR BREG
&M  SET &M + 1
  AIF ( &M NE 10 ) .MORE
MEND
```

nested.asm

```
MACRO
  ADDNUM &X, &Y
  MOVER AREG, X
  ADD AREG, Y
MEND
```

PN Table
&X
&Y

EVN Table
&M

SSN Table

Macro Definition Table Initial

Addr	Label	Opcode	Operands
208		MOVER	AREG,X
209		MOVER	BREG,Y
210		LCL	(E, 1)
211	(E, 1)	SET	0
212		ADDNUM	AREG,BREG
213		INCR	AREG
214		INCR	BREG
215	(E, 1)	SET	(E, 1)+1
216		AIF	((E, 1)NE10).MORE
217		MEND	

Macro Definition Table Nested

Addr	Label	Opcode	Operands
203		MOVER	AREG,X
204		ADD	AREG,Y
205		MEND	

Macro Definition Table Combined

Addr	Label	Opcode	Operands
208		MOVER	AREG,X
209		MOVER	BREG,Y
210		LCL	(E, 1)
211	(E, 1)	SET	0
212		MOVER	AREG,X
213		ADD	AREG,Y
214		MEND	
215		INCR	AREG
216		INCR	BREG
217	(E, 1)	SET	(E, 1)+1
218		AIF	((E, 1)NE10).MORE
219		MEND	

Q2:

```
%{
#include <stdio.h>
#include <string.h>
int op = 0, oprs = 0, valid = 1, top = -1, l = 0, j = 0;
char operands[10][10], operators[10][10], stack[100];
}%
%%

"+"|"-"|"*"|"/" {
    op++;
    strcpy(operators[l], yytext);
```



```

    l++;
}

[0-9]+|[a-zA-Z][a-zA-Z0-9_]* {
    oprs++;
    strcpy(operands[j], yytext);
    j++;
}

"(" {
    top++;
    stack[top] = '(';
}

")" {
    if (stack[top] != '(') {
        valid = 0;
    } else if (oprs > 0 && (oprs - op) != 1) {
        valid = 0;
    } else {
        top--;
        oprs = 1;
        op = 0;
    }
}

"{" {
    top++;
    stack[top] = '{';
}

"}" {
    if (stack[top] != '{') {
        valid = 0;
    } else if (oprs > 0 && (oprs - op) != 1){
        valid=0;
    } else {
        top--;
        oprs = 1;
        op=0;
    }
}

"[" {
    top++;
    stack[top] = '[';
}

```

```

"]" {
    if (stack[top] != '[') {
        valid = 0;
    } else if (oprs > 0 && (oprs - op) != 1){
        valid=0;
    } else {
        top--;
        oprs=1;
        op=0;
    }
}

"\n" return 0;
%%

int yywrap(){ return 1; }
int main(){
    int k;
    printf("Enter the arithmetic expression: ");
    yylex();

    if (valid == 1 && top == -1) {
        printf("\nValid Expression!\n");
        printf("\nThe operators are: \n");
        for(int i = 0; i < 1; ++i)
            printf("%s ", operators[i]);
        printf("\nThe identifiers are: \n");
        for(int i = 0; i < j; ++i)
            printf("%s ", operands[i]);
        printf("\n");
    }
    else
        printf("\nInvalid Expression!\n");

    return 0;
}

```

```
(ss) → lab-exam git:(master) X ./a.out  
Enter the arithmetic expression: (a+b*(c+d))
```

Valid Expression!

The operators are:

+ * +

The identifiers are:

a b c d

```
(ss) → lab-exam git:(master) X ./a.out
```

```
Enter the arithmetic expression: ((a++
```

Invalid Expression!

```
(ss) → lab-exam git:(master) X █
```