Abstract Machines

Steppers, retained worlds and semantic connections in Mettapedia

Mettapedia Working Notes


16 October 2026

Abstract

An abstract machine records unfinished work, its environment or world, and what has become observable. This overview connects the functional, categorical, call-by-need, refocusing, GSLT, rho, C and proof machines through their steppers, observers and resumption laws. Scoped, licensed composition supplies a common checking interface; costed relational stages and functional path transport supply two constructed categorical organizations of machines. The common execution contracts preserve distinct evaluation strategies and logical theories. Deterministic regions, probabilistic execution, zippers and typed graph holes supply ingredients of a candidate computational-metagraph machine. Diagrams distinguish constructed connections from remaining obligations.

1 One map, several machines

The language rules say what a computation means. The machine says how its unfinished work is represented. A VM additionally supplies a code image, loader and instruction-admission contract. A native implementation must realize those representations and transitions under its memory and service assumptions. Each connection needs its own theorem or qualification evidence. Section 13 develops the corresponding proof-checking machine: what follows from what, under which conditions, and how its evidence composes.



Similar outputs on examples test a connection. They do not replace a general correspondence theorem between independently defined semantics.

Family	Distinguishing retained information
CEK / Krivine	Value environments and argument frames / unevaluated closures.
Categorical CAM	Register, compiled closures, remaining code and value stack.
Branch-local Need	Cell origins, memo states, branch worlds and reuse identity.
Refocusing	Legal context stack, focused redex and ordered candidate attempts.
GSLT / rho	Scoped search jobs, unmet obligations and occurrence-bearing receipts.
C-language core	Byte memory, continuations, pending expression occurrences.

The historical *Categorical Abstract Machine* and the machine for the *C language* are different instances. Neither supplies a universal fastest strategy. The broader observer and logical-world foundation is developed in `papers/metatheory.tex`.


2 What the common stepper must retain

An individual run records an execution sequence; MeTTa need not promise one global answer enumeration order. Cross-machine observations may retain the multiset of full answer occurrences, including multiplicity, bindings and provenance, while forgetting enumeration. Stronger ordered theorems qualify a selected worker policy. Within each worker, resumption keeps its captured publication and remaining work without replay or omission. Bounded selection can choose different valid occurrences under different strategies. Observable effects and causal dependencies require their own preservation laws.

The simplest core is a state type, a loader and a partial step function. A missing step alone does not tell us whether a program answered or got stuck. The productive event interface therefore makes successful completion explicit:

$$\mathsf{step} : S \longrightarrow \mathsf{Option}\big(\mathsf{Transition}(S, E, V, Q)\big).$$

Here E is an event, V a verdict and Q a request. A transition can perform silent administration, publish events, finish, fail with events, or call out while saving its continuation. An absent transition is reported as stuck.



The arrows show possible transition or outcome kinds, not a sequence that visits every box. Exhausting fuel retains a residual; it proves neither completion nor divergence.

A finite runner returns an ordered event list and an outcome. After fuel exhaustion, running longer uses the saved residual and appends only the newly produced events. A suspended request instead needs explicit response delivery; extra fuel does not supply its answer. Finishing, faults, suspension, stuckness and exhaustion remain distinct. Separate price functions account for instructions, allocations or other declared resources. An administrative rank excludes an infinite silent stretch when its hypotheses hold; it does not assume the whole program terminates.

Three different choices in a stepper

Semantic alternatives, redex selection within a branch, and scheduling between branches have different contracts. For a pure snapshot, expanding one branch b can replace its frontier occurrence by the complete bag of its successors:

$$F' = (F - \{b\}) + \mathsf{Succ}(b).$$

Choosing which b to expand need not discard any semantic alternative. Choosing one successor and forgetting the others changes the computation. Occurrences remain distinct even when their

printed terms agree. Fairness is a separate obligation for an infinite search; a finite pause establishes no exhaustive answer collection.

Redex selection inside a branch must still follow its evaluation policy. Call-time choice illustrates why unrestricted term rewriting is insufficient: copies of one shared choice must not become independent choices. Let-rewriting provides an explicit reduction presentation with soundness and completeness against its call-time-choice semantics [3]. Our branch-local Need instance has its own independently stated judgments and adequacy laws; that precedent does not establish native MeTTa adequacy automatically.

A source-level step also need not be one implementation instruction. Clements, Flatt and Felleisen separately prove preservation by instrumentation and reconstruction of the source reduction sequence [2]. The corresponding obligation here is a constructed source/configuration map and a productive block simulation. A debugger may expose that semantic view without making all optimizer frames ordinary program observations.

Scheduling shared effects requires further evidence: commuting actions, isolation, or an explicit serialization policy. The answer observer must also be declared. Alpha-renaming of internal bindings cannot erase a string that an ordinary operation has already produced from a variable's displayed name. These distinctions prevent a scheduler-independence claim from silently changing sharing, effects, or the language's observations.

The strongest useful form of correspondence

A related source/native pair should reproduce the same selected occurrences, with related residuals, at every relevant observation boundary. Native administration may take several steps for one source step. A ranked block simulation licenses that difference without erasing observable failures. The backward direction establishes no invention; the forward direction establishes that source behavior is realized. Cost bounds need an explicit resource model in addition to behavioral correspondence.

A logical machine with replaceable backends

The stable MeTTa machine is specified at the level of scoped evaluation operations. Its configuration retains the term or task, binding constraints, continuation, answer occurrences, observable world and required authority. The selected language profile determines argument evaluation, rule freshening, choice sharing, returned-value treatment and effects. A frame's address, hash-table layout or symbol number belongs to a backend realization. Logical object identity, freshness and ownership remain obligations wherever the declared operations can observe them; changing addresses does not license merging identities.

The representation boundary is a relation $R(b, s)$ between a backend state b and a logical configuration s. Several backend states may represent the same configuration. At the declared observation boundaries, a logical step $s \xrightarrow{e} s'$ must be realized by a finite backend block $b \xRightarrow{e} b'$ with $R(b', s')$, and backend behavior must satisfy the applicable reflection law. The block may contain internal administration; productivity and endpoint laws prevent that administration from concealing divergence, stuckness or faults. This is a behavioral obligation. A uniform bound on the number or physical cost of backend instructions requires a separate argument.

The existing event-machine interface now proves this finite-block connection without a uniform cost premise. `Machine.run_related_of_one` derives whole-prefix correspondence from local implementations of individual inspections. Its resumption corollary retains the matched checkpoint and appends only the suffix. Local implementations in both directions give equal completed observations. Their outcomes retain faults, stuckness, requests and related saved states; a separate corollary reflects unbounded execution within the current interaction region. The local contracts compose through the actual middle state. Costed stages retain their stronger resource law.

A checked control makes the difference concrete: each logical publication has size-dependent internal work, with no single instruction bound for all admitted states. Both directions preserve its duplicate publications and completed observations; resumption appends the saved suffix, while restarting repeats the prefix. Existing forward-only controls still demonstrate that preservation alone cannot establish completion reflection. These generic laws do not supply the missing local CeTTa, Rust or SWI implementation instances.

The local obligations concern loading, scoped query and binding operations, invocation and return, host effects, retained control and observation. Their constructed laws are inputs to the existing run-composition theorems. Assuming the complete run correspondence as an implementation field would not discharge those obligations. A new storage representation can replace one backend instance while the language judgments and logical machine remain unchanged. Representation differences can be hidden only when the declared operations and future continuations respect the proposed relation; this includes the identities correlating several uses of one unresolved variable.

Implementation evidence has its own scope. A formal proof about a memory model, a source-fragment correspondence under ABI and service assumptions, and an executable conformance test support different claims. In particular, a model theorem conditional on a backend contract is not an unconditional correctness theorem for the compiled evaluator. Physical helper proofs strengthen an instance; they do not become definitions of MeTTa evaluation. The independent fixed C-core development remains a separate substantial instance of the common theory.

The same comparison framework also guides machine redesign. Explicit continuations can replace hidden evaluator calls; one invocation dispatcher can replace duplicated classification; a retained binding representation can replace repeated reconstruction. These are machine refinements when the specified observations are preserved. They earn efficiency claims only through an appropriate cost comparison and measurements of the actual implementation. A small change to the evaluation policy may instead yield a more coherent language. Such a change is an explicitly compared semantic candidate, with programs distinguishing the two policies and laws explaining the gain. It is not evidence for equivalence under the old observation. The relevant choices include fault versus ordinary failure, repeated evaluation versus ready values, and who may inspect, advance or publish a retained computation. A licensed transition and possession of authority to perform it remain separate judgments. Execution determinism, answer cardinality and probabilistic meaning are separate dimensions (Section 14). Focused graph holes and changes of resolution follow in Sections 15 and 16.1.

Existing owners. `Mettapedia/Machines/MachineSubstrate.lean`, `Mettapedia/Machines/ProductiveCoreAdapters.lean`, `Mettapedia/GSLT/Distinction/ProductiveBlocks.lean`, `Mettapedia/GSLT/Distinction/SpanTransport.lean`, `Mettapedia/GSLT/Distinction/SimulationComposition.lean`, `Mettapedia/GSLT/Distinction/OrderedAdministration.lean`.


> **Boundary.** These are common execution interfaces. They do not make the selected logical kernels equal, or automatically prove a native evaluator refines them.

3 CEK and Krivine: one syntax, different demands

Both examples use de Bruijn lambda terms with natural-number literals. The CEK-shaped machine implements left-to-right call by value. Its environment contains values; its continuation first remembers an argument, then the evaluated function. The Krivine-shaped machine uses call by name: its argument stack contains closures whose evaluation is deferred.


CEK stepper

For an application, evaluate the operator, evaluate the argument, and enter the function's captured environment extended by the argument value.



Krivine stepper

Push the argument closure, enter the operator, and bind the saved closure when a lambda is reached. A variable lookup resumes its closure.



The existing `CEK.eval_to_machine` and `Krivine.eval_to_machine` theorems construct machine paths from successful independent evaluator results, uniformly in the surrounding continuation. The common adapters expose checked answer boundaries, finite traces, resumption and computational accounts. This endpoint development does not mechanize the entire CPS/defunctionalization derivation.


A discriminating term is $(\lambda x.\lambda y.x)\ 7\ \Omega$. Call by value evaluates the discarded divergent argument, so its evaluator returns no answer at every finite fuel. Call by name reaches 7 without demanding that argument. This is a proved strategy difference, not an implementation defect.

Existing owners. `Mettapedia/Machines/FunctionalCorrespondence.lean`, `Mettapedia/Machines/MachineSubstrate.lean`, `Mettapedia/Machines/ProductiveFunctionalMachines.lean`.

> **Boundary.** Call by name does not memoize. Repeated demand may repeat work; branch-local call by need requires the additional cell and cache laws below.

4 The historical Categorical Abstract Machine

The CAM follows Cousineau–Curien–Mauny's source strategy and instruction tables [1]. One indexed source grammar contains variables, lambda, application, pairs and projections, with literals and Boolean conditionals enabled by its extension index. Source closures retain source bodies; machine closures retain compiled instruction lists.



The tree machine and the value-graph machine share one instruction table. On the tree machine's instructions they move in lock step; recursion and delay run only on the graph.

Application compiles to saving the environment, evaluating the operator, restoring the environment, evaluating the argument, constructing their pair, and applying. The actual state retains the register, remaining instructions and stack throughout this work. The executable `step` agrees in both directions with the independent `Transition` rules.

The shared compiler and code/value decoder have proved inverses on their admitted images, including captured closure environments. `evaluation_iff_execution` connects independent evaluation to completed neutral-profile execution at both indices; completion requires empty code and stack. A conditional evaluates its condition, restores the saved environment and runs only the selected arm. A non-Boolean condition can be stuck. `Lambda.proposition_3_2` connects historical scoped weak source reduction to execution and readback at either syntax index, including literal and conditional source terms and captured scoped environments. The strategy does not reduce under a lambda. Typed source formation constructs actual Cartesian closed morphisms; `Typed.evaluation_iff_strict_execution` and the meaning theorems connect the active instruction table to that interpretation.

The historical constant-free compiler remains the disabled-index specialization; its no-quotation/no-branch laws and typed Cartesian-closed results keep that scope. The enabled source uses the existing native quotation/branch instructions.

Recursion and delayed evaluation follow the paper's Sections 4 and 5 on a value graph. Heap cells are couples, closures and frozen computations. Allocation appends a cell; `wind` updates the second component of an existing couple, as LISP's `rplacd` does. Recursion compiles as in the paper's Table 6 and leaves the cyclic closure $c = C{:}(s, c)$ in the register. `freeze` builds a frozen computation and `unfreeze` forces it at strict positions (Table 7); forcing is by name. The module records two corrections to the published listing: `unfa` and `unfb` rebuild the couple with exchanged components, and the `letrec` code of Section 5 has a stray `swap`.

An independent big-step judgment covers recursion, frozen values and strict primitives. `evaluation_iff_execution` relates it to completed execution without assuming termination; executions keep the caller's code and stack and never change existing cells. Heap words represent source values by finite derivations. A cycle represents both a recursive value and its unfolding (`Represents.not_functional`), so source syntax is not observable on the graph; represented words agree with

the depth-indexed unfoldings of their values, and bisimilarity is agreement at every depth (`Represents.bisimilar_iff`). `refinement` and `abstraction` are cost-one simulations between the tree machine and the graph machine on the tree's instructions. Allocation keeps the heap topologically ordered; `wind` breaks the order, and its cycle has no tree unfolding (`windHeap_no_unfolding`). Controls run the paper's factorial and lazy stream, a divergent loop, and stuck cases.

A memoizing variant uses the existing branch-local demand store. Each frozen cell has its own allocation identity and immutable origin. Starting evaluation records an owner; nested update frames retain the caller until the result can be committed. Later forces read the completed cache without restarting its producer. Separate allocations of equal source terms remain separate demands.


The independent source judgments `Need.Evaluation`, `Need.Invocation` and `Need.Force` use source constructors, an arena and a demand store. They have no machine control or transition premise. `Need.evaluation_iff_execution` proves both directions for complete values and the entire retained world, including recursion, conditionals, cached hits and nested updates. Its source-arena condition requires stored closure and suspension bodies to be compiled source terms; the empty loader establishes that condition directly. Active ownership blocks recursive demand. This is explicit memoizing semantics, distinct from the historical by-name strategy.

Existing owners. `Mettapedia/Machines/CategoricalAbstractMachine.lean`, `Mettapedia/Machines/CategoricalAbstractMachineGraph.lean`, `Mettapedia/Machines/CategoricalAbstractMachineControls.lean`.

> **Boundary.** Cartesian closure supplies typed meaning, not recursion or update; the graph machine gives those their own operational laws. The extended readback and memoizing correspondence are constructed. Logical instruction counts do not by themselves establish physical performance or a native-code compiler.

5 Branch-local Need: choose once, reuse in that branch

The existing call-time-choice core separates value expressions from computations. The distinction follows the call-time-choice separation between shared demand and unrestricted rewriting [3]. Its runtime distinguishes a memoized implicit suspension, a resampled implicit thunk, and explicitly quoted code. A cell retains its original code and environment while its cache changes state.



Both uses share one chosen value in their own branch. A cache written in W_a does not become the cache of W_b. Separate argument occurrences can still make independent choices.

The natural semantics `Derives` is independently defined. The `adequacy` and `observes_iff_halts` results connect it to the unchanged branch-local Need machine in both directions, keeping the ordered list of outcomes and duplicate occurrences. Failure and blackhole outcomes are explicit. The strict-position theorem ensures primitives receive normal forms under the modeled binding policies.


Quoted code is a value until explicit activation. Structural observation may materialize an implicit pending cell under its original world and force rights; it must not infer execution permission from a callable-looking written subtree.

Existing owners. `Mettapedia/Machines/BranchLocalNeed/CallTimeChoiceSpec.lean`, `Mettapedia/Machines/BranchLocalNeed/CallTimeChoiceBackward.lean`, `Mettapedia/Machines/BranchLocalNeed/CallTimeChoiceStrict.lean`, `Mettapedia/Machines/BranchLocalNeed/SharedContinuationInstance.lean`.

> **Boundary.** This is source/model adequacy. Full native heap, producer/world identity, resource retention and evaluator correspondence require their own joins.

6 Refocusing: retain the route to the next redex

A reduction evaluator repeatedly decomposes a term, contracts a redex, and plugs the result back into its context. Refocusing keeps the context and searches from the contractum, avoiding unnecessary reconstruction when the strategy's laws justify it [4].



Frames are supplied by the evaluation strategy; their kinded stacks reuse `Quiver.Path`. A structural syntax position alone does not authorize evaluation. Traversal supplies local inspection and frame-resumption equations. The branching strategy supplies candidates in order and ordered instantiations for each candidate.

Inspection and rejected candidate attempts are administrative work, ranked by `SearchCredits`. A focused computational step remains visible even if its source and target terms are equal. A rejected candidate can be an empty block; an observable fault or unmatched redex cannot be discarded on that basis.

`refocusingComplete` constructs reverse tracing from local unique-decomposition laws. `blockSimulation`, `frontiers` and `outcomes` preserve ordered alternatives, multiplicity and pending work. `observable_stable` and `erasure_licensed` record the fault boundary. `Authored.ruleScan_simulation` supplies an actual GSLT rule-scan instance.

Where generalization is still needed

Several legal redex positions require an explicit position-selection policy. The present unique-decomposition instance must not be silently treated as a theorem about every parallel or nondeterministic traversal. Effectful attempts also need a history model: erasing a rejected attempt is licensed only if its observable commitments are accounted for.


Existing owners. `Mettapedia/Machines/Refocusing.lean`, `Mettapedia/Machines/RefocusingControls.lean`, `Mettapedia/OSLF/MeTTaIL/DerivedContexts.lean`.

> **Boundary.** The authored rule scan is a real anchor. It does not yet establish the full native evaluator's contextual traversal or administrative rank.

7 HE and Prime: the retained representation boundary

HE, PeTTa and declared Prime profiles are distinct language selections. A common machine substrate can retain the selected package and its own state without making those dialects interchangeable. Changing the selected interpretation requires a justified crossing, not merely a new label.

The implementation boundary matters. LeaTTa is an auxiliary interpreter; its correctness and conformance to HE are not acceptance conditions for the CeTTa machine correspondence. A theorem about LeaTTa's instruction worker establishes a property of that worker, even when its source judgment is independently specified. It supplies no CeTTa transition map by itself. HE claims must be checked against the independent judgments, the published semantics and Rust HE; any disagreement remains explicit. The native target is CeTTa's retained driver with its actual instruction phases, saved child stacks, binding environments and delivery state.



The independent argument judgment constructs an ordered history of selected values and exact intermediate bindings. `RetainedArgumentSpecification.arguments_history_iff` gives both directions at that semantic boundary. Leaf and nonleaf service packages connect further parts of the independent evaluation.

Live scope is part of the evaluation judgment. A recursive equation call freshens its private variables away from the arguments, current bindings and saved caller context. This matters even for a single rule: an inner call to `inc` must not reuse the outer call's private variable. The executable evaluator, declarative relations and contextual step relation carry this scope explicitly. Context replacement consequently requires the appropriate agreement of live variable inventories.

Resource exhaustion is a separate observation from completed failure. The checked recursive machine retains the pending task and requests further resources when its evaluation depth or a supporting query is insufficient. Its depth-coverage checks follow the actual recursive dependencies; a successful check proves stability under every additional depth allowance. A completed checked run also certifies the whole evaluator result at every greater evaluation depth, for each of its six entry points and internal list traversals. The proof increases the depths in every saved caller frame, not only the currently selected task. Equal answers at two shallow depths would not suffice: both can be empty while a deeper run returns a value. For all six entry points this completed execution constructs the existing evaluation certificate, including its eventual-stability witness and retained live scope. It is still a theorem about this evaluator profile; its matching and typing leaves do not disappear from the independent-language boundary.

Binding materialization now has a structural sufficient depth. A resolver marks fresh assigned keys, and syntax traversal decreases the current atom's height. The finite remaining-key set and the maximum stored value height give a decreasing rank for both ordinary and equality-aware resolution, including compound values and detected cycles. Control forms use this proved bound instead of a fixed numerical cutoff. Cycle detection is a different operation: the existing finite dependency analysis checks the complete graph of assigned values and their equality classes. Its result is equivalent to the independent absence-of-cycles judgment and can retain an explicit cycle witness. Every

stored assignment matters, including a value hidden by a later lookup entry. Satisfiability together with nonvariable assignment payloads proves this admission condition by strict descent of interpreted term size. Nonvariable lookup results alone do not: a shadowed variable assignment is a counterexample. The older finite list evaluator is still an approximation: an empty list from that evaluator alone does not certify completed failure.

The service adapter uses this checked machine. Replenishment preserves its selected alternatives, caller stack, world and already emitted results. Completed checked executions refine the corresponding finite evaluator run; the resource request is propagated through the C service caller. Thus a shallow budget suspends a recursive service, while a sufficiently provisioned three-call example returns the successive values 3, 7 and 12.

The same checked execution has an actual data representation. Each advance reads its supplied configuration and preserves every saved frame, published occurrence and pending resource request. Reading after encoding is an identity; malformed input is refused. The shared partial-reader adapter has identity and composition laws and preserves the exact finite run, its suspended residual, stuckness and unbounded exhaustion. Its logical step account excludes the physical cost of encoding and decoding. In particular, an encoded exhausted or suspended run cannot become an accepted empty result.

Application selection also retains history. A selected branch starts after the preceding branches have advanced the state; its seed and entry state are therefore part of the correspondence. The shared argument-fold laws retain this chronological origin. A theorem about normalization from empty bindings cannot replace a theorem about that reached environment. General conversion soundness must supply normalization and binding invariants at the retained endpoint; the concrete nested identity and constructor examples establish those conditions directly. General normalization adequacy remains a separate obligation.

The equation-query observation retains a physical row together with the same raw rule, freshened pair, match, ambient merge and emitted work item. The explicit-scope query is sound at this boundary and observationally complete for any legal private freshening of that same row. A constructed permutation fixes the query, incoming bindings and retained caller names; valuation reindexing preserves the full output solution theory. Private binding records need not have identical spellings, and this existence theorem does not count semantic derivations. Separate laws for the actual HE continuation retain the changed binding frame of each instantiated body beneath any saved caller stack. Their finite realizations inherit completion, representation and exact saved-residual resumption from one shared proof. The service adapter carries each full value/binding occurrence into both its event log and endpoint reply; structured and represented execution share that result. The typed application continuation also retains those full results, including the actual success-priority filtering. A typed duplicate-equation control returns both changed frames to a saved caller through the real callback transitions. The argument continuation now resumes each head's remaining arguments under that head's selected frame. A second argument following two equation results keeps both changed endpoints; restoring the common input frame preserves the packet values and fails the full-result observation. The same control law covers changed error and Empty results: it publishes that occurrence without evaluating the pending argument suffix. Its independent history records either the completed packet or the first failure and the unexecuted suffix. A saved head-return frame needs only the residual children; it does not replay the completed head. Duplicate rejected casts remain separate occurrences, and the public success-priority judgment excludes successful alternatives only when total rejection has independently been established.

The following query-item and materialized-entry laws additionally concern an auxiliary minimal interpreter. They describe useful representation boundaries, but do not identify that interpreter with Rust HE or construct a CeTTa step map. Completing its instruction coverage is not a prerequisite for the native correspondence.

The scoped-query completeness law additionally constructs the interpreter's actual `queryOpItemsOf`

`Rule` work item and its `evalResult` continuation, preserving the entire saved minimal stack. These work items are already merged; the older HE equation task expects pre-merge candidates. Bounded HE application now has a constructed observation law at every fuel. The existing canonical native model promotes it to equality after actual materialization, and to invocation congruence because `evalOp` substitutes before dispatch. This does not license raw shape inspection of unresolved syntax, or establish transport through every later typed RHS. The actual query-item theorem uses the same materialization boundary to identify its emitted continuation with the independently freshened source result after substitution.

An independent normal finite presentation of the binding equations now supplies the materialized source entry. Its one-pass result and the actual query value agree up to renaming residual variables, by the existing principality theorem. Exact function arity, the broader function-head test and embedded-instruction classification are preserved separately. A raw head guard on this normal source value constructs both the independent raw-completion judgment and the actual finished query item. Function entries instead supply alpha-related body witnesses. This applies at the existing query materialization boundary; it does not authorize evaluating held operands or inserting substitution into raw structural instructions. Transporting arbitrary unresolved source syntax or executing every related body remains a further obligation.

Function completion preserves fuel, native state, pending alternatives, saved callers and earlier results. Open `cons-atom`/`decons-atom` steps and their `chain`/`return` bodies are constructed on both sides. The finished chain handler materializes its raw result under the selected output bindings; no fixed-result premise is needed by the general bridge. A bound head becomes a symbol while two correlated free occurrences stay shared. The actual complete driver suffix retains its pending queue and earlier results. Materialized entry is a separate operation: raw primitives do not substitute. A bound tail alias distinguishes those entries, and empty deconstruction exposes an uncovered source fault.

Unify has sound and complete finite endpoints, including shared and reflexive variables, success and refusal. Source and native merge orientations need only agree on their complete solution theories. The actual candidate list retains its occurrences; fallback syntax stays raw until materialization.

A caller-indexed terminal observer agrees with the actual function handler after materialization, and its prefix law preserves faults and publication. The nearest saved caller stays raw as the `NoReturn` subject; without a caller, the terminal is blamed. The existing source judgments now retain that caller and protect entered chain/function syntax in the query scope. This is the full-syntax frame policy; Rust's placeholder frames require an adapter. Malformed forms and the difference between core HE and extended LeaTTa instruction classifiers delimit those auxiliary results. These source judgments now materialize every finished function-body result before classifying it as terminal or scheduling an exposed instruction. The independent relation is generated by finite binding-equation presentation, exists exactly for satisfiable frames, and agrees with the actual resolver up to residual variable renaming. Controls expose both a return marker and a further instruction through a bound variable. This corrects raw-syntax terminal classification; the general body/typed-continuation correspondence induction remains open.

Equation producers now earn this materialization from their actual matched output frame and retain the saved continuation. Native producers declare a separate raw-or-materialized binding mode, independently of whether they have completed interpretation. Raw delivery keeps the authored atom literally; materialized delivery must supply its independent presentation. These policies do not identify raw LeaTTa callbacks with Rust's post-merge materialization.

A continuation slot is distinct from its binding environment

The distinction has an executable counterexample:

```
!(function (chain (unify $x A B refused) $x (return $x)))
```

Rust HE returns `B`. An earlier CeTTa image returned `A`, although renaming the chain destination to `$y` produced `B`. The child unification constrains `$x` to `A` and selects the branch `B`; these are different pieces of information. Chain substitutes the selected value into its saved template and carries the child's bindings separately. Applying those bindings to the template first erases the slot. For $\beta(x) = A$, the two operations need not commute:

$$[x := B](\beta(x)) = A \qquad \neq \qquad \beta([x := B](x)) = B.$$

The repaired instruction path retains literal instruction operands and performs the selected substitution before entering the continuation with its reached environment. This also protects a nested instruction's future destination from premature substitution. It does not turn minimal chain's structural substitution into capture-avoiding lambda substitution: replacing a slot can also replace the same name inside a nested instruction's syntax. Each language profile must state the operation it actually provides.

Raw instruction shape checks expose another boundary. A variable constrained to an expression is still a variable at a raw `cons-atom` or `decons-atom` operand; substitution is licensed at the instruction's specified boundary, rather than inserted before every shape test. For `unify`, success requires a surviving match and merge. A match whose merge conflicts with the incoming bindings selects the failure branch with the original environment, rather than silently losing that occurrence.

The runtime qualification compares these cases with Rust HE across the declared HE profiles and both canonical and fallback execution paths. Nested collection additionally preserves captured bindings, repeated equal occurrences and one committed effect across every scheduler pause. The implementations can enumerate the same completed multiset in different orders; exact resumption continues to preserve each implementation's own chronology. These are local instruction and runtime results, not the complete native/source simulation.

A raw rewrite result still has a return continuation

The root rewrite relation and the public evaluator observe different boundaries. For example:

```
(= (freeze $x) NotReducible)
!(freeze (+ 1 2))
```

Rust HE returns `(freeze 3)`. The argument has already been evaluated; the returned protocol symbol asks the owning invocation to retain that assembled call. An earlier CeTTa image instead published `NotReducible`; an intermediate repair restored the unevaluated `(freeze (+ 1 2))`. Neither observation implements that return rule. The independent source relation also lacked this stage on its successful equation and emitted-grounded branches. A checked counterexample exposed the source defect independently of the native implementation.

Let a be the assembled invocation, v its raw result, D its selected return demand and β its reached bindings. The ordinary return judgment has three cases:

$$\mathrm{return}_D(a, v, \beta) = \begin{cases} [(a, \beta)] & v = \mathsf{NotReducible}, \\ [(v, \beta)] & v \text{ is Empty or an error}, \\ \mathrm{eval}_D(v, \beta) & \text{otherwise.} \end{cases}$$

This is an intermediate judgment; the public observation still performs its own filtering. The repaired source rules and retained worker both represent this continuation explicitly. The invocation, bindings and demand survive a scheduler pause. Restoring the invocation does not evaluate its arguments again. In particular, a raw successor alone is insufficient evidence for replacing a public call: its ordinary return evidence is also required. The smaller atomic-contraction fragment licenses non-protocol successors; the staged machine continues to cover protocol replies.

The selected native return clauses also have checked partial projections. Their source squares cover refusal, stopped replies and the actual typed callback request, retaining the assembled invocation and reached frame. The ordinary callback's variant-only operand and its fully materialized source value remain separate readbacks. A direct corollary applies when those inputs already agree; general open-input transport is still a proof obligation. The generic retained adapter starts after the C child push. A constructed native-memory join now supplies that entry from selected parsed field updates, operand reads, scalar initialization and intrusive push/pop. The paused sequencer's advanced counter determines the occurrence, while the active return frame's copied row supplies its environment. The retained residual contains the actual stack address, child address and complete storage. Selected owned-data copy paths now derive identical scalar, binding-row, variant and goal-map images from the actual stores and array transfers. Repeated payload cells survive, while equal contents in separately allocated arrays retain distinct physical identities. The retained binding path copies through the actual temporary and aggregate assignment; the resulting child-request equality also preserves decoding refusal. These are data projections at explicit successful helper boundaries. Allocation, retention, index rebuilding, cache refresh, materialization, payload decoding and ABI layout remain separate contracts; the result does not establish the entire native caller body or a loader from arbitrary source syntax.

One materializer boundary now executes the complete parsed variant-only helper together with its actual presence and storage helpers. For a live inline outcome with null variant storage, it returns the stored atom and preserves arbitrary disjoint framed memory. The proof supplies neither a materializer-result oracle nor a helper-noninterference assumption. Controls separate null input, answer-reference inflation, dead or malformed storage, and a retained unfinished cut. The full parsed helper is also checked on its zero-binding and populated-cache paths, under the actual automatic storage entry and exit contract. A populated cache need not equal the stored atom; the full helper returns that cache, whereas the variant-only helper ignores it. The controls refute unconditional agreement between these two readbacks and show that a pause before the cache write retains that write without replaying it after resumption. Nonzero binding materialization, allocation and ABI interpretation remain separate joins.

The physical statement profile separates by-value record admission from logical cell extent. An extent supplies an array stride; it does not imply that a pointer or integer local is a record. The explicit finite record inventory selects aggregate copying and automatic record storage. One checked profile consequently supports pointer-array addressing and reads, scalar pointer assignment and complete two-cell record copying together. A pointer supplied as that record's source is refused. Byte extents and native layout agreement remain independent representation obligations.

The finite physical Atom reader also distinguishes numbered symbols from managed symbols whose stored number is zero. Managed symbols retain their exact spelling bytes and length, including embedded NUL and invalid UTF-8; conversion to a source String requires a checked UTF-8 boundary. Actual forwarding, terminal-tag inspection and owned byte reads compose with the existing graph reader. Repeated child pointers preserve repeated positions, while equal contents at distinct addresses preserve distinct storage nodes. The sorted frame-directory reader separately executes the parsed probe loop: capacity, half-load and full-epoch invariants earn completion without assuming a successful lookup. These are physical helper correspondences, with table publication, native layout and borrowed lifetime still explicit.

The actual open-addressed handle directory now also executes its helper after loading each reached epoch. The by-value reference check, automatic storage, full-epoch comparison and lexical cleanup compose into the complete parsed `find_ref` body. Its retained runner preserves the exact unfinished suffix and does not repeat a completed helper effect. A separate physical symbol-table proof executes the actual span lookup, retaining the distinct seven-tenths load invariant, native-width index arithmetic and byte comparison. The shared source reader admits the actual const character-pointer view by an independent C11 type judgment; it preserves nullable pointer identity and the operand's reached effects without inventing storage ownership. The coherent seven-owner cohort

passes strict checking and audits 7,141 kernel declarations and 3,946 theorem declarations; 55 generated implementations are validated separately. These source/helper joins do not yet close nonzero binding materialization or the complete activation and caller-return paths.


The current function-entry projection reads the body, checks its expression kind and records the selected native profile flag before deciding whether to push an instruction child. The checked branch preserves the parent stack, original bindings and private outcome target. Compatibility stepping, minimal-instruction stepping and a raw return are separate admissions to that branch. An ordinary evaluator call belongs to the other branch; lack of a projection for that call does not establish native failure. This selected entry theorem and the existing function-return square retain their independent body-execution and materialization obligations.

Provenance is essential here. A raw invocation refusal, a held Atom operand and a value explicitly completed by a native producer are different events, even when their syntax is the same symbol. Globally interpreting all completed values again would lose that distinction. A concrete Rust-compatibility defect exposed this boundary: `get-state` previously kept a stored callable unevaluated and omitted its effects. The repaired compatibility path first uses ordinary application admission, then emits its raw host result through the retained return continuation. Incompatible codomains are rejected at the owning call before the stored child runs. `get-atoms` retains its declared Atom demand, so stored callable data remains data. Explicit minimal `eval` uses the raw operation without adding ordinary return. Other profiles retain their declared completed-host policy. These producer-specific controls do not establish unrestricted HE conformance.

The same native qualification exposed two additional boundary errors. First, `case` must retain the source occurrence's bindings while matching and entering a branch. An Empty occurrence contributes neither a value nor its bindings; its empty fallback uses the incoming environment. Second, disabling an unbounded execution accelerator must not silently turn a requested lazy selection into eager evaluation. The repaired paths agree on both selected answers and committed effects. Pause/resume controls exercise the saved invocation and each allowed retained prefix.

Existing owners. `Mettapedia/Languages/MeTTa/HE/Spec/Eval.lean` and `Spec/Eval/Minimal.lean`; `Mettapedia/Languages/MeTTa/HE/Eval.lean`, `EvalSpec.lean`, `Correctness.lean`, `RecursiveTasks.lean`, `RecursiveMachine.lean`, `FirstSuccessSourceExecution.lean`, and `CeTTaRuntimeContracts.lean` (`CallReturnControl`); CeTTa's `eval_he_boundary.inc`, `eval_he_canonical.inc` and `eval_he_execution.inc`.

> **Boundary.** The source return judgments and their maintained evaluator refinement are kernel-checked. The native results additionally have executable Rust, profile, GC and retained-execution controls. These are separate evidence boundaries; the full native C simulation is still an obligation.



Local retained equation execution. The body returns through the saved continuations; it does not replace its changed bindings by the pre-call frame. This continuation law does not identify the fuelled HE and explicit-scope LeaTTa query policies, or establish their full independent recursive-source correspondence.

Native retained execution supports pause, continuation, inspection and cancellation. Checked readback components preserve contextual bindings and distinguish pending computation from written syntax, under explicit representation assumptions.


The general correspondence still needs arbitrary nesting, scope, quotation, typed raw arguments, shared choices, branch worlds, demands, ownership, effects and residuals. Flattened answer equality cannot establish this: losing a binding world may change a later demand.

Existing owners. `Mettapedia/Languages/MeTTa/HE/RetainedArgumentSpecification.lean`, `Mettapedia/Languages/MeTTa/HE/ScopedEquationQuery.lean`, `Mettapedia/Languages/MeTTa/HE/LeaTTaScopedQuery.lean`, `Mettapedia/Languages/MeTTa/HE/FirstSuccessSourceExecution.lean`, `Mettapedia/Languages/MeTTa/HE/ReflectedStepSharing.lean`, `Mettapedia/Languages/MeTTa/Bridges/GSLT/CeTTaNeedHistory.lean`, `Mettapedia/Languages/MeTTa/Bridges/GSLT/CeTTaFrameWriteback.lean`.

> **Boundary.** The model proofs and runtime controls are distinct evidence. They do not constitute a complete theorem about compiled CeTTa execution, nor freeze the eventual Prime candidate calculus.

8 GSLT and rho: retain searches, publish occurrences

The scoped GSLT scheduler advances actual premise, matcher and query frames. It retains pending tasks, proved results and unresolved obligations. PeTTa's authored program driver packages these searches into resumable jobs. Its aggregate and publication are deliberately distinct: a later job may already have results while an earlier incomplete job still controls their public order.



The actual `rho:run:resume-search` equation advances the pending `ProgramObservation` and returns the full updated `RhoSearch`. The evaluator-return and completion theorems cover that quoted equation, including unchanged ambient state and empty effect queues. `Search.resume_valid` retains earned validity, and publication grows by prefix.

A released receipt supplies a source-valid rho step modulo structural congruence. The existing `step_sound`, `step_quiescent` and saturation results distinguish a step, quiescence and insufficient search allowance. Empty publication establishes quiescence only when the search is complete. Stopping with no answer so far is not evidence that there is no answer.

The shared trajectory law is instantiated by scheduled states and actual PeTTa jobs/programs:

$$\mathsf{resume}(s, m+n) = \mathsf{resume}(\mathsf{resume}(s, m), n).$$

The units differ: scheduled fuel counts ticks; PeTTa adds allowance per job. Publication cursors emit only a newly released suffix and keep absolute occurrence ordinals, including equal-valued duplicate answers.

Existing owners. `Mettapedia/OSLF/MeTTaIL/StructuralDescentScheduledExecution.lean`, `Mettapedia/Languages/MeTTa/PeTTa/Bridges/MeTTaIL/GeneralProgramResumptionExecution.lean`, `Mettapedia/Languages/MeTTa/PeTTa/Bridges/MeTTaIL/RhoRunnerExecution.lean`.

Retained `Execution` adds successive completed COMM commitment and cancellation to the search state. A commit selects one completed publication, records its before/receipt/after triple, and begins a new search for the successor process. Its quoted `rho:run:commit-candidate` equation checks the entire supplied receipt wire against that local selection. A foreign candidate or an immediate stale candidate does not extend the history. Resume preserves the committed prefix; cancellation preserves history and drops live work. `Execution.advance_add` instantiates the shared resumable trajectory. Its fuel counts commit attempts, including no-ops; matcher allowance is resumed separately. A two-communication control keeps both commits in chronology.

Every execution reached by any sequence of retained operations is sound (`Retained.Reached.sound`): its history is a chronological sequence of committed depth-one COMMs from the canonical start (`Retained.Reached.chain`), its live search runs at that history's endpoint, and a done phase there is exact quiescence. A commit placed at the wrong state, or with a result that is not the receipt's, is not a chronicle. Under the common owned host (`Retained.owned_publication`) committed COMMs reach the world exactly once, copies of used tickets are refused, and the delivered history is that chronological COMM sequence.


Selection need not always use the first published receipt. `commitPublished` validates membership of the complete supplied receipt, including its matcher, source job, bindings and premise history. Two ground communications in disjoint multiset components construct a retained diamond (`disjoint_retained_diamond`): each edge is an actual completed search and licensed commit. Both schedules reach the same process; their chronological histories remain distinct, with equality only under the declared causal observer.

The local dependency interface names input, output and fresh allocation occurrences. Distinct keys retain distinct resources even when their process values coincide. Fresh, live and spent states prevent reusing a consumed key. The actual read program produces the candidate's dependencies; disjoint read/write footprints prove that an unrelated commit preserves its validation. `replay_after_history_refused` excludes reusing a consumed occurrence through any later accepted history. Cancellation closes the owned publication channel, and stale reads publish no world change even with a current ticket. The quoted `rho:run:commit-published` and cell-store commands have source execution and store-refinement proofs, as well as matching native controls. An old whole-process search receipt is never relabelled for the successor: its search is rebuilt there, while the local dependency certificate can survive independent updates.

> **Boundary.** A commit's independent rho-step licence requires valid search and a well-typed process. The quoted bridge uses the pinned depth-one COMM plan and prepared encoded values. The owned host is a sequential model of authority; durable or distributed exclusive delivery is a host obligation, and fairness over all alternatives is not proved here.

9 World queries: what can safely survive a change?

A pure adaptive query can choose its next read from a previous result. Its observation therefore contains both its answer and the ordered reads it actually performed. A read certificate records complete values, including absence and complete ordered match lists.



Suppose the query reads all matches at a key and gets $[a, a]$. Replacing that list by $[a, a, b]$ changes the read even though both results are nonempty. Replacing it by $[a]$ loses an occurrence. Reordering it can change a first answer. An empty result must also be recorded: a later insertion invalidates the earlier absence. An update to an unread key can remain compatible.

`run_eq_of_agrees` proves that agreement on the complete performed certificate preserves the query's answer and read path. `Retained.resumeValidated` checks the performed prefix before executing any pending read. `Retained.validated_fresh` connects an accepted earned prefix to fresh execution of the original query in the new world.

Snapshot continuation is a different policy. A residual may already have closed over a captured answer, and retains it even when the current store changes. Failed validation does not retroactively turn that old residual into a fresh query. Starting the original pure query again is possible; replaying committed effects to refresh knowledge needs a separate effect contract.


Writes computed from reads follow the same rule. An owner runs a transaction, a pure query whose answer is a list of writes, on the snapshot it saw and proposes the writes with the complete read certificate. The ledger commits the proposal only when every recorded read agrees with the current store. An accepted proposal writes what its transaction would write now (`commit_fresh`), so accepted commitments are serializable (`commitAll_serial`); a proposal is refused exactly when one of its reads changed (`commit_refused_iff`). Two increments of one counter from the same snapshot commit once; rerunning the refused one on a fresh snapshot commits it; writing both blindly loses an update. The ledger is a retained state for the owned host, which publishes each accepted write list once (`ledger_published_once`).

Existing owners. `Mettapedia/Machines/ReadOnlyQuery.lean`, `Mettapedia/Machines/ReadCertifiedQueryReuse.lean`, `Mettapedia/Machines/ValidatedCommit.lean`, `Mettapedia/Coalgebra/CoherentPrefixTower.lean`.

> **Boundary.** This is a pure read interface. Query identity, program revisions, ownership and service authority are additional dependencies; an unchanged read list alone does not validate a changed program or authorize consumption.

10 Effects, services and the limit of a copied continuation

An effect session retains an actual driver residual, the current interpreted world, and its committed event history. Continuing advances the residual and interprets only the new event suffix. Splitting a budget preserves all three components, including when the handler performs a non-idempotent increment.



The independent recursive `Runs` relation supplies the meaning of children and caller continuations. Explicit frames realize that meaning with the exact ordered trace. `Session.resume_add` gives the complete sliced state law. `Session.cancel` discards pending execution and preserves the committed world/history; later resumes stutter.

Pairwise commuting actions permit a permutation theorem for the final world. The ordered trace still records a different schedule. A negative control shows a reversed noncommuting pair changes the world. Commutation must be proved for the actual actions and interference conditions.

The general event machine also has resumable service handling. A request can run another machine while retaining the caller and service continuations; faults, stuck endpoints and divergence remain distinct from replies. This is related to the handler-as-computation approach of interaction trees [5]; the present interface uses explicit states and finite budgets.


Owned interaction

The pure session and cursor laws do not enforce exclusive ownership: copying an earlier cursor can redeliver, and restarting a program can repeat an increment. The owned host adds consuming authority. A retained computation begins under a ticket; submitting its derived actions consumes the ticket, applies the actions once to the shared world and issues the successor ticket. A used ticket is refused (`Owned.used_ticket_refused`), so copies of a computation act at most once (`Owned.copies_act_once`); a cancelled computation refuses further work, private forks never touch the shared world, and every reached host state accounts its world as the initial world under the delivered actions. For commuting actions the final world does not depend on the interleaving (`interpret_commute_past`, `interpret_interleaving`); a noncommuting pair is a negative control. External crash recovery, durable exactly-once delivery and the disposition of non-droppable obligations need a service protocol beyond this sequential host.

Existing owners. `Mettapedia/Machines/OwnedPullDriver.lean`, `Mettapedia/Machines/ExecutionHistoryReadout.lean`, `Mettapedia/Machines/ResourceOwnership.lean`, `Mettapedia/GSLT/Distinction/ProductiveBlocks.lean`.

11 The fixed C-language machine

The fixed core is a source language over the existing C11 semantic modules: typed integer operations under a selected integer model and signed-conversion policy, byte memory with effective types, automatic object scopes and array pointers. Names resolve through the lexical scopes of the current activation. Pure expressions read integer elements, compute, take addresses and move pointers within live arrays. Statements assign through places, set pointer variables, call functions recursively with parameter objects, return values, branch, loop, break and continue, open blocks that reserve declared objects and retire every owned lifetime on every exit, allocate and release dynamic objects, and suspend on external requests.



The executable step is sound and complete for an independent step relation whose premises are the memory, scope and expression judgments (`step_iff`), up to the two choices C11 leaves open: the identity of each new object and whether an allocation succeeds. Undefined behaviors stop with their reason: arithmetic overflow or division by zero, an access to a dead, indeterminate, out-of-bounds or misaligned element, a trap representation, a pointer formed outside its array, an invalid or repeated release, or a used missing return. A constraint violation and a failed host service are reported separately. As a common event machine the core publishes each step as an occurrence with its actual configurations, and budget slicing resumes the retained configuration exactly.

The Cesta reader is a static checker for the core fragment. Names resolve through the C block scopes, operands are integers or pointers to a declared integer type, and calls are checked against the signatures of the program's functions and of the host's services. Interleaved declarations become nested blocks; `E1[E2]`, `&*E` and `&E1[E2]` follow their C11 equivalences; returned values and service arguments are converted to the declared types; the end of `int main` returns `0`. Every reading function is equivalent to an independent reading relation (`readUnit_iff`). Constructs outside the fragment are refused, not approximated. Sources parsed by the Cesta binary run on the core to the values GCC and Clang compute. On the undefined controls, AddressSanitizer and UndefinedBehaviorSanitizer report the use after scope, use after release, double release and overflow under both compilers; only Clang reports the pointer formed past its array.

Requests are served by service machines through the common callback protocol (`served_call`); running services as machines is a compilation stage from atomic answers (`servedStage`). With the retained HE evaluator as the service, a C loop calling a MeTTa function returns what GCC computes for the same loop over a C definition, and the trace contains exactly the evaluator's result occurrences (`metta_call_publishes_evaluator_meaning`). Several results, or an unreadable one, stop the program with the service's fault: a reply never selects one result from several.

The located layer remains the place for side effects inside expressions. Its expression scheduling makes full-expression boundaries and unsequenced conflicts explicit, and `StatementExecution.execute_iff` connects its executable transition to independent rules.

The common fixed/located fragment now has a constructed translation. An executable lowering

agrees with an independent admission relation for arbitrary finite pure expressions and for assignment, conditionals, loops, break, continue and return. Pure expression schedules preserve the same scalar and semantic memory. An assignment additionally executes its actual conversion, store and returned-value occurrences. Both legal store/result orders reach the same boundary; neither may bypass an unfinished operand.

`statement_step_simulation` and `control_step_simulation` replace one fixed-core control step by its actual located expression and boundary steps. Their finite-history composition covers arbitrary admitted successful runs. `Block.finished_realization` then executes the final verdict on the existing budgeted runner and retains the complete receipt list and unused schedule suffix. The common memory relation preserves object allocation and lifetime headers as well as contents; reads outside their admitted live catalogue are refused. A counter loop reaches zero with the committed values $[2, 1, 0]$ under both store/result policies.


Different legal evaluation orders can encounter different first faults when both pure operands fail. The cross-layer observer therefore distinguishes a defined scalar result from failure without identifying those diagnostics. Each located execution retains its own exact fault and chronological prefix. The whole-run reverse construction now discovers the owning source control through every partial expression and assignment history. Its `ReachedControl.step` either constructs a genuine source step or strictly decreases finite pending-expression work. Thus arbitrary source loops remain possible while an infinite stretch of source-free administration is excluded. `terminal_observation_iff` proves preservation and reflection of complete success or refusal under the admitted scheduler. The schedule license checks the actual next ready occurrence; an unready operation is malformed scheduling, not source undefined behavior. `ReachedControl.run` additionally retains the earned source prefix and exact receipts at every budget exhaustion and selection request. No supplied decomposition into source blocks is required.

Existing owners. `Mettapedia/Languages/C11/FixedCore.lean`,
`Mettapedia/Languages/C11/FixedCoreStatements.lean`,
`Mettapedia/Languages/C11/CestaFixedCore.lean`,
`Mettapedia/Languages/C11/FixedCoreServices.lean`,
`Mettapedia/Languages/MeTTa/HE/RecursiveService.lean`,
`Mettapedia/Languages/C11/LocatedStatements.lean`,
`Mettapedia/Languages/C11/StatementExecution.lean`,
`Mettapedia/Languages/C11/ExpressionEventHistory.lean`,
`Mettapedia/Languages/C11/StatementMachineRefinement.lean`.

> **Boundary.** Object layouts are the selected ABI's, an explicit parameter; pointer variables hold an abstract provenance-carrying value; external services answer each request at most once. Named extensions outside the core include calls inside expressions, pointer-typed objects in byte memory, structures, floating types, `for`, `do`, `switch` and `goto`, array initializers, function pointers and threads. The common-fragment translation does not additionally cover calls, allocation instructions or side-effecting operands. These remain available only at their separately specified machine boundaries.

12 Regional machines and explicit crossings

A useful machine comparison fixes three things: a region of admitted programs, the observations to preserve, and the resource objective. Removing an observation can permit more representations, but does not by itself establish a faster implementation. Operational accounts and measured native costs are different claims.



A crossing states what is translated, which observer is preserved, what dependency/authority evidence travels, and how return or refusal behaves. Pairwise agreement is insufficient for arbitrary networks: composed paths must satisfy the applicable compatibility laws. Existing gluing results cover equation models over a shared binding algebra, equivalence-valued view systems with trivial cycle transport, and compatible causal histories with explicit read/write and observation hazards. None of these identifies arbitrary guest logics or supplies their complete native execution. A general sheaf account of regional machines still needs its actual restriction and gluing maps. Trivial cycle transport concerns changes of view that claim to preserve the same object. An effectful computation cycle can change the world and emit events; it is not such an identity transport.

Observation, demand and retention are separate controls

An observer chooses what distinctions a user sees. Demand chooses how much work is requested. Retention chooses what remains available for inspection or continuation. `once` and `select k` bound requested successful occurrences; they are not general permission to erase faults, reorder effects or discard owned pending work. Zooming out can license a coarser readout; zooming in later is possible only if the required information was retained.

Machines do not impose one universal logic

Conversion within one shared logic and transport between distinct logical guests have different contracts. A selected machine family retains each kernel's own state and question type. It does not make HOL, dependent type theory and set theory one calculus. A stable guest can remain stable while Prime's candidate develops, provided the crossings state their assumptions.

ZINC [6] is useful historical comparison for an ML implementation. Here ZAM denotes a *zipper abstract machine*, which is a different idea and is discussed in Section 15. No general WAM optimality theorem is claimed. New regional machines can be derived or compared through these interfaces, then judged by correspondence and an explicit cost model.

> **Boundary.** The integration target is faithful higher-order MeTTa execution. CAM and the fixed C core supply substantial instances and reusable laws; they do not displace that language-facing purpose.


12.1 Modules, presentations and necessary machine state

A module assembles declarations and their selected policy layers. A GSLT states their operational meaning. A regional machine realizes that meaning with its own representation and control. These are distinct objects: joining declarations neither selects an evaluation strategy nor proves that two machines can interact safely.

Universality and the absence of a globally best optimizer do not determine how many machine families an implementation must expose. One interpreter can itself dispatch among several strategies. Regional specialization is justified by a stated program region, correspondence and resource objective, rather than inferred from undecidability alone.

A region can support a portfolio of implementations, including difficult higher-order regions; it need not have one fixed algorithm. Vampire provides an operational precedent for scheduling configurable proof strategies from workload features [26]. The existing bounded-search portfolio retains private batches, distinguishes cutoff from exhaustion and publishes one strategy's batch. Combining strategies' rediscovered answers would require a separate occurrence correspondence. Fair scheduling alone does not certify exhaustion after a finite budget.

Constraint-solving backends are also candidates for finite collection matching. A checked encoding must relate decoded solutions to the declared source matches, preserving their occurrence identities. Auxiliary Boolean assignments need not correspond one-to-one with those matches, so ordinary model counting does not automatically count semantic answers. SAT witnesses and checked unsatisfiability certificates can justify different conclusions; the encoding and coverage obligations remain [27]. Specialized AC representations can also be effective for important restricted rule classes [28]. The general complexity bound does not choose the best implementation for a workload.



An admitted execution region restricts a backend's qualification, not the module format. A first-order backend can refuse a presentation containing binders while retaining that presentation for a suitable scoped interpreter. A general interpretation path and its specialized realizations should share an independent source observation; the existence of that path does not by itself establish coverage of every binder or premise form.

The presentation and its surface syntax also have different responsibilities. The existing five-field `LanguageDef` carries sorts, constructors, equations and rewrites; `ExtendedLanguageDef` attaches independently authored dependent layers. A proof calculus is one such layer. Several concrete syntaxes can elaborate to this shared structure. Upstream syntax is an interchange route, not a requirement that every local extension fit a historical grammar. Improvements to notation must preserve binding, declaration origins and the laws of the selected layers.

Four current boundaries must not be conflated: the closed-theory `moduleTheory!` Lean quotation; the structured `module/1` envelope; textual `.module` languages; and the live runner's emitted MeTTa program. The quotation and envelope already have structural elaboration laws. The runner's `ReadAfterRender` theorem concerns MeTTa program text, not the upstream module grammar. A

canonical portable surface now establishes

$$\mathsf{readBytes}(\mathsf{renderBytes}(P)) = \mathsf{some}(P),$$

with a separate elaboration theorem into the existing assembled presentation. The character reader uses the existing lexer/parser/atom-reader pipeline; the byte reader validates UTF-8. The complete finite `LanguageDef` codec retains binders, collection metadata, equations and scoped premises. Dependent layers carry an explicit indexed codec; proof calculi, export names and products are concrete instances. This does not claim that every Lean function or relation has a finite serialization.

The surface is an inert `(module:document payload)` declaration. Origin-bearing entries survive the text boundary before the existing import contract decides sharing or collision. Unknown envelope payloads remain data; a declared layer rejects an incompatible schema. The canonical syntax does not implement a historical upstream grammar. Preserving comments, formatting and import expressions still requires a separate source representation: an assembled presentation cannot reconstruct information it has discarded.

A finite rule list need not imply first-order syntax: its rules can have binders and higher-order premises. An effectively enumerable rule family additionally needs a finite generator description and evidence for each selected instance. An arbitrary semantic relation in Lean's abstract `GSLT` record need not be effectively enumerable or serializable. Keeping that semantic generality is compatible with requiring explicit presentation and realization evidence at an executable boundary.

Even a simple specialization must carry the typing boundary. A variable-root rule $x : \mathsf{Nat} \rightsquigarrow \mathsf{zero}$ structurally matches a Boolean term if its type is forgotten. Checked invocation-sort selection must exclude that candidate before execution, retaining the original indices of later rules. Comparing two untyped implementations would miss this error. The same contract must fix when query inputs become available. In the checked provider profile considered here, an output of the current query does not retroactively satisfy a required input to that query.

The question of necessary state is relative to the admitted observations and future interactions. Write

$$s \approx_{O,\mathcal{C}} t \quad \Longleftrightarrow \quad \forall C \in \mathcal{C}, \quad O(C[s]) = O(C[t]).$$

The observation may include outcomes, residuals, effects or probability laws. An encoding supporting every such interaction cannot identify states outside this equivalence. Turning it into a machine quotient additionally requires stability under the actual transitions and contexts. This identifies necessary distinctions, not a fastest implementation or a computable finite quotient.

The contextual observed-coalgebra owner constructs a quotient, its transition square and exact factorization for compatible natural consumers. That owner uses labelled set-valued futures: order, multiplicity and probability require their additional representations and laws. Its quotient is not already the complete MeTTa machine. The ordered-machine bridge also reads an ordered successor list as a GSLT membership relation; that modal view alone forgets list order and repeated successors. Occurrence simulations transport these ordinary modal formulas without a positional alignment. The converse fails for occurrence preservation: a one-successor machine and a machine with two equal successor occurrences satisfy the same formulas, while their occurrence bags have different cardinality. This limitation is proved in the native-type bridge.


Admitted region	Useful machine structure	Distinction to preserve
Functional terms	CEK, Krivine, CAM or Need	Strategy, captured environment, shared demand
Rule search	Retained matcher and frontier	Occurrence identities, selected traversal, residual work
Reflective processes	Communication/reaction machine	Names, quotation, ports, permitted scheduling
Certificate checking	Decoder, proof state and snapshot	Declared theory, references, checked evidence
Probabilistic programs	Kernel-valued machine and history	Draw identity, scores, captured random values

Algebraic operational semantics connects syntax and behavior through a distributive law when the required rule-format and categorical hypotheses hold [30]. Polynomial syntax alone does not provide that law. Likewise, module-join compatibility is distinct from preservation of conversion or effects. The existing first-match priority counterexample fails substitution stability; ordinary relational rewriting has its own substitution theorem.

Existing owners. `Mettapedia/GSLT/LanguageDef/ModuleAlgebra/Semantics.lean`, `Mettapedia/GSLT/LanguageDef/ExtendedLanguageDef.lean`, `Mettapedia/GSLT/LanguageDef/ModuleAlgebra/UpstreamTheoryQuotation.lean`, `Mettapedia/GSLT/LanguageDef/ModuleFormat/Authoring.lean`, `Mettapedia/GSLT/LanguageDef/ModuleFormat/Text.lean`, `Mettapedia/GSLT/LanguageDef/ModuleFormat/Portable.lean`, `Mettapedia/Languages/MeTTa/PeTTa/Bridges/MeTTaIL/GeneralLiveRunnerEmission.lean`, `Mettapedia/Machines/BoundedSearchPortfolio.lean`, `Mettapedia/GSLT/Logic/ContextualObservedCoalgebraQuotient.lean`, `Mettapedia/OSLF/Framework/OrderedSystemNativeTypes.lean`, `Mettapedia/GSLT/Dedukti/LeanMinusPriority.lean`.

12.2 Staged lowering and runtime interaction

There are two different ways for one language machine to use another. *Staged lowering* transforms the source before execution. *Runtime interaction* keeps both computations alive across requests and returns. Both need semantic preservation, but they retain different states. Operational semantics based on explicit language boundaries is established work [7]; hygienic macro binding also has its own semantic models [8].



Cesta's current macro engine instantiates templates, resolves explicit binding origins, introduces fresh locals, and emits C. Argument metadata distinguishes syntax, values and modifiable places, with evaluation contracts. For the checked narrowing library, source and target types are syntax; the input value and output place are evaluated once by the emitted C. Macro expansion does not execute the input expression. The native compiler supplies active-header name inventory and checks the final C. This is a staged language layer; it is not an extra interpreter running beside the resulting native program.


The current GSLT driver instead retains a licensed request and actual search state for every job. Requests carry the presentation/environment, permissions, binding context, expected type, source and physical rule/site identity. Receipts retain matcher choices, captured and completed assignments, premise history, and local and reconstructed targets. The quoted authored equations are connected to PeTTa evaluation. The general target-step theorem requires an equation-free, checked-stratified plan and sufficient search allowance. Its exact canonical reduct-list theorem has a narrower root query-profile scope. A presentation emitter and a general whole-run loop still need their complete integrated proofs.

Treating an expander as an abstract machine can clarify its own binding and phase semantics. It does not require paying for that machine at program runtime: justified lowering can remove it. A live heterogeneous computation needs runtime crossing rules in addition to staged source transformations.

Existing owners. `Mettapedia/GSLT/LanguageDef/MacroTemplateNames.lean`, `Mettapedia/GSLT/LanguageDef/MacroDefinitionPorts.lean`, `Mettapedia/GSLT/LanguageDef/MacroCheckedNarrowing.lean`, `Mettapedia/Languages/MeTTa/PeTTa/Bridges/MeTTaIL/GeneralProgramDriverExecution.lean`.

12.3 A computational-metagraph machine as a candidate

A candidate Meta-MeTTa machine would retain regional computations at nodes and pending crossings at edges. Admission, transfer, advancement, reply, refusal, cancellation and dependency validation would be explicit steps. This heterogeneous machine remains an integration target.



The state needs continuations, ordered occurrences, dependency evidence, consuming authority and committed history. Each crossing must realize an independent semantics preserving the selected observations.

`MachineCore.familyCore` retains heterogeneous state/question types but cannot change the selection. `Machine.handle` constructs interaction with retained caller and service states. `ScheduledFrontier` preserves occurrence slots across differing completion times, under independence hypotheses. Publication, read-validation and effect-session laws still need the common ownership join.

`GSLT.Poly.BindingSignature` represents binding terms as a context-indexed free monad. The indexed polynomial client in `GSLT.Poly.SortedTraversal` retains argument occurrences and reply slots. Neither polynomial structure nor a slot determines a child's interpretation or force rights.

In the MM2 evidence-material theory, two actual matcher paths conclude the same fact but deliver different origin lists. Their consuming continuation cannot factor through conclusion support. An ordered material batch or receipt retains enough information; the recovery theorem uses a classical partial inverse, rather than an executable native decoder.


Native MM2 controls separately run a finite staged consumer on three input occurrences, two with equal payloads. Shared choice gives six deliveries; separate choice coordinates give twelve. Sequence fields recover their order. Retained cursors preserve the answers and three counter updates across reloads. Restarting repeats an update; changing the captured environment changes later answers. `head 1` alone still permits sibling writes. This does not establish a general MeTTa correspondence or external-effects protocol.

Producer identity supports sharing; delivery identity supports occurrence observation. Indexed set storage can retain both views. The richer encoding then carries the surrounding machine's cursor, world and commitment protocol.

Existing owners. `Mettapedia/Machines/MachineSubstrate.lean`, `Mettapedia/GSLT/Distinction/ProductiveBlocks.lean`, `Mettapedia/GSLT/Distinction/OrderedSimulationSpans.lean`, `Mettapedia/GSLT/Distinction/CausalGluing.lean`, `Mettapedia/GSLT/Scope/Holonomy.lean`, `Mettapedia/GSLT/LanguageDef/ModuleAlgebra/SemanticGluing.lean`, `Mettapedia/GSLT/Poly/SortedTraversal.lean`, `Mettapedia/GSLT/Logic/ProgrammableSpaceMM2EvidenceMaterial.lean`.

12.4 The trinity as a fibred web of presentations

The language-facing trinity names intensional mathematics, extensional mathematics and a GSLT-IL operation presentation. These are semantic roles, not necessarily separate kernels. The contextual computational-trinity framework compares programs, proofs or typed terms, and generalized elements in spaces. Each face is a presheaf over contexts, so substitution is part of the presentation rather than an untracked surrounding operation.



Comparison means a commuting triangle of natural maps. Exactness additionally requires invertible maps. The abstract construction does not instantiate the whole native DTT/HOL/set/GSLT triangle.

Actual categorical owners already have different variances. Theory models reindex by reducts along theory arrows, forming a Grothendieck fibration. Typed open code has forward transport and cocartesian lifts. Finite retained execution paths form another category-valued index. These constructions do not make every theory arrow an executable, resource-safe or conservative machine crossing. The complete step, residual and observer comparison must be added for the actual route. The additive world-model doctrine likewise cannot silently justify deleting a record or normalizing a Bayesian update.

The STT/DTT and selected set-family bridges are scoped interpretations. Representing a HOL formula does not prove it; a native inhabitant is not automatically a source HOL derivation. Logical borrowing needs the selected conservativity contract. Adding a stronger conversion bubble also needs its own substitution and join laws. Two component normalizers do not necessarily decide their combined conversion.

Hyperset presentations retain graph occurrences; material equality quotients by bisimulation. A dependent consumer therefore needs family and section descent before those distinctions are erased. Internal coalgebraic membership and the host's well-founded membership remain distinct. Initial/final comparisons also keep their bounds and existence hypotheses: identifying an initial algebra with a final well-founded coalgebra does not prove that every set functor has either [29]. Unrestricted powerset has no set-sized fixed point. Qualified bounded constructions state their size conditions separately.

Existing owners. `Mettapedia/Computability/ComputationalTrinity.lean`, `Mettapedia/GSLT/LanguageDef/TheoryGraphModels.lean`, `Mettapedia/Languages/MeTTa/PrimeCandidates/ContextualDataFibration.lean`, `Mettapedia/GSLT/Core/OperationalPathFibration.lean`, `Mettapedia/TypeTheory/MaterialSets/Hypersets/FamilyDescent.lean`, `Mettapedia/Logic/WorldModel/Indexed/Doctrine.lean`.

13 Proof machines: scoped, licensed composition


What follows from what, under which conditions?

A checking machine makes a proposed answer to this question inspectable. The local rules specify the permitted connections; evidence identifies the connection being proposed; composition connects its output to the next input. The interface shared by proof checking and rewrite checking is therefore *scoped, licensed composition*. This identifies a common organization, while leaving each presentation responsible for its own judgments, equality, binding and resource rules.

Write

$$T; \Gamma \vdash e : A \longrightarrow B$$

for a supplied piece of evidence e connecting boundaries A and B under presentation T and scoped conditions Γ. The notation is schematic: the boundaries may be premise contexts and conclusions, rewrite states, or typed interfaces carrying a world and resource obligations. An independent judgment determines which such connections are licensed. The machine realizes its checking discipline.



A boundary states what must fit. The selected theory determines whether evidence is reusable, whether an input must be consumed, and which conversions are admissible.

This perspective is continuous with the categorical treatment of proofs and programs as composable processes [15], and with rewriting logic's treatment of computation by proof terms [16]. Variable binding requires its own substitution algebra, including weakening, capture avoidance and metasubstitution [17]. These ingredients explain how a small checker can serve many presentations without choosing one object logic as their common meaning.

There are distinct categorical levels here. A rule with several premises is naturally a generator of a multicategory; substitution composes proofs into its premise slots. A sequence of unary rewrites instead gives paths in a free category. Exchange, contraction and weakening require the structural laws of the selected calculus. The category of checking machines describes realizations of these proof structures, with operational observations and costs. It is not the proof category itself. This agrees with the nLab's accounts of deductive systems, multicategories and syntactic categories [32]. Institutions additionally organize signatures, models and satisfaction under change of notation; they do not by themselves provide an executable certificate checker.

Storage navigation is a further realization level. A cursor, stack, stream, tree focus or dependency schedule may organize the same proof evidence. None is a primitive of every proof calculus. A focused position can be an observation of a machine—an account of what it is currently attending to—but a comparison must state whether it preserves that focus or hides it. Forgetting navigation need not forget the proof's premise dependencies. The dependency direction is from source rules to checking realizations and then to storage adapters, rather than from a particular backend to logic. For the authored-calculus classifying category, closed source derivations are equivalent to arrows from the empty premise context to a singleton goal; the two executable maps preserve the actual proof term. VibeITP and Metamath connect their source judgments at this level, before choosing graph replay or retained source-address checking.

13.1 Local evidence, exact checking and coverage

For one admitted effective presentation, let $\mathsf{Cert}_T(\Gamma; A, B)$ be the supplied certificate data and let $\mathsf{Valid}_T(\Gamma; A, e, B)$ be the independent validity judgment. The local checker earns

$$\mathsf{check}_T(\Gamma, A, e, B) = \mathsf{true} \quad \Longleftrightarrow \quad \mathsf{Valid}_T(\Gamma; A, e, B).$$

The separate coverage theorem relates this judgment to the intended source relation:

$$A \ \mathsf{Step}_{T,\Gamma} \ B \quad \Longleftrightarrow \quad \exists e.\ \mathsf{Valid}_T(\Gamma; A, e, B).$$

The first theorem qualifies the submitted evidence. The second establishes which source steps have a representation in that evidence language. Neither asserts that a search procedure will find the evidence within a given budget. Existential coverage alone also supplies no polynomial-time certificate translator.

For an ordinary calculus with implication elimination, a local rule is

$$\frac{T; \Gamma \vdash p : A \qquad T; \Gamma \vdash q : A \Rightarrow B}{T; \Gamma \vdash \mathsf{mp}(p, q) : B}.$$

Its checker resolves the two premise citations, checks the rule instance and compares the claimed conclusion. A resource-sensitive rule instead states how its inputs are split or shared. Local computation can instantiate a rule; evidence must still establish its side conditions. A negative premise such as "no equation applies" requires a checked exhaustion argument or a justified index certificate.

Declaration identity belongs to this boundary. Content addressing can locate a rule, while exact comparison or stated digest assumptions establish which rule was found. A repeated declaration can have several occurrences despite identical content. Certificate references must retain the occurrences required by the observer. The host additionally identifies the theory it intended to authorize: a valid proof under a packet's supplied theory does not identify that theory with an externally requested one.

13.2 Proof terms, slots and retained ambiguity

A proof term records enough information to reconstruct the licensed use. For an authored rewrite this can be a rule occurrence, a typed site, matching choices, premise references and equation evidence. Deterministic fields can be computed during replay. The current `GeneralRewriteRecipeExpansion` distinguishes a compact invocation from its expanded firing receipt and proves sound expansion and reconstruction of valid expanded firings.

Consider a two-input rule $r : (A, A) \to B$ and evidence p, q of A. The terms $r(p, q)$ and $r(q, p)$ record different slot assignments. Their conclusions may coincide; identifying the derivations requires an explicit equation or observer. Unique scoped names for slots, together with a substitution, can encode the assignment. They do not remove choices caused by collection matching, equations or alternative premise derivations.

Ambiguity may be useful compression. A packed proof structure can retain a family of alternatives, just as a packed parse forest retains multiple parses. Its boundary must say whether it certifies one selected derivation, all represented derivations, or a complete collection of derivation occurrences. Finding one valid branch licenses an existential claim. Certifying every represented branch requires their local validity; claiming that the family contains every source answer additionally requires coverage and multiplicity laws. Backend traversal order grants none of those permissions.

The following quantities are distinct:

stored nodes, reference uses, derivations distinguished by the selected observer.

A shared node can have many uses. Two positional replay choices can yield the same firing observation, while two identical declaration copies can generate distinct answer occurrences. The quotient must name what it forgets and prove that the remaining consumer descends through it.


Sharing can change certificate size exponentially. A fixed example in `ProofSharingBounds` has an axiom q_0 and the rules $q_n, q_n \vdash q_{n+1}$. Every accepted proof tree of q_n contains exactly $2^{n+1} - 1$ nodes. A chronological DAG instead stores $n + 1$ nodes and two references at each nonbase node. Its checked input size is at most $4(n+1)^2$ even with unary rule and reference indices. The resulting theorem excludes every polynomial-size translation from this calculus's DAGs to its trees. This is a lower bound for the target representation, rather than a claim about the behavior of one unfolding algorithm. It does not separate Frege from extended Frege.

Textual parsing is another boundary. A structural certificate reader is not the lexer and grammar of its source language. Source ambiguity must survive in the packed parse result until an explicit policy selects, ranks or rejects it. Binding lowering then preserves the selected scopes. The portable presentation roundtrip supplies a proved textual surface for its supported document schema; it does not identify every upstream module grammar with that surface.

13.3 The algebra of checked composition

Five operations expose the common algebra:

Operation	Evidence being composed	Required law
Sequence	$A \xrightarrow{p} B \xrightarrow{q} C$	Exact joining boundary.
Hole filling	Premise outputs into an open derivation	Substitution respects scope and the selected structural rules.
Context	A local rewrite inside $C[-]$	The context is licensed and replacement preserves its typing and binding interface.
Sharing	Several references to stored evidence	Every reference use remains justified and counted where required.
Parallel	Two orders of independent actions	Checked residual edges close the selected square.



Temporal composition and premise substitution are distinct constructions. A particular checker realization relates them by adequacy.

The common executable law is

$$\mathsf{replay}(s, p +\!\!+ q) = \mathsf{replay}(s, p) \gg\!= (\lambda t.\, \mathsf{replay}(t, q)).$$

It holds for success and refusal in `DerivationGraph.replayFrom_append_eq`; the authored rewrite instance is `GeneralRewriteRecipeComposition.Trace.replay_append`. Its categorical readout is

composition of *partial state transformations*. A bare Boolean verdict forgets the intermediate state needed for composition. On successful paths, identity and concatenation give a category of checked executions.

Open derivations have another category: `CertificateGSLTClassifyingCategory` takes premise contexts as objects and vectors of open derivations as morphisms. Composition substitutes those vectors into premise holes. Its existing Cartesian structure licenses reuse and discard. A multi-input or linear presentation needs its corresponding multicategorical or monoidal structure; these structural permissions are not consequences of sequencing alone.

The authored checker already realizes the other three operations. `GeneralRewriteRecipeContext` transports local receipts through admitted typed contexts, including binders. `GeneralRewriteRecipeDAG` admits local recipes and reuses the existing shared-certificate checker for references and joins. `GeneralRewriteRecipeParallel` checks four original residual firings, independent addresses, stable site labels and literal endpoint closure; the accepted square constructs an existing Mazurkiewicz swap. It does not infer the missing residuals from two disjoint sites. Changed provider worlds or observable effects require further independence evidence.


13.4 Checking whether another machine was stepped correctly

Let M have states S and an independently stated transition relation $s \longrightarrow_M t$. Suppose local certificates c have earned the exactness and coverage contracts above. A submitted finite execution is

$$s_0 \xrightarrow{c_1} s_1 \xrightarrow{c_2} \cdots \xrightarrow{c_n} s_n.$$

The checking machine threads the actual state s_i and validates c_{i+1} against the proposed s_{i+1}. Induction on the submitted sequence proves that acceptance is equivalent to validity of all its local certificates. Coverage then represents every finite M-execution. The induction uses the actual intermediate state, so scope, heap, continuation and world components cannot be reset between steps.

A checked instruction log is evidence of machine execution; a source evaluation derivation supplies evidence for the source judgment. Adequacy relates their claims. One possible result, completed evaluation and a complete result multiset are different judgments: the latter two require the corresponding terminal or exhaustive-branching evidence, including duplicate occurrences and pending work.



The checked machine and its checking machine are separate roles. A machine can play either role once the relevant evidence interface is constructed. An empty path alone proves neither program formation nor loading validity.

This applies to proof-kernel instructions as readily as to CAM instructions, rho communications or ISA transitions, when their local certificate contracts are available. The authored GSLT implementation supplies one concrete route: `GeneralRewriteRecipe.check_exact` checks its independent receipt judgment, and `exists_checked_iff_step` covers the original equation-saturated step relation. Composed recipes reach the existing finite may-reachability native types. That modal readout establishes the witnessed finite path; exhaustive search, termination and physical execution cost have their own obligations.

Checking a run of K_M is another instance of the same pattern. Such reflection requires an encoding of K_M and adequacy of its transition certificates. Encoding its states as numbers or graphs preserves only the distinctions proved for that encoding. It does not turn a certificate about a checker's run into unconditional soundness of every theory that checker might load.

13.5 Reconstruction, elaboration and reproducible hints

A partial reconstructor r can process output from an external prover, tactic or repair procedure. With destination checker c, publication is

$$\mathsf{reconstruct}_{c,r}(A, o) = r(A, o) \gg\!= (\lambda p.\ \mathsf{if}\ c(A, p)\ \mathsf{then}\ \mathsf{some}(p)\ \mathsf{else}\ \mathsf{none}).$$

It returns p exactly when r returned p and c accepted it. No soundness of the producer is assumed. Producer failure and checker refusal both publish nothing; the submitted-output coverage

theorem states exactly which accepted certificates the producer can return. Composing two such stages retains both checking boundaries. This is a general reconstruction interface, not a completed translation of an arbitrary ATP proof format.

An elaboration has another obligation: an accepted source certificate must produce accepted destination evidence. Existing local elaborations compose and lift to articles. Polynomial output size, actual translation time and logical soundness are separate properties. An output-size bound yields a size simulation; it does not manufacture an executed polynomial-time translator. A model interpretation likewise supplies no resource bound.

For reproducible checking, fix a deterministic strategy $f : S \to S$ and an explicit observation $v : S \to V$ with decidable equality on V. A checkpoint (k_i, z_i) requests k_i strategy ticks followed by the comparison $v(f^{k_i}(s_i)) = z_i$. The checker continues from its *computed* internal state, never from a replacement state supplied by the certificate. On success,

$$s_{\text{final}} = f^{\sum_i k_i}(s_0), \qquad \mathsf{tickCalls} = \sum_i k_i.$$

This remains true when v forgets private theory, ownership or environment data. A wrong checkpoint refuses at that boundary, retaining the work count of the attempted gap. Checkpoint sequences compose from the actual residual.

Fuel alone records the budget; checkpoints additionally cross-check selected residual observations; a full trace records one observation per tick. The formal materializer produces exactly n trace entries from budget n. All three replay the specified computation: checkpoints alone do not make the intervening computation cheaper. Tick calls, observation comparisons, stored observation sizes and native instructions require distinct accounts. Implementation heartbeats are not interchangeable with these strategy ticks.

The Lean4Lean instance uses its existing finite-catalog beta/delta/head algorithm. Its checkpoints include the expression and a terminal flag. Acceptance proves a path in the independent head-event relation and an endpoint with no remaining head event. Completeness is relative to this strategy reaching a common head-normal form. The raw self-application term Ω remains pending at every budget, yet every submitted finite normalization certificate is refused. This instance neither requires nor asserts termination of arbitrary Lean conversion, and it is not the complete Lean type-checking kernel.

The algorithmic and ideal judgments must also be distinguished. Lean4Lean implements a particular checking algorithm and separately studies the declarative type theory; verification of its implementation is partial work [20]. An exact contract for an algorithmic judgment does not decide every ideal equality. If a family of budgets enumerates exactly the same algorithmic successes, an ideal equality absent from that set remains absent at every budget. This is a theorem about the acceptance boundary, independent of implementation heartbeats.

Within a fixed formed-expression fibre, checked comparisons may instead be leaves of explicit reflexivity, symmetry and transitivity recipes. The checker computes their endpoints and refuses a mismatched intermediate join. It has exact authority for the equivalence closure $\mathrm{EqvGen}(R_{\text{alg}})$ of the independent leaf relation. Soundness into ideal equality follows from a sound leaf interpretation. Completeness for ideal equality additionally requires the generation theorem $R_{\text{ideal}} \subseteq \mathrm{EqvGen}(R_{\text{alg}})$; it is not supplied by fuel or by categorical composition alone. On raw syntax, ideal typed equality need not be reflexive: formation remains an explicit obligation before entering this fibre. The finite nontransitive control in the library illustrates this distinction without claiming to be a counterexample from Lean's full conversion implementation.

Lean4Less gives a concrete reason to separate these routes: it replaces selected implicit proof-irrelevance and K-like conversions with explicit equality proofs and transports, then checks the output with those conversion features disabled [21]. This is an elaboration between equality profiles, with separate declaration, universe and resource obligations. Destination rechecking can validate a

proposed output even when the producer is partial; neither a total translator nor a polynomial size bound follows from that check. The present boundary theorems do not complete either external system's metatheory.

The practical propositional connection reuses Lean's verified LRAT checker for RUP, RAT and deletion actions [27]. Its adapter preserves native clause satisfaction pointwise, including repeated literals and clauses. Accepted refutations imply an empty-clause derivation in the independently complete resolution calculus. That implication supplies no polynomial LRAT-to-resolution compiler. The public checker may stop at a successful empty-clause action, so its verdict does not validate an unused action suffix.

Finite intuitionistic and classical Hilbert certificates are checked directly by their formula instances and ordered premises. The existing standard Hilbert calculi in Foundation supply the independent source judgments; soundness and tree/DAG coverage are proved against them. The classical profile admits excluded middle, while the intuitionistic profile refuses that rule. A computable elaborator now returns terms in the existing `PropDeriv` family from accepted certificates, using the supplied children and a computed finite lookup rather than choosing an existential proof. The retained-term interface publishes a term exactly when the native checker accepts the requested formula.

Intuitionistic non-theorems have a complementary finite certificate: a partial-order table, a persistent atomic valuation, and a refuting world. The checker validates those tables and computes the Kripke semantics of the formula. Soundness follows through the independent source semantics; Foundation's finite-model completeness supplies a finite data certificate for every non-theorem. A two-world control refutes excluded middle, while malformed orders, nonpersistent valuations and out-of-range worlds refuse.

Proof and countermodel certificates are countably encoded as finite data. Enumerating those codes until one validates gives an executable terminating decision procedure for the original intuitionistic theorem judgment. Termination uses the two coverage theorems, not an ideal decision oracle. Submitted proofs or countermodels can be checked first as hints; incorrect hints are skipped and the same total search remains available. The least successful index is bounded by the code of any supplied valid certificate. This exhaustive construction proves decidability. Its search order has no practical complexity claim and is separate from the native replay kernel.

The classical extension checker adds literal hypotheses $p_i \leftrightarrow A_i$ with fresh names. It refuses a name appearing in the final claim, any earlier declaration, or its own right-hand side. Definitions are hypotheses, never additional substitution-closed axiom schemes. A valuation of the old vocabulary extends in declaration order to satisfy every definition while preserving the claim. Consequently the extension checker has exactly the ordinary classical theorems. Native tree and shared-DAG coverage are proved. The direct Frege-DAG embedding retains all formulas, parent references and node counts, and has the same replay verdict; no tree expansion is involved.

Literal elimination of definitions has a separately measured cost. The admitted chain $p_{i+1} \leftrightarrow (p_i \wedge p_i)$ has encoded size at most $5(n+1)(n+2)$, including unary name costs and the final reference. The specified last-definition-first unfolding algorithm returns a formula with exactly $2^{n+1}-1$ nodes. This bounds that literal materialization policy. It is not a lower bound on every equivalent formula, nor a separation between unrestricted Frege and extended Frege. An executed Cook–Reckhow polynomial bound remains a further obligation.

13.6 Retained checking, suspension and evidence release

A checking configuration retains what its remaining work needs:


$$K = (T, \Gamma, \mathsf{cache}, \mathsf{boundary}, \mathsf{residual}, \mathsf{obligations}, \mathsf{status}).$$

The concrete representation may use references and shared tables. World revisions, provenance and consuming rights enter those components where the selected calculus requires them. Accepting a

local instruction extends the checked prefix; final acceptance additionally requires the requested root and all obligations required for that claim.

As one storage realization, the authored-calculus cursor instantiates this retained machine directly. Its completed successful runs are exactly licensed runs of the original source rows, including unused rows in the submitted schedule. VibeITP's instance preserves its independently specified static theorem judgment and auxiliary term-operation judgments. Metamath's projected snapshot connects common graph acceptance to successful original normal-label execution under its projection and empty-stack hypotheses. Neither connection replaces parser provenance or native storage refinement.

Portable calculus modules retain both the complete term-language base and the proof-calculus layer. The verified text reader, followed by the original calculus validator, recovers the exact selected package. Malformed text, another layer schema and failed validation cannot select that package. This is the portable module data surface, separate from the upstream theory-builder grammar. Reading declarations grants no theorem authority.



Missing evidence, exhausted checking budget and an unanswered external request are different suspension reasons. Refusing the supplied certificate establishes neither falsity nor unreachability of its claim.

The retained law is

$$\mathsf{advance}(m+n, K) = \mathsf{advance}(n, \mathsf{advance}(m, K)).$$

It compares complete checkpoints. MM0 assertion execution and the HOL Light source receiver already instantiate `ResumableTrajectory`. For MM0, the command tail and unification continuation remain live; final assertion validation is a separate observer. For HOL Light, `EventWork` retains the accepted theory/proof state, remaining JSON events and refusal status. A refused event stays at the residual's head. Accepted receipt prefixes grow without replay, and two separately identified reflexivity events with the same conclusion remain two occurrences. The budget counts source events, whose local costs need not coincide.

The authored recipe DAG and equation-application DAG now have retained workers over their original nodes and checkers. Each checks one submitted row per transition, retaining the last accepted table and the entire refused suffix. Their completed verdicts are exactly the existing certificate verdicts, and their actual runs finish within the number of rows plus one finishing transition. The rho tree worker similarly inspects one original inference occurrence per transition, with exact recursive-checker agreement and a bound of the tree's node count plus one. Endpoint formation remains an additional rho request-boundary check. These bounds count calls of the local worker; they do not price every internal substitution or equality operation. For authored GSLTs, existence of an actual terminated checker run with an accepted root is equivalent to inhabiting the existing reaching native

type for an equation-respecting target predicate. The native-type readout therefore comes from the original finite rewriting semantics, rather than a command layer with an unspecified local step.

All these workers are objects of the existing machine category at their own observation interfaces. The MM0 instance keeps its command and unification microsteps, the HOL Light instance keeps its registered source-event receiver, and the Lean4Lean head-profile instance keeps its actual head strategy. Choosing a common observation interface and proving a bounded stage between two objects are additional obligations. Object construction alone supplies no translation of one native logic into another.

Retention is governed by future use, not by a requirement to keep every detail forever. For ordinary value readouts d in a declared consumer family $\mathcal{D}$, replacing a detailed record by $q(x)$ is licensed when

$$\forall d \in \mathcal{D}\ \exists \bar{d}. \qquad d = \bar{d} \circ q.$$


Dependent evidence additionally needs coherent family and section descent. An outstanding obligation must be discharged or transferred under its own authority contract. Once a recipient owns the needed evidence and every remaining local consumer factors through the retained summary, the sender may release detail that no longer serves those obligations. A newly admitted consumer cannot recover erased distinctions merely by requesting them.

13.7 A category of machines and realization stages

For fixed event, verdict and request types (E, V, Q), the existing `ObservedMachine` bundles an actual state carrier S and productive stepper $M : S \to \mathsf{Option}(\mathsf{Transition}(S, E, V, Q))$. Its morphisms are the existing `Stage` contracts: a relation between source and target states, a forward cost-bounded simulation and completion reflection. Identity uses the equality relation at bound one. For stages (R, c) and (S, d), composition has

$$(S \circ R)(x, z) \iff \exists y.\ R(x, y) \wedge S(y, z), \qquad \mathsf{cost} = dc.$$

`Stage.refl_comp`, `Stage.comp_refl` and `Stage.comp_assoc` supply the category laws. The `ObservedMachine.relabelFunctor` maps a common observation interface to another while retaining the underlying state carriers. Noninjective label maps can forget distinctions; each dependent consumer needs its own descent law before using that coarser view.



Composition retains the declared relational contract and resource bound. It neither selects a compiler implementation nor identifies all intermediate execution witnesses.

The controls make the distinction concrete: two stages with bound three require composite bound nine; the proposed sum six fails. A checker/interpreter round trip preserves its final observation but differs from the identity stage because its retained cost bound is three. The bound is a proved account for the chosen machine transitions, not a measurement of native time. The present `Stage` contract reflects completion; preserving stuckness versus silent divergence requires further endpoint laws. An existing negative control relates a stuck source to a spinning target under the weaker contract. The extra `MatchesStuck` obligation excludes that case.

There is also a general finite-trace relational envelope. Fix observable words w, with internal steps erased by a declared observer. For branching machines, take relations R satisfying

$$R(s,u) \ \wedge \ s \overset{w}{\Longrightarrow}_M t \quad \Longrightarrow \quad \exists v.\, u \overset{w}{\Longrightarrow}_N v \ \wedge \ R(t,v).$$

Equality is an identity relation. Relational composition preserves this law: choose the intermediate related state, match the source path in the middle machine, then match that middle path in the final machine. Relational unit and associativity laws therefore give a category at this extensional contract level. This mathematical schema states a finite may-preservation profile; backward, divergence, probability and resource obligations enrich it separately. The concrete kernel-checked category above currently uses deterministic steppers, whose schedules may realize branching source calculi only through their own adequacy theorem.


Vacuous relations are not executable realizations. Loading must relate every admitted source entry to an actual target entry; representation, request/reply and authority laws complete the applicable contract. Furthermore, forgetting the middle state can erase information required by a dependent result. `DependentComposition.Path` retains that state as data; its descent theorems identify when transport is independent of the chosen middle witness. Thus a category of endpoint contracts and a richer account of executions can coexist, with information release justified at the selected boundary.

13.8 Fibres, crossings and a machine of machines

The functional GSLT construction is already literal category theory. `OperationalTranslation` preserves equations and source steps; `CoveredTranslation` additionally covers target steps at image states. The functor `executionIndex` sends each operational theory L to its category of finite execution paths. Its Grothendieck construction has objects (L, s) and arrows

$$(L,s) \longrightarrow (K,t) \quad = \quad (f : L \to K,\ p : F(f)(s) \longrightarrow t).$$

For $f : L \to K$, $g : K \to H$ and compatible paths p, q, the composite is $(g \circ f, F(g)(p); q)$. Identity and associativity follow from the base and fibre laws and the functor laws. This is a constructed total category for functional operational transport. Its underlying proposition-valued steps do not distinguish two rule occurrences with identical endpoints; receipts or labelled edges retain such distinctions when required.



A functional path map supplies a commuting square. Relational block simulations instead retain related endpoints and their actual matching paths; their coherence is an additional construction.

The executable `GSLTILNativeKernel` separates stepping inside a fibre from crossing an explicit route. The installed `GSLTILAuthoredFibre` uses the actual authored rewrite checker and its source-coverage theorem. It currently installs no translation routes. Its `at`/`via` dispatcher can host locally justified routes, but does not manufacture their interpretations, resource transport or conservativity.

A broader web can retain relational simulations and comparison cells instead of forcing all crossings into state functions. Horizontal paths then concern executions within a regional machine; vertical comparisons relate configurations of different machines; a cell supplies the matched execution evidence. These cells need their own composition and coherence laws. Substitution, logical interpretation, world update and authority transport retain different preservation contracts even when they occur in one diagram. This is the remaining generalization, not an implication of the Grothendieck name.

13.9 Regional kernels, semantic faces and open-ended reflection

The checking machine has an operational run; its accepted evidence inhabits an intensional derivation judgment; model interpretation supplies an extensional face. These comparisons form the computational trinity around the checker. Logical soundness goes from derivations to validity in the selected models. Logical completeness, where established for the particular fragment, goes in the other direction. Coverage of certificate representations is instead a comparison with derivations. These three claims have different hypotheses and do not identify the faces.

MM0 makes the distinction between its readable specification and binary proof program explicit [18]. Its verifier computes with stacks, hypotheses, terms and binder data, and declaration agreement binds that computation to the intended specification and preceding environment. HOL Light supplies kernel-authorized inference through the LCF interface [19]; its theorem cache and receipt graph have a separate retained execution account. Megalodon checks typed proof objects with normalization and delta expansion under its selected environment. OpenTheory articles give a textual proof stack machine [24]; CakeML includes a verified article checker and Candle's HOL Light implementation [23]. These are regional realizations, with distinct logical commitments and checking disciplines.

Lambdapi and HOL Light exercise different binder obligations. Lambdapi's restricted higher-order rewrite patterns test scoped matching under binders [22]. HOL Light's primitive replay tests term/type instantiation and theorem construction. Real HE and PeTTa evaluation kernels must likewise use their own independent judgments: a certified rewrite at one atom's root does not establish the dialect's nested evaluation, quoted/raw arguments, complete result multiplicity or retained effects.

Structural compilation of an admitted profile and checking a finite execution are complementary hosting routes. Partial recursive checkers admit finite bounded-evaluation witnesses [25]; actual hosting still requires the source encoding, target certificate construction and checker adequacy. A p-simulation further requires a polynomial-time proof translator under declared encodings, hence polynomial output size. A short operation name does not make a large substitution or conversion cheap. Shared-node size, expanded uses and executed work require separate accounts.

Small primitive inventories, weak logical assumptions and cheap checking are different objectives. The existing inference-basis theory supplies inclusion-minimal generating subsets for a finite inventory, including incomparable minima with no least generating basis. It supplies neither an efficient minimizer nor a universal least kernel. The common interface is licensed composition; individual presentations choose their generating rules and prove their interpretation.

An interactive prover additionally retains open goals, scoped metavariables, substitutions and delayed constraints. Its search may diverge or remain incomplete even when each closed certificate is finitely checkable. Reflection makes these presentations and checking processes available as data. Goertzel's reflective metagraph account motivates this internal availability of rules and their transformations [12]. Weinbaum's open-ended intelligence motivates admitting new vocabularies and observers rather than requiring a final fixed inventory [31]. The architectural proposal is to combine that openness with explicit crossings: changing a theory exposes new commitments, replacing a machine preserves the declared observations, and neither silently changes what an earlier certificate

proved.

Existing owners. Mettapedia/Logic/DerivationGraph.lean,
Mettapedia/GSLT/LanguageDef/CertificateGSLTClassifyingCategory.lean,
Mettapedia/OSLF/MeTTaIL/GeneralRewriteRecipe.lean,
Mettapedia/OSLF/MeTTaIL/GeneralRewriteRecipeExpansion.lean,
Mettapedia/OSLF/MeTTaIL/GeneralRewriteRecipeComposition.lean,
Mettapedia/OSLF/MeTTaIL/GeneralRewriteRecipeContext.lean,
Mettapedia/OSLF/MeTTaIL/GeneralRewriteRecipeDAG.lean,
Mettapedia/OSLF/MeTTaIL/GeneralRewriteRecipeExecution.lean,
Mettapedia/OSLF/MeTTaIL/GeneralRewriteRecipeParallel.lean,
Mettapedia/GSLT/Distinction/SimulationComposition.lean,
Mettapedia/GSLT/Distinction/SimulationCompositionControls.lean,
Mettapedia/GSLT/Distinction/DependentComposition.lean,
Mettapedia/GSLT/Core/OperationalPathFibration.lean,
Mettapedia/GSLT/LanguageDef/GSLTILAuthoredFibre.lean,
Mettapedia/Languages/MM0/Formats/MMB/MachineCost.lean,
Mettapedia/Languages/MM0/MeTTa/Formats/MMB/ExecutedSoundness.lean,
Mettapedia/Languages/HOLLight/IncrementalExecution.lean,
Mettapedia/Languages/HOLLight/KernelAtlas.lean,
Mettapedia/Languages/MeTTa/EquationKernel/Execution.lean,
Mettapedia/Languages/ProcessCalculi/RhoCalculus/NativeExecution.lean,
Mettapedia/Languages/Lean/HintedHeadConversion.lean,
Mettapedia/Languages/Lean/Lean4LessCheckerBoundary.lean,
Mettapedia/Logic/EqualityRecipe.lean,
Mettapedia/Computability/FuelledConversionEvidence.lean,
Mettapedia/Machines/ExecutionHints.lean,
Mettapedia/GSLT/LanguageDef/KernelCheckingClasses.lean,
Mettapedia/GSLT/Logic/PropositionalLRAT.lean, Mettapedia/Logic/PropositionalExtension.lean,
Mettapedia/Logic/IntuitionisticDecision.lean,
Mettapedia/Logic/PropositionalHilbertChecking.lean,
Mettapedia/Logic/ProofSharingBounds.lean, Mettapedia/Coalgebra/CoherentPrefixTower.lean,
Mettapedia/Logic/InferenceBasis.lean.

Boundary. Local authored checking, its composition operations, functional path transport, costed stage composition, checked reconstruction and the retained native checker instances are constructed at their stated contracts. Authored packet coverage uses the existing admission compiler and an empty dynamic provider; textual module parsing is a separate front end. The finite-trace relational envelope is a mathematical schema. A complete heterogeneous execution/certificate web, its route authentication, general relational coherence and native physical resource bounds remain further constructions.

14 Execution contracts: determinism is one dimension

A deterministic implementation can enumerate many answers, compute an entire distribution, or simulate concurrent processes under a selected schedule. A sampler can return exactly one answer while representing a nontrivial probability law. These properties therefore cannot be represented by one exclusive choice between deterministic, nondeterministic and probabilistic.

Dimension	Contract question	Distinguishing example
Transition	At most one next state?	An ordered search driver steps deterministically through many alternatives.
Cardinality	How many successful occurrences in a completed run?	Two equal answers count twice.
Completion	Is any work still pending?	One answer followed by a suspended branch is not a closed singleton.
Probability	What measure describes outcomes?	A fair and a biased coin have the same finite support.
Concurrency	Which enabled actions may be scheduled?	Two independent actions can commute without one global deterministic schedule.
Commitment	Which alternatives or effects may be discarded?	`once` selects a success; it does not prove there was only one.

Cardinality belongs to a calling mode and its world

The existing answer grades bound the number of occurrences in a completed answer collection: zero, exactly one, zero-or-one, one-or-more, or unrestricted. Relational choice adds occurrence counts; an exclusive conditional combines bounds by an interval hull. Sequential binding applies a bound separately to each reachable input occurrence with its bindings. Types, instantiation, termination, faults and effects remain additional obligations. A declaration of `det` expresses a contract; an optimization needs evidence for the actual calling mode and relevant provider revision.

The current weighted cardinality consumer accepts a complete cut only when it is empty or contains one returned occurrence. It preserves that occurrence's coefficient, including zero. A cut with a pending state is refused even if its current returned prefix has length one. The accepted result is stable under further resumption. This is a representation theorem about an already computed cut, not a procedure for deciding termination or safely pruning an unfinished search. Probing for another answer can perform effects, force otherwise unused work, or diverge.


What a deterministic region can improve

The independently defined queued and direct executors already agree on ready operands, functional primitives, worlds, ordered effects, failures and instruction-boundary residuals. Their primitive invocation counts agree; their modeled dispatch counts differ. This licenses eliminating that queue within the admitted region. It establishes no native speedup and does not yet cover arbitrary expressions, binding merges or concurrent mutation.

Existing owners. `Mettapedia/Machines/AnswerCardinality.lean`, `Mettapedia/Machines/DeterministicRegion.lean`, `Mettapedia/Machines/OccurrenceMachine.lean`, `Mettapedia/GSLT/Dynamics/WeightedBranchingCardinality.lean`.

14.1 Probabilities, coefficients and schedules

A coefficient is not automatically a probability. The weighted resumption interfaces work with algebraic coefficients and preserve pending contributions and occurrence identity. A probabilistic interpretation additionally needs nonnegative mass and a specified normalization or subnormalization law. An importance weight, a scheduling priority, a cost and an ownership permission are different quantities even when they use similar algebraic notation.



A scheduler selects an enabled action; a probabilistic kernel specifies its stochastic transition. Relational alternatives need not carry a canonical probability law. A point mass recovers deterministic transition.

Combining nondeterministic choice with probability is a semantic choice: the available scheduler information and the order of the two effects matter. One cannot assume that an arbitrary combination of the familiar monads has the desired distributive laws [11]. A machine contract should state the admissible policies and what the observer compares: possibilities, ordered occurrences, trace distributions, or another declared quantity.

The existing finite probabilistic systems use subdistributions and account for missing mass as declared refusal. Their probabilistic bisimulation retains more information than the support relation. However, the system record does not itself prove that its kernel follows the underlying GSLT rewrite relation; that is an operational bridge still to construct. Erasing probabilities to possibility support cannot justify a probability-preserving implementation. For a continuous distribution, a singleton can have probability zero without being an impossible value; positive point mass is not a general support test.

Sampling, scoring and resumption

A retained draw needs its dynamic occurrence identity and original world. Resuming a committed draw must reuse its result. Calling a resampled suspension creates a new occurrence; merely sharing written syntax does not establish stochastic independence. Independence requires a law for the actual joint execution, often conditional on captured latent variables.


Scoring generally produces an unnormalized measure. Forming a posterior requires an evidence mass Z with $0 < Z < \infty$; zero or infinite evidence needs explicit treatment. Retention must preserve committed factors and avoid applying them again. Existing coefficient plumbing is useful here, but it does not supply this entire probability-and-authority contract.

> **Boundary.** No production port is licensed solely by cardinality or coefficient laws. The complete world, bindings, effect history, faults, ownership and residual demand must travel through the same constructed correspondence.

Existing owners. `Mettapedia/GSLT/Dynamics/WeightedResumption.lean`, `Mettapedia/GSLT/Dynamics/WeightedBranchingResumption.lean`, `Mettapedia/GSLT/Distinction/Probabilistic/System.lean`, `Mettapedia/GSLT/Distinction/Probabilistic/Semiring.lean`, `Mettapedia/ProbabilityTheory/IndependentFiniteSampling.lean`.

15 Focus, zippers and typed graph holes

For regular tree syntax, the derivative of a datatype describes its one-hole contexts [9]. A zipper retains a focused subtree and the context needed to rebuild its surroundings [10]. Indexed polynomials extend this organization with context and sort information; dissections distinguish already processed positions from remaining positions. These are representation and navigation tools. A legal position is not by itself permission to evaluate, force, sample or commit an effect.



The existing PathMap zipper interface transports query membership under iteration and store-agreement hypotheses. Concrete flat and trie instances prove particular traversal and rebuilding laws. This is useful ZAM structure; it is not a proof of the full native Rust machine, ordered query multiplicity, or its world and demand semantics. A membership theorem alone cannot establish that two equal rows produce two answer occurrences.

A shared hole needs an interface, not just a path

Replacing a shared subgraph affects every alias to it. A graph hole therefore needs the incoming and outgoing ports crossing its boundary, their scoped types, identity and sharing requirements, and the resources or obligations that move with them. A single tree path loses those other connections. Cycles require the corresponding consistency and update rules. Bag or set quotients also need occurrence identities when their physical ordering is not canonical.

Goertzel's reflective metagraph account makes programs and rewrite rules graph data [12]. Graph rewriting's preserved interface and gluing conditions are useful guidance: a replacement must account for the links it preserves and those it removes. This motivates a runtime contract; it does not already provide a typed effectful graph-hole machine.


Different holes have different filling rules

An unknown source fragment, a paused computation, a stochastic latent variable, an external response and an unfulfilled proof obligation are not interchangeable. The existing pure higher-order hole evaluator retains environments and indeterminate operations. Its filling/resumption equivalence has a termination condition. Its controls show that divergent call-by-value fillers and effectful reordering can break an unrestricted equivalence. The tree multi-hole monad also deliberately permits capture; it is not a ready-made hygienic shared-graph interface. Filling must establish the applicable scope and execution contract.

Existing owners. `Mettapedia/GSLT/Poly/BindingSignature.lean`, `Mettapedia/GSLT/Poly/SortedTraversal.lean`, `Mettapedia/OSLF/PathMap/ZipperExecution.lean`, `Mettapedia/OSLF/PathMap/Trie/HuetZipper.lean`, `Mettapedia/OSLF/Programs/HoleEvaluation.lean`, `Mettapedia/OSLF/MeTTaIL/MultiHoleContext.lean`, `Mettapedia/GraphTheory/Representation/Metagraph.lean`.

15.1 A core MAM for heterogeneous retained computations

The strongest candidate here separates execution, dependency accounting and reflection. They refer to the same occurrence identities, but they need not use one physical representation. A machine can execute a compact packed region while exposing a metagraph view on demand. Reflection need not allocate a public syntax object for every primitive instruction.



Dashed regions mark unconstructed general interfaces. All regional calls use the crossing contract; the connecting lines do not assert an ISA or higher-order probability correspondence already exists.

The proposed retained state includes local computations, typed open boundaries, shared producer/use identities, ordered alternatives, world dependencies, committed draws and factors, consumed rights, and selected observations. Its transitions admit and focus a region, advance it, deliver a request or reply, fill an authorized hole, validate dependencies, pause, or dispose of cancelled obligations. Sampling and scoring come from an admitted regional semantics. Neither graph shape nor a type annotation silently authorizes them. Logical guests retain their own judgment systems; a common port protocol does not make their propositions interchangeable.

Qualification would lift local correspondences through admitted graph contexts, fillings and crossings. At publication, suspension and return, the chosen trace observations and related residuals must survive together. Probabilistic regions compare the resulting laws under declared scheduling policies, or a stated coupling bound; equal possible values are insufficient. These compatibility laws must be proved for the actual assembly. Listing types and authority metadata does not establish them.

An ISA region would load code with an instruction-validity contract and retain registers, memory, faults and external-service state. Its source translation must state ABI and memory assumptions. The existing register-code machine supplies a narrower lowering and execution connection; a proposed `lts:isa` interface is not established by that result. Cesta macro elaboration belongs to a staging phase, before the resulting C/native region.

A GSLT interpreter is a general rule-execution machine. Calling it UTM-tier requires an encoding of universal computation and a correspondence theorem. Even such a theorem would not preserve fairness, ordered occurrences, costs, probability laws or ownership automatically. Those are regional contracts, not consequences of computational universality.

> **Boundary.** This architecture is a research target assembled from existing owners. It is not an implemented universal MAM or a claim that one representation is optimal for every region. Its first consumer remains the actual MeTTa source/native and owned-interaction connection.

Existing owners. `Mettapedia/Machines/RegisterCode.lean`, `Mettapedia/Languages/TuringMachine/MathlibBridge.lean`, `Mettapedia/GSLT/Dynamics/ObservationSchedulerSufficiency.lean`, `Mettapedia/GSLT/Dynamics/ScheduleObservationFactorization.lean`.

16 Higher-order probabilistic holes

Consider a hole with type

$$\square_{\text{make}} : \text{Unit} \longrightarrow \mathcal{P}(\text{Unit} \longrightarrow \mathcal{P}\text{Bool}),$$


where $\mathcal{P}$ denotes a probability computation. A consumer obtains f from `make ()`, calls f twice, and returns the pair (a, b). There are two well-typed fillings:

Shared draw	Fresh draw per call
`cached () =` draw $z \sim \text{Bernoulli}(1/2)$ return $(\lambda().\ \text{return}\ z)$	`fresh () =` return a closure which, on every call, draws a fresh $z \sim \text{Bernoulli}(1/2)$ and returns z.

Both give a fair marginal for either individual call. Their joint laws differ:

Filling	$(0,0)$	$(0,1)$	$(1,0)$	$(1,1)$
Shared draw	$1/2$	0	0	$1/2$
Fresh draws	$1/4$	$1/4$	$1/4$	$1/4$

Thus $\Pr(a = b)$ is respectively 1 and $1/2$. Matching the hole's type or one call's marginal cannot license replacing one filling by the other. One shared draw has one producer with two use edges; two independent draws have two dynamic sampling occurrences, even if their source syntax is equal.




Two semantic routes remain open

An operational route places measures over encoded closures and retained machine states, with application specified by the evaluator. A denotational route supports function spaces directly. Ordinary measurable spaces are insufficient for the desired general higher-order structure; quasi-Borel spaces provide a compositional alternative [13], with domain-theoretic extensions for recursion and recursive types [14]. Neither route should be confused with the existing mixture-of-kernels or probabilistic-HOL-model modules, which do not implement a general probabilistic lambda calculus. The small example above is a mathematical discriminator, not a newly proved machine instance.

Existing owners. `Mettapedia/ProbabilityTheory/HigherOrderProbability/Basic.lean`, `Mettapedia/ProbabilityTheory/HigherOrderProbability/GiryMonad.lean`, `Mettapedia/ProbabilityTheory/IndependentFiniteSampling.lean`.

16.1 Zooming requires a law for future computation

Let $v : S \to C$ forget details of a fine state. Equal coarse readouts now are insufficient: different hidden states can react differently to the next command. An exact coarse machine needs a law relating its future transitions to those of the fine machine, for the declared action and observer family.



For finite probabilistic states, existing strong lumpability says that states in one view fibre have the same aggregated next-state law for every admitted action. It constructs a representative-independent coarse kernel and proves

$$v_*(\mu \text{ bind } K_a) = (v_*\mu) \text{ bind } \overline{K}_a.$$

Here v_* is pushforward. Without this condition, retain additional state or history, restrict actions/observers, or accept a weaker approximate contract. A policy depending on hidden details also needs its own factorization law.

Existing probabilistic-square results offer a finite controlled-chain route to approximation: local couplings bound expected discrepancy, and Lipschitz and discount hypotheses control its accumulated observational effect. They are not exact quotients or reversible maps. Numerical closeness also depends on the observer: a finite floating-point distribution and a continuous law can be maximally different in total variation despite close numerical samples. A metric suited to the permitted queries may be more appropriate.

Zooming in can expose retained fine state or reconstruct an authorized view. It cannot recover arbitrary forgotten choices from a non-injective quotient. For the shared-draw example, the first call's marginal hides the captured draw and whether subsequent calls reuse it; reconstructing by resampling can break those correlations. Similarly, replaying a native trace must not repeat committed effects. Observation, demand and retention therefore remain separate in-language controls.

The remaining research question

The missing joint theory is typed open-metagraph filling with scope, shared identity, effects, probability and ownership, together with observation maps that commute with continuation. Useful research would compare existing models, identify incompatibilities, and work one higher-order shared/fresh example through both exact finite execution and a continuous denotation. General recursion, conditioning and scheduling must keep their explicit conditions; universal complete inference is not a consequence of a universal machine.

Existing owners. `Mettapedia/ProbabilityTheory/FiniteLumpability.lean`, `Mettapedia/Cybernetics/ApproximateAdequacy/ProbabilisticSquares.lean`, `Mettapedia/GSLT/Dynamics/ObservationSchedulerSufficiency.lean`, `Mettapedia/GSLT/Dynamics/ScheduleObservationFactorization.lean`.

17 Qualification and the remaining joins

An earlier shared resumption package extended eight existing semantic modules without adding a Lean module. Its clean canonical build completed 5,547 jobs; 27 strict package/consumer checks and the declaration audit passed. The audit covers 2,528 declarations, including 1,109 theorems, using only `propext`, `Classical.choice` and `Quot.sound`. The 1,058 GSLT controls produced identical output on CeTTa's PeTTa dialect, the shared PeTTa checkout and the existing empty-superpose fork.

The earlier value-graph CAM, owned host with the retained rho chronicle, fixed C core, its Cesta reader and its services were qualified together: the C11 and HE language hubs build in 9,372 jobs, and the principal theorems and controls of these packages use only the same three axioms. Their controls run Cesta-parsed C programs to the values GCC and Clang compute, and serve C requests by the HE evaluator.

The joined resolver and machine migration has passed a serial strict check of 288 affected modules, including the recursive C-to-MeTTa service controls and the translated MM0 and HOL consumers. An earlier 98-module receipt qualifies the corresponding intermediate source state. The HE oracle gate passes all 33 fixtures; the two-realization native gate passes all 258 controls. The latter compares occurrence multisets across realizations and retains each execution's own history. A subsequent complete GSLT runner gate passes 1,230 named controls in 34 families, with identical outputs on CeTTa and PeTTa, including the retained COMM controls. These runtime checks do not establish source/native correspondence for arbitrary programs.

The query layer now proves that successful variable resolution is unique across fuel and visited sets. In a binding record admitted by the native loop filter, every successful recursive read agrees with public instantiation, and the selected non-variable class value satisfies its instantiation equation. That selected-value theorem is deliberately distinct from satisfaction of every stored constraint: a raw record can contain another, inconsistent value in the same class. The matcher now constructs the required consistency invariant through its actual insertions, reconciliation and merges. On float-free inputs its native instantiation satisfies every stored constraint; successful native matches consequently pass the full independent dependency criterion. The reverse matcher correspondence and its direct consumers have been checked with that constructed invariant.

A structural change of binding layout is distinct from erasing execution occurrences. Permuting the assignment and equality lists preserves all class-dependency edges, semantic acyclicity and the executable cycle decision. The lower equality-graph theorem requires only equal edge membership; it does not identify the classes' enumeration order. Conversely, adding an equality may create a cycle: the open assignment $x = f(y)$ becomes cyclic after $x = y$. Recursive correspondence therefore retains both the worker's exact record and the independent source record, related at their declared representation boundary.

Representative order admits a more precise law than graph invariance. Appending an already-stored equality preserves the first-appearance order, every ordered class, its selected residual variable and its ordered direct values. The extra native relation occurrence is retained. By contrast, permuting two edges with the same membership can change the representative from a to c. Removing such a repeated logical edge preserves these observations; arbitrary edge permutation does not justify that stronger conclusion.

A stronger record-permutation contract fails even on coherent alias frames. Take assignments $x \mapsto F(z)$, $y \mapsto F(w)$, $z \mapsto A$, $w \mapsto A$ with equality edges (x, y) and (z, w), then merge a fresh private assignment to B. The actual HE-model reconciliation duplicates the edge (z, w); the independent singleton source merge preserves the two-edge list. A checked inversion proves that no source endpoint is a permutation of the three-edge result. Both endpoints nevertheless have the same complete solution theory and the same tested joint readout, including two uses of one open residual variable. This is a counterexample to the representation contract, not an observable Rust

or CeTTa defect.

The replacement must retain the concrete worker record for resumption and compare its public observations through one coherent semantic readback. Separate alpha witnesses for each value would not suffice: they could forget whether two results share one residual variable. The existing presentation-principality laws now connect to the executable HE binding model's actual equality-aware resolver. Ordered class selection and the unresolvable-value shortcut are checked against the canonical valuation; the executable structural coverage bound supplies sufficient read depth. Coherent acyclic records consequently yield one residual renaming for the whole observation tuple, including repeated variables and private-frame extensions. This is a theorem about the executable binding model, with the actual C materializer correspondence still separate.

Joint alpha comparison alone does not license replaying a continuation under the same commitments. An arbitrary extension of the observed variable map may move an unobserved constrained name. For full solution-theory equality, the comparison now has a stronger constructed form: one residual permutation aligns the entire observed tuple, fixes every source model valuation pointwise, and fixes every name outside the two observed residual supports. It therefore preserves the complete source binding theory. The finite extension is made inside fibres of the model-observation map, rather than choosing an arbitrary permutation of names. Scoped observational equivalence alone does not supply this stronger conclusion: a private equality may be visible only in one of the two full theories.

The independent source endpoint need not itself be a coherent input to that resolver. Its ordered equation fold constructs a normal exact finite presentation. Mutual factorization of this presentation and the actual principal readout yields one residual permutation for the complete observed tuple. Thus source materialization is constructed even when directly running the executable resolver on the source record would give an incorrect principal observation. Repeated public and residual variables are compared together, rather than by unrelated per-value alpha witnesses.

The chronological presentation is an additional representation convention, not a consequence of the published binding theory. For the single equality $\mathsf{public} = \mathsf{private}$, the current equation fold eliminates public, while the executable binding resolver retains it as the class representative. A checked counterexample therefore refutes literal equality between those two materializers, even at sufficient depth. The independent query judgment now follows the published candidate-first merge order. A constructed reversed-merge theorem transports the existing query witness without changing its native binding record: both independent endpoints have exactly the same full solution theory, although their row layouts need not agree. Neither result licenses erasing variable spellings from observable text.

That convention is nevertheless functional on fixed ordered rows. Simultaneous induction through the three presentation-matching judgments proves uniqueness of their output substitution; induction through the equation fold then proves uniqueness of the complete presentation. Every satisfiable record consequently has one joint historical readout for all operands. This does not make it invariant under row permutation: the equation lists $[(a, b), (a, c)]$ and $[(a, c), (a, b)]$ have the same complete solution theory, but the fold reads (a, a) as (c, c) and (b, b) respectively. Both the positive folds and rejection of the opposite literal result are kernel checked.

The mismatch is reached by an actual open query from an empty caller. For the rule `(= (share \$x) \$x)`, the maintained query and merge produce an alias between the public argument and a fresh rule variable. The native-model request retains the public representative; the historical source fold cannot emit it. Thus restricting the old equation-body contract to reached caller records would still not repair that contract's hardwired materializer. This is a counterexample to that source-model interface, rather than a failure of the successful query.

The readback comparison also has a uniform executable form. Resolve the complete finite binding support once and retain the nonidentity results as a finite substitution. This one table agrees with every atom at sufficient resolver depth, is normal and presents exactly the source solution theory. It is not selected separately for each operand. A model-fixed residual permutation relates it to the

independent chronological presentation. This constructs a finite representation of the executable HE binding model; it does not establish the corresponding C decoder, nor determine a source profile's history-sensitive representative policy.

The existing evaluator now carries this choice in one retained `BindingFrame`. Its raw constraints are accompanied either by the historical readout or by a finite table with a `ReadoutCertificate`. The certificate relates that table to an independent equation fold through a model-fixed residual permutation and certifies agreement for every future operand. Renaming transports the constraints, the table and the certificate together. It does not rename a previously produced string.

The current logical store now constructs such a presentation from its own contents. Complete row enumeration retains each slot's generation, write metadata and unbound status. Stored values carry their lexical context; qualification names a variable by its full logical reference, so equal source spellings in different frames remain distinct. The scoped preparation entry checks every stored payload and the entire operand tuple against the actual frame inventories and one explicit global-name context. An undeclared name cannot silently become a shared global.

For unique acyclic assignments, the existing dependency-cycle decision constructs a decreasing natural-number rank through the finite dependency scheduler. The existing substitution fold then constructs the normal table and its independent equation-presentation certificate. Admission requires no supplied variable ordering. Every live operand uses that same table. Repeated uses remain correlated, known unbound slots remain open, and stale contextual references are refused. The scheduling witness establishes admissibility; it does not select a common observable representative policy for all dialects.

An actual write into an open logical slot preserves the complete frame inventory and adds exactly its new binding equation. Scope-checked preparation and the two actual cycle checks reconstruct the updated certificate. The stronger solution theory absorbs the old table for the entire pending tuple, earning selected-frame renewal. An overwrite need not strengthen that theory, and a scoped cyclic write can remain a valid storage operation while falling outside this finite-tree readout admission. These results concern one shared-store lineage. Rational values, correspondence with a language's unification operation and physical implementation are separate obligations.

The normalized view also supplies a constructed immediate-function instance. After an actual open-slot write and successful preparation, the existing worker loads that view and the independent source step uses its certified selected frame. Both reach the same invocation result through the actual call and return transitions. The laws retain arbitrary caller and older continuation data, a prior publication prefix and exact saved resumption. They do not identify the raw store snapshot with a literal worker binding record: loading the normalized view is an explicit representation step.

This is one mutually recursive evaluator, not a second selected evaluator. All twelve judgment families carry the same frame. Pure transitions preserve it literally; an actual query, merge or cast may renew its readout alongside that operation's independent premise. A retained activation cannot silently reselect a different valid table. Historical-mode preservation is proved through the complete rule block. Existing function, raw-call, typed-return and generated-dispatch consumers have been adapted through the complete frame and explicit historical projections.

The source-execution relation additionally requires agreement with the actual native-model table on every operand. An open query from an empty caller now constructs the selected next frame from its physical source occurrence. The controls follow two uses of one residual variable through a later real unification and function return, obtaining `Pair A A`. They also reject unlicensed table reselection, retain opaque rendered strings, and distinguish an unfinished open call from its checked completion. These results concern the maintained binding/control machine. A selected source derivation that chooses another representative is not thereby proved to reflect into Rust or C execution. Raw opaque binding payloads remain restricted to historical frames until their actual saved representation carries the selected table.

Binding refinement supplies a separate compositional law. If a later frame has a stronger complete

solution theory, its normal finite presentation absorbs the earlier presentation on every syntactic operand. The same law holds for an ordered tuple of pending operands, preserving repeated uses and shared variables. Actual successful match/merge and independent evaluator extension laws now supply the required refinement; the published type service earns its extension laws from its own matching and candidate scan. Covered resolver calls may use different sufficient depths before and after refinement. Rendered strings remain opaque: this absorption theorem does not identify evaluation of an earlier string with rendering a later representative.

The necessary coherence is also constructed by actual merge replay. Starting with a unique, equality-free seed, each value conflict and class join preserves pairwise agreement at a fixed canonical dependency frontier. Recursive unifiers are confined to strictly smaller dependencies; their replay establishes the pivot equations needed at the joined class. Induction on the final dependency order then supplies canonical coherence. For non-variable input assignments and a common finite-term model, the actual solution-intersection law earns output loop freedom as well. Thus a successful merge from an actual open match yields a principal executable readout without assuming caller coherence or output correspondence. Independent match and merge completeness then construct the candidate-first source endpoint, its entire solution theory and its exact freshness support. These are primitive query-boundary results; transporting an arbitrary open continuation remains a separate obligation. Duplicate native relation rows remain present throughout.

The independent unify and equation-query judgments now use `LogicalMergeRel`: a successful merge has exactly the conjunction of the two input constraint theories, exactly their union of support names, and a finite model. This contract prescribes no relation-list layout or residual representative. A concrete readout is a separate retained datum. Raw merge replay supplies compatibility evidence when its output has an earned model; neither an arbitrary raw merge nor its structural loop filter alone proves consistency. A pure conservative-signature theorem transports native solution implication to the larger structural atom signature, preserving the existing model observations without importing an evaluator into the source rules.

The constructed operation `QueryBindingProjection.AliasReadout` handles bare aliases in the incoming record. It exposes those assignments as equality constraints before actual reconciliation and retains the structural cycle filter. Each surviving occurrence earns the exact conjunction of the original input theories, unchanged name support, a finite model and one certified readout table. That table absorbs the old selected table across the whole pending tuple. The result list is literally unchanged on callers whose assignments contain no bare variables, including its order, multiplicity and residual spelling. A crossed-alias control succeeds with all five observed positions shared; structural occurs checks, rigid disagreement and inconsistent seeds still refuse. The maintained recursive worker now uses this operation at primitive unification and equation-query reconciliation boundaries; its coverage checks and task denotation use the same boundary. The general raw merge algorithm is unchanged. Stability after covered discovery does not establish general source discovery completeness or justify treating budget exhaustion as refusal.

Scoped comparison has explicit composition laws. Complete solution-theory equality composes with the same added constraints; a scoped comparison requires those new constraints' entire support to lie in its observation scope. The negative controls distinguish these obligations. A tautological equality changes freshness support while preserving every solution, and adding a constraint on a hidden name can destroy scoped equivalence. Hygiene support therefore remains a separate contract, rather than being inferred from semantic redundancy.

The existing substitution algebra now also proves a support-determination law. Two first-order substitutions produce the same pattern exactly when their materialized variable values agree on that pattern's variable occurrences. Consequently, they give the same template whenever its variables are covered by the pattern. The source type-valuation interface is proved to realize that same operation. An unused environment entry may differ; an uncovered template variable need not agree. These laws concern structural substitution and do not assume a quotient by object-language equations.

The ordinary recursive source family now constructs worker paths through equation bodies, arguments and retained caller stacks. One uniform grammar supports both relation-list permutation and complete solution-theory plus hygiene-support comparison. The latter retains an independently certified source readout table and agreement with every covered native-model read. Principal native frames construct sufficient instances of this relation; they are not required of every related frame. Its completion, encoded execution, resumption, collection and service-handler laws preserve each exact worker occurrence. Nested calls, a recursive `peel` definition and duplicate physical equation declarations are checked. The query-admission constructor now covers arbitrary finite closed first-order patterns, including several and repeated variables, with a covered body vocabulary. It constructs the match, merge, model, loop-freedom and body materialization evidence from the actual hygienic query hit. The semantic comparison admits alias-bearing reached callers and constructs the next principal frame by reconciliation. A nested-call control retains three then four equality occurrences while the corresponding independent source layout differs. Completion, a reached pause, service delivery and one joint residual observation are checked together. This remains a closed-query, pattern-covered literal-result theorem. Open-query continuation transport, general polymorphic/host cases remain outside that family's automatic construction.

Typed invocation has a further constructed composition boundary. Declared singleton arrows earn actual first-success selection and matcher coverage from argument-domain evidence. The resulting head and argument paths compose with an admitted minimal function body and its actual typed-return children, preserving every ordered occurrence and the reached binding frame. The raw-domain `function` annotation supplies a concrete instance: its body syntax remains held until invocation, then a binding-changing body returns two correlated uses through the ordinary receiver. A reached checkpoint retains the nonempty bindings, caller and pending syntax and resumes exactly. These constructions inhabit the existing recursive application judgment. A nested duplicate-equation control follows ordinary return demand into a typed function that changes bindings; its saved checkpoint retains both receivers and the second source occurrence. Resumption preserves both results, their separate reached bindings and an arbitrary older stack and output prefix. This is admitted local source preservation and checked worker execution; unrestricted source reflection, general polymorphic selection and physical backend correspondence remain separate obligations.

The independent source evaluator has a simultaneous renaming action on all twelve evaluator, return and minimal-control judgments. It transports the whole space, live scope, saved caller, binding record and returned occurrences. Its inverse reflects derivations, including the public success-priority rule. The published type service is proved invariant by constructing lookup, casts, argument applicability and the complete ordered candidate scan; arbitrary foreign services remain explicitly transported components. This action does not establish unchanged-default native adequacy.

Diagnostic rendering makes that distinction observable. A malformed minimal `unify` embeds its rendered source atom, including fresh variable names, inside a message symbol. Renaming variable leaves does not rewrite characters already stored in that symbol. A checked source counterexample refutes unchanged-renderer equivariance, whereas the named transported renderer admits the renamed derivation. The following context also distinguished an actual CeTTa compatibility defect from Rust HE:

```
(= (malformed)
   (function (chain (unify $a A B) $r (return $r))))
!(case (malformed)
   (((Error $s IncorrectNumberOfArguments) code) ($other text)))
```

Rust returns `text`; the former compatibility boundary returned `code`. The repaired boundary returns `text` and retains the source subject. Successful four-argument calls and the other declared profiles retain their behavior. This is a contextual branch, so treating diagnostic text as non-normative would not establish contextual equivalence. The native formatter's finite buffer remains a separate implementation limit.

There is also a fixed contextual separation, rather than only different printed replies. Change one private rule variable from `\$a` to `\$z`, keeping the public rule name and the entire observer unchanged. The observer catches the message, formats it as a string, sorts it against a fixed marker ending at the diagnostic prefix followed by `\$m`, and tests whether that marker is first. Rust HE and both CeTTa execution paths return `False` for the first program and `True` for the second. Two activations of either program retain its respective Boolean. Ordering is decided at the private letter, before the fresh numeric suffix; no generated identifier is guessed. Well-formed primitive controls return the same non-error token. Thus unrestricted contextual alpha-invariance is false for this full observer language, even though the structural error subjects are alpha-equivalent. A representation-independent profile must specify its diagnostic and reflection policy; the binding-theory comparison alone cannot establish that policy.

The distinction persists without an error. Consider this successful minimal unification and its raw formatting result:

```
(= (probe)
   (function
     (chain (unify $a $z (format-args "{}" ($a)) Fail) $selected
       (chain (eval $selected) $text (return $text)))))
```

Rust HE retains the left variable's spelling; the earlier CeTTa image retained the right variable's spelling. Sorting the returned string against the fixed marker `"\$m"` converts this difference to opposite ground Booleans, before either numeric suffix matters. Swapping the two operands reverses both results. These are equal first-order solution theories with different observations in an unchanged context. The repaired HE-compat primitive now retains the left representative after a successful match of two distinct variables. Bound caller values, conflicts, both execution paths and the previous raw-case protocol pass the independent runtime controls; the other profiles retain their declared behavior. This narrow repair does not reverse every matcher call: other profiles deliberately orient their matches, and external matching services may be asymmetric. The required comparison must retain each profile's actual representative and materialization policy.

Fresh identity display is a separate observable boundary. A reflexive `unify \$a \$a` keeps the same representative letter in both engines, yet formatting exposes different generated suffixes. A fixed lexical marker turns that difference into opposite ground Booleans on the pinned activation. Unlike the letter-based control, this witness depends on that activation's fresh supply. Correcting alias orientation alone therefore cannot establish unrestricted equivalence for literal variable formatting; the freshness and rendering policy must also belong to the declared profile.

A query can expose this choice without comparing different implementations or changing the program. On the pinned Rust HE implementation, the following closed program returns either ground Boolean on different executions:

```
(Pair $v $v)
!(let $text (match &self (Pair $a $z) (format-args "{}" ($a)))
   (let $sorted (sort-strings ($text "$m"))
     (== (car-atom $sorted) "$m")))
```

Thirty-two fresh runs produced fifteen `False` and seventeen `True` observations; repeated queries also varied within one process. The bound-value control always returned `True`, and a query imposing conflicting rigid values always returned the empty bag. The relevant source route is `GroundingSpace::single_query`: it collects query variables in a `HashSet`, then calls `narrow_vars`. The latter copies query variables first and dependency variables second, choosing the first copied member as each retained class's representative. One enumeration is shared across the query's physical hits; it is not a separate choice for each occurrence in a returned term. Both tested CeTTa execution paths instead retained the stored variable's spelling and returned `True`. These observations expose a representation choice through ordinary string operations. They do not establish

that HE promises deterministic spelling. They do rule out deriving unrestricted contextual conformance solely from equal binding solution theories: the adapter must justify the actual narrowing and rendering policies as well.

A further compatibility control exposed a missing root-invocation route: ordinary `case A ((A Hit))` returns `Hit`, while invoking that same form through minimal `eval` returned `NotReducible` on the earlier CeTTa image. Rust HE returns `Hit` through both routes. Its standard library defines `case` by a minimal function body: it evaluates the scrutinee and selects a branch. Arithmetic calls and ordinary effect calls remain raw. Its `switch-minimal` protocol nevertheless enters a selected `function` delimiter and converts selected `NotReducible` to `Empty`; a bare `return` or `chain` remains syntax. A function returning a print call yields that call without printing it. Thus neither blanket holding nor blanket evaluation describes this boundary. The native ordinary-case implementation alone does not supply this reflected root invocation. Replacing the missing route by complete branch evaluation would also be incorrect when the selected branch contains effects. The repaired HE-compatibility route reuses the existing scrutinee capture and first-match builder, publishes the substituted template with its actual bindings, and leaves function entry to the existing raw-return continuation. Native controls retain duplicate scrutinee occurrences, select only the first matching clause, distinguish a missed clause from an empty scrutinee, and check the raw effect boundary. An independent comparison against Rust passes on both native execution paths with bounded and unbounded scheduling and collection enabled; the earlier image remains a negative control. Other profiles retain their declared behavior. This is a qualified native repair, not a whole-interpreter source correspondence theorem.

Minimal invocation must also expose the standard library's actual one-step program. In Rust HE, `eval (let $a 7 $a)` returns `(unify 7 $a $a Empty)`, rather than the final value 7. The caller's continuation and demand decide whether that program subsequently runs. The compatibility implementation now installs the actual library equation on its imported-library boundary. Querying that equation, raw invocation and full evaluation consequently use the same stored occurrence; repeated user equations retain their separate alternatives. An intrinsic that merely synthesizes the same final value would not establish this source-observation property.

A second native repair composes minimal function completion with the caller's typed result continuation. A named untyped function that returns `(println! 9)` prints once; a bare function with the declared `Atom` return demand keeps that expression as data. A named function whose body is `(println! 9)` without a return marker instead yields `NoReturn` and does not print. Independent replay of a named `chain/let/eval` example now returns 7 on Rust HE and both native execution paths. A subsequent compatibility query repair publishes a terminal variable under its unique projected query representative and rewrites the carried bindings consistently. It does not choose a name when two query variables share that terminal. The six earlier letter-representative failures are closed in the recorded 96-cell correlation gate. Generated private suffixes and multiply represented classes retain their separate observable boundaries; this is not unrestricted literal-name conformance.

A nonempty returning-function example exposed an additional native crossing:

```
(= (wrap $x $y) (function (return (got $x $y $x $y))))
!(let ($r) (collapse (wrap $a $a)) (== $r (got $a $a $a $a)))
```

Before the repair, canonical native execution returns `True`, while the noncanonical delimiter returns `False`: its collected value contains the private terminal of the rule-variable chain. Both paths now use the same compatibility-profile query-representative operation. The canonical `CALLER` frame already applies its reached environment; that application has not been replaced by a synthesized answer. The repaired image passes 80 maintained fixture executions and 20 independently replayed focused controls, including the earlier failing image. Its retained-execution gate checks a returned effect with a bound argument at 52 pause points, with cancellation, and commits the effect once. Extended and formal profiles retain their own readout policies. These executions do not supply

the still-missing general physical proof for nonempty binding application and `CALLER`; the Rust representative boundary below also remains explicit.

The same investigation exposed an independent source-model defect:

```
(= (foo) (function (SomeValue)))
!(eval (foo))
```

Both Rust HE and the two native execution paths return `(Error (foo) NoReturn)`. The former source rules admitted `(Error (SomeValue) NoReturn)` because equation and host invocation completion omitted the saved call. The four raw/typed equation/host rules now supply the assembled invocation as the nearest caller. Embedded minimal instructions retain their ambient continuation. Generic exact laws for closed data bodies cover both historical and retained finite readouts; a negative control rules out the old body-origin answer at this completion boundary. The correction uses the existing judgments, rather than a second evaluator. Two maintained Rust fixtures exercise raw and full evaluation.

A second source-model defect concerned the boundary between ordinary and minimal invocation. The actual annotated call `(function (return 7))` returns 7 on Rust HE and both native paths, whereas the former full source judgment admitted its unchanged wrapper. Its equation fallback had not excluded embedded instructions. An ordinary `unify` could also publish its selected template without passing the ordinary typed return gate. With `(= (f) Value)`, ordinary `(unify X X (f) Fail)` returns `Value`, while the explicit raw `eval` form returns `(f)`. The repaired source judgment delegates embedded invocation to the existing minimal relation and then to the existing ordinary return relation. Their exact composition law retains the reached binding frame and selected demand; it preserves the separate producer-completed native lane. Malformed-unify diagnostics now belong to the primitive step and retain their declared renderer. A negative control excludes the unchanged function wrapper and another excludes erasing a selected binding readout. Successful primitive selection also has to read its template through the selected frame. With `(= (f A) Hit)`, the program `(unify \$x B (f \$x) Fail)` returns `(f B)`. Constraint evidence alone would permit publishing the unread template; it does not determine the emitted syntax. The repaired success rule requires the actual match/merge candidate, frame renewal and exact materialization. Refusal instead retains the identical complete frame and the raw fallback. Separate controls preserve two uses of one variable, keep variable-looking string data opaque, and reject discarding the retained readout. An exhausted equation query uses `NotReducible`; the ordinary return gate restores its saved invocation. This query fallback is distinct from a host operation's empty-result protocol.

The maintained corpus now passes 40 Rust cases, with all earlier bags unchanged and source anchors checked. The frozen native compatibility image also passes all 40 cases under both canonical execution settings: 80 executions, with multiplicity preserved and no alpha normalization. The coherent eight-owner repair passes strict compilation. Its audit covers 6,805 kernel declarations and 3,629 theorem declarations, using only the standard three Lean axioms; 16 generated compiler implementations are validated separately. These are source-model repairs and local adequacy results, not whole-interpreter correspondence.

The retained source admission now constructs minimal data, admitted unification success and genuine no-match, cons/decons, recursive function bodies and ordinary embedded calls in the existing mutual family. Successful unification uses the actual match and merge to construct the selected next frame. Each function-body result is read in its own reached frame before the continuation resumes an instruction. Ordinary calls compose that minimal execution with the independent typed-return judgment. Checked completion and saved resumption preserve the same admission, original caller and prior output. Controls retain two pending uses through a real binding change and an actual four-step checkpoint. Completed producer provenance keeps function-looking result data separate from emitted code.

Equation admission now composes the actual query occurrence, prepared input, emitted producer

execution and typed return. Function-producing equations run their bodies through the same primitive and continuation machinery before resuming the ordinary receiver. The three ordered occurrence coordinates remain distinct; the previous nonfunction equation path is a proved singleton-producer specialization. Checked completion determines the entire delivered result list and publication prefix, and each occurrence has an independently derived source call at its reached frame. Two identical physical equations retain two results and distinct fresh bindings. An actual thirteen-step checkpoint retains an active function, the second producer and the ordinary receiver, then resumes exactly. Nine executions on Rust HE and both native canonical settings agree on twelve ground observations, including the original caller in a non-returning function error.

Raw invocation and structural `chain` now compose in this same mutual admission family. Raw `eval` reads its actual input frame, runs the selected equation's producer and returns through the raw receiver. A chain reads each child's reached frame, substitutes its explicit destination into the saved syntax, then resumes the existing minimal continuation under the original caller and live scope. It does not install that structural destination as a new binding assignment. The constructed completion, whole-result-list uniqueness, per-occurrence source meaning and saved resumption laws apply to these admitted requests. They do not assume a completed suffix or a whole-run correspondence as local evidence.

Checked controls compose a raw query, two identical physical equations, function-producing bodies, a two-use chain template and an enclosing function. An actual twenty-step checkpoint retains seven continuation frames and both fresh nonempty result bindings; resumption delivers both occurrences. A binding-changing unification also reaches both pending uses correctly. Separate controls distinguish genuine query absence, ordinary restoration, internal `Empty` and depth suspension. Three Rust/native executions agree on twelve ground observations. General non-symbol-headed raw invocation, all-filtered queries, polymorphic applicability, embedded-head typing and effectful host/world composition remain separate admission obligations.

The authored `switch-minimal` library has a separate boundary. Rust gives it the type `(-> Atom Expression Atom)`; it is not an embedded primitive. Ordinary invocation and raw invocation both hold the selected `(f)` in the example above. The source model's unconditional switch shortcut has been removed in favor of actual authored equations. The repaired frozen native compatibility image now agrees with Rust on both entries; its seven boundary programs pass in both native canonical execution settings. This closes the concrete library-return discrepancy. The general retained invocation correspondence remains a separate obligation.

An open-answer control exposes a stronger representative boundary than printing. Consider

```
!(let ($r)
  (collapse (let (pair $x $y) (pair $a $b) (got $x $y)))
  (== $r (got $a $b)))
```

In 24 fresh processes of the pinned Rust HE 0.2.10 executable, this program returns `True` 13 times and `False` 11 times. The result is a ground Boolean, so renaming printed result variables cannot explain the difference away. The branch's equality-class representative is materialized into the collapsed atom; its branch bindings are then absent from the outer comparison. A native candidate consistently selects the earliest left-operand variable and returns `True` under both execution settings. The unchanged corpus and separate duplicate-occurrence controls pass, but this policy is not thereby literal equivalence to all Rust observations. A proposed deterministic readout contract must state what correlation with caller variables survives collapse. Complete solution-theory preservation before projection does not alone preserve later literal-equality observations after the binding context has been discarded.

One actual full-evaluation behavior remains under investigation. Bare `(function (println! 9))` prints nothing but returns an unresolved `$result#17` on a fresh pinned Rust process; a preceding evaluation changes its generated identity. The named non-returning form gives the expected caller-

origin error. Native compatibility instead retains the minimal `NoReturn` result for the bare form. The unresolved internal plan variable, the minimal error and the caller's full result are distinct observations. A proposed semantic repair must identify that boundary and state its profile explicitly; inventing a matching fresh-name counter would not explain it.

An isolated SWI-PeTTa experiment illustrates the distinction between machine refinement and a small semantic change. Direct `(/ 1 0)` and its `eval` entry raise the host zero-divisor exception. Dynamic `(reduce (/ 1 0))` catches every host exception and instead fails as a Prolog goal, so subsequent top-level commands continue. Removing that catch in one isolated process makes dynamic dispatch propagate the same exception; an explicit MeTTa catch then receives the structured error. Ten program pairs retain successful arithmetic, duplicate answers, ordinary failure, unknown syntax and shared variables while exposing that deliberate fault-policy change. The production translator is unchanged. This experiment proves neither a general SWI compiler correspondence nor a speedup; it identifies a small candidate whose semantic benefit can be assessed against actual programs.

The existing PeTTa source and streaming owners now carry a destination-aware relational continuation alongside the eager policy. Destination matching may reject a rigid data skeleton before evaluating its contents; a primitive producer can instead commit its effect before its result fails to match the destination. The local native goal-array square retains older requests, bindings, world and occurrence positions. Its admitted structural region is explicit: list cells, rational terms and specialized scalar routing require their own readbacks. A suspended child reply is distinct from a request for another child, and consumed rows cannot be replayed.

The finite store presentation now instantiates this destination return step. Scope-checked preparation supplies the actual equations and one table for the value, destination, result and older goals. The independent return judgment accepts or refuses exactly when its materialized counterpart does. Successful resolution constructs one residual-variable permutation for the entire live tuple. Future solutions of the extended equations absorb the earlier table, preserving repeated uses. The actual saved-cursor laws retain the world, output, caller context and pending goal occurrences; resumption uses that cursor rather than repeating the earlier print. Refusal completes the branch with its reached world and differs from budget exhaustion. This instance uses finite first-order constraints within the declared acyclic store profile. Its event carrier is empty: the retained-world result is not a physical C receipt theorem. Choice, collection and additional primitive or equation invocation policies need their remaining operational joins.

Argument return has a separate local source judgment: its saved continuation is a younger/older list split, represented by a checked finite delimiter. A normal value continues the whole pending list. An error bypasses the younger argument work and constrains the outer destination with the reached equations. Refusal preserves the reached world; a malformed delimiter is a distinct boundary. Actual argument scheduling preserves delimiter validity, as does every exhausted prefix, so an admitted run cannot reach that malformed state at any budget. The scope-checked current-store instance uses one table for the returned value and every younger and older goal operand. The print step commits its output before result matching, and arbitrary saved prefixes compose with exact resumption. Other invocations retain their resolved arguments and continuation as requests; retaining a request is not executing it.

Collection exposes a further source-model defect:

```
!(let ($a $b) (collapse (superpose ($x $x))) (== $a $b))
```

SWI-PeTTa and the native PeTTa path both return `false`. Each collected answer has its own fresh variables, while repeated uses within that answer remain shared. The current eager logical collector instead reuses the same variable across the two answers and returns `true`; a kernel-checked computation establishes that disagreement. A maintained four-query reference also retains duplicate ground answers, tests binding one answer before reading the other, and distinguishes sharing within

an answer from sharing between answers. Both implementations pass all four observations. A faithful collection rule must copy an answer and its associated retained syntax with one renaming, independently of other answer copies. Renaming printed output cannot repair the ground Boolean disagreement.

The retained terminal-copy component is now constructed in the existing scope carrier. An actual completed destination run determines its terminal prefix; the collector reads that reached cursor, appends its value, equations and occurrence, then computes independent answer copies before installing the saved caller. The laws retain the reached shared world, caller bindings and context, older alternatives and prior answer metadata. One injective renaming serves each answer and its associated syntax, with disjoint complete tuples between answers. A kernel computation of two actual returns followed by the existing equality operation gives `false`.

The existing retained driver now also has an explicit scoped destination profile. Its finite loader jointly qualifies authored code, cells, operands and caller context. The scheduler constructs child entry, follows actual equation and primitive operations, copies completed answers, restores the caller and retains the shared world. Empty search is distinguished from refusing one branch; faults and associated work retain the exact saved scope. Every finite prefix preserves scope nesting, and every published occurrence has independently satisfiable reached constraints. Local mutable-operation laws preserve the identity inventory from the actual supported payloads. Controls execute nested collection, within-answer correlation, distinct answer copies and effectful refusal with exact resumption. The old eager default remains unchanged. Arbitrary dynamically created variable names, complete provenance through future world updates and execution of associated work remain further obligations; the profile is not a whole-language or physical backend correspondence theorem.

Finite clause selection likewise executes the existing solver rather than receiving a chosen solution. A shared freshening covers the pattern and body; the independent common-solution judgment characterizes both acceptance and refusal. Physical source occurrences, including identical equations, survive selection. The current-store instance supplies one readout for all pending operands and retains the selected body as work for the actual continuation.

Type-search paths and answer occurrences have different roles. The actual Rust evaluator chooses the first successful pair in the flattened scan of function types and their applicability bindings. For example,

```
(: ident (-> Atom Atom))
(: ident (-> Number Number))
(= (ident $x) $x)
!(collapse (ident 7))
```

returns `(7)` in both the pinned Rust evaluator and native compatibility settings. One arrow with two successful argument-type paths likewise produces one answer. Repeating the defining equation instead produces `(7 7)`. The older all-candidate Lean evaluator duplicates the first example; retaining every successful binding from one callback also duplicates the second. These controls identify model discrepancies. A faithful implementation must honor the declared selection boundary while retaining subsequent equation occurrences; backend scheduling freedom does not authorize extra answers.

Polymorphic instantiation exposes another source-model boundary:

```
(: ident (-> $t $t))
(= (ident $x) $x)
!(Pair (ident 7) (ident True))
```

The pinned Rust and native compatibility executions return `Pair 7 True`. The maintained retained worker currently rejects the second call because its annotation lookup reuses the declaration's variable after the first call has constrained it to `Number`. A call-site instance must freshen the whole

arrow against the complete saved configuration, preserving repeated domain and return variables within that arrow while separating successive calls. Raw declaration lookup remains useful for inspection. This is a model scope defect, not evidence that either checked implementation rejects the program.

The first-success worker now also uses the common checked resource interface. Its coverage predicate follows the failed applicability prefix and selected candidate, then stops; an unselected divergent suffix creates no obligation. Depth exhaustion retains a request and complete saved configuration. Genuine empty completion is distinct. A completed checked execution gives the same full result at every larger pending evaluator depth, with exact structured and encoded resumption. The recursive controls construct the required checked runs. Finite source evidence alone does not yet construct sufficient coverage for every bounded matcher leaf. A stronger constructed route now adds local coverage for precisely the reached type selections, casts, query, merge and materialization leaves. Induction on that source derivation yields a finite checked worker path and hence a sufficient scheduler budget, valid at every larger budget. Every actual exhausted scheduler checkpoint resumes to the same completed occurrences from its saved state. Closed type casts obtain their local bound from syntax size; arbitrary open or foreign leaf coverage remains an explicit further construction.

Variable support is also preserved through the actual native binding operations. Every name returned by reconciliation or merge comes from an input equation or binding record. Recursive resolution introduces no name outside its input term and the complete caller record; projection introduces no name outside that record, even if an unbound name was requested. Freshness therefore includes dependencies inside open stored values. A local may acquire equality aliases during matching while its class remains valueless. Assigning a closed value to such a class retains the complete caller, and the executable loop check still selects success or refusal. The existing fresh-variable API is derived from this class-level law.

The shared binary argument fold also records each result's physical input occurrence and the state reached after all earlier input occurrences. Its origin theorem retains arbitrary incoming bindings and both actual merge/projection boundaries. Equal first results can therefore lead to different later effects without being merged: the controls execute the next argument in successive states, while a changed terminal suppresses that argument entirely. These are laws of the existing worker's chronology, not a global MeTTa enumeration policy.

These are package-specific qualification results, not completion of every machine or of the whole source/native goal. Separate historical receipts qualify earlier CAM, VM and native-boundary packages. A full joined acceptance must identify the exact current sources, assumptions, executable consumers and relevant runtime gates.

Package	Remaining constructed connection
Common theory	Legal contextual closure and observer/scheduling joins for the actual language instances.
MeTTa	Complete source/configuration/native correspondence at arbitrary nesting, preserving raw/quoted boundaries, sharing, worlds, occurrences and each worker's retained history. Live-scope equation lookup and checked completion now support nested calls and recursive services; the complete contextual correspondence remains open. LeaTTa-only coverage and conformance are optional supporting results; they do not discharge the CeTTa connection or block its acceptance.
Interaction	Complete contextual MeTTa/effectful interaction joins. The retained rho runner now constructs both orders of disjoint COMMs, with exact histories, dependency validation, cancellation and no replay. Crash recovery and distributed agreement are separate host assumptions.
CAM	Joined current-source qualification. Extended scoped readback and memoizing execution now have bidirectional correspondences with their independent source judgments, including captured scope and nested demand.
Fixed C core	The common fixed/located fragment now covers successful and faulting source histories, licensed expression/assignment refusals and exact retained budget splits. Its whole-run reverse simulation discovers the owning source controls from arbitrary licensed located histories, including partial assignments and loops. Joined current-source qualification remains. Named extensions such as `for`, `do`, `switch`, array initializers and calls inside expressions remain outside the fixed core.
Joined acceptance	Full relevant runtime gates and current-source audits through the shared interfaces. Recursive MeTTa services and retained logical checkers have package-specific qualification; this does not supply the whole source/native correspondence.

The priority is to close the complete MeTTa representation and owned interaction joins. The productive block laws, actual retained searches and world-query certificates already provide reusable pieces. Extending another independent framework would not replace those connections.

References

[1] G. Cousineau, P.-L. Curien and M. Mauny. *The categorical abstract machine*. Science of Computer Programming 8(2), 173–202, 1987. https://doi.org/10.1016/0167-6423(87)90020-7.

[2] J. Clements, M. Flatt and M. Felleisen. *Modeling an Algebraic Stepper*. ESOP 2001, Lecture Notes in Computer Science 2028, 320–334. https://doi.org/10.1007/3-540-45309-1_21.

[3] F. J. López-Fraguas, E. Martin-Martin, J. Rodríguez-Hortalá and J. Sánchez-Hernández. *Rewriting and narrowing for constructor systems with call-time choice semantics*. Author manuscript, 2012. https://arxiv.org/abs/1209.2617.

[4] O. Danvy and L. R. Nielsen. *Refocusing in Reduction Semantics*. BRICS Report RS-04-26, 2004. https://www.brics.dk/RS/04/26/BRICS-RS-04-26.pdf.

[5] L. Xia, Y. Zakowski, P. He, C.-K. Hur, G. Malecha, B. C. Pierce and S. Zdancewic. *Interaction Trees: Representing Recursive and Impure Programs in Coq*. Proceedings of the ACM on Programming Languages 4, POPL, Article 51, 2020. https://doi.org/10.1145/3371119.

[6] X. Leroy. *The ZINC Experiment: An Economical Implementation of the ML Language*. INRIA technical report 117, 1990. https://xavierleroy.org/publi/ZINC.pdf.

[7] J. Matthews and R. B. Findler. *Operational Semantics for Multi-Language Programs*. ACM Transactions on Programming Languages and Systems 31(3), Article 12, 2009. https://doi.org/10.1145/1498926.1498930.

[8] M. Flatt. *Binding as Sets of Scopes: Notes on a New Model of Macro Expansion for Racket*. https://users.cs.utah.edu/~mflatt/scope-sets-2/.

[9] C. McBride. *The Derivative of a Regular Type is its Type of One-Hole Contexts*. Extended abstract, 2001. http://strictlypositive.org/diff.pdf.

[10] G. Huet. *The Zipper*. Journal of Functional Programming 7(5), 549–554, 1997. https://www.cs.tufts.edu/comp/150FP/archive/gerard-huet/zipper.pdf.

[11] D. Varacca and G. Winskel. *Distributing probability over non-determinism*. Mathematical Structures in Computer Science 16(1), 87–113, 2006. https://www.cl.cam.ac.uk/~gw104/distprobnd_journal.pdf.

[12] B. Goertzel. *Reflective Metagraph Rewriting as a Foundation for an AGI "Language of Thought"*. arXiv:2112.08272. https://arxiv.org/abs/2112.08272.

[13] C. Heunen, O. Kammar, S. Staton and H. Yang. *A Convenient Category for Higher-Order Probability Theory*. LICS, 2017. https://arxiv.org/abs/1701.02547.

[14] M. Vákár, O. Kammar and S. Staton. *A Domain Theory for Statistical Probabilistic Programming*. Proceedings of the ACM on Programming Languages 3, POPL, Article 36, 2019. https://arxiv.org/abs/1811.04196.

[15] J. C. Baez and M. Stay. *Physics, Topology, Logic and Computation: A Rosetta Stone*. In B. Coecke (ed.), *New Structures for Physics*, Lecture Notes in Physics 813, pp. 95–172, 2010. https://doi.org/10.1007/978-3-642-12821-9_2; https://arxiv.org/abs/0903.0340.

[16] J. Meseguer. *Conditional rewriting logic as a unified model of concurrency*. Theoretical Computer Science 96(1), pp. 73–155, 1992. https://doi.org/10.1016/0304-3975(92)90182-F.

[17] M. Fiore and D. Szamozvancev. *Formal Metatheory of Second-Order Abstract Syntax*. Proceedings of the ACM on Programming Languages 6, POPL, 2022. https://doi.org/10.1145/3498715; https://arxiv.org/abs/2201.03504.

[18] M. Carneiro. *Metamath Zero: The Cartesian Theorem Prover*. arXiv:1910.10703. https://arxiv.org/abs/1910.10703.

[19] J. Harrison. *HOL Light: An Overview*. https://www.cl.cam.ac.uk/~jrh13/papers/hollight.html.

[20] M. Carneiro. *Lean4Lean: Verifying a Typechecker for Lean, in Lean*. arXiv:2403.14064, version 3, 2025. https://arxiv.org/abs/2403.14064.

[21] R. Vaishnav. *Lean4Less: Eliminating Definitional Equalities from Lean via an Extensional-to-Intensional Translation*. ICTAC 2025. https://rish987.github.io/files/lean4less.pdf; https://github.com/Deducteam/Lean4Less.

[22] Lambdapi contributors. *Lambdapi User Manual: Commands, rewrite rules*. https://lambdapi.readthedocs.io/en/stable/commands.html.

[23] CakeML contributors. *CakeML projects and verified applications*. https://www.cakeml.org/projects.html; https://cakeml.org/.

[24] J. Hurd. *OpenTheory Article File Format*. https://www.gilith.com/opentheory/article.html.

[25] Mathlib contributors. *Gödel numbering for partial recursive functions*. `Mathlib.Computability.PartrecCode`, especially `exists\_code`, `evaln\_sound`, `evaln\_complete` and `primrec\_evaln`. https://leanprover-community.github.io/mathlib4_docs/Mathlib/Computability/PartrecCode.html.

[26] M. Rawson and G. Reger. *Dynamic Strategy Priority: Empower the strong and abandon the weak*. PAAR, 2018. https://rawsons.uk/michael/papers/PAAR-2018.pdf.

[27] L. Cruz-Filipe, M. J. H. Heule, W. A. Hunt Jr., M. Kaufmann and P. Schneider-Kamp. *Efficient Certified RAT Verification*. CADE, 2017. https://www.cs.cmu.edu/~mheule/publications/lrat.pdf.

[28] S. Eker. *Associative-Commutative Rewriting on Large Terms*. RTA, 2003. https://maude.cs.illinois.edu/papers/abstract/EkerACrewriting_2003.html.

[29] J. Adámek, S. Milius, L. S. Moss and L. Sousa. *Well-pointed coalgebras*. Logical Methods in Computer Science 9(3:2), 2013. https://lmcs.episciences.org/704/pdf.

[30] D. Turi and G. Plotkin. *Towards a Mathematical Operational Semantics*. Proceedings of LICS, 1997, pp. 280–291. https://homepages.inf.ed.ac.uk/gdp/publications/Math_Op_Sem.pdf.

[31] D. R. Weinbaum (Weaver). *Open-Ended Intelligence*. PhD thesis, Vrije Universiteit Brussel, 2018, especially Chapters 5 and 7.

[32] nLab contributors. *Deductive system*, *multicategory*, *syntactic category*, and *institution*. https://ncatlab.org/nlab/show/deductive+system; https://ncatlab.org/nlab/show/multicategory; https://ncatlab.org/nlab/show/syntactic+category; https://ncatlab.org/nlab/show/institution.