curl "https://bootstrap.pypa.io/get-pip.py" -o "get-pip.py"
apt-get install python
apt install python-pip
python get-pip.py --user

sudo pip install awscli --user

sudo apt install awscli
aws configure

aws ec2 describe-regions --output table

aws ec2 create-security-group --group-name aws-cli-demo --vpc-id vpc-75ce600d --description "security group for development environment"

aws ec2 authorize-security-group-ingress --group-name test1234 --protocol tcp --port 22 --cidr 0.0.0.0/0

aws ec2 create-key-pair --key-name test --query 'KeyMaterial' --output text > test1.pem

chmod 400 test1.pem

aws ec2 run-instances --image-id ami-db710fa3 --subnet-id subnet-5a75b83c --security-group-ids sg-0d843f7c --count 1 --instance-type t2.micro --key-name test --query 'Instances[0].InstanceId'

ssh -i "test1.pem" ubuntu@ec2-34-217-99-215.us-west-2.compute.amazonaws.com

aws ec2 describe-instances --instance-ids i-04a0ee743861c3185

aws ec2 create-tags --resources i-04a0ee743861c3185 --tags Key=Name,Value=test

aws ec2 describe-instances --filters "Name=tag:Name,Values=MyInstance"

aws ec2 stop-instances --instance-ids i-0435a20c5376a62f4

==========
Easticip:--
==========

aws ec2 allocate-address

aws ec2 associate-address --instance-id i-07ffe74c7330ebf53 --public-ip 198.51.100.0

---

s3:--
---
aws s3 mb s3://testing123456567 ----------> creating bucket

aws s3 rb s3://testing123456567 ---------- removce bucket

aws s3 ls ----------> list all buckets

aws s3 ls s3://samples1234 -------->

sudo aws s3 cp include.yml s3://samples1234

aws s3 presign s3://awss3demo12/voter.jpg ---> make public

aws s3 website s3://awss3demo12 --index-document index.html --error-document error.html

// Copy MyFile.txt in current directory to s3://my-bucket/path
$ aws s3 cp MyFile.txt s3://my-bucket/path/

// Move all .jpg files in s3://my-bucket/path to ./MyDirectory
$ aws s3 mv s3://my-bucket/path ./MyDirectory --exclude '*' --include '*.jpg' --recursive

// List the contents of my-bucket
$ aws s3 ls s3://my-bucket

// List the contents of path in my-bucket
$ aws s3 ls s3://my-bucket/path/

aws s3 rb s3://jenkinss312 --force

// Delete s3://my-bucket/path/MyFile.txt
$ aws s3 rm s3://my-bucket/path/MyFile.txt

// Delete s3://my-bucket/path and all of its contents
$ aws s3 rm s3://my-bucket/path --recursive

Ref link: - https://www.thegeekstuff.com/2019/04/aws-s3-cli-examples/

---
glacier:--
---

aws glacier create-vault --vault-name my-vault --account-id 847986217538

aws glacier upload-archive --account-id 847986217538 --vault-name demotest --body TechdatCommunicationss.war


```
{
    "location": "/847986217538/vaults/demotest/archives/2iq4zTun2TBaeEpKa1oHJkNAuJCRr1mxBZ0LObx9oR18RzKj7BgmoF1LHHJECc2zoEU5-ONU4kukY5sqxMpEBfDkiq1yHQb9NpZbUKG7DZSRan9flRh6vFXxox3NcVrtNiLnPeJpYw",
    "checksum": "cbc5fe0b694593bf444aaf95737bef69b00368340047a1feb73c41cee847e4b2",
    "archiveId": "2iq4zTun2TBaeEpKa1oHJkNAuJCRr1mxBZ0LObx9oR18RzKj7BgmoF1LHHJECc2zoEU5-ONU4kukY5sqxMpEBfDkiq1yHQb9NpZbUKG7DZSRan9flRh6vFXxox3NcVrtNiLnPeJpYw"
}
```

aws glacier describe-vault --vault-name testing --account-id 426831777344

aws glacier delete-vault --vault-name my-vault --account-id -