

Step-1

- > Create New Project
- > select Java With Ant > Java Web
- > Select Web Application
- > Name the Project
- > Add Server Tomcat (Add > Apache Tomcat or TomEE)
- > Server Location Browse (This Pc > Local Disk(C) > Program Files > Apache Software > Tomcat 10.1 > Username= admin > Password =Password

Step-2

- > Index.html create already once you done the step for project above
- > Write code in index.html

[Code]

```
<!DOCTYPE html>
<html>
<head>
<meta charset="UTF-8">
<title>Insert title here</title>
</head>
<body>
<form action="FirstServlet" method="get">
Name:<input type="text" name="userName"/><br/>
<input type="submit" value="submit"/>
</form>
</body>
</html>
```

Step-3

- > Create a FirstServlet (Go to the project window > Right click on Source Package > new > Servlet > Give name (FirstServlet) > Next > Tick the Checkbox (Add information to deployment descriptor) > Finish)
- > Write code in FirstServlet

[Code]

```
import java.io.*;
import jakarta.servlet.*;
import jakarta.servlet.annotation.WebServlet;
import jakarta.servlet.http.*;
@WebServlet("/FirstServlet") // annotation

// this annotation is used for replacing xml file
public class FirstServlet extends HttpServlet {

    // class name is FirstServlet which extends HttpServlet
    public void doGet(HttpServletRequest request, HttpServletResponse response)
    {
        try {
            response.setContentType("text/html");
            /* The response's character encoding is only set
from the given content type if this method
is called before getWriter is called.
This method may be called repeatedly to
change content type and character encoding.*/
            PrintWriter out = response.getWriter();

            /*T he Java PrintWriter class ( java.io.PrintWriter ) enables you to
write formatted data to an underlying Writer .
For instance, writing int, long and other primitive data
formatted as text, rather than as their byte values*/
            String n = request.getParameter("userName");

//request.getParameter takes the value from index.html file
// where name is username
            out.print("Welcome " + n);

// out.println is used to print on the client web browser

//url rewriting is used for creating session
// it will redirect you to SecondServlet page
            out.print("<a href='SecondServlet?uname=" + n + "'>visit</a>");

            out.close();
        }
        catch (Exception e) {
```

```

        System.out.println(e);
    }
}
}

```

Step-4

Again same step as (SecondServlet)

--> Create a SecondServlet (Go to the project window > Right click on Source Package > new > Servlet > Give name (SecondServlet) > Next > Tick the Checkbox (Add information to deployment descriptor) > Finish)
 --> Write code in SecondServlet

[code]

```

import java.io.*;
import jakarta.servlet.*;
import jakarta.servlet.annotation.WebServlet;
import jakarta.servlet.http.*;

@WebServlet("/SecondServlet") // annotation
public class SecondServlet extends HttpServlet {

    public void doGet(HttpServletRequest request, HttpServletResponse response)
    {
        try {

            response.setContentType("text/html");
            /*
             * The response's character encoding is only set from the given
             * content type if this method is called before getWriter is called.
             * This method may be called repeatedly to change content type and
             * character encoding.
             */
            PrintWriter out = response.getWriter();
            /*
             * The Java PrintWriter class ( java.io.PrintWriter ) enables you to
             * write formatted data to an underlying Writer . For instance,
             * writing int, long and other primitive data formatted as text,

```

```
        * rather than as their byte values
        */
        // getting value from the query string
        String n = request.getParameter("uname");
        out.print("Hello " + n);
        /* out.println is used to print on the client web browser */
        out.close();
    }
    catch (Exception e) {
        System.out.println(e);
    }
}
}
```

Step-5

--> Run the Program of FirstServlet