

Intelligent Function Module
Start I/O:0000 QD77MS4 Simple Motion Module
Synchronous Parameter

09-07-2026

Item	Axis #1	Axis #2	Axis #3	Axis #4
Synchronous control module setting	Set each module parameter.			
Main shaft				
Main input axis				
Pr.400:Type	0:Invalid	0:Invalid	0:Invalid	0:Invalid
Pr.400:Axis No.	0	0	0	0
Sub input axis				
Pr.401:Type	0:Invalid	0:Invalid	0:Invalid	0:Invalid
Pr.401:Axis No.	0	0	0	0
Main shaft composite gear				
Pr.402:Main	1:Input+	1:Input+	1:Input+	1:Input+
Pr.402:Sub	0:No Input	0:No Input	0:No Input	0:No Input
Main shaft gear				
Pr.403:Numerator	1	1	1	1
Pr.404:Denominator	1	1	1	1
Main shaft clutch				
Main shaft clutch control setting				
Pr.405:ON control mode	0:No Clutch (Direct Coupled Operation)	0:No Clutch (Direct Coupled Operation)	0:No Clutch (Direct Coupled Operation)	0:No Clutch (Direct Coupled Operation)
Pr.405:OFF control mode	0:OFF Control Invalid	0:OFF Control Invalid	0:OFF Control Invalid	0:OFF Control Invalid
Pr.405:High-speed input request signal	0	0	0	0
Pr.406:Main shaft clutch reference address setting	0:Current Value after Main Shaft Composite Gear	0:Current Value after Main Shaft Composite Gear	0:Current Value after Main Shaft Composite Gear	0:Current Value after Main Shaft Composite Gear
Pr.407:Main shaft clutch ON address	0 pulse	0 pulse	0 pulse	0 pulse
Pr.408:Movement amount before main shaft clutch ON	0 pulse	0 pulse	0 pulse	0 pulse
Pr.409:Main shaft clutch OFF address	0 pulse	0 pulse	0 pulse	0 pulse
Pr.410:Movement amount before main shaft clutch OFF	0 pulse	0 pulse	0 pulse	0 pulse
Pr.411:Main shaft clutch smoothing system	0:Direct	0:Direct	0:Direct	0:Direct
Pr.412:Main shaft clutch smoothing time constant	0 ms	0 ms	0 ms	0 ms
Pr.413:Slippage at main shaft clutch ON	0 pulse	0 pulse	0 pulse	0 pulse
Pr.414:Slippage at main shaft clutch OFF	0 pulse	0 pulse	0 pulse	0 pulse
Auxiliary shaft				
Pr.418:Type	0:Invalid	0:Invalid	0:Invalid	0:Invalid
Pr.418:Axis No.	0	0	0	0
Auxiliary shaft composite gear				
Pr.419:Main shaft	1:Input+	1:Input+	1:Input+	1:Input+
Pr.419:Auxiliary shaft	0:No Input	0:No Input	0:No Input	0:No Input
Auxiliary shaft gear				
Pr.420:Numerator	1	1	1	1
Pr.421:Denominator	1	1	1	1

Intelligent Function Module
Start I/O:0000 QD77MS4 Simple Motion Module
Synchronous Parameter

09-07-2026

Item	Axis #1	Axis #2	Axis #3	Axis #4
Auxiliary shaft clutch				
Auxiliary shaft clutch control setting				
Pr.422:ON control mode	0:No Clutch (Direct Coupled Operation)	0:No Clutch (Direct Coupled Operation)	0:No Clutch (Direct Coupled Operation)	0:No Clutch (Direct Coupled Operation)
Pr.422:OFF control mode	0:OFF Control Invalid	0:OFF Control Invalid	0:OFF Control Invalid	0:OFF Control Invalid
Pr.422:High-speed input request signal	0	0	0	0
Pr.423:Auxiliary shaft clutch referen address setting	0:Auxiliary Shaft Current Value	0:Auxiliary Shaft Current Value	0:Auxiliary Shaft Current Value	0:Auxiliary Shaft Current Value
Pr.424:Auxiliary shaft clutch ON address	0 pulse	0 pulse	0 pulse	0 pulse
Pr.425:Movement amount before auxiliary shaft clutch ON	0 pulse	0 pulse	0 pulse	0 pulse
Pr.426:Auxiliary shaft clutch OFF address	0 pulse	0 pulse	0 pulse	0 pulse
Pr.427:Movement amount before auxiliary shaft clutch OFF	0 pulse	0 pulse	0 pulse	0 pulse
Pr.428:Auxiliary shaft clutch smoothing system	0:Direct	0:Direct	0:Direct	0:Direct
Pr.429:Auxiliary shaft clutch smoothing time constant	0 ms	0 ms	0 ms	0 ms
Pr.430:Slippage at auxiliary shaft clutch ON	0 pulse	0 pulse	0 pulse	0 pulse
Pr.431:Slippage at auxiliary shaft clutch OFF	0 pulse	0 pulse	0 pulse	0 pulse
Speed change gear				
Pr.434:Speed change gear arrangement	0:No Speed Change Gear	0:No Speed Change Gear	0:No Speed Change Gear	0:No Speed Change Gear
Pr.435:Speed change gear smoothing time constant	0 ms	0 ms	0 ms	0 ms
Speed change ratio				
Pr.436:Numerator	1	1	1	1
Pr.437:Denominator	1	1	1	1
Output axis				
Cam axis cycle unit				
Pr.438:Unit setting selection	0:Use Unit of Main Input Axis	0:Use Unit of Main Input Axis	0:Use Unit of Main Input Axis	0:Use Unit of Main Input Axis
Pr.438:Unit	0:mm	0:mm	0:mm	0:mm
Pr.438:Number of decimal places	0	0	0	0
Pr.439:Cam axis length per cycle	4194304 pulse	4194304 pulse	4194304 pulse	4194304 pulse
Pr.441:Cam stroke amount	419430.4 μm	419430.4 μm	419430.4 μm	4194304 pulse
Pr.440:Cam No.	0	0	0	0
Pr.444:Cam axis phase compensatic advance time	0 μs	0 μs	0 μs	0 μs
Pr.445:Cam axis phase compensatic time constant	10 ms	10 ms	10 ms	10 ms
Pr.446:Synchronous control deceleration time	0 ms	0 ms	0 ms	0 ms
Pr.447:Output axis smoothing time constant	0 ms	0 ms	0 ms	0 ms

Intelligent Function Module
Start I/O:0000 QD77MS4 Simple Motion Module
Synchronous Parameter

09-07-2026

Item	Axis #1	Axis #2	Axis #3	Axis #4
 Synchronous control initial position parameter	Set the parameter for the initial alignment when starting the synchronous control.			