🫀 MLOps Experiential Learning Assignment 01: End-to-End Production Machine Learning System

Course Code: AIML ZG523 — Machine Learning Operations (MLOps)
Programme: M.Tech in Artificial Intelligence & Machine Learning (BITS Pilani WILP)
Student Name: Kiran Kumar
Student ID: `2025AE05377`
Submission Date: October 2026
Repository URL: https://github.com/goelkiran/heart-disease-mlops
Video Demonstration Walkthrough Link: Click to Watch Video Walkthrough (YouTube)
API Serving Target: `http://localhost:8000` (Docker Container / Kubernetes Service)

---

1. Executive Summary & Problem Formulation

1.1 Clinical Background & Problem Statement

Cardiovascular diseases (CVDs) remain the leading cause of global mortality, accounting for an estimated 17.9 million deaths annually according to the World Health Organization (WHO). Early detection and clinical risk stratification can significantly mitigate adverse cardiac events. However, deploying machine learning diagnostic aids in clinical environments requires far more than high offline accuracy. Clinical deployments demand:
1. **End-to-End Reproducibility**: Exact tracking of data versions, feature transformers, hyperparameters, and model weights.
2. **Automated Quality Gates**: CI/CD pipelines that enforce linting, unit testing, and model invariance checks before any deployment.
3. **Cloud-Native Scalability & Isolation**: Containerized serving environments decoupled from host dependencies with strict resource boundaries.
4. **Resilient Production Observability**: Continuous telemetry to track inference latencies, throughput, prediction drift, and operational error rates.


This project delivers an end-to-end, enterprise-grade MLOps solution for heart disease risk classification using the **UCI Heart Disease Dataset (Cleveland Clinic Foundation)**. The pipeline transitions raw clinical data into a containerized microservice orchestrated via

Kubernetes, instrumented with MLflow experiment tracking, automated with GitHub Actions CI/CD, and monitored via Prometheus and Grafana.

---

2. System Architecture & Topology Design

The system adheres to standard production MLOps reference architecture (Level 2 maturity), comprising five decoupled lifecycle phases:



2.1 Component Specifications

Architecture Tier	Technologies Utilized	Operational Responsibility
Data Ingestion & Cleaning	Python, Pandas, NumPy, Requests	Automated dataset download, schema validation, binary target mapping, missing value imputation.
Feature Transformation	Scikit-Learn `ColumnTransformer`, `StandardScaler`	Leak-free median imputation for numerical data and one-hot encoding for categorical variables.
Model Governance	MLflow 3.x, SQLite Tracking Store	Logging hyperparameters, cross-validation ROC-AUC scores, confusion matrices, and model artifacts.
CI/CD Quality Assurance	GitHub Actions, Flake8, Pytest	Automated static linting, unit test execution (11 tests), and container build verification.
Container Serving	Docker (Multi-stage build), Uvicorn, FastAPI	Lightweight Python 3.12-slim image (<250MB), unprivileged security context (`appuser`), `/predict` endpoint.
Orchestration	Kubernetes (Deployment, Service)	Self-healing pods (2 replicas), rolling update strategy, liveness and readiness health probes.
Telemetry & Observability	Prometheus, Grafana, Structured JSON Logger	Real-time monitoring of request latency, throughput, prediction volume, and HTTP status codes.

---

3. Data Acquisition & Exploratory Data Analysis (EDA)

3.1 Dataset Schema & Clinical Indicators

The dataset comprises 303 patient records across 14 clinical variables collected from the Cleveland Clinic Foundation:

Feature Name	Clinical Description	Data Type	Permissible Range / Values
`age`	Patient age in years	Continuous (Integer)	29 to 77
`sex`	Biological sex	Binary	1 = Male; 0 = Female
`cp`	Chest pain type	Categorical (1–4)	1: Typical Angina, 2: Atypical Angina, 3: Non-anginal, 4: Asymptomatic
`trestbps`	Resting blood pressure on admission	Continuous (Integer)	94 to 200 mm Hg
`chol`	Serum cholesterol level	Continuous (Integer)	126 to 564 mg/dl
`fbs`	Fasting blood sugar > 120 mg/dl	Binary	1 = True; 0 = False
`restecg`	Resting electrocardiographic results	Categorical (0–2)	0: Normal, 1: ST-T wave abnormality, 2: Left ventricular hypertrophy
`thalach`	Maximum heart rate achieved during stress test	Continuous (Integer)	71 to 202 bpm
`exang`	Exercise-induced angina	Binary	1 = Yes; 0 = No
`oldpeak`	ST depression induced by exercise relative to rest	Continuous (Float)	0.0 to 6.2 mm
`slope`	Slope of the peak exercise ST segment	Categorical (1–3)	1: Upsloping, 2: Flat, 3: Downsloping
`ca`	Major vessels colored by fluoroscopy	Discrete (0–3)	0.0, 1.0, 2.0, 3.0 (4 missing records)

Feature Name	Clinical Description	Data Type	Permissible Range / Values
`thal`	Thallium scintigraphy stress test defect	Categorical (3, 6, 7)	3.0: Normal, 6.0: Fixed defect, 7.0: Reversible defect (2 missing)
`target`	Angiographic disease status	Binary (Cleaned)	0 = Absence (<50% diameter narrowing), 1 = Presence (>50% narrowing)

3.2 Target Class Balance

The original Cleveland dataset records angiographic disease severity on an integer scale from 0 to 4. For clinical binary triage, values >0 represent disease presence. After conversion:
- **Class 0 (Disease Absent)**: 164 patients (54.1%)
- **Class 1 (Disease Present)**: 139 patients (45.9%)




Figure 1: Target variable distribution across the cleaned Cleveland dataset showing balanced distribution (54.1% absent vs 45.9% present).

3.3 Correlation & Multicollinearity Analysis

To evaluate linear associations between clinical predictors and angiographic heart disease presence, a Pearson correlation matrix was computed across all 14 variables:




Figure 2: Pearson correlation heatmap revealing high predictive associations for fluoroscopy vessels (`ca`), exercise depression (`oldpeak`), and maximum heart rate (`thalach`).

3.4 Numerical Feature Distributions & Physiological Boxplots

The continuous variables (`age` , `trestbps` , `chol` , `thalach` , `oldpeak`) were profiled for skewness, clinical outliers, and differential medians across patient diagnostic cohorts:




Figure 3: Histograms and kernel density estimates (KDE) for continuous clinical variables.




Figure 4: Comparative boxplots demonstrating pronounced separation in maximum heart rate (`thalach`), exercise ST depression (`oldpeak`), and serum cholesterol (`chol`) across diagnostic cohorts.

Key Exploratory Findings:

1. **Exercise ST Depression (`oldpeak`)**: Patients with heart disease exhibit significantly higher

median ST depression (1.4 mm vs 0.2 mm), confirming myocardial ischemia during physical exertion.
2. **Maximum Heart Rate (`thalach`)**: Healthy individuals achieve substantially higher maximum heart rates during stress testing (median 162 bpm) compared to cardiac patients (median 142 bpm).
3. **Fluoroscopy Vessels (`ca`)**: The presence of colored coronary vessels correlates heavily ($r = +0.46$) with multi-vessel coronary artery disease.

---

4. Feature Engineering & Preprocessing Pipeline

4.1 Data Leakage Prevention via Scikit-Learn Pipelines

A frequent anti-pattern in machine learning deployments is computing scaling parameters (mean, standard deviation) or imputation medians across the entire dataset prior to train-test splitting. This introduces subtle data leakage, inflating offline validation scores.

Our pipeline strictly isolates training and test partitions using `StratifiedShuffleSplit` (80% train = 242 records, 20% test = 61 records) and encapsulates all transformations within a leak-free `ColumnTransformer`:

```
numerical_transformer = Pipeline([
    ("imputer", SimpleImputer(strategy="median")),
    ("scaler", StandardScaler()),
])

categorical_transformer = Pipeline([
    ("imputer", SimpleImputer(strategy="most_frequent")),
    ("onehot", OneHotEncoder(handle_unknown="ignore", sparse_output=False)),
])

preprocessor = ColumnTransformer(
    transformers=[
        ("num", numerical_transformer, NUMERICAL_COLS),
        ("cat", categorical_transformer, CATEGORICAL_COLS),
    ]
)
```

By binding the preprocessor and estimator into a single serialized `Pipeline` object (`best_model.joblib`), raw unnormalized JSON requests arriving at the serving API are automatically preprocessed using the exact training statistics.

---

5. Model Development, Tuning & Evaluation

5.1 Evaluated Model Architectures

To satisfy the multi-model comparison requirement, we developed and tuned two distinct classification paradigms:

1. **Regularized Logistic Regression (Linear Baseline)**:
- Optimized with L_2 penalty to control multicollinearity and stabilize weight estimates.
- Tuned hyperparameter: Inverse regularization strength $C \in [0.01, 0.1, 1.0, 5.0, 10.0]$ with `liblinear` and `lbfgs` solvers.

2. **Random Forest Classifier (Non-Linear Ensemble)**:
- Bagging ensemble of decision trees with bootstrap aggregation.
- Tuned hyperparameters: `n_estimators` $\in [50, 100, 200]$, `max_depth` $\in [4, 6, 8, \text{None}]$, `min_samples_split` $\in [2, 4, 8]$, and `class_weight` $\in [\text{balanced}, \text{None}]$.

5.2 5-Fold Stratified Cross-Validation & Test Benchmarks

Metric	Logistic Regression ($C=5.0$, `liblinear`)	Tuned Random Forest ($N=100$, `split=4`)	Clinical Importance
5-Fold CV ROC-AUC	**0.9029 ± 0.038**	**0.9073 ± 0.041**	Cross-validation stability across folds
Held-Out Test Accuracy	**86.89%**	**88.52%**	Overall correct triage percentage
Held-Out Test Precision	**83.33%**	**83.87%**	Minimizing false positives (unnecessary catheterizations)
Held-Out Test Recall (Sensitivity)	**89.29%**	**92.86%**	**Critical**: Minimizing missed cardiac cases (false negatives)
Held-Out Test F1-Score	**0.8621**	**0.8814**	Harmonic mean of precision and recall
Held-Out Test ROC-AUC	**0.9621**	**0.9416**	Discrimination capability across all decision thresholds

5.3 Comparative ROC Curves & Confusion Matrices






Figure 5: Comparative ROC Curves on the held-out test set demonstrating Logistic Regression ($AUC=0.9621$) outperforming Random Forest ($AUC=0.9416$).

Logistic Regression Confusion Matrix	Random Forest Confusion Matrix
	
28 True Negatives, 5 False Positives, 3 False Negatives, 25 True Positives	*28 True Negatives, 5 False Positives, 2 False Negatives, 26 True Positives*

5.4 Champion Model Selection Rationale

While Random Forest achieved marginally higher raw test accuracy (88.52% vs 86.89%) and recall (92.86% vs 89.29%), **Logistic Regression achieved a superior ROC-AUC of 0.9621** and provides linear explainability essential for clinical auditability. The pipeline serializes the champion model artifact (`best_model.joblib`) for zero-overhead inference.

---

6. Experiment Tracking & Model Governance with MLflow


6.1 Local SQLite Tracking Store Architecture

Rather than relying on ephemeral directory tracking, our system configures a durable SQLite backend store (`sqlite:///mlflow.db`). This supports concurrent run execution, metric comparison, and artifact versioning:

```
mlflow.set_tracking_uri(f"sqlite:///{DB_PATH}")
mlflow.set_experiment("heart-disease-uci-experiment")
```

6.2 MLflow Dashboard & Run Telemetry

Every candidate model run captures:
1. **Hyperparameters**: Regularization coefficient C, solver, tree depth, sample splits, estimator count.
2. **Cross-Validation Metrics**: K-fold mean ROC-AUC and standard deviation.
3. **Test Partition Metrics**: Accuracy, Precision, Recall, F1-Score, ROC-AUC.
4. **Visual Artifacts**: Confusion matrix plots, ROC curves, comparative benchmark figures.
5. **Model Binary**: Pinned Scikit-Learn model package with conda dependencies and cloudpickle signature.



Screenshot 1: MLflow UI dashboard displaying candidate model runs (`Logistic_Regression_L2`, `Random_Forest_Tuned`) with recorded validation and test metrics.


---

7. CI/CD Automation & Automated Testing

7.1 Automated Pytest Suite (11 Test Cases)

To guarantee production stability before deployment, our test suite enforces strict invariants across three test modules:

1. `test_data.py` **(Data Pipeline Invariants)**:
2. Verifies conversion of multi-class targets to binary ${0, 1}$.
3. Asserts zero NaN or infinite values after `ColumnTransformer` execution.
4. Enforces presence of all 13 clinical input features.
5. `test_model.py` **(Inference & Behavioral Invariants)**:
6. Validates that output probabilities reside strictly in $[0.0, 1.0]$.
7. Validates confidence bounds and risk classification thresholds.
8. Verifies that batch predictions preserve record order and shape.
9. Asserts that omitting required clinical features raises descriptive `ValueError`.
10. `test_api.py` **(HTTP Integration & Schema Invariants)**:
11. Tests `/health` status and uptime availability.
12. Tests `/predict` with valid clinical inputs.
13. Tests Pydantic validation rejects unphysiological inputs (e.g. age $= 250$).
14. Verifies Prometheus `/metrics` scraping endpoint exposes valid OpenMetrics text.



Screenshot 2: Complete execution of the 11-test pytest validation suite passing in under 3 seconds.

7.2 GitHub Actions Workflow (`.github/workflows/ci.yml`)

The automated CI/CD pipeline triggers on every push and pull request to `main`:
1. **Stage 1 (Lint & Static Analysis)**: Runs `flake8` to catch syntax errors, undefined variables, and cyclomatic complexity violations.
2. **Stage 2 (Unit Testing)**: Executes `pytest` with JUnit XML test result reporting.
3. **Stage 3 (Model Training Smoke Test)**: Ingests raw data and executes `train.py` to confirm deterministic reproducibility.
4. **Stage 4 (Docker Build & Container Smoke Test)**: Builds the container image and queries `/health` inside the containerized environment.

---

8. Containerization & Cloud-Native Kubernetes Deployment

8.1 Multi-Stage Dockerfile Optimization

The serving container employs a multi-stage Dockerfile based on `python:3.12-slim`:
- **Builder Stage**: Installs system compilers, wheels, and requirements in `/root/.local`.
- **Runner Stage**: Copies only installed site-packages into an unprivileged user context (`appuser`, UID 1000).
- **Security Hardening**: Runs as non-root, prevents privilege escalation, and excludes build tools from the final image.
- **Image Footprint**: Optimized to $<240\text{ MB}$ compared to $>1.2\text{ GB}$ for standard Python images.




Screenshot 3: Multi-stage Docker build, unprivileged container execution, and live inference verification via curl.

8.2 Kubernetes Deployment & Resilience

The Kubernetes manifest (`k8s/deployment.yaml`) enforces:
1. **Replication**: 2 replica pods for high availability.
2. **Zero-Downtime Rolling Updates**: `maxSurge: 1`, `maxUnavailable: 0`.
3. **Health Probes**:
- `readinessProbe`: Queries `/health` every 10s to ensure traffic is only routed to warm pods.
- `livenessProbe`: Restarts deadlocked containers if `/health` fails for 3 consecutive checks.
4. **Resource Constraints**:

- CPU Request: `100m`, Limit: `500m`.
- Memory Request: `128Mi`, Limit: `512Mi`.
5. **Service Exposure**: NodePort service on `:30080` and LoadBalancer on port `80`.




Screenshot 4: Kubernetes deployment status showing dual healthy replica pods, active LoadBalancer service, and zero-downtime rollout.

---

9. Telemetry, Monitoring & Production Observability

9.1 FastAPI Interactive Documentation & Live Inference


The service exposes interactive OpenAPI Swagger documentation at `/docs` with strict Pydantic payload validation:



Screenshot 5: FastAPI Swagger interactive documentation (`/docs`) showing schema definitions and `/predict` endpoint testing.

9.2 Prometheus Metrics Instrumentation

The FastAPI application natively exports OpenMetrics telemetry at `/metrics`:
- `http_requests_total`: Counter tracking inbound requests categorized by `method`, `endpoint`, and `status_code`.
- `http_request_duration_seconds`: Histogram measuring API latency with buckets ranging from 5 ms to 2.5 seconds.
- `model_predictions_total`: Counter tracking inference volume segmented by `predicted_class` (0 vs 1) and `risk_level` (Low, Moderate, High).



```
# HELP python_gc_objects_collected_total Objects collected during gc
# TYPE python_gc_objects_collected_total counter
python_gc_objects_collected_total{generation="0"} 967.0
python_gc_objects_collected_total{generation="1"} 91.0
python_gc_objects_collected_total{generation="2"} 20.0
# HELP python_gc_objects_uncollectable_total Uncollectable objects found during GC
# TYPE python_gc_objects_uncollectable_total counter
python_gc_objects_uncollectable_total{generation="0"} 0.0
python_gc_objects_uncollectable_total{generation="1"} 0.0
python_gc_objects_uncollectable_total{generation="2"} 0.0
# HELP python_gc_collections_total Number of times this generation was collected
# TYPE python_gc_collections_total counter
python_gc_collections_total{generation="0"} 376.0
python_gc_collections_total{generation="1"} 34.0
python_gc_collections_total{generation="2"} 3.0
# HELP python_info Python platform information
# TYPE python_info gauge
python_info{implementation="CPython",major="3",minor="12",patchlevel="14",version="3.12.14"} 1.0
# HELP http_requests_total Total HTTP Requests
# TYPE http_requests_total counter
http_requests_total{endpoint="/health",method="GET",status_code="200"} 3.0
http_requests_total{endpoint="/predict",method="POST",status_code="422"} 1.0
http_requests_total{endpoint="/predict",method="POST",status_code="200"} 2.0
http_requests_total{endpoint="/metrics",method="GET",status_code="200"} 1.0
http_requests_total{endpoint="/docs",method="GET",status_code="200"} 2.0
http_requests_total{endpoint="/openapi.json",method="GET",status_code="200"} 2.0
http_requests_total{endpoint="/favicon.ico",method="GET",status_code="404"} 1.0
# HELP http_requests_created Total HTTP Requests
# TYPE http_requests_created gauge
http_requests_created{endpoint="/health",method="GET",status_code="200"} 1.7923151847472541e+09
http_requests_created{endpoint="/predict",method="POST",status_code="422"} 1.7923152119161515e+09
http_requests_created{endpoint="/predict",method="POST",status_code="200"} 1.7923152176145866e+09
http_requests_created{endpoint="/metrics",method="GET",status_code="200"} 1.7923152224899294e+09
http_requests_created{endpoint="/docs",method="GET",status_code="200"} 1.7923189248412392e+09
http_requests_created{endpoint="/openapi.json",method="GET",status_code="200"} 1.7923189253417468e+09
http_requests_created{endpoint="/favicon.ico",method="GET",status_code="404"} 1.7923189629888808e+09
# HELP http_request_duration_seconds HTTP Request Latency in Seconds
# TYPE http_request_duration_seconds histogram
http_request_duration_seconds_bucket{endpoint="/health",le="0.005"} 2.0
http_request_duration_seconds_bucket{endpoint="/health",le="0.01"} 3.0
http_request_duration_seconds_bucket{endpoint="/health",le="0.025"} 3.0
http_request_duration_seconds_bucket{endpoint="/health",le="0.05"} 3.0
http_request_duration_seconds_bucket{endpoint="/health",le="0.1"} 3.0
http_request_duration_seconds_bucket{endpoint="/health",le="0.25"} 3.0
http_request_duration_seconds_bucket{endpoint="/health",le="0.5"} 3.0
http_request_duration_seconds_bucket{endpoint="/health",le="1.0"} 3.0
http_request_duration_seconds_bucket{endpoint="/health",le="2.5"} 3.0
http_request_duration_seconds_bucket{endpoint="/health",le="+Inf"} 3.0
http_request_duration_seconds_count{endpoint="/health"} 3.0
http_request_duration_seconds_sum{endpoint="/health"} 0.009540319442749023
http_request_duration_seconds_bucket{endpoint="/predict",le="0.005"} 1.0
http_request_duration_seconds_bucket{endpoint="/predict",le="0.01"} 1.0
http_request_duration_seconds_bucket{endpoint="/predict",le="0.025"} 2.0
http_request_duration_seconds_bucket{endpoint="/predict",le="0.05"} 2.0
http_request_duration_seconds_bucket{endpoint="/predict",le="0.1"} 3.0
http_request_duration_seconds_bucket{endpoint="/predict",le="0.25"} 3.0
http_request_duration_seconds_bucket{endpoint="/predict",le="0.5"} 3.0
http_request_duration_seconds_bucket{endpoint="/predict",le="1.0"} 3.0
http_request_duration_seconds_bucket{endpoint="/predict",le="2.5"} 3.0
http_request_duration_seconds_bucket{endpoint="/predict",le="+Inf"} 3.0
http_request_duration_seconds_count{endpoint="/predict"} 3.0
http_request_duration_seconds_sum{endpoint="/predict"} 0.07905435562133789
http_request_duration_seconds_bucket{endpoint="/metrics",le="0.005"} 1.0
http_request_duration_seconds_bucket{endpoint="/metrics",le="0.01"} 1.0
http_request_duration_seconds_bucket{endpoint="/metrics",le="0.025"} 1.0
http_request_duration_seconds_bucket{endpoint="/metrics",le="0.05"} 1.0
http_request_duration_seconds_bucket{endpoint="/metrics",le="0.1"} 1.0
http_request_duration_seconds_bucket{endpoint="/metrics",le="0.25"} 1.0
http_request_duration_seconds_bucket{endpoint="/metrics",le="0.5"} 1.0
http_request_duration_seconds_bucket{endpoint="/metrics",le="1.0"} 1.0
http_request_duration_seconds_bucket{endpoint="/metrics",le="2.5"} 1.0
http_request_duration_seconds_bucket{endpoint="/metrics",le="+Inf"} 1.0
http_request_duration_seconds_count{endpoint="/metrics"} 1.0
http_request_duration_seconds_sum{endpoint="/metrics"} 0.0014376640319824219
http_request_duration_seconds_bucket{endpoint="/docs",le="0.005"} 2.0
http_request_duration_seconds_bucket{endpoint="/docs",le="0.01"} 2.0
http_request_duration_seconds_bucket{endpoint="/docs",le="0.025"} 2.0
http_request_duration_seconds_bucket{endpoint="/docs",le="0.05"} 2.0
http_request_duration_seconds_bucket{endpoint="/docs",le="0.1"} 2.0
http_request_duration_seconds_bucket{endpoint="/docs",le="0.25"} 2.0
http_request_duration_seconds_bucket{endpoint="/docs",le="0.5"} 2.0
http_request_duration_seconds_bucket{endpoint="/docs",le="1.0"} 2.0
http_request_duration_seconds_bucket{endpoint="/docs",le="2.5"} 2.0
http_request_duration_seconds_bucket{endpoint="/docs",le="+Inf"} 2.0
http_request_duration_seconds_count{endpoint="/docs"} 2.0
http_request_duration_seconds_sum{endpoint="/docs"} 0.0009837150573730469
http_request_duration_seconds_bucket{endpoint="/openapi.json",le="0.005"} 1.0
http_request_duration_seconds_bucket{endpoint="/openapi.json",le="0.01"} 1.0
http_request_duration_seconds_bucket{endpoint="/openapi.json",le="0.025"} 2.0
http_request_duration_seconds_bucket{endpoint="/openapi.json",le="0.05"} 2.0
http_request_duration_seconds_bucket{endpoint="/openapi.json",le="0.1"} 2.0
http_request_duration_seconds_bucket{endpoint="/openapi.json",le="0.25"} 2.0
http_request_duration_seconds_bucket{endpoint="/openapi.json",le="0.5"} 2.0
http_request_duration_seconds_bucket{endpoint="/openapi.json",le="1.0"} 2.0
http_request_duration_seconds_bucket{endpoint="/openapi.json",le="2.5"} 2.0
http_request_duration_seconds_bucket{endpoint="/openapi.json",le="+Inf"} 2.0
http_request_duration_seconds_count{endpoint="/openapi.json"} 2.0
http_request_duration_seconds_sum{endpoint="/openapi.json"} 0.011897087097167969
http_request_duration_seconds_bucket{endpoint="/favicon.ico",le="0.005"} 1.0
http_request_duration_seconds_bucket{endpoint="/favicon.ico",le="0.01"} 1.0
http_request_duration_seconds_bucket{endpoint="/favicon.ico",le="0.025"} 1.0
http_request_duration_seconds_bucket{endpoint="/favicon.ico",le="0.05"} 1.0
http_request_duration_seconds_bucket{endpoint="/favicon.ico",le="0.1"} 1.0
http_request_duration_seconds_bucket{endpoint="/favicon.ico",le="0.25"} 1.0
http_request_duration_seconds_bucket{endpoint="/favicon.ico",le="0.5"} 1.0
http_request_duration_seconds_bucket{endpoint="/favicon.ico",le="1.0"} 1.0
http_request_duration_seconds_bucket{endpoint="/favicon.ico",le="2.5"} 1.0
http_request_duration_seconds_bucket{endpoint="/favicon.ico",le="+Inf"} 1.0
http_request_duration_seconds_count{endpoint="/favicon.ico"} 1.0
http_request_duration_seconds_sum{endpoint="/favicon.ico"} 0.0005207061767578125
# HELP http_request_duration_seconds_created HTTP Request Latency in Seconds
# TYPE http_request_duration_seconds_created gauge
http_request_duration_seconds_created{endpoint="/health"} 1.7923151847477667e+09
http_request_duration_seconds_created{endpoint="/predict"} 1.7923152119161515e+09
http_request_duration_seconds_created{endpoint="/metrics"} 1.7923152224899294e+09
http_request_duration_seconds_created{endpoint="/docs"} 1.7923189248412392e+09
http_request_duration_seconds_created{endpoint="/openapi.json"} 1.7923189253417468e+09
http_request_duration_seconds_created{endpoint="/favicon.ico"} 1.7923189629888808e+09
# HELP model_predictions_total Total Predictions by Class
# TYPE model_predictions_total counter
model_predictions_total{predicted_class="1",risk_level="High"} 2.0
# HELP model_predictions_created Total Predictions by Class
# TYPE model_predictions_created gauge
model_predictions_created{predicted_class="1",risk_level="High"} 1.7923152176140313e+09
```

Screenshot 6: Prometheus OpenMetrics scraping endpoint (`/metrics`) displaying real-time request counts and latency histograms.

9.3 Structured JSON Audit Logging

Every HTTP interaction logs a structured payload including timestamp, HTTP verb, endpoint, client IP, unique `X-Request-ID` , and duration in milliseconds, fulfilling clinical audit requirements.

10. Conclusion & Reproducibility Verification

This project demonstrates a complete, robust, and reproducible MLOps lifecycle. From automated ingestion of the UCI Heart Disease dataset through MLflow experiment tracking, containerization, and Kubernetes orchestration, every operational requirement has been rigorously validated.

Summary Checklist of Mandatory Deliverables

- [x] UCI Heart Disease ingestion and data cleaning script (`src/download_data.py` , `src/data_prep.py`)
- [x] Publication-grade EDA figures in `report/figures/` (Class balance, Correlation, Numerical distributions, Boxplots)
- [x] Logistic Regression (L_2) and Tuned Random Forest with 5-fold Stratified CV
- [x] Full MLflow experiment tracking with SQLite backend (`mlflow.db`)
- [x] Serialized pipeline artifact (`artifacts/best_model.joblib`)
- [x] 11 Automated Pytest unit and integration tests (100% passing)
- [x] GitHub Actions CI/CD workflow (`.github/workflows/ci.yml`)
- [x] Multi-stage, unprivileged Dockerfile and `docker-compose.yml`
- [x] Kubernetes deployment and service manifests (`k8s/deployment.yaml` , `k8s/service.yaml`)
- [x] Prometheus `/metrics` export and Prometheus + Grafana monitoring compose stack
- [x] Complete technical report with 9 figures, 6 screenshots, and 5-minute video recording script