



Reference Configuration - Rancher Kubernetes Engine

SUSE Linux Enterprise Server 15-SP2, Rancher
Kubernetes Engine 1.2.9

Reference Configuration - Rancher Kubernetes Engine: Including integration content from Supermicro

SUSE Linux Enterprise Server 15-SP2, Rancher Kubernetes Engine 1.2.9

The purpose of this document is to provide an overview and procedure of implementing SUSE (R) and partner offerings for Rancher Kubernetes Engine (RKE), a Kubernetes distribution that runs entirely within containers on bare-metal and virtualized nodes. RKE solves the problem of installation complexity and the operation is both simplified and easily automated, while entirely accommodating the operating system and platform it is running on.

Disclaimer: The articles and individual documents published in the SUSE Best Practices series were contributed voluntarily by SUSE employees and by third parties. If not stated otherwise inside the document, the articles are intended only to be one example of how a particular action could be taken. Also, SUSE cannot verify either that the actions described in the articles do what they claim to do or that they do not have unintended consequences. All information found in this article has been compiled with utmost attention to detail. However, this does not guarantee complete accuracy. Therefore, we need to specifically state that neither SUSE LLC, its affiliates, the authors, nor the translators may be held liable for possible errors or the consequences thereof.

Publication Date: 2021-06-15

SUSE LLC

1800 South Novell Place

Provo, UT 84606

USA

<https://documentation.suse.com> ↗

Contents

1	Introduction	1
1.1	Motivation	1
1.2	Scope	2
1.3	Audience	2
2	Business aspect	3
2.1	Business problem	3
2.2	Business value	4
3	Architectural overview	6
3.1	Solution architecture	6
4	Component model	8
4.1	Component overview	8
4.2	Software - Rancher Kubernetes Engine	8
4.3	Software - SUSE Linux Enterprise Micro	10
4.4	Compute Platform	11
5	Deployment	12
5.1	Deployment overview	12
5.2	Compute Platform	12
	SYS-120C-TN10R Rack Servers	12 • SYS-620C-TN12R Rack Servers 14
5.3	SUSE Linux Enterprise Server	15
5.4	Rancher Kubernetes Engine	17

6 Summary 23

7 References 24

Glossary 26

A Appendix 29

A.1 Compute Platform Bill of Materials 29

A.2 Software Bill of Materials 32

A.3 Documentation Configuration / Attributes 34

8 Legal Notice 35

9 GNU Free Documentation License 36

1 Introduction

On the digital transformation journey to a full cloud native landscape, utilization of microservices becomes the main approach with the dominant technology for such container orchestration being Kubernetes¹ With its large community of developers and abundant features and capabilities, Kubernetes has become the defacto standard and is included across most container-as-a-service platforms. With all of these technologies in place, both developer and operation teams can effectively deploy, manage and deliver functionality to their end users in a resilient and agile manner.

1.1 Motivation

As developers and organizations continue their journey from simple, containerized microservices towards having these workloads orchestrated and deployed where ever they need, being able to install, monitor and use such Kubernetes infrastructures is a core need. Such deployments, being Cloud Native Computing Foundation (CNCF²) conformant and certified³ are essential for both development and production workloads.

Solving common frustrations around installation complexity, Rancher Kubernetes Engine reduces many host dependencies and provides a stable path for deployment, upgrades, and roll-backs for core use cases.

Once on such a digital transformation journey, some of the next focus areas are:

- Compute Platform

¹ <https://kubernetes.io/> ↗

² <https://www.cncf.io/> ↗

³ <https://www.cncf.io/certification/software-conformance> ↗

- To optimize availability, performance, scalability and integrity, assess current system platforms or acquire and utilize new variations from:
 - Independent Hardware Vendors (IHV), such as Supermicro (<https://www.supermicro.com/en>)  ® , as the platform for physical, baremetal, hypervisors and virtual machines

1.2 Scope

The scope of this document is to provide a layered *reference configuration* for Rancher Kubernetes Engine. This can be done in a variety of scenarios to create an enterprise Kubernetes cluster deployment anywhere.

1.3 Audience

This document is intended for IT decision makers, architects, system administrators and technicians who are implementing a flexible, software-defined Kubernetes platform. One should still be familiar with the traditional IT infrastructure pillars — networking, computing and storage — along with the local use cases for sizing, scaling and limitations within each pillars' environments.

2 Business aspect

Agility is driving developers toward more cloud native methodologies that focus on microservices architectures and streamlined workflows. Container technologies, like Kubernetes, embody this agile approach and help enable cloud native transformation.

By unifying IT operations with Kubernetes, organizations realize key benefits like increased reliability, improved security and greater efficiencies with standardized automation. Therefore, Kubernetes infrastructure platforms are adopted by enterprises to deliver:

Cluster Operations

Improved Production and DevOps efficiencies with simplified cluster usage and robust operations

Security Policy & User Management

Consistent security policy enforcement plus advanced user management on any Kubernetes infrastructure

Access to Shared Tools & Services

A high level of reliability with easy, consistent access to a broad set of tools and services

2.1 Business problem

Many organizations are deploying Kubernetes clusters everywhere – in the cloud, on-premises, and at the edge - to unify IT operations. Such organizations can realize dramatic benefits, including:

- Consistently deliver a high level of reliability on any infrastructure
- Improve DevOps efficiency with standardized automation
- Ensure enforcement of security policies on any infrastructure

However, simply relying on upstream Kubernetes alone can introduce extra overhead and risk because Kubernetes clusters are typically deployed:

- Without central visibility
- Without consistent security policies
- And must be managed independently

Deploying a scalable kubernetes infrastructure requires consideration of a larger ecosystem, encompassing many software and infrastructure components and providers. Further, the ability to continually address the needs and concerns of:

Developers

For those who just focus on writing code to build their apps securely using a preferred workflow, providing a simple, push-button deployment mechanism of their containerized workloads where needed.

IT Operators

General infrastructure requirements still rely upon traditional IT pillars are for the stacked, underlying infrastructure. Ease of deployment, availability, scalability, resiliency, performance, security and integrity are still core concerns to be addressed for administrative control and observability.

Beyond just the core infrastructure software layers of managed Kubernetes clusters, organizations may be also be impacted by:

Compute Platform

Potential inconsistencies and impacts of multiple target system platforms for the distributed deployments of the cluster elements, across:

- physical, baremetal, hypervisors and virtual machines

2.2 Business value

With Rancher Kubernetes Engine, the operation of Kubernetes is easily automated and entirely independent of the operating system and platform running. Using a supported version of the container runtime engine, one can deploy and run Kubernetes with Rancher Kubernetes Engine. It builds a cluster from a single command in just a few minutes, and its declarative configuration makes Kubernetes upgrades atomic and safe.

By allowing operation teams to focus on infrastructure and developers to deploy code the way they want too, SUSE and the Rancher offerings helps bring products to market faster and accelerate an organization's digital transformation.

SUSE Rancher is a fundamental part of the complete software stack for teams adopting containers. It provides DevOps teams with integrated tools for running containerized workloads while also addressing the operational and security challenges of managing multiple Kubernetes clusters across any targeted infrastructure.

Developers

SUSE Rancher makes it easy to securely deploy containerized applications no matter where the Kubernetes infrastructure runs — in the cloud, on-premises, or at the edge. Using Helm or the App Catalog to deploy and manage applications across any or all these environments, ensuring multi-cluster consistency with a single deployment process.

IT Operators

SUSE Rancher not only deploys and manages production-grade Kubernetes clusters from datacenter to cloud to the edge, it also unites them with centralized authentication, access control and observability. Further, it streamlines cluster deployment on bare metal or virtual machines and maintains them using defined security policies.

With this increased consistency of the managed Kubernetes infrastructure clusters, organizations benefit from an even higher level of the Cloud Native Computing model where each layer only relies upon the API and version of the adjacent layer. For example:

Supermicro is a leading innovator of server and storage solutions. By developing and using a Building Block approach, Supermicro can bring cutting edge solutions to market faster with our partners faster than other suppliers. Supermicro has a wide range of servers which are optimized for various workloads. Customers are able to take advantage of the latest technologies sooner, and with less impact on the environment through the Supermicro resource saving architecture. The Supermicro product line ranges from small, low power systems for the Edge, to larger multiprocessor systems in the data center.

3 Architectural overview

This section outlines the core elements of the Rancher Kubernetes Engine solution, along with the suggested target platforms and components.

3.1 Solution architecture

The figure below illustrates the high-level architecture of Rancher Kubernetes Engine:



FIGURE 3.1: ARCHITECTURE OVERVIEW - RANCHER KUBERNETES ENGINE

FixMe-Authentication Proxy

A user is authenticated via Rancher Kubernetes Engine and then, if authorized, can access both the Rancher Kubernetes Engine environment and the downstream clusters and workloads.

FixMe-API Server

This provides the programmatic interface backend for user, command-line interactions with Rancher Kubernetes Engine and the managed clusters.

FixMe-Data Store

The purpose of this service is to capture the configuration and state of Rancher Kubernetes Engine and the managed clusters to aid in backup and recovery processes.

FixMe-Cluster Controller

Interacting with a cluster agent on the downstream cluster, the cluster controller allows the communication path for users and services to leverage for workloads and cluster management.

FixMe-Once setup, users can potentially interact with Rancher Kubernetes Engine through the web-based user interface (UI), the command-line interface (CLI), and programatically through the application programming interface (API). Depending upon the assigned roles, group membership and privileges, a user could:

- manage all clusters, users, roles, projects
- deploy new clusters, import other clusters, or remove existing ones
- manage workloads across respective or labeled clusters
- simply view clusters or workloads, or just benefit from what is running

FixMe-For the best performance and security, the recommended deployment is a dedicated Kubernetes cluster for the Rancher management server. Running user workloads on this cluster is not advised. After deploying Rancher, you can create or import clusters for running workloads.

FixMe-NOTE: Regardless of the deployment target, Rancher Kubernetes Engine should always run on a node or cluster that is separate from the downstream clusters that it manages. Running user workloads on this cluster is not advised.

4 Component model

FixMe-This section describes the various components being used to create a Rancher Kubernetes Engine deployment, in the perspective of top to bottom ordering. Once completed, the Rancher Kubernetes Engine instance enables the management of multiple Kubernetes clusters, as shown in the following figure:

4.1 Component overview

By utilizing:

- Kubernetes Platform - Rancher Kubernetes Engine
- Operating System - `ifdef::iSLES[SUSE Linux Enterprise Server] ifdef::iSLEMicro[SUSE Linux Enterprise Micro]`
- Compute Platform

one can create the necessary infrastructure and services. Further details for these components are described in the following sections.

4.2 Software - Rancher Kubernetes Engine

FixMe-Rancher Kubernetes Engine is packaged as a single binary, which is about 50 megabytes in size. Bundled in that single binary is everything needed to run Kubernetes anywhere, including low-powered IoT and Edge-based devices. The binary includes:

- the container runtime
- any important host utilities like
 - iptables, socat and du.

FixMe-The only OS dependencies are the Linux kernel itself and a proper dev, proc and sysfs mounts (this is done automatically on all modern Linux distributions). `{pn_K3s}` bundles the Kubernetes components:

- kube-apiserver,
- kube-controller-manager,

- kube-scheduler,
- kubelet and
- kube-proxy

into combined processes that are presented as a simple server and agent model, as represented in the following figure:



FIGURE 4.1: FIXME-OVERVIEW OF RANCHER KUBERNETES ENGINE

Rancher Kubernetes Engine can run as a complete cluster on a single node or can be expanded into a multi-node cluster. Besides the core Kubernetes components, these are also included:

- containerd,
- Flannel,
- CoreDNS,
- ingress controller and
- a simple host port-based service load balancer.

FixMe-All of these components are optional and can be swapped out for your implementation of choice. With these included components, you get a fully functional and CNCF-conformant cluster so you can start running apps right away. Rancher Kubernetes Engine is now a CNCF Sandbox project, being the first Kubernetes distribution ever to be adopted into sandbox.

Learn more information about Rancher Kubernetes Engine at <https://rancher.com/docs/rke/latest/en/>.

As Rancher Kubernetes Engine relies upon being deployed on a Kubernetes platform, the next section describes such a suggested component layer.

4.3 Software - SUSE Linux Enterprise Micro

SUSE Linux Enterprise Micro combines the assurance of enterprise-grade security and compliance with the immutability and portability of a modern, lightweight operating system. The top 4 features are:

Immutable OS

Immutable design ensures the OS is not altered during runtime and runs reliably every single time. Security signed and verified transactional updates are easy to rollback if things go wrong.

Security and Compliance

Fully open source and built using open standards, SUSE Linux Enterprise Micro leverages SUSE Linux Enterprise common code base, to provide FIPS 140-2, DISA SRG/STIG, integration with CIS and Common Criteria certified configurations. Includes fully supported security framework (SELinux) with policies.

Architectural Flexibility

Both Arm and x86-64 architectures are supported so you can deploy edge applications with confidence across multiple architectures.

Kubernetes-Ready

You can easily combine SUSE Linux Enterprise Micro with the latest cloud-native technologies including SUSE Rancher, Rancher Kubernetes Engine, Longhorn persistent block storage, and K3s, the world's most popular Kubernetes distribution for use in low resource, distributed edge locations.

As a result, you get an ultra-reliable infrastructure platform that is also simple to use and comes out-of-the-box with best-in-class compliance. Furthermore, SUSE's flexible subscription model ensures enterprise assurance for any edge, embedded or IoT deployment without vendor lock-in. A free, evaluation copy can be [downloaded \(https://www.suse.com/download/sle-micro/\)](https://www.suse.com/download/sle-micro/) or if the organization already has subscriptions, both install media and updates can be obtained from [SUSE Customer Center \(https://scc.suse.com/login\)](https://scc.suse.com/login).

With the flexibility of SUSE Linux Enterprise Micro, multiple compute platform variants can be considered, as outlined in the next section.

4.4 Compute Platform

Leveraging the enterprise grade functionality of the operating system mentioned in the previous section, many compute platforms can be the foundation of the deployment:

Supermicro servers take advantage of the latest CPU technologies available. The new servers have been shown to produce more work per watt than ever before. Thus, additional workloads can not only be performed in less time, but at a lower cost as well. Supermicro systems can support up to 6TB of memory per socket.



Note

A sample bill of materials, in the [Appendix A, Appendix](#), cites the necessary quantities of all components, along with a reference to the minimum resource requirements needed by the software components.

5 Deployment

This section describes the process steps for the deployment of the Rancher Kubernetes Engine solution. It describes the process steps to deploy each of the component layers starting as a base functional *proof-of-concept*, having considerations on migration towards *production*, providing *scaling* guidance that is needed to create the solution.

5.1 Deployment overview

The deployment stack is represented in the following figure:



FIGURE 5.1: SUSE RANCHER DEPLOYMENT STACK

and details are covered for each layer in the following sections.



Note

The following section's content is ordered and described from the bottom layer up to the top.

5.2 Compute Platform

5.2.1 SYS-120C-TN10R Rack Servers

<https://www.supermicro.com/en/products/system/Cloud/1U/SYS-120C-TN10R> 

ULTIMATE FLEXIBILITY

- CPU: Up to 270W and 40 cores
- Memory: 4TB DDR4-3200 memory in 16 DIMM slots w/ support of Intel Optane PMEM 200 series

- Storage: Up to 10x all hybrid drive bays (NVMe/SAS/SATA) + Flexible internal storage options (dual NVMe M.2 / SATADOM)
- Expansion: Up to 2 standard PCIe 4.0 FHHL expansion slots + 2 AIOM for OCP 3.0 NIC; Building block solution for different applications and environment
- 860W Platinum level redundant PWS

EFFICIENT AND COST-EFFECTIVE

- Cost optimized for large volume deployment
- Tool-less mechanical design for rapid deployment
- Hot-swap storage and PWS for easy maintenance.
- IPMI, serial port and service tag for easy management

COMPACT

- Compact system design makes no waste of internal space
- < 600mm chassis depth
- Fully utilized system resource with 12 NVMe, 4 PCIe 4.0 x16 + 2 PCIe 4.0 x8 expansion

SECURE

- Security is top priority
- TPM 1.2/2.0, signed firmware, Silicon Root of Trust
- Secure Boot, System Erase
- FIPS Compliance, Trusted Execution Environment

APPLICATION READY

- Balanced architecture between CPUs and optimized for scalable compute, database, GPU, tiered storage and I/O intensive applications
- Support open standards like OpenBMC and OCP 3.0

KEEP IT GREEN

- Optimized thermal design
- High efficiency Platinum level PWS (AC/DC)
- Reduced waste with bulk packaging and customizable accessories

5.2.2 SYS-620C-TN12R Rack Servers

<https://www.supermicro.com/en/products/system/Cloud/2U/SYS-620C-TN12R> 

ULTIMATE FLEXIBILITY

- CPU: Up to 270W and 40 cores
- Memory: 4TB DDR4-3200 memory in 16 DIMM slots w/ support of Intel Optane PMEM 200 series
- Storage: Up to 12 all hybrid drive bays (NVMe/SAS/SATA) + Flexible internal storage options (dual NVMe M.2 / SATADOM)
- Expansion: Up to 6 standard PCIe 4.0 expansion slots + 2 AIOM for OCP 3.0 NIC; Up to 2 FHFL DW GPUs or 6 LP GPUs
- Building block solution for different applications and environment
- 1200W Titanium level redundant PWS

EFFICIENT AND COST-EFFECTIVE

- Cost optimized for large volume deployment
- Tool-less mechanical design for rapid deployment
- Hot-swap storage and PWS for easy maintenance.
- IPMI, serial port and service tag for easy management

COMPACT

- Compact system design makes no waste of internal space
- < 650mm chassis depth
- Fully utilized system resource with 12 NVMe, 4 PCIe 4.0 x16 + 2 PCIe 4.0 x8 expansion

SECURE

- Security is top priority
- TPM 1.2/2.0, signed firmware, Silicon Root of Trust
- Secure Boot, System Erase
- FIPS Compliance, Trusted Execution Environment

APPLICATION READY

- Balanced architecture between CPUs and optimized for scalable compute, database, GPU, tiered storage and I/O intensive applications
- Cost and performance optimized down to component level
- Support open standards like OpenBMC and OCP 3.0


WE KEEP IT GREEN

- Optimized thermal design
- High efficiency Titanium level PWS (AC/DC)
- Reduced waste with bulk packaging and customizable accessories

5.3 SUSE Linux Enterprise Server

Utilize an enterprise-grade Linux operating system , like SUSE Linux Enterprise Server, as the base software layer.

Preparation(s)

To meet the solution stack prerequisites and requirements, SUSE operating system offerings, like [SUSE Linux Enterprise Server \(https://www.suse.com/products/server/\)](https://www.suse.com/products/server/)  can be utilized.

1. Ensure these services are in place and configured for this node to use:

- Domain Name Service (DNS) - an external network-accessible service to map IP Addresses to hostnames
- Network Time Protocol (NTP) - an external network-accessible service to obtain and synchronize system times to aid in timestamp consistency
- Software Update Service - access to a network-based repository for software update packages. This can be accessed directly from each node via registration to

- the general, internet-based [SUSE Customer Center \(https://scc.suse.com/login\)](https://scc.suse.com/login) (SCC) or
- an organization's [SUSE Manager \(https://www.suse.com/products/suse-manager/\)](https://www.suse.com/products/suse-manager/) infrastructure or
- a local server running an instance of [Repository Mirroring Tool \(https://documentation.suse.com/sles/15-SP2/single-html/SLES-rmt/#book-rmt\)](https://documentation.suse.com/sles/15-SP2/single-html/SLES-rmt/#book-rmt) (RMT)



Note

During the node's installation, it can be pointed to the respective update service. This can also be accomplished post-installation with the command-line tool named [SUSEConnect \(https://www.suse.com/support/kb/doc/?id=000018564\)](https://www.suse.com/support/kb/doc/?id=000018564).

Deployment Process

On the compute platform node, install the noted SUSE operating system, by following these steps:

Deployment Consideration(s)

To further optimize deployment factors, leverage the following practices:

- *Automation*
 - To reduce user intervention, unattended deployments of SUSE Linux Enterprise Micro can be automated

- for ISO-based installations, by referring to the [AutoYaST Guide](https://documentation.suse.com/sle-micro/5.0/single-html/SLE-Micro-autoyast/#book-autoyast) (<https://documentation.suse.com/sle-micro/5.0/single-html/SLE-Micro-autoyast/#book-autoyast>) ↗
- for raw-image based installation, by configuring the Ignition and Combustion tooling as described in the [Installation Quick Start](https://documentation.suse.com/sle-micro/5.0/single-html/SLE-Micro-installation/#article-installation) (<https://documentation.suse.com/sle-micro/5.0/single-html/SLE-Micro-installation/#article-installation>) ↗

5.4 Rancher Kubernetes Engine

Utilize an enterprise-grade Linux operating system , like SUSE Linux Enterprise Server, as the base software layer.

Preparation(s)

To meet the solution stack prerequisites and requirements, SUSE operating system offerings, like [SUSE Linux Enterprise Server](https://www.suse.com/products/server/) (<https://www.suse.com/products/server/>) ↗ can be utilized.

1. Ensure these services are in place and configured for this node to use:

- Domain Name Service (DNS) - an external network-accessible service to map IP Addresses to hostnames
- Network Time Protocol (NTP) - an external network-accessible service to obtain and synchronize system times to aid in timestamp consistency
- Software Update Service - access to a network-based repository for software update packages. This can be accessed directly from each node via registration to

- the general, internet-based [SUSE Customer Center \(https://scc.suse.com/login\)](https://scc.suse.com/login) (SCC) or
- an organization's [SUSE Manager \(https://www.suse.com/products/suse-manager/\)](https://www.suse.com/products/suse-manager/) infrastructure or
- a local server running an instance of [Repository Mirroring Tool \(https://documentation.suse.com/sles/15-SP2/single-html/SLES-rmt/#book-rmt\)](https://documentation.suse.com/sles/15-SP2/single-html/SLES-rmt/#book-rmt) (RMT)



Note

During the node's installation, it can be pointed to the respective update service. This can also be accomplished post-installation with the command-line tool named [SUSEConnect \(https://www.suse.com/support/kb/doc/?id=000018564\)](https://www.suse.com/support/kb/doc/?id=000018564).

Deployment Process

The primary steps for deploying this Rancher Kubernetes Engine Kubernetes are:



Note

Installing Rancher Kubernetes Engine requires a client system (i.e. admin workstation) that has been configured with kubectl.

1. Download the Rancher Kubernetes Engine binary according to the instructions on product [documentation \(https://rancher.com/docs/rke/latest/en/\)](https://rancher.com/docs/rke/latest/en/) page, then follow the directions on that page, but with the following exceptions:
2. Create the cluster.yml file with the command `rke config`



Note

See product documentation for [example-yamls \(https://rancher.com/docs/rke/latest/en/example-yamls/\)](https://rancher.com/docs/rke/latest/en/example-yamls/) and [config-options \(https://rancher.com/docs/rke/latest/en/config-options/\)](https://rancher.com/docs/rke/latest/en/config-options/) for detailed examples and descriptions of the cluster.yml parameters.

- It is recommended to create a unique SSH key for this Rancher Kubernetes Engine cluster with the command `ssh-keygen`
 - Provide the path to that key for the option "Cluster Level SSH Private Key Path"
 - The option "Number of Hosts" refers to the number of hosts to configure at this time
 - Additional hosts can be added very easily after Rancher Kubernetes Engine cluster creation
 - For this implementation it is recommended to configure one or three hosts
 - Give all hosts the roles of "Control Plane", "Worker", and "etcd"
 - Answer "n" for the option "Enable PodSecurityPolicy"
3. Update the `cluster.yml` file before continuing with the step "Deploying Kubernetes with RKE"
 4. If a load balancer has been deployed for the Rancher Kubernetes Engine control-plane nodes, update the `cluster.yml` file before deploying Rancher Kubernetes Engine to include the IP address or FQDN of the load balancer. The appropriate location is under `authentication.sans`. For example:

```
authentication:
  strategy: x509
  sans: ["rancher.susealliances.com"]
```

5. Verify password-less SSH is available from the admin workstation to each of the cluster hosts as the user specified in the `cluster.yml` file
6. When ready, run `rke up` to create the RKE cluster
7. After the `rke up` command completes, the RKE cluster will continue the Kubernetes installation process

- Monitor the progress of the installation:
 - Export the variable KUBECONFIG to the absolute pathname of the kube_config_cluster.yml file. I.e. `export KUBECONFIG=~/.rke-cluster/kube_config_cluster.yml`
 - Run the command: `watch -c "kubectl get deployments -A"`
 - The cluster deployment is complete when elements of all the deployments show at least "1" as "AVAILABLE"
 - Use Ctrl+c to exit the watch loop after all deployment pods are running



Tip

To address *Availability* and possible *scaling* to a multiple node cluster, etcd is enabled instead of using the default SQLite datastore.

Deployment Consideration(s)

To further optimize deployment factors, leverage the following practices:

- *Availability*
 - A full high-availability Rancher Kubernetes Engine cluster is recommended for production workloads. For this use case, two additional hosts should be added; for a total of three. All three hosts will perform the roles of control-plane, etcd, and worker.
 1. Deploy the same operating system on the new compute platform nodes, and prepare them in the same way as the first node
 2. Update the cluster.yml file to include the additional node
 - Using a text editor, copy the information for the first node (found under the "nodes:" section)

- The node information usually starts with "- address:" and ends with the start of another node entry, or the beginning of the "services: " section, i.e.

```
- address: 172.16.240.71
  port: "22"
  internal_address: ""
  role:
    - controlplane
    - worker
    - etcd

. . .

labels: {}
taints: []
```

- Paste the information into the same section, once for each additional host
 - Update the pasted information, as appropriate, for each additional host
3. When the cluster.yml file is updated with the information specific to each node, run the command rke up
- Run the command: watch -c "kubectl get deployments -A"

- The cluster deployment is complete when elements of all the deployments show at least "1" as "AVAILABLE"
- Use Ctrl + c to exit the watch loop after all deployment pods are running

After this successful deployment of the Rancher Kubernetes Engine solution, review the [product documentation \(https://rancher.com/docs/rke/latest/en/\)](https://rancher.com/docs/rke/latest/en/) for details on how to directly utilize this Kubernetes cluster. Furthermore, by reviewing the SUSE Rancher [product documentation \(https://rancher.com/docs/rancher/v2.5/en/\)](https://rancher.com/docs/rancher/v2.5/en/) this solution can also be:

- imported (refer to sub-section "Importing Existing Clusters"), then
- managed (refer to sub-section "Cluster Administration") and
- accessed (refer to sub-section "Cluster Access") to address orchestration of workloads, maintaining security and many more functions are readily available.

6 Summary

Using components and offerings from SUSE and the Rancher portfolio streamlines the ability to quickly and effectively engage in a digital transformation, taking advantage of cloud native resources and disciplines. Using such technology approaches lets you deploy and leverage transformations of infrastructure into a durable, reliable enterprise-grade environment.

Simplify

Simplify and optimize your existing IT environments

- FixMe-Using Rancher Kubernetes Engine enables you to simplify Kubernetes cluster deployment and management of the the infrastructure components.

Modernize

Bring applications and data into modern computing

- FixMe-With Rancher Kubernetes Engine, the digital transformation to containerized applications can benefit from the ability both to manage many target clusters, for each of the respective user bases and to facilitate the actual workload deployments.

Accelerate

Accelerate business transformation through the power of open source software

- FixMe-Given the open source nature of Rancher Kubernetes Engine and the underlying software components, you can simplify management and make significant IT savings as you scale orchestrated, microservice deployments anywhere you need to and for whatever use cases are needed in an agile and innovative way.

7 References

WHITE PAPERS

- A Buyer's Guide to Enterprise Kubernetes Management Platforms - <https://info.rancher.com/enterprise-kubernetes-management-buyers-guide> ↗
- How to Build an Enterprise Kubernetes Strategy - <https://info.rancher.com/how-to-build-enterprise-kubernetes-strategy> ↗

BOOKS

- Kubernetes Management - <https://info.rancher.com/kubernetes-management-for-dummies-rancher-and-suse-0-0> ↗

TRAINING

- SUSE - <https://training.suse.com/> ↗
- Rancher - <https://rancher.com/training/> ↗

WEBSITES

- SUSE - <https://www.suse.com> ↗
- SUSE Customer Center (SCC) - <https://scc.suse.com/login> ↗
- Products
 - SUSE Rancher - <https://rancher.com/products/rancher/> ↗ (documentation (<https://rancher.com/docs/rancher/v2.5/en/>) ↗)
 - Rancher Kubernetes Engine (RKE) - <https://rancher.com/products/rke/> ↗ (documentation (<https://rancher.com/docs/rke/latest/en/>) ↗)
 - K3s - <https://rancher.com/products/k3s/> ↗ (documentation (<https://rancher.com/docs/k3s/latest/en/>) ↗)
 - SUSE Linux Enterprise Micro (SLEMicro) - <https://www.suse.com/products/micro/> ↗ (documentation (<https://documentation.suse.com/sle-micro/5.0/>) ↗)
 - SUSE Linux Enterprise Server (SLES) - <https://www.suse.com/products/server/> ↗ (documentation (<https://documentation.suse.com/sles/15-SP2/>) ↗)

- SUSE Manager - <https://www.suse.com/products/suse-manager/>  (documentation (<https://documentation.suse.com/suma/4.2/>) )
- SUSE Repository Mirroring Tool (RMT) - <https://www.suse.com/products/server/>  (documentation (<https://documentation.suse.com/sles/15-SP2/single-html/SLES-rmt/#book-rmt>) )
- Projects
 - Rancher Kubernetes Engine Government (RKE2) - <https://github.com/rancher/rke2>  (documentation (<https://docs.rke2.io/>) )

Glossary

- Document Scope

Reference Configuration

A guide with the basic steps to deploy the layered stack of components from both the SUSE and partner portfolios. This is considered a fundamental basis to demonstrate a specific, tested configuration of components.

Reference Architectures ¹

A guide with the general steps to deploy and validate the structured solution components from both the SUSE and partner portfolios. This provides a shareable template of consistency for consumers to leverage for similar production ready solutions, including design considerations, implementation suggestions and best practices.

Best Practice

Information that can overlap both the SUSE and partner space. It can either be provided as a standalone guide that provides reliable technical information not covered in other product documentation, based on real-life installation and implementation experiences from subject matter experts or complementary, embedded sections within any of the above documentation types describing considerations and possible steps forward.

- Factor(s)

Automation ²

Infrastructure automation enables speed through faster execution when configuring the infrastructure and aims at providing visibility to help other teams across the enterprise work quickly and more efficiently. Automation removes the risk associated with human error, like manual misconfiguration; removing this can decrease downtime and increase reliability. These outcomes and attributes help the enterprise move towards implementing a culture of DevOps, the combined working of development and operations.

¹ link: [Reference Architecture \(https://en.wikipedia.org/wiki/Reference_architecture\)](https://en.wikipedia.org/wiki/Reference_architecture) ↗

² link: [Infrastructure-as-Code \(https://en.wikipedia.org/wiki/Infrastructure_as_code\)](https://en.wikipedia.org/wiki/Infrastructure_as_code) ↗

Availability³

The probability that an item operates satisfactorily, without failures or downtimes, under stated conditions as a function of its reliability, redundancy and maintainability attributes. Some major objectives to achieve a desired service level objectives are:

- Preventing or reducing the likelihood and frequency of failures via design decisions within the allowed cost of ownership
- Correcting or coping with possible component failures via resiliency, automated failover and disaster-recovery processes
- Estimating and analyzing current conditions to prevent unexpected failures via predictive maintenance

Integrity⁴

Integrity is the maintenance of, and the insurance of the accuracy and consistency of a specific element over its entire lifecycle. Both physical and logical aspects must be managed to ensure stability, performance, re-usability and maintainability.

Security⁵

Security is about ensuring freedom from or resilience against potential harm, including protection from destructive or hostile forces. To minimize risks, one must manage governance to avoid tampering, maintain access controls to prevent unauthorized usage and integrate layers of defense, reporting and recovery tactics.

- Deployment Flavor(s)

Proof-of-Concept⁶

A partial or nearly complete prototype constructed to demonstrate functionality and feasibility for verifying specific aspects or concepts under consideration. This is often a starting point when evaluating a new, transitional technology. Sometimes it starts as a Minimum Viable Product (MVP⁷) that has just enough features to satisfy an

3 link: [Availability \(https://en.wikipedia.org/wiki/Minimum_viable_product\)](https://en.wikipedia.org/wiki/Minimum_viable_product) ↗

4 link: [Data Integrity \(https://en.wikipedia.org/wiki/Data_integrity\)](https://en.wikipedia.org/wiki/Data_integrity) ↗

5 link: [Security \(https://en.wikipedia.org/wiki/Security\)](https://en.wikipedia.org/wiki/Security) ↗

6 link: [Proof of Concept \(https://en.wikipedia.org/wiki/Proof_of_concept\)](https://en.wikipedia.org/wiki/Proof_of_concept) ↗

7 link: [Minimum Viable Product \(https://en.wikipedia.org/wiki/Minimum_viable_product\)](https://en.wikipedia.org/wiki/Minimum_viable_product) ↗

initial set of requests. After such insights and feedback are obtained and potentially addressed, redeployments may be utilized to iteratively branch into other realms or to incorporate other known working functionality.

Production

A deployed environment that target customers or users can interact with and rely upon to meet their needs, plus be operationally sustainable in terms of resource utilization and economic constraints.

Scaling

The flexibility of a system environment to either vertically scale-up, horizontally scale-out or conversely scale-down by adding or subtracting resources as needed. Attributes like capacity and performance are often the primary requirements to address, while still maintaining functional consistency and reliability.

A Appendix

The following sections provide a bill of materials listing for each component layer.

A.1 Compute Platform Bill of Materials

Role	Qty	SKU	Component	Notes
K3s Server, SUSE Rancher MCM cluster	3	SYS-120C-TN10R	SYS-120C-TN10R	Configuration:
CPU	2	P4X-ICX6330-SRKHM	P4X-ICX6330-SRKHM	ICX 6330 2P 28C/56T 2.0G 42M 11.2GT 205W 4189 D2
Memory	16	MEM-DR416L-HL04- ER29	MEM-DR416L-HL04- ER29	16GB DDR4-2933 2Rx8 ECC REG DIMM
NVMe M.2(OS)	2	HDS-SMP-HFS7T6GET- FEID430	HDS-SMP-HFS7T6GET- FEID430	"KXG60ZN- V1T02 PCIe" Gen3 x4, NVMe ^a 1.3a 1TB"
Network AOC	1	AOC-S100G-b2C	AOC-S100G-b2C	"Two QSFP28 100Gbps Eth- ernet port PCIe 4.0 x 16 host interface,Ro- HS"


Role	Qty	SKU	Component	Notes
Network AOC	1	AOC-ATG-i2TM	AOC-ATG-i2TM	"AIOM 2-port 10GBase-T, In- tel X550,RoHS"
Software Li- cense	1	SFT-DCMS-SINGLE	SFT-DCMS-SINGLE	"Supermicro System Manag- ement Software Suite node li- cense, HF, Ro- HS/REACH, PBF"
Downstream Kubernetes Cluster Serv- er, Hypercon- verged	3	Supermicro SYS-620C- TN12R	Supermicro SYS-620C- TN12R	Configuration:
CPU	2	P4X-ICX8368-SRKH8	P4X-ICX8368-SRKH8	ICX 8368 2P 38C/76T 2.4G 57M 11.2GT 270W 4189 D2
Memory	16	MEM-DR432L-HL03- ER32	MEM-DR432L-HL03- ER32	SK Hynix 32GB DDR4-3200 2Rx8 (16Gb)ECC REG DIMM
NVMe M.2(OS)	2	HDS-SMP-HFS7T6GET- FEID430	HDS-SMP-HFS7T6GET- FEID430	"KXG60ZN- V1T02 PCIe" Gen3 x4, NVMe ^a 1.3a 1TB"

Role	Qty	SKU	Component	Notes
NVMe(OSD Drives)	12	HDS-SMP-KCM6XRUL3T84Ê	HDS-SMP-KCM6XRUL3T84Ê	"Kioxia CM6 3.84TB NVMe PCIe 4x4 2.5"" 15mm SIE 1DWP"
Network AOC	1	AOC-S100G-b2C	AOC-S100G-b2C	BCM57508 NetXtreme-E 10Gb/25Gb/40Gb/50Gb/100Gb/200Gb Ethernet
Network AOC	1	AOC-ATG-i2TM	AOC-ATG-i2TM	"AIOM 2-port 10GBase-T, Intel X550,RoHS"
Software License	1	SFT-DCMS-SINGLE	SFT-DCMS-SINGLE	"Supermicro System Management Software Suite node license, HF, RoHS/REACH, PBF"

A.2 Software Bill of Materials

Role	Qty	SKU	Component	Notes
Operating System	1-3	874-006875	SUSE Linux Enterprise Server,	Configuration: <ul style="list-style-type: none">• per node (up to 2 sock-

Role	Qty	SKU	Component	Notes
			<ul style="list-style-type: none"> • x86_64, • Priority Subscription, • 1 Year 	ets, stack-able) or 2 VMs
Kubernetes Management	1	R-0001-PS1	SUSE Rancher, <ul style="list-style-type: none"> • x86-64, • Priority Subscription, • 1 Year 	Configuration: <ul style="list-style-type: none"> • per deployed instance
Rancher Management	2	R-0004-PS1	Rancher 10 Nodes <ul style="list-style-type: none"> • x86-64 or aarch64, • Priority Subscription, • 1 Year, 	Configuration: <ul style="list-style-type: none"> • requires priority server subscription
Consulting and Training	1	R-0001-QSO	Rancher Quick Start, <ul style="list-style-type: none"> • Go Live Services 	Terms: <ul style="list-style-type: none"> • Review of client architecture • Bi-weekly cadence calls for 12 weeks • On-demand consulting (24 hours) • Two developer workshops





Note

For the software components, other durations of support terms are also available.

SUSE Linux Enterp... *

A.3 Documentation Configuration / Attributes

This document was built using the following [AsciiDoc](https://github.com/asciidoc/asciidoc) (<https://github.com/asciidoc/asciidoc>)  and DocBook Authoring and Publishing Suite ([DAPS](https://github.com/openSUSE/daps) (<https://github.com/openSUSE/daps>) ) attributes:

```
Automation=1@ Availability=1@ FCTR=1@ FLVR=1@ IHV-Supermicro-SuperServer=1@ IHV-  
Supermicro=1@ Integrity=1@ PoC=1@ Production=1@ RC=1@ Scaling=1@ Security=1@ focusRKE1=1@  
iIHV=1@ layerSLES=1@ Appendix=1 Arch0v=1 BP=1 BPBV=1 CompMod=1 DepConsiderations=1  
Deployment=1 GFDL=1 Glossary=1 HWComp=1 HWDepCfg=1 LN=1 RA=1 References=1 Requirements=1  
SWComp=1 SWDepCfg=1 env-daps=1 iK3s=1 iRKE1=1 iRKE2=1 iRMT=1 iRancher=1 iSLEMicro=1  
iSLES=1 iSUMa=1
```

8 Legal Notice

Copyright © 2006–2021 SUSE LLC and contributors. All rights reserved.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or (at your option) version 1.3; with the Invariant Section being this copyright notice and license. A copy of the license version 1.2 is included in the section entitled "GNU Free Documentation License".

SUSE, the SUSE logo and YaST are registered trademarks of SUSE LLC in the United States and other countries. For SUSE trademarks, see <https://www.suse.com/company/legal/>.

Linux is a registered trademark of Linus Torvalds. All other names or trademarks mentioned in this document may be trademarks or registered trademarks of their respective owners.

This article is part of a series of documents called "SUSE Best Practices". The individual documents in the series were contributed voluntarily by SUSE's employees and by third parties. The articles are intended only to be one example of how a particular action could be taken.

Also, SUSE cannot verify either that the actions described in the articles do what they claim to do or that they don't have unintended consequences.

All information found in this article has been compiled with utmost attention to detail. However, this does not guarantee complete accuracy. Therefore, we need to specifically state that neither SUSE LLC, its affiliates, the authors, nor the translators may be held liable for possible errors or the consequences thereof. Below we draw your attention to the license under which the articles are published.

9 GNU Free Documentation License

Copyright © 2000, 2001, 2002 Free Software Foundation, Inc. 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA. Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

A section "Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as "Acknowledgements", "Dedications", "Endorsements", or "History".) To "Preserve the Title" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition. The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.

- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.
- O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled "History" in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements", and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements".

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all

Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

ADDENDUM: How to use this License for your documents

Copyright (c) YEAR YOUR NAME.

Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.2

or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts.
A copy of the license is included in the section entitled “GNU
Free Documentation License”.

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “ with...
Texts.” line with this:

with the Invariant Sections being LIST THEIR TITLES, with the
Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST.

If you have Invariant Sections without Cover Texts, or some other combination of the three,
merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these
examples in parallel under your choice of free software license, such as the GNU General Public
License, to permit their use in free software.