

INFO 2310

Topics in Web Programming
Ruby on Rails

Last week on INFO2310

- Added our first ActiveRecord relation
- Discussed the application.css file
- Used ActiveRecord callbacks and a conditional validator to add a password field to our User Model
- You wrote the User.authenticate function

Week 5

Logging in
&& Customizing the Page

Go ahead and login to Amazon and start your
EC2 instances

Login to PuTTY

- open PuTTY
- On the left panel, navigate to Connection->SSH->Auth
 - Next to "Private key file for authentication:", click "Browse", and select the *.ppk file you created on the previous step.
- Then, navigate to Connection->Data
 - For "Auto-login username", type "ec2-user"
- Navigate to "Session" (the very top)
 - Copy the "Public Domain Name" of your EC2 instance; you can see this on the instances page of the Amazon console, when an instance is selected
 - Paste it into the "Host Name (or IP address)" field
- Click "Open"

Login to WinSCP

- Open WinSCP
 - Paste in your domain to "Host name", as you did in PuTTY
 - Type "ec2-user" for the "User name"
 - Click "..." to select your private key file
 - Click "Login"
- Set Notepad++ as the default editor.
 - Click Options->Preferences
 - Select "Editors" from the left tab
 - Click Add
 - Select "External Editor"
 - Find Notepad++ (C:\Program Files (x86)\Notepad++)
 - Click "Open", then "Okay"
 - Drag it to the top of the editor list

Today's branch

Since we are working on a new feature today,
let's start on a feature branch

git status

should display nothing to commit

git checkout -b login

checkout a new branch

git branch

view branches

Remembering Logins

Now we have a function to checks a user's credentials

=> `User.authenticate`

What do we do with it?

We want a user to login, and then begin a session, which persists until they log out.

Let's be RESTful

While we won't actually be storing any session data in the database (we'll use cookies), we will model logins in a RESTful manner just the same.

We will think of logging in as *creating* a Session *resource*. Logging out is *destroying* that resource.

Remeber?

config/routes.rb

resources :users

HTTP Verb	Path	Action	used for
GET	/users	index	lists all the users
GET	/users/new	new	displays an HTML form for creating a new user
POST	/users	create	creates a new user
GET	/users/:id	show	display a specific user
GET	/users/:id/edit	edit	displays an HTML form for editing a user
PUT	/users/:id	update	updates a specific user
DELETE	/users/:id	destroy	delete a specific user

We don't quite need all that

config/routes.rb

resources :sessions, only: [:new, :create, :destroy]

HTTP Verb	Path	Action	used for
GET	/sessions/new	new	displays an HTML form for creating a new session
POST	/sessions	create	creates a new session
DELETE	/sessions/:id	destroy	delete a specific user

Along with the mappings from URL to controller and function, this gives us some helper functions to access these URLs in other parts of our app.

new_session_path	=> "/sessions/new"
sessions_path	=> "/sessions"
session_path(id: 5)	=> "/sessions/5"

And the controller

app/controllers/sessions_controller.rb

```
class SessionsController < ApplicationController
```

```
  def new  
  end
```

```
  def create  
  end
```

```
  def destroy  
  end
```

```
end
```

A login form

the **form_for** helper is used to produce the HTML for a form.

We've seen it before in

app/views/users/_form.html.erb

app/views/micro_posts/_form.html.erb

form_for produces the HTML for a web form. If you pass it an instance of an ActiveRecord class, as we did in the two partials above, it will infer the appropriate URL and action (POST/PUT) for the form.

However, unlike before, we don't have a Session ActiveRecord model. We can still use **form_for**, we just have to pass it more information; specifically, the model the form is for, and the url it should submit to.

e.g.

form_for(:document, url: "/documents")

would create a form for a document which posts to **"/documents"**

You go!

Start with a file at **app/views/sessions/new.html.erb**

Change the "Logout" link in the header to be a "Login" link which points to your new login form.

The form should POST to `"/sessions"`, but don't worry about it working yet. In fact, it's fine if it crashes when you submit it.

Specs

We will spend today working through the `spec/requests/session_spec.rb` file, so let's copy that over from `lecture_5.txt`.

But we won't be able to make all the specs pass in one go; so here's how to run the subset of them we are interested in first:

```
bundle exec rspec spec/requests/session_spec.rb -e "login form"
```

Flash Variables

Are great ways to display notification or error messages.

Rails persists them to the subsequent request and then deletes them.

Here's one in action

```
def set_user_name_to_matt
  user = User.find_by_id(params[:id])

  if user && user.update_attributes(name: "matt")
    flash[:notice] = "Updated name to Matt"
    redirect_to user_path(user)
  else
    flash[:error] = "Unable to update name to Matt"
    redirect_to root_path
  end
end
```


Adding flash variables to our layout

`app/layouts/application.html.erb`

```
<div class="container">
```

```
  <% flash.each do |key, value| %>
```

```
    <div class="alert alert-<%= key %>"><%= value %></div>
```

```
  <% end %>
```

```
  <%= yield %>
```

```
  <hr />
```

```
  <%= render 'layouts/footer' %>
```

```
</div>
```

See full file in `lecture_5.txt`

Let's use flash variables

To tell users whether they have logged in successfully or not.

Fill in the code in

app/controllers/sessions_controller.rb

for the **create** function

to accomplish this you should use the **User.authenticate method** you have already built.

When you are in a controller function you can access data from the web request using the **params** hash.

e.g.

params[:session][:email]

should yield the email from the form you created in the previous step

Your task

Get the following specs to pass

```
bundle exec rspec spec/requests/session_spec.rb -e "submitting the login form"
```

By filling in the code in the **create** function, and redirecting to the user's profile page if they login successfully, and to the home page if they fail

If they succeed, give them a flash :notice of "Welcome, <their email address>!" message.

If they fail, display a flash :error of "Invalid email/password combination"

We still aren't *actually* logging them in yet; that's next.

Cookies!

Finally, we are at a spot to actually log people in. Let's use a cookie to remember who the current user is.

In Rails, we can write cookies by setting keys on the **cookies** hash.

```
cookies[:current_user_id] = user.id
```

Then in subsequent requests we can read them back:

```
current_user_id = cookies[:current_user_id]
```

Logging in

Let's remember the current user id on successful logins using a cookie.

current_user

Next we need some helper methods to facilitate working the currently authenticated user.

We'll have several, so lets start a new module, at **app/helpers/session_helper.rb**

What's a module?

A set of functions with a common purpose that can be included in other Ruby classes.

Unlike inheritance, a Ruby class may include many modules (but may only inherit from one parent class).

Sometimes they are called "mixins" because they "mixin" functionality to a class. This is a very powerful tool for reusing code.

module SessionHelper

app/helpers/session_helper.rb

```
def sign_in(user)
  cookies[:user_id] = user.id
  self.current_user = user
end
```

```
def sign_out_user
  cookies.delete :user_id
end
```

```
def current_user=(user)
  @current_user = user
end
```

```
def current_user
  @current_user ||= User.find_by_id(cookies[:user_id])
end
```

```
def signed_in?
  !current_user.nil?
end
end
```


Helpers

Helpers are automatically included for us to use in views, but we will need to include our helper ourselves if we wish to use the functions in controllers. Which we do.

```
app/controllers/application_controller.rb  
class ApplicationController < ActionController::Base  
  protect_from_forgery  
  include SessionHelper  
end
```

Including the SessionHelper module is effectively the same as defining the methods *on* the ApplicationController class; but it's much cleaner to keep them in a separate module

Customize our header

Now that we have a concept of WHO is currently viewing our app, we can start making it behave more like an actual website.

Using our new **SessionHelper** functions, lets make the following changes to our header:

- If someone is logged in:
 - Display a "Logout" link instead of a "Login" link
 - Set the link for "My Profile" to point to the `current_user`'s profile page
 - Set the link for "My Account" to point the page for editing the `current_user`
 - Hide the "Sign Up" button on the home page
- If someone is not logged in
 - Hide the links for "My Profile" and "My Account"

When you're done, more specs should be passing:

```
bundle exec rspec spec/requests/session_spec.rb -e "customized header"
```

Logging out

In our `sessions_controller`, implement the **destroy** function.

The destroy function should log out the current user (we already have the function to do this in our **SessionHelper** module), put a flash notice on the page that reads "Logged out <email>", and redirect to the home page.

Once it works, the whole **spec/requests/sessions_spec.rb** should be passing.

But it's also nice to *only* run the tests you are trying to fix (it's faster).

```
bundle exec rspec spec/requests/sessions_spec.rb -e "logging out"
```

Once those pass, all your tests should be passing

```
bundle exec rspec
```

Commit time

git status # see what we modified

git add -A # add all the changes

git commit -m "authentication"

git checkout master # merge it back into master

git merge login

git push origin master # github

git push heroku master # heroku

Today we...

- Created the login form
- Used a cookie to remember who the current user is
- Customized our layout for the current user
- Implemented logging out

OH

Now until 4pm

Monday from 7-8pm