

INFO 2310

Topics in Web Programming
Ruby on Rails

Week 7

Pagination

&& AJAX

&& Avatars

Go ahead and login to Amazon and start your EC2 instances

Login to PuTTY

- open PuTTY
- On the left panel, navigate to Connection->SSH->Auth
 - Next to "Private key file for authentication:", click "Browse", and select the *.ppk file you created on the previous step.
- Then, navigate to Connection->Data
 - For "Auto-login username", type "ec2-user"
- Navigate to "Session" (the very top)
 - Copy the "Public Domain Name" of your EC2 instance; you can see this on the instances page of the Amazon console, when an instance is selected
 - Paste it into the "Host Name (or IP address)" field
- Click "Open"

Login to WinSCP

- Open WinSCP
 - Paste in your domain to "Host name", as you did in PuTTY
 - Type "ec2-user" for the "User name"
 - Click "..." to select your private key file
 - Click "Login"
- Set Notepad++ as the default editor.
 - Click Options->Preferences
 - Select "Editors" from the left tab
 - Click Add
 - Select "External Editor"
 - Find Notepad++ (C:\Program Files (x86)\Notepad++)
 - Click "Open", then "Okay"
 - Drag it to the top of the editor list

Today's branch

Since we are working on a new feature today,
let's start on a feature branch

git status

should display nothing to commit

git checkout -b pagination

checkout a new branch

git branch

view branches

lecture_7_spec.rb

Go ahead and download the `lecture_7_spec.rb` from

https://raw.githubusercontent.com/goggin13/curails-mg343/master/spec/requests/lecture_7_spec.rb
(also linked from the course website syllabus page, under today's lecture).

Put the spec at **`spec/requests/lecture_7_spec.rb`**

Note that lots of specs today are from the **`lecture_6_spec.rb`** file (things we didn't get to last week); so as we progress we will swap back and forth between the two. Just take note when you are running the commands that you are using the correct file.

Last week we used the 'faker' gem to generate a set of realistic dummy data. Now we have too much of a good thing, so we'll need to put some structure around paginating our users and micro_posts.

Pagination

Do you like writing pagination logic?

Me neither; just the type of boring task we don't want to rewrite ourselves.

Rails core will not help us in this case, but there's a widely used gem that will.

will_paginate to the rescue.

will_paginate

Let's add the **will_paginate** gem to our gem file

We'll also add **bootstrap_will_paginate** which will adjust the css around the pagination to play nicely with our existing bootstrap css.

```
gem 'faker'
```

```
gem 'will_paginate'
```

```
gem 'bootstrap-will_paginate'
```

Then run

```
bundle install
```

will_paginate

All it takes to start using will_paginate is to provide it with a collection built with the "paginate" method, which it has added to all of our ActiveRecord models.

e.g. in the controller

User.all

=>

@users = User.paginate(page: params[:page])

And in a view...

<%= will_paginate @users %>

Let's set it up together for our users index; then you can paginate a user's micro_posts on their profile page.

app/controllers/users_controller.rb

def index

@users = User.paginate(page: params[:page])

...

app/views/users/index.html.erb

<%= will_paginate @users %>

<% @users.each do |user| %>

<tr>

<td><%= user.name %></td>

....

</tr>

<% end %>

<%= will_paginate @users %>

bundle exec rspec spec/requests/lecture_6_spec.rb -e "paginating users"

should be passing if we got this stage right

Paginate User's MicroPosts

- In the **show** action of **app/controllers/users_controller.rb**, create a collection of `micro_posts` for that user, using the `paginate` method (hint; you need to create a new variable, unlike we did with `@users` previously).
- Instead of the default 30 per page, display just 10 `micro_posts` per page.
 - **`@collection.paginate(page: params[:page], per_page: 10)`**
- Update **app/views/users/show.html.erb** to use the **`will_paginate`** function with the collection you defined in the controller function

```
bundle exec rspec spec/requests/lecture_6_spec.rb -e "paginating  
micro_posts"
```

should be passing now

User's Feed Round I

We'll start with this function in **user.rb**

```
def feed(paginate_options={page: 1})  
  micro_posts.paginate(paginate_options)  
end
```

Currently this is just a paginated collection of the user's posts. Next week we will enhance it to include the user's posts AND everyone they are following.

User's Feed Round I

You are already **will_paginate** pro's, so we will just go through this together quickly.

Our goal is to render out the feed on the home page. So we'll start with creating a variable in the **home** controller action for our feed:

```
def home
  if signed_in?
    @feed = current_user.feed page: params[:page]
  end
end
```

User Feed Round I

Then on the home page, we can render them out:

```
<% if signed_in? %>
  <%= will_paginate @feed %>
  <div id="user_feed">
    <%= render @feed %>
  </div>
  <%= will_paginate @feed %>
<% else %>
  <p>
    <%= link_to 'Sign Up', new_user_path, class: 'btn btn-primary btn-large' %>
  </p>
<% end %>
```

bundle exec rspec spec/requests/lecture_7_spec.rb -e "user feed"

should tell us if we got it right

Posting from the home page

Let's update the home page so a user can post a MicroPost from there upon logging in (a la, Twitter, our soon to be forgotten rival).

We'll walk through these updates together.

Creating MicroPosts

Currently, when you visit **/micro_posts/new** you have to manually edit the `user_id` of the `micro_post`. This is silly.

Let's remove the "user_id" field from the `micro_posts` form (**`app/views/micro_posts/_micro_post.html.erb`**) altogether.

And then use the **`build`** method of a user's `micro_posts` collection to fix this.

current_user.micro_posts.build

This handy function "builds" a new `micro_post` that belongs to the current user. This `micro_post` is not saved to the database, but the `user_id` is already set = `current_user.id`.

def create

```
@micro_post = current_user.micro_posts.build(params[:micro_post])
```

```
...
```

Now, whenever a `micro_post` is created, it will belong to the `current_user`.

To the home page

Now, we're set to drop our `micro_post` form into the home page.

```
<% if signed_in? %>
```

```
  <%= render 'micro_posts/form' %>
```

```
<%= will_paginate @feed %>
```

```
<div id="user_feed">
```

```
  <%= render @feed %>
```

```
</div>
```

We'll also need to add an `@micro_post` variable to **`app/controllers/static_pages_controller.rb`** (which is no longer so aptly named...).

`app/controllers/static_pages_controller.b`

```
def home
  if signed_in?
    @micro_post = MicroPost.new
    @feed = current_user.feed page: params[:page]
  end
end
```

Page reloads?*

Let's take a look at how we can submit our new form with AJAX.

There are many existing solutions and opinions on the easiest, cleanest way to integrate AJAX with your Rails forms.

Here's a great blog entry on the many ways to AJAXify your Rails actions
-> <http://blog.madebydna.com/all/code/2011/12/05/ajax-in-rails-3.html>

Some primary features of Rails 4 (beta released last week!) are aimed at easing AJAX integration.

Check out the Rails 4 release notes here:

-> <http://weblog.rubyonrails.org/2013/2/25/Rails-4-0-beta1/>

*2008 called; they want their web page back.

Step 1 : Update the form

app/views/micro_posts/_form.html.erb

```
<%= form_for(@micro_post) do |f| %>
```

```
=>
```

```
<%= form_for(@micro_post, remote: true) do |f| %>
```

Content-Types

- **html:**
 - Server returns HTML, which can be inserted into the page
- **json:**
 - Server returns JSON objects, which we can manipulate via JavaScript as we please (perhaps creating DOM elements ourselves and inserting them into the page).
- **script:**
 - Server returns a snippet of JavaScript, which is evaluated.
 - This is the default when we set **remote: true**

Step 2 : Edit our controller

app/controllers/micro_posts_controller.rb

```
def create
```

```
  @micro_post = current_user.micro_posts.build(params[:micro_post])
```

```
  respond_to do |format|
```

```
    if @micro_post.save
```

```
      ...
```

```
      format.js { render :partial => "micro_posts/show" }
```

```
    else
```

```
      ...
```

```
      format.js { render :partial => "micro_posts/error" }
```

```
    end
```

```
  end
```

```
end
```


Step 3 : Create a `_show.js` partial

`app/views/micro_posts/_show.js.erb`

```
// Get the HTML for a rendered MicroPost
```

```
var html = '<%= j(render(:partial => "micro_post", :object => @micro_post))%>';
```

```
// create a JQuery DOM element we can insert (and hide it so we can fade it in)
```

```
var element = $(html).hide();
```

```
// Add it to the user feed, and then fade it in
```

```
$('#user_feed').prepend(element);
```

```
element.fadeIn(1000);
```

```
// Reset the post input to empty
```

```
$('#new_micro_post input[type="text"]').val("");
```

Step 4 : Create a `_error.js` partial

`app/views/micro_posts/_errors.js.erb`

```
var errors = $('<div class="alert alert-error"/>');
```

```
<% @micro_post.errors.full_messages.each do |error| %>  
  errors.append('<p><%= j(error) %></p>');  
<% end %>
```

```
// Display errors before the form
```

```
$('#new_micro_post').prepend(errors);  
errors.fadeOut(3000);
```

script content-type

Let's walk through this one briefly; it was not particularly intuitive for me.

User types a
post and
clicks "Create
Micro post"
button

A screenshot of a web form titled "INFO 2310". The form has a header section with the title "INFO 2310" and a subtitle "This is a sample website used in INFO 2310 to learn Ru 140 character chunks." Below the header is a section labeled "Content" containing a text input field with the value "Hello World" and a "Create Micro post" button. At the bottom of the form are two identical navigation links: "← Previous 1 2 3 4 5 Next →".

INFO 2310

This is a sample website used in INFO 2310 to learn Ru 140 character chunks.

Content

Hello World

Create Micro post

← Previous 1 2 3 4 5 Next →

← Previous 1 2 3 4 5 Next →

These are the options we set on the form

```
<%= form_for(@micro_post, remote: true) do |f| %>
```

They tell Rails to intercept our form submission (which would reload the page, normally), package up the data the form *would* have sent, and send it to the server via *AJAX*.

Our controller **create** action receives the same data as it would have were the form submitted normally; but the **content-type** header tells it to return JavaScript instead of HTML.

Specifically, the content type maps the response to the line we added in our controller

```
format.js { render :partial => "micro_posts/show" }
```

The Rails server renders the 'micro_posts/show' partial in the same manner as if it were an HTML view; only in this case the embedded ruby snippets are producing JavaScript instead of HTML.

The Rails JavaScript that intercepted our form submission is waiting for the server to respond.

When the server responds (with the JavaScript code from our 'show' partial), the browser evaluates the JavaScript code that was returned.

This allows it to, among other things, insert elements into the DOM.

And clear the input field.



Thoughts

I like this solution because:

- We are reusing our server side ERB templates for displaying our MicroPosts. The logic for what a MicroPost looks like is still encapsulated inside the **_micro_post.html.erb** partial. This feels nice and DRY.
- Once I was over (what was for me) a conceptual hurdle of the server returning JS that was then executed by the browser, it feels pretty straightforward.

I dislike this solution because:

- Creating a MicroPost via AJAX is now coupled with the templates we wrote in **_micro_post.js.erb**.
- The JS we are writing in these partials doesn't feel very modular, and would prove trickier to reuse versus writing code in the normal **app/assets/javascripts** path.

Testing JavaScript

To test the JavaScript we just implemented, we need *something* to parse and run it.

A common solution for Rails is to use Selenium, which is an API (with bindings for Ruby along with almost every other popular language) for controlling a browser.

We do not have Selenium set up on the EC2 instances, and it would be a slightly tricky task since we would have to install and run a browser in 'headless' mode (EC2 instances don't have a monitor, in case you haven't noticed).

We'll punt on this here; but it's a must have for your future Rails work.

this test only really checks the correct form elements are being rendered on the page
bundle exec rspec spec/requests/lecture_7_spec.rb -e "posting from the home page"

Deleting MicroPosts (via AJAX)

Our next goal is to be able to delete MicroPosts via AJAX. You'll do more of the driving on this one.

We can accomplish this in 3 easy steps.

We will be using a Destroy ***link*** not a ***form*** as we just did, but the steps are identical.

Step 1

Add a link to destroy a MicroPost to the MicroPost partial (**app/views/micro_posts/_micro_post.html.erb**). If you need to remember the code for this link, look inside of **app/views/micro_posts/index.html.erb**.

- Only show this link if the `micro_post` belongs to the current user.
- Add the argument **remote: true** to the **link_to** function to turn it into an AJAX link
- Use the MicroPost id to add an id to the `<p>` tag that wraps the HTML for a MicroPost. You'll need this later to remove this element from the page.

Step 2

Create a file at **app/views/micro_posts/_destroy.js.erb** which removes the HTML from the page for a given MicroPost; use the id of the MicroPost in conjunction with the id you used in the previous step.

Step 3

Add a call to the **destroy** function in **micro_posts_controller.rb** to render our partial from step 2.

bundle exec rspec spec/requests/lecture_7_spec.rb -e "deleting micro_posts"
should pass afterwards

Next week...

- We will finish up our MicroPost app
- I'll take a poll at the end of class as to what you want to see with our two remaining sessions* post Spring Break
- Some options:
 - Build a Photo Gallery
 - Using Heroku plugins (Email, Monitoring, Memcache...)
 - Play with some benchmarking tools and scaling techniques
 - Keep adding features to our current app
 - comments, tags, likes...
 - **I'm open to suggestions if you have anything you'd really like to see/work on**

Commit time

git status # see what we modified

git add -A # add all the changes

git commit -m "pagination"

git checkout master # merge it back into master

git merge pagination

git push origin master # github

git push heroku master # heroku

Today we...

- Used the will_paginate gem to paginate our users and micro_posts
- Took a first swing at the user feed
- Allowed users to post from the home page via AJAX
- Allowed users to delete their micro_posts via AJAX