

User Guide

Csound for Android

Michael Gogins

23 August 2019

This is an extremely basic guide to using the Csound for Android app. It should be just enough to get you started if you already have some experience with Csound or, at least, some other “Music N” type software synthesizer.

Changes in This Version

This version of Csound for Android features many changes and improvements:

- The app is now built for 64 bit CPU architecture.
- The included FluidSynth opcodes have been updated to work on 64 bit CPU architectures.
- A wider selection of plugin opcodes is now included.
- Audio input and output are now implemented using the current version of Google’s Oboe library, which encapsulates differences between audio drivers on different Android platforms. Oboe is integrated with Csound in a new CsoundOboe C++ class. The current version of Oboe seems to perform with fewer dropouts.
- The app now has a built-in text editor based on Ace, replacing CodeMirror. The editor includes find and replace functions. The editor now has specific modes for .csd files and .html files.
- The user interface is tabbed for instantly switching between editing and performing.
- There are now 9 built-in sliders.
- The *User Guide* has been updated with information about issues and workarounds.
- The *Csound Reference Manual* appears in its own tab.

Introduction

The Csound for Android app is an Android version of Csound, an audio and music synthesis and processing language of great power, created by Barry Vercoe in 1984, maintained with almost complete backward compatibility since then, and widely used and taught for the creation of electroacoustic and computer music. Despite its age, Csound continues to be actively developed. It has many advanced features for sound synthesis including user-designable instruments, an easy to learn programming language, several phase vocoders, several sample players, a plethora of digital oscillators, filters, and envelope generators, and transparent multi-threading for higher performance of some types of pieces on multi-core systems.

The Csound for Android app is by Victor Lazzarini, Steven Yi, Michael Gogins, and others, and is

currently maintained by Michael Gogins in the [csound-extended](#) repository. The app contains virtually all of Csound, including many of the more frequently used plugin opcodes:

- The signal flow graph opcodes, for chaining instruments into effects chains and so on.
- The Fluidsynth opcodes for playing SF2 samples.
- The libstdutil library.
- The scanned synthesis opcodes.
- The Open Sound Control (OSC) opcodes which allow Csound to communicate over networks with other software in a low-latency and flexible manner.
- The Doppler opcode.

User Interface

The Csound for Android user interface uses tabs for easy and swift changes of context, for example between editing and performing. All tabs share the same builtin instance of Csound. This enables, for example, a piece to be written in HTML5 but utilize the builtin widgets, and so forth. The tabs are:

- **Editor** – Provides a built-in text editor based on Ace, with find and replace functionality. Press Ctrl-F to invoke the find and replace dialog.
- **Messages** – Shows all diagnostic and informative messages printed by Csound.
- **HTML** – Provides a built-in HTML5-enabled Web browser for the display of custom user interfaces, computer graphics and animations, and so on.
- **Widgets** – Provides a predefined set of 9 sliders, 5 buttons, and a trackpad that send updates to predefined Csound control channels. These widgets are backwards compatible with previous versions of the Csound for Android app.
- **Help** – Provides an embedded browser for the *Csound Reference Manual*.
- **About** – Provides an embedded browser for the Csound home page at <http://csound.com>, enabling users to explore many uses and features of Csound.

The task menu of Csound for Android provides the following functions:

- **New** – Creates a blank template Csound .csd file in the root directory of the user's storage for the user to edit. The .csd file will be remembered and performed by Csound.
- **Open** – Opens a file for editing. The file can be a Csound .csd file, or an HTML5 .html file. Each of these languages has access to the same instance of Csound that is exposed in the HTML tab or to the widgets in the Widgets tab.
- **Save as...** – Saves the current .csd or other file being edited under a new name.
- **Save** – Saves the current .csd or other file being edited to the user's storage.
- **Run/Stop** – If Csound is not running, starts a performance; if Csound is running, stops the performance. If the file is an .html file, it is reloaded in the HTML tab which has access to a Csound object encapsulating the app's builtin instance of Csound. If the Csound options include

-odac, Csound's audio output will go to the device audio output. If the element contains -osoundfilename, Csound's audio output will go to the file soundfilename, which should be a valid Linux pathname in the user's storage filesystem.

- **Examples** – Opens a submenu with various built-in example pieces. These are saved in your device's external public storage Music directory, and then run.
- **User guide** – Opens this basic user guide.
- **Settings** – Includes the following choices. The values of the settings are saved on the device, and restored at the beginning of the next session. Please note, it may be necessary to provide the full path to the Csound app's public data directory as the value of each directory, or as the first part of each directory. This information is printed by the Csound app in the Messages pane when it first starts.
 - **Plugins directory** – Sets the value of the OP CODE6DIR64 environment variable.
 - **Output directory** – Sets the value of the SFDIR environment variable.
 - **Samples directory** – Sets the value of the SSDIR environment variable.
 - **Analysis directory** – Sets the value of the SADIR environment variable.
 - **Include directory** – Sets the value of the INCDIR environment variable.

Predefined Widgets

The predefined widgets on the **Widgets** tab are assigned control channel names `slider1` through `slider9`, `butt1` through `butt5`, `trackpad.x`, and `trackpad.y`. In addition, the accelerometer on the Android device is available as `accelerometerX`, `accelerometerY`, and `accelerometerZ`.

The values of these widgets are normalized between 0 and 1, and can be read into Csound during performance using the `chnget` opcode, like this:

```
kslider1_value chnget "slider1"
```

The buttons send 1 when pressed, and 0 when released. The trackpad sends the `x` and `y` positions whenever the user is moving his or her finger on the trackpad. These positions are remembered when the finger is removed.

User-Defined Widgets

User-defined widgets are defined in an HTML file (Web page), or in a new `<html>` element of the CSD file. This can in principle contain any valid HTML5 code, including document elements, JavaScript, and styles. JavaScript event handlers can be attached to any elements, including range inputs (sliders). Such event handlers can call Java methods of the `CsoundOboe` object (`csound`), for example to get or set control channel values, or to send new score events to Csound.

The ability to send score events to Csound from JavaScript means that JavaScript can be used as a

high-level programming language in an .html file for the purposes of algorithmic composition, even interactive composition. All methods callable from `CsoundAppActivity` and `CsoundOboe` are marked with the `@JavascriptInterface` attribute in the `Csound for Android` source code. For a basic example of a user-defined widget setup, see the `Drone-HTML5.csd` example file. Here is a snippet showing a slider's `onInput` event handler setting a Csound control channel:

```
<script>
function gk_Reverb_FeedbackUpdate(value) {
var numberValue = parseFloat(value)
csoundApp.setControlChannel('gk_Reverb_Feedback', numberValue);
}
</script>
```

Examples

The menu of the Csound app features a number of built-in examples. Selecting an example will cause its file or files to be copied to the app's external public storage Music directory and loaded into the app, ready to be performed or edited. Not all of the examples use the widgets. The examples demonstrate not only some techniques for using the Csound6 Android app, but also a few of the many different ways of making music with Csound.

When I first encountered the Csound app, I was very impressed. Now that I have been able to contribute to its development, I have come to realize that a high end smartphone, not to mention a tablet, is in every sense of the word a real computer. The limits to what can be programmed on it are indefinable. On a high-end personal computer, it is easier to type, and Csound runs quite a bit faster; but there is no *essential* difference between running Csound on a computer and running it on a smartphone.

A Tutorial Example

This example will take you through the process of creating a new Csound piece, step by step. Obviously, this piece is not going to reveal anything like the full power of Csound. It is only intended to get you to the point of being able to create, edit, and run a Csound piece that will actually make sound on your Android device – from scratch.

Run the Csound app...

Press the **New...** button. You should be presented with an input dialog asking you for a filename for your piece. Type in `toot.csd`, and press the **Ok** button. The file will be stored in the root directory of your user storage on your device. You can save the file to another place, if you like.

The text editor should now contain a “template” .csd file. Your job is to fill out the minimum to hear something.

Create a blank line between `<CsOptions>` and `</CsOptions>`, and type `-odac -d -m3`. This means send audio to the real-time output (`-odac`), do not display any function tables (`-d`), and log some informative messages during Csound's performance (`-m3`).

Create a blank line between `<CsInstruments>` and `</CsInstruments>` and type the following

text:

```
sr = 44100
ksmps = 10
nchnls = 1
instr 1
asignal oscil 10000, 440
out asignal
endin
```

This is just about the simplest possible Csound orchestra. The orchestra header specifies an audio signal sampling rate of 44,100 frames per second, with 10 audio frames per control signal sample, and one channel of audio output. The instrument is just a simple sine oscillator. It plays a loud tone at concert A.

Create a blank line between `<CsScore>` and `</CsScore>` and type:

```
i1 0 5
```

This means play instrument 1 starting at time 0 for 5 seconds.

Invoke the **Save** menu item.

Press the Csound app's **Start** button. You should hear a loud sine tone for 5 seconds.

If you want to save your audio output to a soundfile named `test.wav`, change `-odac` above to `-o/sdcard/test.wav`.

That's it!

Issues and Workarounds

Audio Performance

The Android operating system has only recently been given an audio driver layer, AAudio, that is even marginally adequate for musical use. Only recent devices support this, and even some of them have issues. The Oboe driver used by this app can be configured by the user for either AAudio or the older OpenSL ES audio driver to suit your device.

If you experiences glitches or low latency, try the following:

- Look at the Csound messages to see which driver Oboe is using, and use the **Settings, Audio driver** choice to set the other one.
- Experiment with Csound's `ksmps` option in the orchestra header.
- Close all other apps on your device, and clear all caches.
- Turn on Airplane Mode.
- Experiment with your device's Power Saving or Performance mode.

File System

The Android operating system has new and sometimes awkward security restrictions on how applications can read and write files on your device. Applications are required to specify any storage directories on which the user might write files.

For the Csound for Android app, the default public storage directory is `Music`, which on many devices is `/storage/emulated/0/Music`. If your pieces cannot read or write some file, such as a `SoundFont`, sample soundfile, include file, or anything else, try putting everything in this directory. Subdirectories of this should also work. On startup, you can look at the ***Messages*** pane to see what Csound is actually using for the public data directory.

Screen Sizes

The sizes of fonts and widgets in the Csound for Android app can be configured to some extent in the device's Android settings, namely in the ***Settings, Display, Font size and style*** section and ***Screen zoom*** section.

HTML Pieces

When an HTML example loads, the app may briefly display a popup message about a missing `csound.js` file. This message can be ignored and should not recur. The piece should render properly anyway.

If the HTML for the piece is not rendered correctly, it may help to exit the app and reload the piece.

In general, for HTML pieces, it is necessary to click on the ***Run*** button, as for any other Csound piece, before Csound is instantiated in the JavaScript context and can render the piece.