

Midterm 3 Study Guide

Due No due date Points 25 Questions 25 Time Limit 30 Minutes Allowed Attempts Unlimited

Take the Quiz Again

Attempt History

	Attempt	Time	Score
KEPT	Attempt 16	30 minutes	24 out of 25
LATEST	Attempt 20	30 minutes	19 out of 25
	Attempt 19	20 minutes	23 out of 25
	Attempt 18	30 minutes	21 out of 25
	Attempt 17	30 minutes	23.5 out of 25
	Attempt 16	30 minutes	24 out of 25
	Attempt 15	30 minutes	21 out of 25
	Attempt 14	30 minutes	23 out of 25
	Attempt 13	24 minutes	22 out of 25
	Attempt 12	16 minutes	24 out of 25
	Attempt 11	17 minutes	19 out of 25
	Attempt 10	17 minutes	22 out of 25
	Attempt 9	20 minutes	20 out of 25
	Attempt 8	21 minutes	20 out of 25
	Attempt 7	25 minutes	21.5 out of 25
	Attempt 6	25 minutes	21 out of 25
	Attempt 5	30 minutes	17 out of 25
	Attempt 4	21 minutes	23 out of 25
	Attempt 3	26 minutes	19.89 out of 25
	Attempt 2	30 minutes	22.5 out of 25
	Attempt 1	27 minutes	21 out of 25



⚠ Correct answers are hidden.

Submitted Jul 19 at 12:33pm

Question 1

1 / 1 pts

Which of the following loop patterns are used here?

```
string s{"Hello CS 150"};
while (s.size())
{
    if (s.at(0) == 'C') break;
    s = s.substr(1);
}
cout << s << endl;
```

- ☐ iterator or range loop
- ☐ limit loop
- ☒ loop-and-a-half
- ☐ primed loop
- ☒ sentinel loop
- ☒ counter-controlled loop
- ☐ data loop
- ☐ inline test

Question 2

1 / 1 pts

Functions with generic (or type) parameters are known as template functions.

- ☒ True
- ☐ False

Question 3

1 / 1 pts

Which of the following loop patterns are used here?

```
size_t pos = 0;
char ch;
in.get(ch);
while (ch != 'Q')
{
    pos++;
    in.get(ch);
}
```

}

☐ counter-controlled loop

☒ sentinel loop

☒ primed loop

☐ limit loop

☐ data loop

☐ loop-and-a-half

☐ iterator or range loop

☐ inline test



Incorrect

Question 4

0 / 1 pts

What prints?

```
string s("hello");
try {
    if (s.size() > 20) throw 42;
    if (isupper(s.back())) throw "goodbye";
    if (s == "Hello") throw string("hello");
    s[s.size()] = 'x';
    cout << "one\n";
}
catch (const int& e) { cout << "two\n"; }
catch (const string& e) { cout << "three\n"; }
catch (exception& e) { cout << "four\n"; }
catch (...) { cout << "five\n"; }
```

- ☒ Undefined
- ☐ three
- ☐ five
- ☐ four
- ☐ two
- ☐ one

Question 5

1 / 1 pts

What happens when you execute the following (erroneous) code:

```
cout << stoi(42.5) << endl;
```

- ☐ No conversion takes place and the output stream is placed in a failed state.
- ☐ The double 42.5 is truncated to 42 and printed
- ☐ An exception is thrown, which may be caught
- ☒ The code does not compile because the argument is the wrong type.
- ☐ The program prints an error message and terminates since you cannot convert a double to an int

Question 6

1 / 1 pts

Which line fails to work correctly?

```
template <typename T>
void print(const T& item)
{
    cout << item << endl;
}
```

- ☒ None of these
- ☐ print(3 + 2.2);
- ☐ print("hello");
- ☐ print(2 + 2);
- ☐ print(string("goodbye"));

Question 7

1 / 1 pts

Match each item with the correct standard header below.

Read and write characters to memory using streams	sstream
Connect a disk file to an input or output stream.	fstream
Use the predefined stream objects cin and cout	iostream
Determine the category of a character	cctype
Modify the way that memory is converted to characters on input or output	iomanip

Question 81 / 1 pts

What is true about this piece of code?

```
template <typename T, typename U>
T pickle(T& a, const U& b) {
    a += b;
    return b;
}

int main()
{
    int x = 42;
    auto a = pickle(x, 4.5);
    cout << a << endl;
    cout << x << endl;
}
```

- ☐ This code has a syntax error.
- ☐ In main, x prints 46.5
- ☒ In main, a prints 4
- ☐ In main, a prints 4.5
- ☒ In main, x prints 46

Question 91 / 1 pts

A(n) _____ is a statement about a condition which **must be true** when it is encountered in your code.

- ☐ exception
- ☐ postcondition
- ☐ precondition
- ☒ assertion

Question 101 / 1 pts

Assuming the following variable definition, which statement creates an object which refers to the first element in v, and which allows you to change v?

vector<double> v{1.2, 2.3, 3.4};

- ☒ auto a = begin(v);
- ☐ auto d = cend(v);
- ☐ None of these
- ☐ auto b = end(v);
- ☐ auto c = cbegin(v);

Question 111 / 1 pts

To count the number of elements in a vector that match a particular condition, use the STL function:

- ☐ find

☒ count_if

☐ count

☐ minmax_element

☐ search

Question 121 / 1 pts

Assuming the following variable definition, which statement creates an object which refers to a position immediately following the last element in `v` and which allows you to change the elements in `v`?

vector<double> v{1.2, 2.3, 3.4};

☐ `auto c = cbegin(v);`

☐ `auto d = cend(v);`

☐ `auto a = begin(v);`

☐ None of these

☒ `auto b = end(v);`



IncorrectQuestion 130 / 1 pts

Assume `vector<int> v`; Writing `cout << v.front();` throws a runtime exception.

☒ True

☐ False

Question 141 / 1 pts

When passing a structure variable to a function, use *non-const reference* if the intent is to modify the actual argument.

☒ True

☐ False

Question 151 / 1 pts

User-defined scalar types are created with the `enum class` keywords in C++.

☒ True

☐ False

IncorrectQuestion 160 / 1 pts

Which line will not compile?

int main()
{
 vector<int> v{1, 2, 3};
 auto size = v.size();

 cout << v.back() << endl; // 1.
 cout << v.front() << endl; // 2.
 cout << v.at(0) << endl; // 3.
 cout << v.at(size) << endl; // 4.
 cout << v.pop_back() << endl; // 5.
}

☒ 4

☐ 5

☐ 1

☐ 2

☐ 3

IncorrectQuestion 170 / 1 pts

Assuming the following variable definition, which statement creates an object which refers to the last element in `v` and which prohibits you from changing `v`?

```
vector<double> v{1.2, 2.3, 3.4};
```

- ☐ `auto a = begin(v);`
- ☐ `auto c = cbegin(v);`
- ☐ `auto b = end(v);`
- ☒ `auto d = cend(v);`
- ☐ None of these

Question 18

1 / 1 pts

What is printed when you run this code?

```
int *n(nullptr);
cout << &n << endl;
```

- ☐ No output; compiler error.
- ☐ The address value 0
- ☐ The word "nullptr"
- ☒ The address value where *n* is stored
- ☐ No compilation errors, but undefined behavior

Question 19

1 / 1 pts

Which line has *undefined* output?

```
double speed[5] = {. . .};
```

- ☒ `cout << speed[5] << endl;`
- ☐ `cout << speed[1] << endl;`
- ☐ `cout << speed[0] << endl;`
- ☐ `cout << speed[4] << endl;`
- ☐ None of these

Question 20

1 / 1 pts

C++ arrays have no support for bound-checking.

- ☒ True
- ☐ False

Incorrect

Question 21

0 / 1 pts

What prints?

```
int a[] = {1, 3, 5, 7, 9};
int *p = a;
cout << ++*p;
cout << *p << endl;
```

- ☐ 13
- ☐ 22
- ☐ 33
- ☒ None of these
- ☐ 12

Question 22

1 / 1 pts

Which area of memory are global variables stored in?

- ☐ Stack

☐ Text

☒ Static storage area

☐ Heap

Incorrect

Question 23

0 / 1 pts

Which of these lines correctly prints 3?

```
struct S {
    int a = 3;
    double b = 2.5;
};
```

S obj, *p = &obj;

☐ cout << p.a << endl;

☐ cout << *p.a << endl;

☒ cout << *(p).a << endl;

☐ cout << *(p.a) << endl;

☐ cout << (*p).a << endl;



Question 24

1 / 1 pts

C++ arrays can be allocated with a size of 0.

☐ True

☒ False

Question 25

1 / 1 pts

Which assigns a value to the first position in *Letters*?

```
char letters[26];
```

☐ *letters + 1 = 'b';

☐ *(letters + 1) = 'a';

☐ *letters = "a";

☒ *letters = 'a';

☐ *letters[0] = 'a';