Linear Search Efficiency

One thing that we can tell from this short experiment is that if a name is not in the directory, we'll have to look through all 1,000 names to find that out. As a result, (assuming that the time to compare each name is constant), the running time of linear search grows proportionally with the size of the directory we're searching. If we had a directory of 10,000 names it would be roughly ten times slower than our version with 1,000 names.

However, that is the **worst case**. Most of the time you will find the name you are looking for and won't need to compare all one thousand names.

In the **best case**, the name you'll decide that you only need to look up **Kimberly Thompson**, the first name on the list, and your program will seem to run like lightning. **On average**, though, assuming the names are randomly distributed throughout the directory, you'll have to search through **500** names (or half of the total array) to find the one you want.

In Computer Science we have a particular terminology for discussing the runtime efficiency of algorithms. We say that **linear search** is an **O(n)** algorithm, (which mean **on the order of n**), because the time to find your element increases in a linear manner as the number of elements in the array (n) increases. This is known as **Big-O notation**.

Even more specifically, we can say that our implementation:

- Has a worst case of O(n). We will always have to search through the entire directory if a name is not found.
- Has a best case of O(1) meaning that if we always search for the first name on the list, we'll find it in constant time.
- Has an average case of (n/2), meaning that on average, we'll find the name by searching half of the the array. Some will be more, some less, but it will average out.



This course content is offered under a CC Attribution Non-Commercial license. Content in