Limit Bounds

A limit loop first does a calculation, and then checks to see if the calculation has reached a limit. Limit loops are used extensively in scientific, financial and graphical computing. Kinds of limits include reduction to zero, bisection, non-convergence tests (as in Calculus) and successive approximations. You'll use several of those in Lecture.

Here is a limit loop whose limit is the reduction to zero. This computes the sum of the digits in an integer, **n**:

```
int temp = n;
while (temp > 0)
{
    sum += temp % 10;
    temp /= 10;
}
cout << "The sum of the digits in " << n << " is " << sum << endl;</pre>
```

- The expression temp % 10 always returns the last digit in the positive integer temp.
- The expression temp / 10 returns the number without its final digit.

In this case, the condition that is being tested is the value of temp, which is changed each time through the loop. Once n reach its limit (0), the loop terminates.

Note that instead of changing n itself, the solution creates a separate variable named temp. This is better style because it doesn't confuse the concept of a parameter or input variable, with that of a local variable used for the function output. In this case, if the loop had used n then the last output statement would have been incorrect.

More Loop Plans

Here are the plans that I created for each of the remaining two functions. Using limit loops, you should be able to complete these on your own.

Here is firstDigit()

```
// result <- |n|
// while result greater or equal to 10
// result <- result / 10
// return result;
```

And, here is numberOfDigits

```
// Assume that 0 is a digit
// result <- |n|
// counter <- 1
// while result is greater or equal to 10
// result <- result / 10
// counter <- counter + 1
// return counter</pre>
```



is course content is offered under a <u>CC Attribution Non-Commercial</u> license. Content in