



CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality
hereby attests that the product(s)

Solar Collector

(Details as per the attached Scope of Certification)
manufactured by:

SIMSEK GUNES KOLLEKTORLERI LTD.STI.

2.INDUSTRIAL ZONE, RASIM DOKUR BLV., 2.MAIN STREET NO:32 AKDENIZ-MERSIN / TURKIYE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

BS EN 12975-1:2006 +A1: 2010

Accordingly, DCLD hereby authorizes the above manufacturer
to affix the DCL Product Conformity Mark on the above-mentioned product(s).

ENG. MAJED AL SHAMSI

Certification and Quality Control of Products Section's Manager
Dubai Central Laboratory Department-Dubai Municipality



Certificate No: CL23020833
Valid Until: 06/07/2027



Current Issue Date: 07/07/2026
Original Issue Date: 07/07/2023



The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate.
This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.

DUBAI CENTRAL LABORATORY DEPARTMENT DCLD-CQPS PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL23020833

Certificate Issued To:

SIMSEK GUNES KOLLEKTORLERI LTD.STI

2.INDUSTRIAL ZONE, RASIM DOKUR BLV., 2.MAIN
STREET NO:32, AKDENIZ-MERSIN / TURKIYE

Applicable Standard Specification:

BS EN 12975-1: 2006 +A1: 2010 : Thermal solar
systems and components – Solar Collectors – Part 1:
General requirements

Applicable Specific Rules:

DM-DCLD-RD-DP21-2178 (IC) : Certification of Solar
Collectors as per BS EN 12975-1: 2006 A1: 2010
DM-DCLD-RD-DP21-2084 (IC) : Guidelines for Factory
Production control Plan for Solar Collector
Manufacturers

S/N	Product Description	Brand Name	Product Details
1	FLAT PLATE SOLAR COLLECTOR Absorber Materials: Tinox Energy Aluminum Selective; Solar Glass: 3,2 Tempered, Low-Iron Oxide Solar Glass; Thermal bottom insulation: 40 mm thickness Rock wool thermal insulation with density of 50 kg/m³, thermal conductivity of 0.035 W/(m.K) Thermal Side Insulation: 15 mm Glass wool with density 48 kg/m³, conductivity of 0.031 W/(m.K). back plate: Embossed Galvanized Base Sheet Casing: Extruded Anodized Aluminum Casing; Sealing materials: Silicon and Absorber (Aluminum Selective Coated); Water + MonoethyleneGlicol	Simsek (ORION 413)	Gross Area of 1.83 m²; Aperture Area of 1.64 m²; Absorber Area of 1.62 m²; Gross Dimensions (without support frame) : 935 x 1960 x 81 mm; Dry Weight : 31 kg; Collector Fluid Volume: 1.01 Liters Material riser pipes and nos of manifolds: 8 nos Copper Pipes and 2 nos manifolds Maximum Operating Pressure 6 bars; Maximum Stagnation Temperature 220

DUBAI CENTRAL LABORATORY DEPARTMENT DCLD-CQPS PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL23020833

2	FLAT PLATE SOLAR COLLECTOR Absorber Materials: Tinox Energy Aluminum Selective; Solar Glass: 3,2 Tempered, Low-Iron Oxide Solar Glass; Thermal bottom insulation: 40 mm thickness Rock wool thermal insulation with density of 50 kg/m³, thermal conductivity of 0.035 W/(m.K) Thermal Side Insulation: 15 mm Glass wool with density 48kg/m³, conductivity of 0.031 W/(m.K). back plate: Embossed Aluminum Base Sheet Casing: Extruded Anodized Aluminum Casing; Sealing materials: Silicon and Absorber (Aluminum Selective Coated);Water + MonoethyleneGlicol	Simsek (ORION 433)	Gross Area of 2.30 m²; Aperture Area of 2.10 m²; Absorber Area of 2.08 m²; Gross Dimensions (without support frame) : 1175 x 1960 x 81 mm; Dry Weight : 38 kg; Collector Fluid Volume: 1.26 Liters Material riser pipes and nos of manifolds: 10 nos Copper Pipes and 2 nos manifolds Maximum Operating Pressure 6 bars; Maximum Stagnation Temperature 220 °C
3	FLAT PLATE SOLAR COLLECTOR Absorber Materials: Tinox Energy Aluminum Selective; Solar Glass: 3,2 Tempered, Low-Iron Oxide Solar Glass; Thermal bottom insulation: 40 mm thickness Rock wool thermal insulation with density of 50 kg/m³, thermal conductivity of 0.035 W/(m.K) Thermal Side Insulation: 15 mm Glass wool with density 48 kg/m³, conductivity of 0.031 W/(m.K). back plate: Embossed Aluminum Base Sheet Casing: Extruded Anodized Aluminum Casing; Sealing materials: Silicon and Absorber (Aluminum Selective Coated); Water + MonoethyleneGlicol	Simsek (ORION 435)	Gross Area of 2.55 m²; Aperture Area of 2.33 m²; Absorber Area of 2.31 m²; Gross Dimensions (without support frame) : 1175 x 2170 x 81 mm; Dry Weight : 42 kg; Collector Fluid Volume: 1.35 Liters Material riser pipes and nos of manifolds: 10 nos Copper Pipes and 2 nos manifolds Maximum Operating Pressure 6 bars; Maximum Stagnation Temperature 220 °C

**DUBAI CENTRAL LABORATORY DEPARTMENT
DCLD-CQPS PRODUCT CONFORMITY CERTIFICATION SCHEME**

**SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL23020833**

- NOTE 1: This document forms an integral part of the Certificate of Product Conformity bearing the same certificate number.
- NOTE 2: The above product shall bear the DCLD Conformity Mark.
- NOTE 3: As applicable, other properties in the product standard specification which were excluded in the specific rules as approved by the certification body authorized personnel are to be verified by the end user of the product (if needed).
- NOTE 4: In accordance with Dubai Municipality requirements, any mandatory product manufactured in a certified factory and not covered under the approved scope of certification shall not be distributed, sold, or used within the Emirate of Dubai.

Original Issue Date : 07-07-2023

Current Issue Date : 07-07-2026

Valid Until : 06-07-2027

ENG. MAJED AL SHAMSI

CERTIFICATION AND QUALITY CONTROL OF PRODUCTS SECTION'S MANAGER