NAME: GOKULAKRISHNAN AS **ROLL NO :250701203**

EXPERIMENT 13

Exp No:13 Experiment to handle missing values and inappropriate data in a given data set

AIM:

Demonstrate an experiment to handle missing data and inappropriate data in a Data set using Python Pandas Library for Data Preprocessing**.**

DESCRIPTION:

Understand the procedure to handle missing and inappropriate data

Hotel.csv

CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary	Age_Group
1	20-25	4	Ibis	veg	1300	2	40000	20-25
2	30-35	5	LemonTree	Non-Veg	2000	3	59000	30-35
3	25-30	6	RedFox	Veg	1322	2	30000	25-30
4	20-25	-1	LemonTree	Veg	1234	2	120000	20-25
5	35+	3	Ibis	Vegetarian	989	2	45000	35+
6	35+	3	Ibys	Non-Veg	1909	2	122220	35+
7	35+	4	RedFox	Vegetarian	1000	-1	21122	35+
8	20-25	7	LemonTree	Veg	2999	-10	345673	20-25
9	25-30	2	Ibis	Non-Veg	3456	3	-99999	25-30
9	25-30	2	Ibis	Non-Veg	3456	3	-99999	25-30
10	30-35	5	RedFox	non-Veg	-6755	4	87777	30-35

ABOUT DATASET:

No.of Columns =9 (called as series – CustomerID, Age_Group, Rating(1-5),Hotel, FoodPreference,

Bill, NoOfPax, EstimatedSalary)

CutomerID: Numerical Continuous data

Age: Categorical Data

Rating (1-5): Numerical Discrete Data

Hotel: Categorical Data

Food: Categorical Data

Bill: Numerical Continuous data

NoOfPax: Numerical Discrete

EstimatedSalary: Numerical Continuous data

CODE:

```
import numpy as np
import pandas as pd
df=pd.read_csv("/content/Hotel.csv")
df
df.duplicated()
df.info()
df.drop_duplicates(inplace=True)
df
len(df)
index=np.array(list(range(0,len(df))))
df.set_index(index,inplace=True)
index
df.drop(['Age_Group_2'],axis=1,inplace=True)
df
df.CustomerID.loc[df.CustomerID<0]=np.nan
df.Bill.loc[df.Bill<0]=np.nan
df.EstimatedSalary.loc[df.EstimatedSalary<0]=np.nan
df
df['NoOfPax'].loc[(df['NoOfPax']<1) | (df['NoOfPax']>20)]=np.nan
df
df.Age_Group.unique()
df.Hotel.unique()
df.Hotel.replace(['Ibys'],'Ibis',inplace=True)
df.FoodPreference.unique()
df['FoodPreference'] = df['FoodPreference'].replace(['Vegetarian', 'veg'], 'Veg')
df['FoodPreference'] = df['FoodPreference'].replace(['non-Veg'], 'Non-Veg')
df['EstimatedSalary'] = df['EstimatedSalary'].fillna(round(df['EstimatedSalary'].mean()))
df['NoOfPax'] = df['NoOfPax'].fillna(round(df['NoOfPax'].median()))
df['Rating(1-5)'] = df['Rating(1-5)'].fillna(round(df['Rating(1-5)'].median()))
df['Bill'] = df['Bill'].fillna(round(df['Bill'].mean()))
df
```

OUTPUT:

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary	Age_Group_2
0	1	20-25	4	Ibis	Veg	1300	2	40000	20-25
1	2	30-35	5	LemonTree	Non-Veg	2000	3	59000	30-35
2	3	25-30	6	RedFox	Veg	1322	2	30000	25-30
3	4	20-25	-1	LemonTree	Veg	1234	2	120000	20-25
4	5	35+	3	Ibis	Vegetarian	989	2	45000	35+
5	6	35+	3	Ibys	Non-Veg	1909	2	122220	35+
6	7	35+	4	RedFox	Vegetarian	1000	2	21122	35+
7	8	20-25	7	LemonTree	Veg	2999	-10	345673	20-25
8	9	25-30	2	Ibis	Non-Veg	3456	3	-99999	25-30
9	9	25-30	2	Ibis	Non-Veg	3456	3	-99999	25-30
10	10	30-35	5	RedFox	non-Veg	6755	4	87777	30-35

	0
0	False
1	False
2	False
3	False
4	False
5	False
6	False
7	False
8	False
9	True
10	False

dtype: bool

```
<class 'pandas.core.frame.DataFrame'>
Index: 10 entries, 0 to 9
Data columns (total 8 columns):
 #   Column           Non-Null Count  Dtype  
---  ------           --------------  -----  
 0   CustomerID       10 non-null     float64
 1   Age_Group        10 non-null     object 
 2   Rating(1-5)      10 non-null     int64  
 3   Hotel            10 non-null     object 
 4   FoodPreference   10 non-null     object 
 5   Bill             10 non-null     float64
 6   NoOfPax          10 non-null     float64
 7   EstimatedSalary  10 non-null     float64
dtypes: float64(4), int64(1), object(3)
memory usage: 720.0+ bytes
```

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary	Age_Group_2
0	1	20-25	4	Ibis	Veg	1300	2	40000	20-25
1	2	30-35	5	LemonTree	Non-Veg	2000	3	59000	30-35
2	3	25-30	6	RedFox	Veg	1322	2	30000	25-30
3	4	20-25	-1	LemonTree	Veg	1234	2	120000	20-25
4	5	35+	3	Ibis	Vegetarian	989	2	45000	35+
5	6	35+	3	Ibys	Non-Veg	1909	2	122220	35+
6	7	35+	4	RedFox	Vegetarian	1000	2	21122	35+
7	8	20-25	7	LemonTree	Veg	2999	-10	345673	20-25
8	9	25-30	2	Ibis	Non-Veg	3456	3	-99999	25-30
10	10	30-35	5	RedFox	non-Veg	6755	4	87777	30-35

10

```
array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
```

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary	Age_Group_2
0	1	20-25	4	Ibis	Veg	1300	2	40000	20-25
1	2	30-35	5	LemonTree	Non-Veg	2000	3	59000	30-35
2	3	25-30	6	RedFox	Veg	1322	2	30000	25-30
3	4	20-25	-1	LemonTree	Veg	1234	2	120000	20-25
4	5	35+	3	Ibis	Vegetarian	989	2	45000	35+
5	6	35+	3	Ibys	Non-Veg	1909	2	122220	35+
6	7	35+	4	RedFox	Vegetarian	1000	2	21122	35+
7	8	20-25	7	LemonTree	Veg	2999	-10	345673	20-25
8	9	25-30	2	Ibis	Non-Veg	3456	3	-99999	25-30
9	10	30-35	5	RedFox	non-Veg	6755	4	87777	30-35

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary
0	1	20-25	4	Ibis	Veg	1300	2	40000
1	2	30-35	5	LemonTree	Non-Veg	2000	3	59000
2	3	25-30	6	RedFox	Veg	1322	2	30000
3	4	20-25	-1	LemonTree	Veg	1234	2	120000
4	5	35+	3	Ibis	Vegetarian	989	2	45000
5	6	35+	3	Ibys	Non-Veg	1909	2	122220
6	7	35+	4	RedFox	Vegetarian	1000	2	21122
7	8	20-25	7	LemonTree	Veg	2999	-10	345673
8	9	25-30	2	Ibis	Non-Veg	3456	3	-99999
9	10	30-35	5	RedFox	non-Veg	6755	4	87777

/tmp/ipykernel_703/2080958306.py:1: FutureWarning: ChainedAssignmentError: behaviour will change in pandas 3.0!
You are setting values through chained assignment. Currently this works in certain cases, but when using Copy-on-Write (which will become the default behaviour in pandas 3.0) this will never work to update the original DataFrame or Series, because the intermediate object on which we are setting values will behave as a copy.
A typical example is when you are setting values in a column of a DataFrame, like:

df["col"][row_indexer] = value

Use `df.loc[row_indexer, "col"] = values` instead, to perform the assignment in a single step and ensure this keeps updating the original `df`.

See the caveats in the documentation: https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy

```
  df.CustomerID.loc[df.CustomerID<0]=np.nan
```

```
/tmp/ipykernel_703/2080958306.py:1: SettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame

See the caveats in the documentation: https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy
  df.CustomerID.loc[df.CustomerID<0]=np.nan
/tmp/ipykernel_703/2080958306.py:2: FutureWarning: ChainedAssignmentError: behaviour will change in pandas 3.0!
You are setting values through chained assignment. Currently this works in certain cases, but when using Copy-on-Write (which will become the default behaviour in pandas 3.0) this will never work to update the original DataFrame or Series, because the intermediate object on which we are setting values will behave as a copy.
A typical example is when you are setting values in a column of a DataFrame, like:

df["col"][row_indexer] = value

Use `df.loc[row_indexer, "col"] = values` instead, to perform the assignment in a single step and ensure this keeps updating the original `df`.

See the caveats in the documentation: https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy
```

```
  df.Bill.loc[df.Bill<0]=np.nan
```

```
/tmp/ipykernel_703/2080958306.py:2: SettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame

See the caveats in the documentation: https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy
  df.Bill.loc[df.Bill<0]=np.nan
/tmp/ipykernel_703/2080958306.py:3: FutureWarning: ChainedAssignmentError: behaviour will change in pandas 3.0!
You are setting values through chained assignment. Currently this works in certain cases, but when using Copy-on-Write (which will become the default behaviour in pandas 3.0) this will never work to update the original DataFrame or Series, because the intermediate object on which we are setting values will behave as a copy.
A typical example is when you are setting values in a column of a DataFrame, like:

df["col"][row_indexer] = value

Use `df.loc[row_indexer, "col"] = values` instead, to perform the assignment in a single step and ensure this keeps updating the original `df`.
```

See the caveats in the documentation: https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy

```
df.EstimatedSalary.loc[df.EstimatedSalary<0]=np.nan
/tmp/ipykernel_703/2080958306.py:3: SettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame
```

See the caveats in the documentation: https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy

```
df.EstimatedSalary.loc[df.EstimatedSalary<0]=np.nan
```

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary
0	1.0	20-25	4	Ibis	Veg	1300.0	2	40000.0
1	2.0	30-35	5	LemonTree	Non-Veg	2000.0	3	59000.0
2	3.0	25-30	6	RedFox	Veg	1322.0	2	30000.0
3	4.0	20-25	-1	LemonTree	Veg	1234.0	2	120000.0
4	5.0	35+	3	Ibis	Vegetarian	989.0	2	45000.0
5	6.0	35+	3	Ibys	Non-Veg	1909.0	2	122220.0
6	7.0	35+	4	RedFox	Vegetarian	1000.0	2	21122.0
7	8.0	20-25	7	LemonTree	Veg	2999.0	-10	345673.0
8	9.0	25-30	2	Ibis	Non-Veg	3456.0	3	NaN
9	10.0	30-35	5	RedFox	non-Veg	6755.0	4	87777.0

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary
0	1.0	20-25	4	Ibis	Veg	1300.0	2.0	40000.0
1	2.0	30-35	5	LemonTree	Non-Veg	2000.0	3.0	59000.0
2	3.0	25-30	6	RedFox	Veg	1322.0	2.0	30000.0
3	4.0	20-25	-1	LemonTree	Veg	1234.0	2.0	120000.0
4	5.0	35+	3	Ibis	Vegetarian	989.0	2.0	45000.0
5	6.0	35+	3	Ibys	Non-Veg	1909.0	2.0	122220.0
6	7.0	35+	4	RedFox	Vegetarian	1000.0	2.0	21122.0
7	8.0	20-25	7	LemonTree	Veg	2999.0	NaN	345673.0
8	9.0	25-30	2	Ibis	Non-Veg	3456.0	3.0	NaN
9	10.0	30-35	5	RedFox	non-Veg	6755.0	4.0	87777.0

```
array(['20-25', '30-35', '25-30', '35+'], dtype=object)
array(['Ibis', 'LemonTree', 'RedFox', 'Ibys'], dtype=object)
array(['Veg', 'Non-Veg', 'Vegetarian', 'non-Veg'], dtype=object)
```

	CustomerID	Age_Group	Rating(1-5)	Hotel	FoodPreference	Bill	NoOfPax	EstimatedSalary
0	1.0	20-25	4	Ibis	Veg	1300.0	2.0	40000.0
1	2.0	30-35	5	LemonTree	Non-Veg	2000.0	3.0	59000.0
2	3.0	25-30	6	RedFox	Veg	1322.0	2.0	30000.0
3	4.0	20-25	-1	LemonTree	Veg	1234.0	2.0	120000.0
4	5.0	35+	3	Ibis	Veg	989.0	2.0	45000.0
5	6.0	35+	3	Ibis	Non-Veg	1909.0	2.0	122220.0
6	7.0	35+	4	RedFox	Veg	1000.0	2.0	21122.0
7	8.0	20-25	7	LemonTree	Veg	2999.0	2.0	345673.0
8	9.0	25-30	2	Ibis	Non-Veg	3456.0	3.0	96755.0
9	10.0	30-35	5	RedFox	Non-Veg	6755.0	4.0	87777.0

RESULT:

Thus, missing values, duplicate records, and inappropriate data in the Hotel dataset were handled successfully using Pandas. Missing values were replaced with suitable statistical values, and the dataset was cleaned for further analysis.