SHIT Sciences Humanities Information Technology

构石

# Correlation Between Coffee Consumption and Bug Density: A Longitudinal Study of Sleep-Deprived Software Developers

Hengist Chan[1], Ofer Yuan[1,*]

Affiliations and funding information

[1] Department of Software Engineering, Hypothetical Research Institute, Shenzhen, China

Correspondence: Hengist Chan (e-mail: hengistchan@outlook.com), Ofer Yuan (e-mail: oferyuan@outlook.com)

This work was supported by SHIT Journal Anonymous Fund (Grant No. PAPER-2026-001)

Abstract—This paper presents a longitudinal study examining the correlation between coffee consumption and software bug density among 10,000 software developers over a 6-month period. We found a significant negative correlation (Pearson r = -0.654, $p < 0.001$) between coffee intake and bug commits. The Spearman correlation was even stronger ($\rho$ = -0.859). Regression analysis indicates that each additional cup of coffee reduces bug count by approximately 3.26. Optimal coffee intake range is 4-6 cups/day. Our findings provide theoretical basis for coffee management strategies in software engineering teams.

INDEX TERMS Coffee Consumption, Bug Density, Sleep Deprivation, Software Engineering, Developer Productivity, Caffeine-Bug Coupling Theory, Longitudinal Study.

IMPACT STATEMENT This research establishes the first quantitative relationship model between coffee consumption and code defects, providing new perspectives for software engineering work environment optimization.

## I. INTRODUCTION

### A. 1.1 The Caffeine Crisis in Software Engineering

The modern software industry operates on an unspoken foundation: caffeine. From Silicon Valley startups to enterprise development teams, coffee consumption has become not merely a cultural phenomenon but a physiological necessity for maintaining competitive productivity levels. Recent industry surveys indicate that 94.3% of software developers consume caffeine daily, with an average intake of 3.7 cups per developer per day (TechCaffeine Report, 2024). This widespread dependency raises fundamental questions about the relationship between chemical stimulation and software quality.

The "Move Fast and Break Things" paradigm, popularized in the 2010s, inadvertently created a generation of developers who equate sleep deprivation with dedication and caffeine with productivity. Tech companies systematically design workspaces with strategically placed espresso machines, normalize late-night coding sessions, and celebrate "crunch time" heroics—all while production bugs continue to proliferate at alarming rates. The Global Software Quality Index (GSQI, 2025) reports that bug-related costs now exceed $2.4 trillion annually, with 67% of these bugs introduced during periods of documented high caffeine consumption and low sleep duration.

This paradox sits at the heart of modern software engineering: the very stimulant that enables extended working hours may simultaneously degrade the cognitive precision required for bug-free code. Yet remarkably, this relationship has received scant academic attention. The software engineering literature abounds with studies on testing methodologies, continuous integration, and code review practices, but remains conspicuously silent on the physiological state of the humans writing the code.

### B. 1.2 Prior Work on Developer Physiology

The intersection of developer physiology and software quality remains woefully underexplored in academic literature, despite its obvious practical significance. What little research exists tends to focus on narrow aspects without developing comprehensive theoretical frameworks.

The foundational work of Johnson & Patel (2018) established the "Sleep-Code Inverse Correlation Principle," demonstrating empirically that developers sleeping fewer than 6 hours produced 2.3× more bugs per 1000 lines of code. However, their study failed to account for caffeine consumption as a confounding variable, leaving open the question of whether sleep deprivation per se, or caffeine-mediated sleep deprivation, drove their observed effects.

Concurrently, the controversial "Caffeine Productivity Paradox" paper by Chen et al. (2019) claimed to identify a "Golden Caffeine Zone" between 200-350mg daily intake where productivity peaked without significant quality

degradation. Their methodology faced criticism for using self-reported bug counts and failing to control for developer experience levels. A subsequent retraction and republication (Chen et al., 2020) with improved controls found much weaker effects, though the "Golden Zone" hypothesis persists in industry folklore.

Williams & Okonkwo (2021) proposed the "Developer Fatigue Accumulation Model," a differential equation framework modeling cognitive decline over extended work periods. While mathematically elegant, their model treated fatigue as purely time-dependent, ignoring the complex dynamics of stimulant-driven alertness cycles that characterize real-world development practices.

The "Bug Genesis Theory" of Mikhailova (2022) represented the first serious attempt to model bug generation as a stochastic process influenced by developer state variables. Her framework introduced the concept of "Cognitive Error Probability" as a function of time-since-sleep, but notably excluded any pharmacological factors—a striking omission given the near-universal caffeine usage in the developer population.

Perhaps the most illuminating data comes not from academia but from internal industry studies, many of which remain proprietary. Leaked findings from a major tech company's 2023 internal audit (anonymized as "Company X") revealed that teams with unlimited free coffee showed 41% higher commit frequency but 58% higher bug density compared to teams with rationed caffeine access. This observational data, while lacking experimental controls, suggests complex non-linear dynamics that existing theoretical frameworks cannot adequately explain.

The existing literature suffers from several systematic limitations. Most studies treat caffeine consumption as a binary variable (consumes/doesn't consume) rather than modeling the continuous dynamics of blood concentration, tolerance accumulation, and circadian interaction effects. Sleep deprivation is similarly oversimplified, typically measured as total hours rather than accounting for circadian timing, sleep quality, or recovery sleep dynamics. Perhaps most critically, no prior work has developed a unified framework integrating caffeine dynamics, sleep debt accumulation, and bug generation as coupled differential systems.

### C. 1.3 Our Contributions

This paper presents the first comprehensive theoretical framework for understanding the tripartite relationship between caffeine consumption, sleep deprivation, and software bug generation. Our contributions span theoretical, methodological, and practical domains:

Theoretical Contributions:

- We develop the Caffeine-Bug Coupling Theory (CBCT), a differential equation framework modeling the dynamic interaction between blood caffeine concentration, sleep debt accumulation, and bug generation rate
- We prove the existence of critical thresholds beyond which "Debug Spirals" become inevitable
- We derive closed-form solutions for optimal coffee scheduling under productivity constraints

Methodological Contributions:

- We introduce four novel metrics—CEI, SDR, BV, and DSS—that provide quantitative tools for assessing developer state and predicting code quality
- We develop non-invasive measurement protocols for real-time tracking of these metrics in production environments
- We establish statistical methods for causal inference in the presence of extensive confounding variables

Practical Contributions:

- We provide evidence-based guidelines for organizational caffeine policies that balance productivity with quality
- We develop prediction algorithms for identifying developers at high risk of bug introduction
- We propose intervention strategies for breaking established Debug Spirals

While this paper focuses on theoretical development, we validate our framework against a longitudinal dataset of 847 developers across 23 organizations, comprising 2.3 million lines of committed code, 127,000 documented bugs, and 15 million caffeine consumption events over 18 months. This validation demonstrates that our theoretical predictions match observed behavior with $R^2 = 0.73$, significantly outperforming baseline models.

Our work bridges the gap between rigorous academic modeling and practical software engineering concerns, providing both theoretical insights and actionable tools for improving software quality while respecting the physiological realities of human developers.

## II. THEORETICAL FRAMEWORK

### A. 2.1 Mathematical Preliminaries

We model the developer as a coupled dynamical system with four primary state variables:

1) C(t) - Blood caffeine concentration at time t (mg/L)
2) S(t) - Sleep debt accumulated at time t (hours)
3) D(t) - Cognitive degradation factor at time t (dimensionless, [0,1])
4) B(t) - Bug density in code produced at time t (bugs/kLOC)

Time t is measured in hours from an arbitrary reference point, typically the start of a work session or the last significant sleep period.

Assumptions:

- Caffeine metabolism follows first-order kinetics with half-life $\tau_c \approx 5$ hours (physiologically realistic)
- Sleep debt accumulates linearly during wakefulness and dissipates during sleep with efficiency $\eta_s$
- Cognitive degradation is a sigmoidal function of combined caffeine and sleep debt states

- Bug generation follows an inhomogeneous Poisson process with rate modulated by cognitive state

## B. 2.2 Coffee Consumption Dynamics Model

Blood caffeine concentration evolves according to a modified exponential decay process with discrete consumption events:

$$\frac{dC}{dt} = -\lambda \cdot C(t) + \sum_i \delta(t - t_i) \cdot c_i \tag{1}$$

Where:

- $\lambda = \ln(2)/\tau_c$ is the elimination rate constant ($\tau_c \approx 5$ hours)
- $\delta(t - t_i)$ is the Dirac delta function representing instantaneous coffee consumption at time $t_i$
- $c_i$ is the caffeine content of the i-th coffee (mg)

Between consumption events, caffeine follows simple exponential decay:

$$C(t) = C(t_0) \cdot e^{-\lambda(t-t_0)} \tag{2}$$

At consumption event $t_i$:

$$C(t_i^+) = C(t_i^-) + c_i \tag{3}$$

For chronic consumption patterns, we introduce a tolerance factor T(t):

$$\frac{dC}{dt} = -\lambda \cdot C(t) \cdot [1 + \kappa \cdot T(t)] + \sum_i \delta(t - t_i) \cdot c_i \tag{4}$$

$$\frac{dT}{dt} = -\gamma \cdot T(t) + \mu \cdot C(t) \tag{5}$$

For regular consumption of c mg every $\Delta t$ hours, the steady-state concentration oscillates between:

$$C_{min} = \frac{c \cdot e^{-\lambda \cdot \Delta t}}{1 - e^{-\lambda \cdot \Delta t}} \tag{6}$$

$$C_{max} = \frac{c}{1 - e^{-\lambda \cdot \Delta t}} \tag{7}$$

Average concentration:

$$\bar{C} = \frac{c}{\lambda \cdot \Delta t} \tag{8}$$

This provides the theoretical foundation for understanding how consumption timing affects baseline caffeine levels.

## C. 2.3 Sleep-Deprivation Impact Factor

Sleep debt S(t) accumulates during wake periods and dissipates during sleep:

$$\frac{dS}{dt} = \begin{cases} +1, & \text{if awake (circadian-adjusted)} \\ -\eta_s \cdot S, & \text{if sleeping} \end{cases} \tag{9}$$

In practice, sleep debt accumulation follows circadian rhythms:

$$\frac{dS}{dt} = [1 - \alpha \cdot \cos(2\pi(t - t_m)/24)] \cdot I_{awake}(t) - \eta_s \cdot S \cdot I_{sleep}(t) \tag{10}$$

Where $t_m$ is the time of maximum circadian alertness (typically $\approx 6$ PM), $\alpha \in [0, 1]$ controls circadian amplitude.

We identify a critical sleep debt $S_{crit} \approx 16$ hours beyond which cognitive function degrades non-linearly:

$$D_{cognitive}(t) = \tanh(S(t)/S_{crit}) \tag{11}$$

This hyperbolic tangent form captures the empirical observation that moderate sleep deprivation ($S < S_{crit}$) produces roughly linear cognitive decline, while severe deprivation ($S > S_{crit}$) leads to catastrophic degradation.

During sleep, sleep debt dissipates with efficiency $\eta_s \approx 1.5$:

$$S(t + t_{sleep}) = S(t) \cdot e^{-\eta_s \cdot t_{sleep}} \tag{12}$$

However, recovery efficiency decreases with circadian misalignment.

## D. 2.4 Bug Generation Probability Distribution

Bug generation is modeled as an inhomogeneous Poisson process with rate $\lambda_{bug}(t)$ modulated by cognitive state:

$$\lambda_{bug}(t) = \lambda_0 \cdot [1 + \alpha_c \cdot C(t) + \alpha_s \cdot S(t) + \alpha_{cs} \cdot C(t) \cdot S(t)] \tag{13}$$

Where:

- $\lambda_0$ is baseline bug rate (bugs/hour of coding)
- $\alpha_c$ captures caffeine effects
- $\alpha_s$ captures sleep deprivation effects
- $\alpha_{cs}$ captures interaction effects

Empirical parameter values based on our longitudinal study:

$$\lambda_0 = 0.12 \text{ bugs/hour} \tag{14}$$

$$\alpha_c = -0.002 \text{ (mg/L)}^{-1} \text{ (mild protective effect at low concentrations)} \tag{15}$$

$$\alpha_s = +0.08 \text{ hour}^{-1} \text{ (strong degradation effect)} \tag{16}$$

$$\alpha_{cs} = +0.0003 \text{ (mg} \cdot \text{hour/L)}^{-1} \text{ (dangerous interaction)} \tag{17}$$

The negative $\alpha_c$ indicates that moderate caffeine improves focus and reduces bugs, while the positive $\alpha_{cs}$ shows that combining caffeine with sleep deprivation creates synergistic cognitive impairment.

For extreme states, we use a non-linear model:

$$\lambda_{bug}(t) = \lambda_0 \cdot \exp(\beta_1 \cdot S(t) + \beta_2 \cdot [C(t) - C_{opt}]^2) \tag{18}$$

Where $C_{opt} \approx 4$ mg/L is the optimal caffeine concentration.

Given coding velocity $v(t)$ in lines/hour, bug density in committed code is:

$$B(t) = \frac{\lambda_{bug}(t)}{v(t)} \tag{19}$$

This accounts for the confounding effect that caffeine increases coding speed $v(t)$ but also affects bug rate $\lambda_{bug}(t)$.

## E. 2.5 Novel Metrics

We introduce four composite metrics:

1) Caffeine Efficiency Index (CEI): Productivity per unit caffeine
2) Sleep Debt Ratio (SDR): Actual sleep / optimal sleep
3) Bug Velocity (BV): Rate of bug introduction (bugs/hour)
4) Developer Sustainability Score (DSS): Composite metric (0-100)

These metrics are defined as follows:

$$CEI(t) = \frac{P(t)}{C(t)} = \text{Productivity per mg caffeine} \tag{20}$$

$$SDR(t) = \frac{S(t)}{S_{crit}} \tag{21}$$

$$BV(t) = \frac{dB}{dt} = \lambda_{bug}(t) - \lambda_{fix}(t) \tag{22}$$

$$\begin{aligned} DSS(t) = {} & w_1 \cdot CEI_{norm}(t) + w_2 \cdot [1 - SDR(t)] \\ & + w_3 \cdot \exp(-BV(t)/\lambda_{ref}) \\ & + w_4 \cdot \exp(-[C(t) - C_{opt}]^2/\sigma^2) \end{aligned} \tag{23}$$

Typical weights: $w_1 = 0.3$ (efficiency), $w_2 = 0.3$ (rest), $w_3 = 0.25$ (quality), $w_4 = 0.15$ (caffeine optimization).

DSS Interpretation:

- DSS > 0.8: Highly sustainable, long-term viable
- DSS = 0.6-0.8: Moderately sustainable, monitor closely
- DSS = 0.4-0.6: Marginally sustainable, intervention recommended
- DSS < 0.4: Unsustainable, immediate intervention required

## III. METHODS

### A. 3.1 Study Design

This multi-center longitudinal study was conducted over 6 months (July 1 to December 27, 2025). The study protocol was approved by the institutional ethics review board (Approval No. SHIT-2026-001).

We employed stratified random sampling to recruit participants from 23 technology companies of varying types. Stratification factors included:

- Company size: Startup (<50), Mid-size (50-500), Large (>500)
- Tech stack: Web development, Mobile development, Systems programming, Data science
- Geographic region: North America, Europe, Asia

Participants were required to install our mobile application, which continuously collected coffee consumption and sleep data in the background. Code commit and bug data were obtained via API integration with company Git repositories.

### B. 3.2 Participants

The final sample included 10,000 software developers:

- Male: 7,420 (74.2%)
- Female: 2,310 (23.1%)
- Other/Unspecified: 270 (2.7%)

Experience level distribution:

- Junior (<2 years): 2,500 (25%)
- Mid-level (2-5 years): 5,000 (50%)
- Senior (>5 years): 2,500 (25%)

Primary programming languages: JavaScript (2,125), Python (1,875), Java (1,500), Go (1,250), TypeScript (1,000), C++ (750), Rust (625), Kotlin (875).

### C. 3.3 Data Collection

Data collection included:

1) Coffee intake (cups/day): Self-reported via mobile app including time, type (espresso, latte, Americano), and quantity
2) Sleep duration (hours/day): Collected via wearables (Fitbit, Apple Watch) and mobile app
3) Bug commits (count/day): Extracted from Git history, defined as commits tagged as "bug", "fix", "issue"
4) Lines of code (lines/day): Daily committed lines (additions + modifications)
5) Covariates: Day of week, weekend status, crunch period, experience level, programming language

Data quality assurance measures included:

- Outlier detection: Excluded records with coffee > 15 cups or sleep > 12 hours
- Missing data: Multiple imputation
- Validation: 10% random sample cross-validated with company records

### D. 3.4 Statistical Analysis

Statistical analysis plan included:

1) Descriptive statistics: Mean, SD, median, quartiles for all variables
2) Correlation analysis: Pearson correlation, Spearman rank correlation
3) Regression models:
   - Linear regression: $Bug = \beta_0 + \beta_1 \cdot Coffee + \varepsilon$
   - Multiple regression: Controlling for sleep, LOC, experience
   - Polynomial regression: Testing non-linear relationships
   - Mixed-effects model: $Bug \sim Coffee + (1|DeveloperID)$
4) Subgroup analysis: By programming language, experience level, day of week
5) Effect sizes: Cohen's d, $\eta^2$, Pearson's r

All tests used two-tailed significance level $\alpha = 0.05$.

| Variable | Mean | SD | Min | Median | Max |
|---|---|---|---|---|---|
| Coffee intake (cups) | 3.83 | 3.51 | 0 | 4 | 15 |
| Sleep hours | 5.60 | 1.37 | 2 | 6 | 9 |
| Bug commits | 14.90 | 17.49 | 0 | 10 | 47 |
| Lines of code | 79.31 | 95.40 | 0 | 45 | 500 |

TABLE I: Descriptive Statistics (n = 1,800,000)




Fig. 1: Relationship between coffee intake and bug commits. Solid line shows linear regression fit ($R^2$ = 0.428).

## IV. RESULTS

### A. 4.1 Descriptive Statistics

Table I presents descriptive statistics for all study variables. The data collection period yielded 1,800,000 daily observation records.

Coffee intake exhibited a right-skewed distribution, peaking at 4-5 cups. Sleep duration was approximately normal, peaking at 5-6 hours. Bug count exhibited clear Poisson distribution characteristics.

### B. 4.2 Correlation Analysis

Table II presents correlation analysis results for main variables.

| Comparison | Pearson r | p-value | Spearman $\rho$ | p-value |
|---|---|---|---|---|
| Coffee vs Bugs | -0.654 | <0.001*** | -0.859 | <0.001*** |
| Sleep vs Bugs | -0.286 | <0.001*** | -0.331 | <0.001*** |
| Coffee vs Sleep | 0.271 | <0.001*** | 0.247 | <0.001*** |

TABLE II: Correlation Analysis (n = 1,800,000)

The most important finding is the strong negative correlation between coffee intake and bug count (Pearson r = -0.654, p < 0.001). This means developers who drink more coffee tend to commit fewer bugs. The Spearman correlation coefficient was even stronger ($\rho$ = -0.859), indicating a non-linear relationship.

Figure 1 shows the scatter plot with regression line.

Figure 2 shows the time trend over the 6-month study period.




Fig. 2: Time trends of coffee intake and bugs during the study period (6-month rolling average).




Fig. 3: Bug density heatmap by experience level and hour.

Figure 3 shows the circadian rhythm pattern of bug density.

Figure 4 shows the productivity-debt tradeoff curves.

Figure 5 shows bug rate comparison by programming language.

Figure 6 shows the correlation heatmap of all variables.

### C. 4.3 Regression Models

Table III presents results from various regression models.

| Model | $R^2$ | $\beta$ (Coffee) | p-value |
|---|---|---|---|
| Linear regression | 0.428 | -3.26 | <0.001*** |
| Multiple regression | 0.460 | -2.89 | <0.001*** |
| Polynomial regression | 0.674 | - | <0.001*** |
| Mixed effects | - | -3.15 | <0.001*** |

TABLE III: Regression Model Comparison

Linear regression indicates that each additional cup of coffee reduces bug count by 3.26 (95% CI: [3.21, 3.31], p < 0.001).

Polynomial regression (including quadratic terms) significantly improved fit ($\Delta R^2$ = 0.246), indicating non-linear relationships. Optimal coffee intake is 4-6 cups/day.

Mixed-effects models controlling for individual differences remained significant ($\beta$ = -3.15, p < 0.001).

### D. 4.4 Subgroup Analysis

Table IV presents subgroup analysis results by programming language and experience level.




Fig. 4: Productivity-debt tradeoff curves. Solid lines show expected productivity under different coffee strategies.




Fig. 5: Bug rate comparison boxplots by programming language.

Day-of-week analysis revealed significant "Monday Effect": Monday showed highest coffee (5.31 cups), lowest bugs (12.21). Weekend coffee dropped to 2.10 cups, bugs rose to 21.73 ($p < 0.001$).

By programming language, C++ showed strongest coffee-bug correlation ($r = -0.695$), Go weakest ($r = -0.625$). Kruskal-Wallis test indicated significant differences between languages ($H = 847.32$, $p < 0.001$).

By experience level, senior developers had 16% fewer bugs than juniors, but also slightly weaker coffee-bug correlation ($r = -0.627$ vs $-0.667$).

## V. DISCUSSION

### A. 5.1 Interpretation of Findings

This study provides the first empirical evidence for the quantitative relationship between coffee intake and software bugs. Our primary finding—strong negative correlation ($r = -0.654$, $p < 0.001$)—supports our hypothesis that caffeine can improve alertness and attention, thereby reducing code defects.

Interestingly, the Spearman correlation coefficient ($\rho = -0.859$) was much stronger than Pearson, indicating non-linearity. Our polynomial regression confirmed this, with optimal coffee intake at 4-6 cups/day. Beyond this range, diminishing returns occur—consistent with the "inverted U-shaped" dose-response curve known in pharmacology.




Fig. 6: Correlation heatmap of all study variables.

| Subgroup | Mean Bugs | Coffee-Bug r | p-value |
|---|---|---|---|
| By Language: | | | |
| Go | 13.00 | -0.625 | <0.001 |
| Kotlin | 13.68 | -0.631 | <0.001 |
| TypeScript | 13.75 | -0.638 | <0.001 |
| Python | 14.52 | -0.645 | <0.001 |
| JavaScript | 15.32 | -0.658 | <0.001 |
| Java | 15.89 | -0.662 | <0.001 |
| Rust | 16.53 | -0.681 | <0.001 |
| C++ | 17.71 | -0.695 | <0.001 |
| By Experience: | | | |
| Senior | 13.13 | -0.627 | <0.001 |
| Mid | 15.11 | -0.659 | <0.001 |
| Junior | 15.68 | -0.667 | <0.001 |

TABLE IV: Subgroup Analysis Results

The "Monday Effect" is particularly noteworthy: highest coffee consumption and lowest defects at the start of the work week. This may reflect the "fresh start" effect combined with Monday work motivation. Conversely, weekend coffee consumption dropped by half, bugs nearly doubled—supporting our theoretical prediction that caffeine state directly affects cognitive performance.

Language differences are also illuminating: C++ and Rust showed strongest coffee-bug correlation, possibly reflecting the stricter memory management requirements of these languages requiring higher cognitive alertness. In contrast, more modern languages like Go and Kotlin may be more tolerant of attention fluctuations due to stronger type systems and error handling.

### B. 5.2 Theoretical Implications

Our results provide empirical support for the Caffeine-Bug Coupling Theory (CBCT). Our differential equation framework accurately captured the dynamic interplay

of caffeine metabolism, cognitive degradation, and bug generation.

Evidence for critical threshold effects is particularly noteworthy: we observed sharply diminishing returns after a certain caffeine threshold. This corresponds to the "Debug Spiral" phenomenon in our theoretical framework—once entering this region, further caffeine increases only exacerbate the problem.

Our four novel metrics—CEI, SDR, BV, and DSS—proved valuable predictive tools. Mixed-effects models showed that controlling for these metrics attenuated the coffee-bug relationship, indicating they partially mediate this relationship.

### C. 5.3 Limitations

This study has several important limitations:

1) Causal inference: Although we used mixed-effects models to control for confounders, the observational design limits causal conclusions. The negative correlation between coffee and bugs may be due to third variables (e.g., task difficulty, project urgency).
2) Self-report bias: Coffee consumption data relied on self-report, potentially subject to recall bias and social desirability bias.
3) Bug definition: Our bug indicator (Git commits tagged as "bug") may not capture all types of code issues, such as performance degradation and security vulnerabilities.
4) External validity: The sample was limited to volunteers, which may not generalize to all software developers. Startup and remote workers may differ particularly.
5) Unmeasured confounders: We could not control for other factors that may affect bug rates, such as code review practices, test coverage, and team dynamics.

Future research should consider randomized controlled trials to establish causal relationships and include more diverse developer populations.

### D. 5.4 Practical Implications

Despite these limitations, our research offers several actionable recommendations for software engineering practice:

1) Coffee strategy: Teams should encourage developers to consume 4-6 cups of coffee daily for optimal performance, but more than 7 cups may have negative effects.
2) Monday focus: Monday should be prioritized for code reviews since bug rates are lowest then.
3) Language-specific training: Teams using C++ and Rust should pay particular attention to developer rest and coffee management.
4) Sustainability monitoring: Our DSS metric can be used to identify developers at risk of unsustainable work patterns.

We caution against using caffeine as the sole driver of productivity. The health consequences of chronic sleep debt outweigh any short-term productivity gains. Organizations should prioritize work-life balance over caffeine dependence.

## VI. CONCLUSION

This paper establishes the quantitative relationship between coffee consumption and software bug density through large-scale longitudinal research. We found significant negative correlation (Pearson r = -0.654, Spearman $\rho$ = -0.859, $p < 0.001$), with optimal coffee intake at 4-6 cups/day.

The main contributions are summarized as follows:

First, we developed the Caffeine-Bug Coupling Theory (CBCT), a mathematical framework modeling caffeine metabolism, sleep debt, and bug generation as coupled differential systems.

Second, we introduced four novel metrics—CEI, SDR, BV, and DSS—providing quantitative tools for assessing developer state and predicting code quality.

Third, we validated our framework through a 6-month longitudinal dataset of 10,000 developers comprising 1.8 million observations.

Fourth, we provided detailed subgroup analysis by programming language, experience level, and day of week, revealing significant heterogeneity.

Fifth, we proposed evidence-based coffee management strategy recommendations for software engineering teams.

Future work will explore the application of our framework in real-time developer health monitoring systems, with intervention studies as the next step for establishing causal relationships.

## VII. MATERIALS AND METHODS

All analyses reported in this paper were conducted using Python 3.9. Data generation, statistical tests, and visualization code are available at GitHub (https://github.com/shit-journal/coffee-bug-correlation).

Main Python packages used: pandas (data processing), numpy (numerical computation), scipy.stats (statistical tests), statsmodels (regression analysis), matplotlib and seaborn (visualization).

All analyses used random seed 42 for reproducibility.

## VIII. SUPPLEMENTARY MATERIAL

Supplementary materials include:

- Complete dataset with 1,800,000 records
- Detailed output of all statistical analyses
- Additional visualizations including subgroup analysis by company size and region
- Data dictionary and codebook

Supplementary materials are available at the paper's homepage.

## IX. ACKNOWLEDGEMENTS

This work was supported by SHIT Journal Anonymous Fund (Grant No. PAPER-2026-001). We thank the IT teams of 23 participating companies, especially the startups that "loaned" developers for this research. We also thank our caffeine suppliers—without you, this research would never have been completed.

Special thanks to the anonymous reviewers of SHIT Journal for their valuable comments, especially regarding the mention of caffeine suppliers in the acknowledgements.

## References

[1] R. C. Atkinson and R. M. Shiffrin, "Human memory: A proposed system and its control processes," Psychol. Rev., vol. 75, no. 8, pp. 512–559, 1968.
[2] J. D. Programmer and K. M. Reviewer, "Coffee: The solution to all software engineering problems," J. Caffeine Stud., vol. 42, no. 1, pp. 1–42, 2024.
[3] A. Nehlig, "Is caffeine a cognitive enhancer?" J. Alzheimers Dis., vol. 20, no. S1, pp. S85–S94, 2010.
[4] B. A. StackOverflower, "How to debug while on your fifth cup of coffee: A case study," Stack Overflow Q., vol. 7, no. 3, pp. 100–115, 2023.
[5] C. H. S. Ruxton, "The impact of caffeine on mood, cognitive function, performance and hydration," Br. J. Nutr., vol. 101, no. 8, pp. 1715–1727, 2009.
[6] X. Y. GitCommiter, "Committing at 3 AM: A survival guide for the sleep-deprived developer," arXiv preprint arXiv:2404.01234, 2024.
[7] S. T. Johnson and A. B. Patel, "Sleep-code inverse correlation principle," J. Softw. Eng., vol. 12, no. 2, pp. 45–67, 2018.
[8] Anonymous, "Leaked: Company X internal audit on coffee and bugs," Whistleblower Weekly, vol. 5, no. 12, 2023.
[9] W. Chen et al., "The caffeine productivity paradox: A golden zone between 200-350mg," Proc. ACM SIGSOFT Symp., pp. 234–245, 2019.
[10] W. Chen et al., "Retraction and republication: The caffeine productivity paradox revisited," J. Softw. Eng., vol. 15, no. 4, pp. 567–580, 2020.
[11] J. K. Williams and C. Okonkwo, "Developer fatigue accumulation model: A differential equation approach," IEEE Trans. Softw. Eng., vol. 47, no. 8, pp. 1567–1582, 2021.
[12] E. Mikhailova, "Bug genesis theory: A stochastic process approach," Empir. Softw. Eng., vol. 27, no. 6, pp. 1–25, 2022.
[13] Global Software Quality Index, "Annual bug cost report," 2025. [Online]. Available: https://gsqi.example.org
[14] TechCaffeine Report, "Caffeine consumption in tech industry," 2024. [Online]. Available: https://techcaffeine.example.org
[15] R. P. Refactorer, "Latte, espresso, or Yerba mate? A comparative analysis of caffeinated beverages in software engineering teams," J. Beverage Stud., vol. 18, no. 7, pp. 88–99, 2022.
[16] M. Debugger, "Statistical methods for ignoring statistical significance," J. Made-Up Stats., vol. 1, no. 1, pp. 999–1001, 2021.
[17] J. Cohen, "Statistical Power Analysis for the Behavioral Sciences," Lawrence Erlbaum Associates, 1988.
[18] J. W. Tukey, "Exploratory Data Analysis," Addison-Wesley, 1977.
[19] A. Gelman and J. Hill, "Data Analysis Using Regression and Multilevel/Hierarchical Models," Cambridge University Press, 2006.
[20] D. Bates, M. Mächler, B. Bolker, and S. Walker, "Fitting linear mixed-effects models using lme4," J. Stat. Softw., vol. 67, no. 1, pp. 1–48, 2015.
[21] S. Weisberg, "Applied Linear Regression," Wiley, 2005.
[22] F. E. Harrell, "Regression Modeling Strategies," Springer, 2015.
[23] R. Ikezaki and S. F. Nomura, "A survey of software engineering metrics," Adv. Comput., vol. 93, pp. 143–201, 2014.
[24] M. Nagappan, T. Ball, and A. E. Hassan, "Software engineering and HCI: Nine stories from the trenches," Proc. 36th Int. Conf. Softw. Eng., pp. 628–637, 2014.
[25] F. Rahman and P. Devanbu, "How, and why, to use GitHub data for empirical software engineering research?" Empir. Softw. Eng., vol. 20, no. 6, pp. 1731–1739, 2015.
[26] E. Kalliamvakou, G. Damian, K. Blincoe, L. Singer, and D. M. German, "The promises and perils of mining GitHub," Proc. 11th Working Conf. Mining Softw. Repos., pp. 92–101, 2014.