

Assignment 2 - Operators in C language

1. Write a program to print unit digit of a given number

Program -

```
#include <stdio.h>

int main()
{
    int n;
    printf("Enter a number: ");
    scanf("%d",&n);
    int unit_digit = n % 10;
    printf("Unit digit is %d",unit_digit);

    return 0;
}
```

Output -

Enter a number: 345
Unit digit is 5

2. Write a program to print a given number without its last digit.

Program -

```
#include <stdio.h>

int main()
{
    int n;
    printf("Enter a number: ");
    scanf("%d",&n);
    printf("Number without it's last digit is %d",n/10);

    return 0;
}
```

Output -

Enter a number: 78923
Number without it's last digit is 7892

3. Write a program to swap values of two int variables

Program -

```
#include <stdio.h>

int main()
{
    int a , b , c;

    printf("Enter the value of a and b: ");
    scanf("%d%d",&a,&b);
    printf("Before swapping: a = %d , b = %d",a,b);
    c = a;
    a = b;
    b = c;

    printf("\nAfter swapping: a = %d , b = %d",a,b);

    return 0;
}
```

Output -

Enter the value of a and b: 4 5
 Before swapping: a = 4 , b = 5
 After swapping: a = 5 , b = 4

4. Write a program to swap values of two int variables without using a third variable.

Program -

```
#include <stdio.h>

int main()
{
    int a , b;

    printf("Enter the value of a and b: ");
    scanf("%d%d",&a,&b);
    printf("Before swapping: a = %d , b = %d",a,b);
    a = a + b;
    b = a - b;
    a = a - b;

    printf("\nAfter swapping: a = %d , b = %d",a,b);

    return 0;
}
```

Output-

Enter the value of a and b: 7 2
 Before swapping: a = 7 , b = 2
 After swapping: a = 2 , b = 7

5. Write a program to input a three-digit number and display the sum of the digits.

Program -

```
#include <stdio.h>
int main()
{
    int num , digit , sum = 0;

    printf("Enter a three digit number: ");
    scanf("%d",&num);

    while(num)
    {
        digit = num % 10;
        num = num / 10;
        sum += digit;
    }

    printf("Sum of it's digits is %d",sum);

    return 0;
}
```

Output -

Enter a three digit number: 345
Sum of it's digits is 12

6. Write a program which takes a character as an input and displays its ASCII code.

Program -

```
#include <stdio.h>
int main()
{
    char ch;
    printf("Enter a character: ");
    scanf("%c",&ch);
    printf("ASCII code of %c is %d",ch,ch);

    return 0;
}
```

Output -

Enter a character: A
ASCII code of A is 65

7. Write a program to find the position of first 1 in LSB.

Program -

8. Write a program to check whether the given number is even or odd using a bitwise operator.

Program -

```
#include <stdio.h>
int main()
{
    int num;

    printf("Enter a number: ");
    scanf("%d",&num);
    if(num & 1)
        printf("Not an even number!");
    else
        printf("Even number!");
    return 0;
}
```

Output -

Enter a number: 24
Even number!

9. Write a program to print size of an int, a float, a char and a double type variable

Program -

```
#include <stdio.h>
int main()
{
    printf("Size of int type variable is %d",sizeof(int));
    printf("\nSize of float type variable is %d",sizeof(float));
    printf("\nSize of char type variable is %d",sizeof(char));
    printf("\nSize of double type variable is %d",sizeof(double));

    return 0;
}
```

Output -

Size of int type variable is 4
Size of float type variable is 4
Size of char type variable is 1
Size of double type variable is 8

10. Write a program to make the last digit of a number stored in a variable as zero. (Example - if x=2345 then make it x=2340)

Program -

```
#include <stdio.h>
int main()
{
    int x;

    printf("Enter a number: ");
    scanf("%d",&x);

    x = (x/10) * 10;

    printf("Resulting number is %d",x);
    return 0;
}
```

Output -

Enter a number: 2345
Resulting number is 2340

11. Write a program to input a number from the user and also input a digit. Append a digit in the number and print the resulting number. (Example - number=234 and digit=9 then the resulting number is 2349)

Program -

```
#include <stdio.h>
int main()
{
    int num , digit;

    printf("Enter a number and a digit: ");
    scanf("%d%d",&num,&digit);

    num = num * 10 + digit;

    printf("Resulting number is %d",num);

    return 0;
}
```

Output -

Enter a number and a digit: 234 9
Resulting number is 2349

12. Assume price of 1 USD is INR 76.23. Write a program to take the amount in INR and convert it into USD.

Program -

```
#include <stdio.h>
int main()
{
    float USD = 76.23;
    int INR;

    printf("Enter the amount in INR: ");
    scanf("%d",&INR);

    USD = INR/USD;

    printf("%d USD is %f INR",INR,USD);

    return 0;
}
```

Output -

Enter the amount in INR: 34
34 USD is 0.446019 INR

13. Write a program to take a three-digit number from the user and rotate its digits by one position towards the right.

Program -

```
#include <stdio.h>
int main()
{
    int num;
    printf("Enter a three-digit number: ");
    scanf("%d",&num);

    printf("Before rotation : %d",num);

    num = ((num % 10) * 100) + (num / 10);
    printf("\nAfter rotation : %d",num);

    return 0;
}
```

Output -

Enter a three-digit number: 546
Before rotation : 546
After rotation : 654