



EXTERNAL PARTNER DOCUMENTATION

SkyLink API

External Integration Guide

Version 1.0 · May 2025 · REST / JSON

About SkyLink API

SkyLink is the official 247Travels flight integration API. It provides programmatic access to real-time flight search, live price verification, and instant PNR generation through a unified, supplier-agnostic REST interface. Powered by Amadeus, Verteil NDC, and Brightsun.

Table of Contents

- 1. Introduction & Overview
- 2. Authentication & Login
- 3. Base URL & Versioning
- 4. Error Handling
- 5. Flight Search
- 6. Flight Pricing
- 7. Flight Reservation
 - 7.1 Traveller Object Structure
 - 7.2 PNR Restrictions
- 8. Workflow Integration Guide
- 9. Rate Limits & Best Practices
- 10. Contact & Support

1. Introduction & Overview

SkyLink is the 247Travels unified flight integration API. It provides your platform with access to live flight inventory, real-time pricing, and instant booking — all through a single, clean REST interface. You do not need to integrate with any airline or GDS system directly; SkyLink handles all of that for you.

Feature	Detail
Protocol	HTTPS REST — JSON request and response bodies
Authentication	JWT Bearer Token (Authorization header)
Search Modes	Local database · Live external inventory
PNR Generation	Instant order creation — no manual ticketing queue
Currency	Multi-currency support
Passenger Types	Adults · Children · Infants
Trip Types	One-way · Round trip · Multi-city

2. Authentication

All SkyLink API endpoints require a valid JWT Bearer token obtained from POST `/api/login`. Include the token in every request header.

Request Header

```
Authorization: Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...
```

Login Endpoint

POST `/api/login`

Obtain JWT Access Token

Authenticates a user and returns a short-lived access token and a long-lived refresh token. Only accounts with the api or admin role can successfully authenticate.

Login Request Parameters

Parameter	Type	Required	Description
email	string	Yes	Registered email address.
password	string	Yes	Account password.
remember_me	boolean	No	Extended session flag. Does not affect token expiry.

Login Response — Success

```
{
  "status": "success",
  "code": "LOGIN_SUCCESS",
  "data": {
    "user_id": "USR-001",
    "email": "partner@example.com",
    "name": "John Doe",
    "role": "api",
    "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
    "refresh_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
    "token_type": "Bearer",
    "expires_in": 900
  }
}
```

Token Details

Field	Type	Description
access_token	string	JWT token. Valid for 15 minutes (900 seconds). Send in Authorization header.
refresh_token	string	Long-lived token. Valid for 15 days. Use to obtain a new access_token.
expires_in	integer	Access token lifetime in seconds. Always 900.
token_type	string	Always "Bearer".

Login Error Responses

Error Code	Description
INVALID_JSON	Request body is not valid JSON.
EMPTY_FIELDS	Email or password missing from request.
INVALID_CREDENTIALS	Email not found or password incorrect.
ACCOUNT_LOCKED	Too many failed attempts. Account temporarily locked.
EMAIL_NOT_VERIFIED	Email address has not been verified.
ACCOUNT_INACTIVE	Account is disabled.
ACCOUNT_BANNED	Account is permanently banned.
ROLE_NOT_PERMITTED	Account role does not have API access (not api or admin).

3. Base URL & Versioning

All API requests are made to:

```
https://247travels.com/api/
```

■ All requests must use HTTPS. HTTP connections will be rejected.

4. Error Handling

SkyLink uses standard HTTP status codes alongside a consistent JSON error body.

HTTP Code	Meaning	Common Cause
200	Success	Request completed successfully
400	Bad Request	Missing or invalid parameters
401	Unauthorized	Missing, invalid, or expired JWT token
403	Forbidden	PNR blocked for this carrier or supplier
404	Not Found	Resource or booking not found
502	Bad Gateway	Supplier API error or unreachable
500	Server Error	Unexpected internal error

Error Response Body

```
{
  "success": false,
  "message": "Human-readable description",
  "error": "Technical detail (supplier errors only)"
}
```

5. Flight Search

The search endpoint returns available flight offers for your requested route. Use `search_mode=local` to query our internal flight database, or `search_mode=external` to query live airline inventory in real time.

POST `/api/flights/search`

Search Available Flights

Returns a list of available flight offers. Each result contains a `booking_token` required to call the pricing and reservation endpoints.

Request Parameters — Core (All Roles)

Parameter	Type	Required	Description
<code>search_mode</code>	string	Yes	"local" — internal database. "external" — live supplier inventory.
<code>from</code>	string	No	Origin IATA airport code. E.g. "LOS". Not required for multicity — auto-derived from <code>routes[0].from</code> .
<code>to</code>	string	No	Destination IATA airport code. E.g. "DXB". Not required for multicity — auto-derived from <code>routes[-1].to</code> .
<code>flights_departure_date</code>	string	No	Departure date YYYY-MM-DD. Not required for multicity — auto-derived from <code>routes[0].date</code> .
<code>flights_return_date</code>	string	No	Return date YYYY-MM-DD. Required when <code>flight_type=roundtrip</code> .
<code>flight_type</code>	string	Yes	"oneway", "roundtrip" (alias: "return"), or "multicity".
<code>adults</code>	integer	Yes	Number of adult passengers. Min 1, max 9.
<code>children</code>	integer	No	Number of child passengers. Default 0.
<code>infants</code>	integer	No	Number of infant passengers. Cannot exceed adults. Default 0.
<code>class</code>	string	No	"economy", "premium_economy", "business", or "first". Default: economy.
<code>currency</code>	string	No	Display currency code. E.g. "NGN", "USD". Default: USD.
<code>routes</code>	array	No	Multi-city legs array. Each item: { "from": "LOS", "to": "LHR", "date": "YYYY-MM-DD" }. Minimum 2 legs required.

Example Request — One Way

```
{
  "search_mode": "external",
  "from": "LOS",
  "to": "DXB",
  "flight_type": "oneway",
  "flights_departure_date": "2026-06-26",
  "adults": 1,
  "children": 0,
  "infants": 0,
  "class": "economy",
  "currency": "NGN"
}
```

```
}
```

Example Request — Round Trip

Add `flights_return_date`. The value "roundtrip" is accepted and normalised internally.

```
{
  "search_mode": "external",
  "from": "LOS",
  "to": "LHR",
  "flight_type": "roundtrip",
  "flights_departure_date": "2026-06-26",
  "flights_return_date": "2026-07-10",
  "adults": 1,
  "children": 0,
  "infants": 0,
  "class": "economy",
  "currency": "NGN"
}
```

Example Request — Multi-City

For multi-city, only the `routes` array is required. You do not need to pass `from`, `to`, or `flights_departure_date` — the system automatically derives the origin from the first leg, the destination from the last leg, and the departure date from the first route date. A minimum of two legs is required.

```
{
  "search_mode": "external",
  "flight_type": "multicity",
  "adults": 1,
  "children": 0,
  "infants": 0,
  "class": "economy",
  "currency": "NGN",
  "routes": [
    { "from": "LOS", "to": "LHR", "date": "2026-06-20" },
    { "from": "LHR", "to": "JFK", "date": "2026-06-27" },
    { "from": "JFK", "to": "LOS", "date": "2026-07-05" }
  ]
}
```

✓ Origin, destination and departure date are resolved automatically from the routes array. In this example the system derives: origin = LOS, destination = LOS, departure = 2026-06-20.

Response — Success

```
{
  "success": true,
  "data": {
    "meta": {
      "search_id": "abc12345",
      "response_time_ms": 2840,
      "offices_searched": 4,
      "offices_with_results": 3,
      "total_flights": 20,
      "origin": "LOS",

```

```
"destination": "DXB",
"currency": "NGN"
},
"flights": [
{
"flight_no": "EK784",
"airline": "EK",
"airline_name": "Emirates",
"departure_code": "LOS",
"arrival_code": "DXB",
"departure_time": "17:40",
"arrival_time": "04:25",
"duration_time": "6h 45m",
"class": "Economy",
"baggage": "30kg",
"price": 759354,
"currency": "NGN",
"booking_token": "btk_3f8a2c1d9e7b..."
}
]
}
```

■ The booking_token returned for each flight result must be passed unchanged to /api/flights/pricing and /api/flights/reserve. Do not modify it.

6. Flight Pricing

The pricing endpoint re-validates a selected flight offer in real time against the live supplier system. It confirms the current price, detects changes since the search, and returns an updated booking_token with refreshed offer IDs.

POST /api/flights/pricing

Verify & Reprice Flight Offer

Confirms availability and current price. Always call this immediately before /api/flights/reserve. Returns updated booking_token with current offer state.

Request Parameters — api role

Parameter	Type	Required	Description
booking_token	string	Yes	Opaque token from /api/flights/search response. Encodes supplier+office+booking_data server-side.
passengers	object	Yes	Passenger counts: { "adults": 1, "children": 0, "infants": 0 }
currency	string	No	Display currency code. E.g. "NGN". Default: USD.
class	string	No	"economy", "premium_economy", "business", or "first". Default: economy.

Example Request

```
{
  "booking_token": "btk_3f8a2c1d9e7b4a5f6c2d1e8f9a0b3c7d",
  "passengers": { "adults": 1, "children": 0, "infants": 0 },
  "currency": "NGN",
  "class": "economy"
}
```

Response — Success

```
{
  "success": true,
  "data": {
    "booking_token": "btk_3f8a2c1d9e7b4a5f6c2d1e8f9a0b3c7d",
    "verified": true,
    "verification_skipped": false,
    "price_changed": false,
    "class_letter_changed": false,
    "cabin_class_shifted": false,
    "original_price": 759354,
    "verified_price": 759354,
    "currency": "NGN",
    "passengers": { "adults": 1, "children": 0, "infants": 0, "total": 1 },
    "expires_at": "2026-05-17 14:30:00",
    "response_time_ms": 1240,
    "message": "Price verified — no change."
  }
}
```

■ Always use the booking_token from THIS response — not the one from search — when calling /api/flights/reserve. The token is refreshed after every pricing call.

7. Flight Reservation (PNR Generation)

The reservation endpoint creates a confirmed PNR immediately. Your PNR is returned in the response as soon as the airline confirms the order.

Payment Responsibility Notice

SkyLink API integration partners are required to collect full payment from their end users prior to calling this endpoint. The `/api/flights/reserve` endpoint does not enforce or process payment — it immediately generates a live airline PNR upon request. Calling this endpoint without prior payment collection constitutes a violation of the SkyLink API Terms of Service and may result in immediate suspension of API access, recovery of outstanding amounts, and legal action where applicable. 247Travels reserves the right to audit reservation activity and enforce accountability at its sole discretion.

POST `/api/flights/reserve`

Generate PNR — Create Flight Order

Submits passenger details and offer data to the supplier to create a confirmed flight booking. Returns the PNR reference immediately.

Request Parameters

Parameter	Type	Required	Description
booking_token	string	Yes	The booking_token from your <code>/api/flights/pricing</code> response.
travellers	object	Yes	Passenger details. See Traveller Object Structure below.
passengers	object	Yes	Passenger counts: { "adults": 1, "children": 0, "infants": 0 }
ticket_time_limit_hours	integer	No	Hours before ticketing deadline. Default 48.

Example Request

```
{
  "booking_token": "btk_3f8a2c1d9e7b4a5f6c2d1e8f9a0b3c7d",
  "passengers": { "adults": 1, "children": 0, "infants": 0 },
  "travellers": {
    "primary_guest": {
      "title": "Mr",
      "first_name": "John",
      "last_name": "Doe",
      "email": "john.doe@example.com",
      "phone": "08012345678",
      "country_code": "234",
      "dob": "1990-01-01",
      "gender": "male",
      "passport_number": "A12345678",
      "passport_expiry": "2030-01-01",
      "passport_issue_date": "2020-01-01",
      "nationality": "NG"
    }
  }
}
```

```

},
"travelers": {
"adult_0": { "...same as primary_guest..." }
}
},
"ticket_time_limit_hours": 48
}

```

Response — Success

```

{
"success": true,
"data": {
"pnr": "ABC123",
"booking_reference": "ABC123",
"booking_token": "btk_3f8a2c1d9e7b4a5f6c2d1e8f9a0b3c7d",
"carrier": "EK",
"status": "confirmed",
"passengers": { "adults": 1, "children": 0, "infants": 0, "total": 1 },
"ticket_time_limit_hours": 48,
"ticket_deadline": "2026-05-19 14:30:00",
"response_time_ms": 4820,
"message": "PNR generated successfully"
}
}

```

7.1 Traveller Object Structure

The travellers object contains `primary_guest` (always required — the lead passenger and booking contact) and `travelers` (additional passengers keyed by type and index).

Field	Type	Description
<code>title</code>	string	Salutation: Mr, Mrs, Ms, Miss, Dr, Prof.
<code>first_name</code>	string	First name exactly as on passport.
<code>last_name</code>	string	Last name / surname as on passport.
<code>other_name</code>	string	Middle or additional given name. Optional.
<code>email</code>	string	Contact email. Required for <code>primary_guest</code> .
<code>phone</code>	string	Phone number digits only. Required for <code>primary_guest</code> .
<code>country_code</code>	string	Phone country dialling code digits only. E.g. "234".
<code>dob</code>	string	Date of birth YYYY-MM-DD. E.g. "1990-01-01".
<code>gender</code>	string	"male" or "female".
<code>passport_number</code>	string	Passport number alphanumeric only.
<code>passport_expiry</code>	string	Passport expiry date YYYY-MM-DD.
<code>passport_issue_date</code>	string	Passport issue date YYYY-MM-DD.
<code>nationality</code>	string	Two-letter ISO country code. E.g. "NG", "GB", "US".

Multi-Passenger traveler Keys

Additional passengers go in the travelers object using these key patterns: adult_0, adult_1 (adults); child_0, child_1 (children); infant_0 (infants). adult_0 always mirrors primary_guest and is skipped internally — do not omit it.

7.2 PNR Restrictions

SkyLink supports three levels of PNR restriction. When triggered, the endpoint returns HTTP 403 with blocked: true before any supplier call is made.

Level	Scope	Description
1 — Supplier block	Entire supplier	All reservations via that supplier are blocked.
2 — Carrier block	Specific airlines	Named carrier codes are blocked under that supplier.
3 — Carrier whitelist	Specific airlines	Only listed carrier codes are permitted.

```
{
  "success": false,
  "blocked": true,
  "carrier": "KQ",
  "message": "KQ reservations are not available at this time."
}
```

8. Workflow Integration Guide

A complete flight booking follows four sequential steps. Each step returns data required by the next — never skip a step.

Step 1 — POST /api/flights/search

Search with search_mode=external. Returns results with booking_token per flight.



Step 2 — POST /api/flights/pricing

Send booking_token. Returns updated booking_token with current pricing.



Step 3 — POST /api/flights/reserve

Send booking_token + passenger details. Returns confirmed PNR immediately — no payment step required.

■ Never reuse a booking_token across multiple reserve calls. The token is marked used=1 after a successful reservation. Always get a fresh token via search → pricing for each new booking attempt.

Important — Payment Obligation

Integration partners must ensure that end-user payment is fully collected and confirmed on their own platform before calling /api/flights/reserve. This endpoint generates a live airline PNR immediately and unconditionally upon every valid request. Generating PNRs without prior payment collection is a breach of the SkyLink API Terms of Service and may result in suspension of API access and recovery of all costs incurred by 247Travels.

10. Rate Limits & Best Practices

Endpoint	Limit	Notes
/api/flights/search	60 / minute	Per authenticated user
/api/flights/pricing	30 / minute	Per authenticated user
/api/flights/reserve	10 / minute	Per authenticated user
/api/login	10 / minute	Per IP address

Best Practices

Cache search results

Offers expire within 10–15 minutes. Cache results and re-search if user takes longer.

Price immediately before reserve

Call /pricing within 5 minutes of /reserve to minimise expiry errors.

Store invoice_id immediately

Save the invoice_id from /reserve before redirecting to payment_url.

Store PNR on receipt

Save the PNR from the status endpoint as soon as has_pnr is true.

Poll status sensibly

Poll /status every 5–10 seconds for up to 5 minutes after payment. Stop on has_pnr or error.

Handle 502 gracefully

Implement user-friendly messaging and a re-search flow for supplier errors.

Refresh tokens proactively

The access_token expires in 15 minutes. Refresh before it expires to avoid mid-flow 401 errors.

10. Contact & Support

For integration support, API credentials, or technical assistance:

Lagos Office	19, Pariola Street, Ogudu G.R.A, Lagos, Nigeria
Abuja Office	T3, 3rd Floor, The Avenue Plaza, 27 Alexandria Street off Aminu Kano Crescent, Bannex Wuse 2, Abuja
Kano Office	12, Zoo Road, beside Sufi Mart, Kano
Phone	+234 705 7000 247 +234 911 1685 247 02014541252
Email	info@247travels.com
Website	www.247travels.com

This document is confidential and intended solely for authorised integration partners of 247Travels. SkyLink API v1.0 — © 2025 247Travels Limited.