A Comparative Analysis of Vision-Based and GPS-Based Speed Estimation Algorithms for Autonomous Vehicles

Denzel Baldacchino
Institute of Information & Communication Technology
Malta College or Arts, Science & Technology
Corradino Hill
Paola PLA 9032
denzel.baldacchino.g52078@mcast.edu.mt

I. Introduction

A. Theme & Topic Rationale

This research focuses on the theme of Intelligent Transport Systems (ITS) and Autonomous Vehicle Sensor Perception. Getting an accurate estimate of a vehicle's speed is super important for safety, especially for Advanced Driver Assistance Systems (ADAS) and autonomous navigation. While GPS is widely used, they frequently encounter signal degradation in urban canyons, tunnels, or adverse weather conditions, which can cause errors due to signal reflections (multipath errors) [1], [2]. On the other hand, estimating speed using dashcam footage is a cheaper, sensor-rich option [3], but it is inherently vulnerable to variations in lighting and computational latency. It's important to compare these two methods against a highly accurate baseline, specifically vehicle CAN-bus data. Such comparison elucidates the specific environmental limitations of each system and offers empirical evidence to inform the development of improved algorithms in the future.

B. Positioning & Research Onion

Based on Saunders' Research Onion [4], this research uses positivism, meaning seeing reality as something objective and separate from what other people think or interpret. The data that will be used is mainly measurable data like speeds, GPS coordinates and pixel shifts, with the researcher acting as an impartial observer by analysing the physical data. This research takes a deductive approach starting with already proved formulae and concepts such as the Haversine formula for GPS speeds and ego-motion tracking and comparing the data with each other to see which is more accurate. Even though the data comes from an archived source (Comma2k19) [5], the main objective for this research is to compare two algorithms under controlled conditions, using a steady CAN-bus ground truth to see how much error each algorithm has. Methodologically, the data is all quantitative because we are turning visual and geospatial information into numbers to analyse and compare statistically meaning there isn't any qualitative data involved. The analysis is cross-sectional, so we are looking at a specific snapshot of data to test how well the algorithms work now, rather than tracking changes over time. Finally, we are collecting secondary data like video clips and GNSS logs to analyse and find the Mean Absolute Error for both algorithms.



Fig. 1. Research Onion [4]

C. Background To This Research Theme

The push towards fully autonomous vehicles has sped up the need for robust environmental awareness. In the past, navigation and speed checks have mostly relied on standard GPS receivers. But since self-driving technology needs accuracy to be down to milliseconds, the usual GPS signals and their delays or noise are not good enough [1]. Currently, recent advances in computer vision have made it possible to figure out "ego-motion", basically how a camera moves through 3D space by tracking features [3]. GPS can fail under bridges and cameras don't work well in the dark or when there is lots of glare due to these drawbacks relying on just one sensor isn't ideal thus the industry is leaning more towards combining different sensors. To manage to incorporate that

well, researchers need to first understand how accurate each sensor is on its own and what kind of errors they might have when tested on real-world situations.

D. Hypothesis

This research works with a clear null hypothesis, which basically says there is no real difference in how accurate the vision-based algorithm is compared to GPS when it comes to estimating the vehicle's true ground speed. On the other hand, the alternative hypothesis suggests that the vision-based method will have a smaller error margin than GPS during normal driving, mainly because commercial GPS units tend to have some delay and noise in their readings.

E. Research Aim & Purpose Statement

The main goal of this study is to compare how accurately a vision-based speed estimation algorithm works versus a GPS-based one, using real-world dashcam footage. Ultimately, we are trying to spot the differences in how both methods measure speed. By testing against a solid ground truth, we hope to get useful insights into how reliable these sensors are, which could help in building safer autonomous vehicle navigation systems.

II. Review of Research Methodology



Fig. 2. Literature Map

In the field of Intelligent Transportation Systems (ITS), the selected methodology fundamentally determines the accuracy of speed estimation. Looking into this research area, you can spot two main methods. Researchers focusing on vision-based speed estimation usually take an experimental, deductive approach based on positivism. Their methods generally entails the collection of primary data through edge-computing cameras, utilising geometric transformations (such as Inverse Perspective Mapping) or pixel-tracking algorithms to ascertain speed based on observable physical displacement.

Conversely, researchers looking at GPS probe data often go for a second, more numbers-driven way of analysing things. Their methodology utilises extensive datasets comprising historical, crowdsourced vehicle trajectories. Instead of conducting real-time physical experiments, their focus is predominantly on statistical modelling, noise mitigation, and using map-matching algorithms to fix those multi-path errors that pop up in city areas.

A. Testing Strategies in the Chosen Context

To implement these methods, a review of the literature identifies three principal testing strategies utilised by researchers to evaluate speed estimation frameworks.

The initial approach is what they call Controlled Closed-Circuit Testing, whereby researchers typically initiate testing within controlled, sterilised environments. They drive their specially equipped vehicles at set speeds around a closed track. This method effectively removes extraneous variables such as traffic occlusion or unpredictable civilian driving behaviour, thereby facilitating a concentrated focus on the mathematical principles underpinning the vision or GPS algorithms.

The second approach is known as 'In-The-Wild' Highway Deployment. To check how well it scales, researchers put cameras on busy motorway overpasses. This testing method relies on obtaining a substantial sample size of uninstrumented civilian vehicles. The speed info from the vision system is then compared with big-picture GPS data from third-party companies to see how accurate it is in real-world conditions and how much delay there might be.

The third method involves Synthetic Simulation (Digital Twins). Researchers are progressively utilising advanced rendering engines to artificially produce precise optical flow fields and pixel displacement data in fake extreme weather scenarios that would be hard to mimic in real life. This methodology serves as an effective means of advancing the mathematical boundaries of speed estimation algorithms.

B. Experimental Variables and Hypothesis Validation

No matter what testing approach you use, researchers need to carefully control and tweak certain experimental variables to prove their ideas. When it comes to independent variables in vision-based studies, they often mess around with the camera angle (pitch and yaw), how far away the camera is from the target, and things like lighting and weather to see how solid the system is. Conversely, in studies involving GPS technology, the primary independent variable manipulated is the 'polling rate', defined as the frequency at which the GPS receiver records a coordinate.

Accompanying these inputs, the universally measured dependent variable across all studies is the calculated velocity, expressed in kilometres per hour (km/h) or metres per second (m/s), along with the error margin, which they usually measure using Root Mean Square Error (RMSE) or Mean Absolute Percentage Error (MAPE).

Furthermore, to institute control variables and prove an alternative hypothesis, such as the proposal that a vision-based model shows greater accuracy than conventional GPS. This is usually done by arming test vehicles with super-calibrated Real-Time Kinematic (RTK) GPS or using LiDAR speed guns. Finally, by isolating these variables, researchers can definitively discover the specific parameters under which their speed estimation models remain valid.

C. Distinguishing Between Academic and Non-Academic Material

When we're looking at these variables and methods, it's important to clearly distinguish between well-tested academic research driven by the industry that isn't academically reviewed. Academic material sourced from peer-reviewed journals, these studies offer transparent methods, publicly accessible datasets (such as BrnoCompSpeed), and standard error metrics. They candidly acknowledge limitations, including camera calibration drift and GPS multipath errors.

Non-academic material, such as industry white papers and promotional reports from ITS hardware manufacturers, offer valuable insights into real-world adoption. However, they often lack methodological transparency. Frequently, they present "best-case scenario" accuracy figures without sufficiently detailing the experimental constraints, thereby rendering them unsuitable for establishing a scientific baseline.

D. Recommended Peer-Reviewed Articles

The following five peer-reviewed articles establish the methodological foundation for the comparison of vision and GPS techniques, each representing distinct layers of Saunders' Research Onion.

[6] operate firmly within a positivist paradigm, employing an experimental strategy through the employment of YOLO object detection in conjunction with vanishing point geometry. This study exemplifies contemporary standards for quantitative methodologies and procedures, avoiding reliance solely on fixed road-width assumptions.

Additionally [7] offer a highly pertinent comparative methodology in their work "Comparison of the GPS and Camera Distance Estimation". Their research demonstrates a deductive approach, establishing a rigorous framework for experimental validation by utilising RTK GPS as an infallible ground truth to test alternative hypotheses against monocular camera estimations.

Furthermore, [8] is integral to its archival research strategy, delineating the methodological evolution in data collection and analysis techniques, from fundamental background subtraction to sophisticated deep learning and optical flow methods.

To effectively contextualise the alternative approach in [9], this study focuses extensively on the specific techniques and procedures necessary for overseeing the inherent noise and low polling rates characteristic of continuous GPS trajectory data, relying heavily on large-scale cross-sectional data collection.

Lastly, [10] employs a strict monomethod quantitative approach, explicitly detailing the mathematical methodology involving virtual intrusion lines and frame-by-frame displacement. This represents a practical realisation of the innermost layers of the research onion, offering a methodology directly applicable to the development of optical flow and dynamic affine calibration prototype designs.

E. Critical Literature Arguments and Knowledge Gaps

A critical synthesis of the literature reveals distinct trade-offs between the two methodologies. Vision-based approaches are often praised for their strong localisation and perfect coverage, capturing every passing vehicle. However, the literature frequently disparages these systems for their fragility. Mathematical calibration is readily compromised by camera vibrations, and accuracy diminishes substantially during night-time or adverse weather conditions.

Conversely, GPS probe data methods are esteemed for their continuous, network-wide coverage and resilience to visual environmental factors. Nonetheless, GPS studies frequently emphasise notable spatial inaccuracies within urban canyon environments, primarily due to signal multipath errors, and these methods are often characterised by low rates.

1) Identifying The Knowledge Gap: While there's plenty of research looking at vision systems in really controlled settings and GPS on open roads, there's still a big gap when it comes to comparing their performance all at once in busy, complicated city environments. Most studies investigate a single technology while presuming the other to be an infallible ground truth. There is a conspicuous absence of empirical research that rigorously evaluates a pure pixel-tracking methodology—specifically utilising Region of Interest (ROI) Dense Optical Flow coupled with dynamic affine calibration—measured directly against consumer-grade GPS data within a real-world urban driving scenario.

III. Reflection on Chosen Methodology

A. Research Question

To critically assess the prevailing paradigms within Intelligent Transportation Systems (ITS), this research is guided by the following principal research question:

- How much does a vision-based speed estimation model that uses Region of Interest (ROI) Dense Optical Flow and dynamic affine calibration vary in accuracy compared to regular GPS probe data when checked against high-quality ground truth in urban driving situations?

B. Research Objectives

To carefully tackle the research question, the following tasks need to be done:

1) **Build a Prototype:** Create a vision-based system using Python and OpenCV to work out how fast a vehicle is going from 2D dashcam footage. This involves measuring how much pixels move around with Dense Optical Flow (using the Farnebäck method) and then scaling that up with a reliable affine calibration model.
2) **Extract secondary data:** Obtain and analyse the corresponding continuous GPS trajectory data pertinent to the identical traffic scenarios.
3) **Carry out an experimental evaluation:** Compare both the vision and GPS estimates to a really accurate baseline (the CAN-bus data from the comma2k19 dataset) using common error metrics like Mean Absolute Error (MAE) and Root Mean Square Error (RMSE).
4) **Identify Limitations:** Analyse the environmental or systemic variables, such as visual noise, computational

latency, or GPS multipath errors, that compromise the performance of each respective technology.

C. Research Philosophies, Approaches and Paradigms

Showing an early grasp of research ideas, this study sticks to a strict positivist way of thinking. Speed and how pixels move are straightforward, measurable things that exist outside of what people interpret.

Hence, the research employs a deductive approach; it commences with established physical and computational theories relating to optical flow, expresses a hypothesis concerning its accuracy in comparison to satellite positioning, and subsequently tests this hypothesis through demanding mathematical analysis. In Saunders' Research Onion model, this lines up with a single-method quantitative approach since the assessment is entirely based on numerical data, not on any qualitative themes.

D. Chosen Methodology

Following a comprehensive review of the existing literature, an experimental quantitative methodology was chosen. To really assess ITS sensors, you need solid, measurable benchmarks. While just a theoretical method might work for software structures, testing real-world sensor perception calls for a hands-on, experimental setup.

By testing a customised optical flow vision prototype against real-world GPS data, this methodology directly addresses the knowledge gap identified in prior literature concerning the comparative accuracy of these systems within dynamic urban environments.

E. Experiment Design and Method of Analysis

The testing strategy centres on a controlled, secondary-data experiment utilising the comma2k19 open-source dataset, which inherently offers synchronised video recordings, consumer-grade GPS, and highly precise CAN-bus ground truth.

To validate the hypothesis, these experimental variables are strictly defined:

- **Independent Variables:** The algorithmic tuning parameters within the vision model, specifically the optical flow percentile thresholds, calibration window lengths, and exponential moving average parameters, as well as the environmental conditions present in the selected video segments, including factors such as lighting and traffic density.
- **Dependent Variables:** The calculated instantaneous velocity (measured in kilometres per hour) generated by both the visual prototype and the GPS sensor, along with the corresponding error margins.
- **Control/Ground Truth Variable:** The actual speed of the vehicle, accurately recorded via the CAN-bus data at a frequency of 100Hz.

Method of Analysis: The vision algorithm goes through the video's frames in the dataset, focusing on a particular area of the road (the ROI) to figure out a main proxy for forward movement. This proxy is then scaled up or down to give a speed array. The speed array lines up in time with the GPS speed data. For the main stats, we use some Python scripts to work out the Root Mean Square Error (RMSE), Mean Absolute Error (MAE), and how the errors trend over time for both systems compared to the CAN-bus ground truth.

F. Reflections on Validity, Reliability, and Generalisability

- **Validity:** The construct validity is solid since the measurement is based on tracking pixel intensity changes over time using Optical Flow. Internal validity is also reliable because we've used the comma2k19 dataset, which gives perfectly synchronized timestamps for the video, GPS, and CAN-bus data. This means all the systems are tested under the same physical conditions.
- **Reliability:** Since the prototype is built on code, it's dependable. If the Python script runs the same video clip again, the way the Farnebäck algorithm and calibration stuff work means you'll get the same numbers every time.
- **Generalisability (Transferability):** The main issue with this research is how well it can be applied elsewhere. Since the testing is done using pre-recorded data (mostly shot on Californian highways and city streets), the results might not hold up in harsh weather (like heavy snow, which messes with optical flow) or on unstructured rural roads unless we specifically look at data from those situations.

G. Ethical Considerations

Since this research uses a quantitative, system-based approach and doesn't involve interacting with people, the ethical risks are low. Still, the main ethical concerns are around how we handle data privacy and secondary data usage. The comma2k19 dataset is open-source and OK for academic research.

If the project produces visual outputs like videos showing optical flow vectors, we need to be careful and anonymise any identifiable info. Any license plates or pedestrian faces that are clearly visible in the dataset clips should be blurred before publication to respect people's privacy.

References

[1] H. Cui and S. S. Ge, "Autonomous vehicle positioning with gps in urban canyon environments," *IEEE Transactions on Robotics and Automation*, vol. 19, no. 1, pp. 15–25, 2003. [Online]. Available: https://ieeexplore.ieee.org/document/1177161

[2] W. Li *et al.*, "Statistical analysis of gnss multipath errors in urban canyons," *IEEE Sensors Journal*, 2025. [Online]. Available: https://ieeexplore.ieee.org/document/11028411

[3] P. P. *et al.*, "Video-based vehicle speed estimation using speed measurement metrics," *IEEE Access*, 2024. [Online]. Available: https://ieeexplore.ieee.org/document/10381710/

[4] M. N. K. Saunders, P. Lewis, and A. Thornhill, *Research Methods for Business Students*, 8th ed. Harlow, U.K.: Pearson, 2019. [Online]. Available: https://www.researchgate.net/publication/240218229_Research_Methods_for_Business_Students

[5] H. Schafer, E. Santana, A. Haden, and R. Biasini, "A commute in data: The comma2k19 dataset," *arXiv preprint arXiv:1812.05752*, 2018. [Online]. Available: https://arxiv.org/abs/1812.05752

[6] V. Macko *et al.*, "Efficient vision-based vehicle speed estimation," *arXiv preprint arXiv:2505.01203*, 2025. [Online]. Available: https://arxiv.org/abs/2505.01203

[7] A. Arabi, A. Haghighat, and C. Jacob, "Comparison of the gps and camera distance estimation," *Sensors*, 2022. [Online]. Available: https://stacks.cdc.gov/view/cdc/229918

[8] D. Fernández Llorca, C. Salinas, M. Jimenez, and I. Parra Alonso, "Vision-based vehicle speed estimation: A survey," *IET Intelligent Transport Systems*, 2021. [Online]. Available: https://www.researchgate.net/publication/348563438_Vision-based_Vehicle_Speed_Estimation_for_ITS_A_Survey

[9] N. T. Do, V. D. Ta, and T. M. Nguyen, "Enhanced deep neural networks for traffic speed forecasting using probe data," *MDPI*, 2024. [Online]. Available: https://www.mdpi.com/2071-1050/16/6/2453

[10] A. Rahimi, "Vehicle speed measurement model for video-based systems," *Diva-Portal*, 2018. [Online]. Available: http://www.diva-portal.org/smash/get/diva2:1258002/FULLTEXT01.pdf