XAMPP Control Panel v3.3.0 [Compiled: Apr 6th 2021]

XAMPP Control Panel v3.3.0

Config | Netstat | Shell | Explorer | Services | Help | Quit

Modules

Service	Module	PID(s)	Port(s)	Actions			
	Apache			Start	Admin	Config	Logs
	MySQL			Start	Admin	Config	Logs
	FileZilla			Start	Admin	Config	Logs
	Mercury			Start	Admin	Config	Logs
	Tomcat			Start	Admin	Config	Logs

20:49:06 [mysql]   Attempting to start MySQL app...
20:49:06 [Apache] Status change detected: running
20:49:06 [mysql]   Status change detected: running
21:47:23 [Apache] Attempting to stop Apache (PID: 21416)
21:47:23 [Apache] Attempting to stop Apache (PID: 5856)
21:47:23 [Apache] Status change detected: stopped
21:47:24 [mysql]   Attempting to stop MySQL app...
21:47:24 [mysql]   Status change detected: stopped

XAMPP Control Panel v3.3.0 [Compiled: Apr 6th 2021]

XAMPP Control Panel v3.3.0

Config | Netstat | Shell | Explorer | Services | Help | Quit

Modules

Service	Module	PID(s)	Port(s)	Actions			
	Apache	16200 22324	80, 443	Stop	Admin	Config	Logs
	MySQL	16460	3306	Stop	Admin	Config	Logs
	FileZilla			Start	Admin	Config	Logs
	Mercury			Start	Admin	Config	Logs
	Tomcat			Start	Admin	Config	Logs

21:47:23 [Apache] Attempting to stop Apache (PID: 5856)
21:47:23 [Apache] Status change detected: stopped
21:47:24 [mysql]   Attempting to stop MySQL app...
21:47:24 [mysql]   Status change detected: stopped
21:48:06 [Apache] Attempting to start Apache app...
21:48:06 [mysql]   Attempting to start MySQL app...
21:48:07 [Apache] Status change detected: running
21:48:07 [mysql]   Status change detected: running

phpMyAdmin

Recent Favorites

- New
- information_schema
- mysql
- performance_schema
- phpmyadmin
- test
- tutor

| Databases | SQL | Status | User accounts | Export | Import | Settings | Replication | Variables | Charsets | Engines | Plugins |

Databases

Create database

| Tutor | utf8mb4_general_ci | **Create** |

Check all Drop

Database	Collation	Action
information_schema	utf8_general_ci	Check privileges
mysql	utf8mb4_general_ci	Check privileges
performance_schema	utf8_general_ci	Check privileges
phpmyadmin	utf8_bin	Check privileges
test	latin1_swedish_ci	Check privileges
tutor	utf8mb4_general_ci	Check privileges

Total: 6

⚠ Note: Enabling the database statistics here might cause heavy traffic between the web server and the MySQL server.

Enable statistics

Server: 127.0.0.1 » Database: tutor

| Structure | SQL | Search | Query | Export | Import | Operations | Privileges | Routines | Events | Triggers | Tracking | Designer | Central columns |

Importing into the database "tutor"

File to import:

File may be compressed (gzip, bzip2) or uncompressed.
A compressed file's name must end in **.[format].[compression]**. Example: **.sql.zip**

Browse your computer: (Max: 40MiB)

Choose File | tutor.sql

You may also drag and drop a file on any page.

Character set of the file:

utf-8

Partial import:

Allow the interruption of an import in case the script detects it is close to the PHP timeout limit.
This might be a good way to import large files, however it can break transactions.

Skip this number of queries (for SQL) starting from the first one:

0

Other options

Enable foreign key checks

Format

SQL

Partial import:

Allow the interruption of an import in case the script detects it is close to the PHP timeout limit.

This might be a good way to import large files, however it can break transactions.

Skip this number of queries (for SQL) starting from the first one:

```
0
```

Other options

Enable foreign key checks

Format

```
SQL                                                                        ⌄
```

Format-specific options:

SQL compatibility mode:

```
NONE                                                                       ⌄
```

Do not use AUTO_INCREMENT for zero values

Import