Toward Chip Integrated Ultra-Low-Noise Lasing Using a Microrod Resonator

Joe Becker
W. Loh, F. Baynes, D. Cole, F. Quinlan, H. Lee,
K. Vahala, S. Papp, S. Diddams

National Institute of Standards and Technology

Joe.Becker@nist.gov

April 15, 2015

Current Laser Technology

As lasers increase in stability they increase in size.



Current Laser Technology

As lasers increase in stability they increase in size.



Whispering Gallery Mode Resonators



Silica Microdisk



H. Lee, Nature Photon, 2012

Silica Microrod



P. Del'Haye, APL, 2013

CaF_2 Resonator

J. Hofer, PRA, 2010
W. Liang, Opt Lett., 2011

Brillouin Lasers





Gain Process

- Brillouin scattering is a nonlinear process where a photon scatters off of a propagating phonon resulting in a backscattered photon which Doppler shifted due to the movement of the phonon.
- SBS and pump fields interfere to drive the phonons to stimulate additional Brillouin scattering.

Why SBS Lasers?

Because they have a high signal to noise ratio!



SBS Laser Noise

SBS laser noise is governed by thermal fluctuations which are much larger than the energy of the phonons.

$$\frac{h\nu}{k_B T} << 1$$



SBS Lasers in Microresonators

Microresonators are a prime candidate for creating ultra-low-noise lasers using SBS, because of their ultra-high Q.



- Their low loss means a lower gain level at steady state operation.
- Lower gain threshold allows for less thermal noise to be added to the signal.
- Non-linear process lead to high signal power.

SBS Laser in Microdisk







Previous Microdisk Work

- We measured a reduction in noise level by generating an SBS laser within a microdisk.
- This system has been shown to be tunable up to THz.
- This SBS laser has be referenced to a cavity for further noise reduction.

Increasing Mode Volume

Moving from a Microdisk to a Microrod

- Microdisk thickness of $\approx 10\mu m$



H. Lee, Nature Photonics, 2012

- Microrod thickness of $\approx 100\mu m$

$$S_{\bar{u}}(\Omega) \propto V_m^{-1}$$

A. Matsko, J. Opt. Soc. Am. B, 2007

- By increasing mode volume we reduce the amount of thermal fluctuations.

Silica Microrod Resonators

CO_2 Laser Machining Microrods

- Fabrication time on the order of minutes
- Material cost of $\approx$ \$0.05 per resonator
- Allows for resonators with larger mode volume



S. Papp, PRX, 2013

Apparatus





Fiber Coupling

- We pull a single mode optical fiber to form a taper with a waist on the order of the wavelength our light.
- With a fiber smaller than the optical mode we are able to overlap modes between the taper and the resonator.
- This allows for a simple fiber integrated system.

SBS Microrod Laser Frequency Noise



SBS Microrod Laser Frequency Noise



SBS Microrod Laser RF Spectrum



SBS Microrod Laser RF Spectrum



Summary of Results

- We observed a two order reduction in noise from the SBS microdisk by changing to the microrod
- We observed an order reduction in linewidth from the SBS microdisk as well

Future Research Directions



- We have observed a free running thermal drift of $7kHz/s$ and would like to make efforts to reduce the drift.

Acknowledgments

A special thanks to:

The NIST Optical Frequency Measurement Lab

- Fred Baynes
- Katja Beha
- Aurélien Coillet
- Daniel Cole
- Pascal Del'Haye
- Scott Diddams
- Adam Green
- William Loh
- Scott Papp
- Frank Quinlan

The Caltech Vahala Group

- Hansuek Lee
- Kerry Vahala

Funding Provided By

The DARPA PULSE Program

Questions?