

```
In [1]: #           Science of Decisions  
#       Interactive Stroop Effect Experiment  
  
#       Analysis Results for Udacity P1 Study  
  
# Prepared by: Laurie S. Reynolds
```

In [3]: *# Read in the data and display as a table*

```
# Some initial imports and settings  
%matplotlib inline
```

```
from IPython.display import display, HTML  
import numpy as np  
import pandas as pd  
import matplotlib.pyplot as plt  
import matplotlib.mlab as mlab  
import math as math  
import scipy.stats as stats
```

```
np.set_printoptions(suppress=True)
```

```
# Read in the data and display as a table
```

```
stroopData = pd.read_csv('/home/laurie/udacity/P1/stroopdata-differences.csv')
```

```
stroopData
```

Out[3]:

	Participant	Congruent	Incongruent	Difference
0	P-100	12.079	19.278	7.199
1	P-101	16.791	18.741	1.950
2	P-102	9.564	21.214	11.650
3	P-103	8.630	15.687	7.057
4	P-104	14.669	22.803	8.134
5	P-105	12.238	20.878	8.640
6	P-106	14.692	24.572	9.880
7	P-107	8.987	17.394	8.407
8	P-108	9.401	20.762	11.361
9	P-109	14.480	26.282	11.802
10	P-110	22.328	24.524	2.196
11	P-111	15.298	18.644	3.346
12	P-112	15.073	17.510	2.437
13	P-113	16.929	20.330	3.401
14	P-114	18.200	35.255	17.055
15	P-115	12.130	22.158	10.028
16	P-116	18.495	25.139	6.644
17	P-117	10.639	20.429	9.790
18	P-118	11.344	17.425	6.081
19	P-119	12.369	34.288	21.919
20	P-120	12.944	23.894	10.950
21	P-121	14.233	17.960	3.727
22	P-122	19.710	22.058	2.348
23	P-123	16.004	21.157	5.153

In [4]: *# Data is not displaying correctly as numbers, verify check the data was imported as floats*
 stroopData.dtypes

Out[4]: Participant object
 Congruent float64
 Incongruent float64
 Difference float64
 dtype: object

In [5]: *# Calculate the percentage difference*

```
stroopData['Percent Diff'] = (stroopData['Difference'] / stroopData['Congruent']) * 100
```

display the data formatted correctly

```
print (stroopData.to_string (justify='right', index=False))
```

Participant	Congruent	Incongruent	Difference	Percent Diff
P-100	12.079	19.278	7.199	59.599305
P-101	16.791	18.741	1.950	11.613364
P-102	9.564	21.214	11.650	121.810958
P-103	8.630	15.687	7.057	81.772885
P-104	14.669	22.803	8.134	55.450269
P-105	12.238	20.878	8.640	70.599771
P-106	14.692	24.572	9.880	67.247482
P-107	8.987	17.394	8.407	93.546233
P-108	9.401	20.762	11.361	120.848846
P-109	14.480	26.282	11.802	81.505525
P-110	22.328	24.524	2.196	9.835185
P-111	15.298	18.644	3.346	21.872140
P-112	15.073	17.510	2.437	16.167982
P-113	16.929	20.330	3.401	20.089787
P-114	18.200	35.255	17.055	93.708791
P-115	12.130	22.158	10.028	82.671063
P-116	18.495	25.139	6.644	35.923222
P-117	10.639	20.429	9.790	92.019927
P-118	11.344	17.425	6.081	53.605430
P-119	12.369	34.288	21.919	177.209152
P-120	12.944	23.894	10.950	84.595179
P-121	14.233	17.960	3.727	26.185625
P-122	19.710	22.058	2.348	11.912735
P-123	16.004	21.157	5.153	32.198200

```
In [9]: # Plot the results sorted by Congruent

# Initialize the plots
fig, ax = plt.subplots(1,1,figsize=(10,10))

# Sort the data by Congruent column
stroopSorted = stroopData.sort_values(['Congruent', 'Incongruent', 'Difference', 'Participant', 'Percent Diff'], ascending=[1, 0, 0, 0,0])


# Create plots for the Incongruent, Congruent and Difference data
incongruentPlot = plt.plot(stroopSorted['Incongruent'], label='Incongruent')
congruentPlot = plt.plot(stroopSorted['Congruent'], label='Congruent')
differencePlot = plt.plot(stroopSorted['Difference'], label='Difference')

# Label the Axes and Title the graph
plt.xlabel('Participants')
plt.ylabel('Time (seconds)')
plt.title('Stroop Experiment Results')

# Use Participant for the x axis tick markers
count = stroopSorted['Congruent'].count()
index = np.arange(count)
plt.xticks(index, stroopSorted['Participant'])
plt.xticks(rotation=50)

# add a legend
plt.legend()

plt.show()
```



```

In [8]: # Caculate descriptive statistics

# Assign column data to variables
participantCol = stroopData['Participant']
incongruentCol = stroopData['Incongruent']
differenceCol = stroopData['Difference']
congruentCol = stroopData['Congruent']
percentDiffCol = stroopData['Percent Diff']

descriptiveStats = pd.DataFrame( columns=['Congruent', 'Incongrue
nt', 'Difference', 'Percent Diff'], index=['count', 'mean', 'medi
an', 'min', 'max', 'std', 'se'])

# Calculate statistics
def calcStats(columnName, columnData) :

    descriptiveStats[columnName]['count'] = columnData.count()
    descriptiveStats[columnName]['mean'] = columnData.mean()
    descriptiveStats[columnName]['median'] = columnData.median()
    descriptiveStats[columnName]['min'] = columnData.min()
    descriptiveStats[columnName]['max'] = columnData.max()
    descriptiveStats[columnName]['std'] = stats.tstd(columnData)
    descriptiveStats[columnName]['se'] = stats.sem(columnData)

# Fill in the table
calcStats('Congruent', congruentCol)
calcStats('Incongruent', incongruentCol)
calcStats('Difference', differenceCol)
calcStats('Percent Diff', percentDiffCol)

# Print out the results
descriptiveStats

```

Out[8]:

	Congruent	Incongruent	Difference	Percent Diff
count	24	24	24	24
mean	14.0511	22.0159	7.96479	63.4162
median	14.3565	21.0175	7.6665	63.4234
min	8.63	15.687	1.95	9.83518
max	22.328	35.255	21.919	177.209
std	3.55936	4.79706	4.86483	42.3156
se	0.726551	0.979195	0.993029	8.63764

```
In [123]: def drawPlot(columnData, colIndex, rowIndex1, rowIndex2, title):
            sortedData = sorted(columnData)

            fig, ax = plt.subplots(1,1,figsize=(10,5))



            fit = stats.norm.pdf(sortedData, descriptiveStats[colIndex]
[roIndex1], descriptiveStats[colIndex][roIndex2]) #this is a
fitting indeed



            plt.plot(sortedData,fit,'-o')

            ax.set_xlim(xmin=0)

            plt.hist(sortedData,normed=True, histtype='stepfilled', alph
a=0.6)
            plt.xlabel('Time (Seconds)')
            plt.ylabel('Probability Density')
            plt.title(title)
            plt.show()

drawPlot(incongruentCol, 'Incongruent', 'mean', 'std', 'Incongru
ent')
drawPlot(congruentCol, 'Congruent', 'mean', 'std', 'Congruent')
drawPlot(differenceCol, 'Difference', 'mean', 'std', 'Differenc
e')
drawPlot(percentDiffCol, 'Percent Diff', 'mean', 'std', 'Percent
Diff')
```



```

In [135]: fig, ax = plt.subplots(1,1,figsize=(10,5))

def drawPlot(columnData, colIndex, rowIndex1, rowIndex2, labelName):
    sortedData = sorted(columnData)

    fit = stats.norm.pdf(sortedData, descriptiveStats[colIndex]
[roIndex1], descriptiveStats[colIndex][roIndex2]) #this is a fitting indeed

    plt.plot(sortedData,fit,'-o')


    ax.set_xlim(xmin=0)

    plt.hist(sortedData,normed=True, histtype='stepfilled', alpha=0.6, label=labelName)
    plt.xlabel('Time (Seconds)')
    plt.ylabel('Probability Density')

plt.title('Congruent and Incongruent')
drawPlot(incongruentCol, 'Incongruent', 'mean', 'std', 'Incongruent')
drawPlot(congruentCol, 'Congruent', 'mean', 'std', 'Congruent')

plt.legend()
plt.show()

```



```
In [132]: # Calculate the t statistic

tstatistic, pvalue = stats.ttest_rel(incongruentCol, congruentCol)

print "T Statistic = %f" % tstatistic
print "P-Value = %g" % pvalue
```

```
T Statistic = 8.020707
P-Value = 4.103e-08
```

```
In [107]: # Cohen's D

cohensD = (descriptiveStats['Incongruent']['mean'] - descriptiveStats['Congruent']['mean']) / descriptiveStats['Difference']['std']

print "Cohen's D: %f " % (cohensD)
```

```
Cohen's D: 1.637220
```

```
In [120]: # Confidence Interval

import math as math

marginOfError = descriptiveStats['Difference']['std']/math.sqrt(descriptiveStats['Difference']['count']) * 1.714

ciLow = descriptiveStats['Difference']['mean'] - marginOfError
ciHigh = descriptiveStats['Difference']['mean'] + marginOfError

print "Margin of Error: %f" % marginOfError
print "Confidence interval: (%f, %f)" % (ciLow, ciHigh)
```

```
Margin of Error: 1.702051
Confidence interval: (6.262741, 9.666843)
```

```
In [112]: # Calculate r squared

tStatisticSquared = tstatistic * tstatistic

rSquared = tStatisticSquared / (tStatisticSquared + 23)

print "r squared: %f" % rSquared
```

```
r squared: 0.736636
```

```

In [104]: # Display the t-critical and t statistic

fig, ax = plt.subplots(1,1,figsize=(12,5))

mean = 0
variance = 1
sigma = math.sqrt(variance)
x = np.linspace(-3,3,100)
y = mlab.normpdf(x,mean,sigma)

plt.vlines(1.714, 0, 0.09)

section = np.arange(1.714, 3, 1/20.)
plt.fill_between(x[78:100],y[78:100], facecolor='blue', alpha=0.5)

ax.annotate('t statistic = 8.021\np-value = 4.103e-08\nConfidence level = 99.9%', xy=(1.5, 0.1), xytext=(1.5,0.32))
ax.annotate('t-critical = 1.714\n(alpha=0.05,df=23)', xy=(1.714, 0.1), xytext=(2.0,0.2),
            arrowprops=dict(facecolor='grey', shrink=0.05),)

plt.title('Statistical Results for Stroop Time Differences')
plt.plot(x,y)

plt.show()

```



In []: