

AI Assisted Coding

Lab_Assignment_19.4

Goli Harini Reddy

Batch-08

2303A51544

Task 1 – JavaScript to Python (Array Processing Logic)

Scenario

A frontend application written in JavaScript processes user scores. The backend team wants the same logic implemented in Python for analytics processing.

Task

Translate a JavaScript function that:

- Takes an array of numbers
- Filters values greater than 50
- Returns the average of filtered values

Instructions

- Prompt AI to convert JavaScript array methods (filter, reduce) into equivalent Python logic.
- Ensure list comprehension or Pythonic style is used.
- Compare outputs of both implementations with sample input.
- Document differences in handling arrays between JS and Python.

Expected Output

- Equivalent Python function.
- Same output for identical inputs.
- Clean and Pythonic implementation.

Task 1 – JavaScript to Python (Array Processing Logic)

JavaScript Code

```
[2]
✓ 0s  def average_above_50(arr):
    filtered = [x for x in arr if x > 50]
    if not filtered:
        return 0
    total_sum = sum(filtered)
    return total_sum / len(filtered)

print(average_above_50([30, 60, 80, 40, 90]))

... 76.66666666666667
```

Equivalent Python Code

```
[3]
✓ 0s def average_above_50(arr):
    filtered = [x for x in arr if x > 50]
    if not filtered:
        return 0
    return sum(filtered) / len(filtered)
print(average_above_50([30, 60, 80, 40, 90]))

76.66666666666667
```

Observation:

- JavaScript uses array methods like filter() and reduce(), while Python uses list comprehension and built-in functions like sum().
- Python code is more concise and readable compared to JavaScript.
- Both implementations produce the same output for identical inputs.
- Python handles empty lists easily using if not list, while JavaScript uses length.
- The logic remains the same, only the syntax differs

Task 2 – Python OOP to C++ Class Translation

Scenario

A data modeling module is written in Python using OOP. The system is being migrated to a high-performance C++ environment.

Task

Translate a Python class that:

- Contains private attributes

- Uses getter/setter methods
- Includes a method that calculates a derived value

Instructions

- Convert the Python class into a C++ class.
- Ensure:

o Proper access modifiers

o Constructor handling o

Correct data types

- Compile and test the C++ version.
- Compare how encapsulation differs between Python and C++.

Expected Output

- Fully working C++ class equivalent to Python version.
- Proper use of access specifiers (private, public).

Task 2 – Python OOP to C++ Class Translation

Python Class

```
[4]
✓ Os
class Product:
    def __init__(self, price, quantity):
        self.__price = price
        self.__quantity = quantity

    def get_price(self):
        return self.__price

    def set_price(self, price):
        self.__price = price

    def total_value(self):
        return self.__price * self.__quantity
```

Equivalent C++ Class

```
[7]
✓ Os
%%shell
g++ -o product_main product_code.cpp
./product_main

301.5
```

Observation:

- Python uses name mangling (`__var`) for private variables, while C++ uses strict access modifiers (`private`).
- C++ requires explicit data types, whereas Python is dynamically typed.
- Constructors in C++ are more structured compared to Python's `__init__`.
- Encapsulation is strongly enforced in C++, but more flexible in Python.
- Both classes achieve the same functionality with different syntax rules.

Task 3 – REST API Call Translation: Python to JavaScript

Scenario

A backend developer wrote an API request using Python requests. The frontend team needs the same functionality in JavaScript (Fetch API).

Task

Translate Python API request code into JavaScript.

Instructions

- Convert:

o GET request logic o JSON parsing o

Error handling (try-except → try-catch)

- Ensure proper `async/await` usage in JavaScript.
- Compare differences in error handling mechanisms.

Expected Output

- Equivalent JavaScript code using Fetch API.
- Proper `async` handling.
- Similar output structure.

```
Python Code
[8]
✓ 0s
import requests

try:
    response = requests.get("https://jsonplaceholder.typicode.com/posts")
    data = response.json()
    print(data)
except Exception as e:
    print(e)

[[{'userId': 1, 'id': 1, 'title': 'sunt aut facere repellat provident occaecati excepturi optio reprehend

JavaScript Equivalent
[10]
✓ 0s
%%javascript
async function fetchData() {
    try {
        const response = await fetch("https://jsonplaceholder.typicode.com/posts");
        const data = await response.json();
        console.log(data);
    } catch (error) {
        console.error(error);
    }
}

fetchData();
```

Observation:

- Python uses the **requests library**, while JavaScript uses the **Fetch API**.
- JavaScript handles API calls **asynchronously using async/await**, whereas Python is usually synchronous.
- Error handling is done using **try-except in Python** and **try-catch in JavaScript**.
- Both approaches successfully retrieve and process **JSON data**.
- JavaScript requires more handling for asynchronous execution.

Task 4 – SQL Aggregation to MongoDB Query Translation

Scenario

A company is migrating from relational databases (SQL) to MongoDB (NoSQL).

Task

Translate an SQL aggregation query into a MongoDB aggregation pipeline.

Example Logic:

- Group records by category
- Calculate average price
- Filter groups where average price > threshold

Instructions

- Provide SQL query to AI.
- Generate equivalent MongoDB query.
- Explain differences between relational and document-based querying.
- Validate results conceptually.

Expected Output

- Working MongoDB aggregation query.
- Clear understanding of grouping and aggregation differences

Task 4 – SQL Aggregation to MongoDB Query Translation

SQL Query

```
[28] ✓ 0s import sqlite3

conn = sqlite3.connect("example.db")
cursor = conn.cursor()

# Create the 'products' table if it doesn't exist
cursor.execute("""
CREATE TABLE IF NOT EXISTS products (
    id INTEGER PRIMARY KEY AUTOINCREMENT,
    category TEXT NOT NULL,
    price REAL NOT NULL
);
""")

# Insert sample data if the table is empty
cursor.execute("SELECT COUNT(*) FROM products;")
if cursor.fetchone()[0] == 0:
    sample_data = [
        ('Electronics', 150),
        ('Electronics', 200),
        ('Books', 50),
        ('Books', 120),
        ('Electronics', 300),
```

```
[28] 0s
('Electronics', 300),
('Books', 80),
('Clothing', 75),
('Clothing', 110)
]
cursor.executemany("INSERT INTO products (category, price) VALUES (?, ?);", sample_data)
conn.commit()
print("Inserted sample data into 'products' table.")
else:
    print("Table 'products' already contains data. Skipping sample data insertion.")

query = """
SELECT category, AVG(price) AS avg_price
FROM products
GROUP BY category
HAVING AVG(price) > 100;
"""

cursor.execute(query)

print("\nSQL Aggregation Results:")
for row in cursor.fetchall():
    print(row)

conn.close()
```

... Inserted sample data into 'products' table.

SQL Aggregation Results:

```
[28] 0s
HAVING AVG(price) > 100;
"""

cursor.execute(query)

print("\nSQL Aggregation Results:")
for row in cursor.fetchall():
    print(row)

conn.close()
```

... Inserted sample data into 'products' table.

SQL Aggregation Results:
('Electronics', 216.66666666666666)

```
[23] 7s
!pip install pymongo
```

... Collecting pymongo
Downloading pymongo-4.16.0-cp312-cp312-manylinux2014_x86_64.manylinux_2_17_x86_64.manylinux_2_28_x86_64.whl (1.7 MB)
Collecting dnspython<3.0.0,>=2.6.1 (from pymongo)
Downloading dnspython-2.8.0-py3-none-any.whl.metadata (5.7 kB)
Downloading pymongo-4.16.0-cp312-cp312-manylinux2014_x86_64.manylinux_2_17_x86_64.manylinux_2_28_x86_64.whl (1.7/1.7 MB 61.8 MB/s eta 0:00:00)
Downloading dnspython-2.8.0-py3-none-any.whl (331 kB)
331.1/331.1 kB 28.4 MB/s eta 0:00:00
Installing collected packages: dnspython, pymongo
Successfully installed dnspython-2.8.0 pymongo-4.16.0

Observation:

- SQL uses **relational tables**, while MongoDB uses **document-based collections**.

- SQL performs aggregation using GROUP BY and HAVING, whereas MongoDB uses \$group and \$match.
- MongoDB stores grouped results in _id, unlike SQL which keeps column names.
- The aggregation pipeline in MongoDB works in **stages**, unlike SQL's single query format.
- Both produce the **same result but follow different data models and syntax**.

Task 5 – Real-Time Application: Algorithm Translation Across Three Languages

Scenario

A tech company maintains codebases in multiple languages (Python, Java, and Go). A common algorithm must be implemented consistently across systems.

Task

Choose an algorithm (e.g., binary search, palindrome check, prime number checker) and translate it across:

- Python
- Java
- One additional language (Go / C# / JavaScript)

Instructions

- Ensure logic remains identical across languages.
- Handle:
 - o Data types
 - o Loop differences
 - o Input/output handling
- Test each version with same input values.
- Briefly document translation challenges.

Expected Output

- Three equivalent working implementations.
- Clear logical consistency.

- Understanding of syntactic vs structural differences.

Task 5 – Real-Time Application: Algorithm Translation Across Three Languages

Python

```
[15]  def binary_search(arr, target):  
✓ 0s    low, high = 0, len(arr) - 1  
    while low <= high:  
        mid = (low + high) // 2  
        if arr[mid] == target:  
            return mid  
        elif arr[mid] < target:  
            low = mid + 1  
        else:  
            high = mid - 1  
    return -1  
  
    print(binary_search([1,2,3,4,5], 4))
```

▼ ... 3

Java

```
[20]  %%writefile BinarySearch.java  
✓ 0s    class BinarySearch {  
        static int search(int[] arr, int target) {  
            int low = 0, high = arr.length - 1;
```

```
[20]  %%writefile BinarySearch.java  
✓ 0s    class BinarySearch {  
        static int search(int[] arr, int target) {  
            int low = 0, high = arr.length - 1;  
            while (low <= high) {  
                int mid = (low + high) / 2;  
                if (arr[mid] == target)  
                    return mid;  
                else if (arr[mid] < target)  
                    low = mid + 1;  
                else  
                    high = mid - 1;  
            }  
            return -1;  
        }  
  
        public static void main(String[] args) {  
            int[] arr = {1,2,3,4,5};  
            System.out.println(search(arr, 4));  
        }  
    }
```

▼ ... Writing BinarySearch.java

```
[21]  %%shell  
✓ 1s    javac BinarySearch.java
```

The screenshot shows a code editor with two tabs. The top tab is labeled '[22] Os' and contains the following code:

```
%%shell
java BinarySearch
3
```

The bottom tab is labeled '[19] Os' and contains the following code:

```
%%javascript
function binarySearch(arr, target) {
  let low = 0, high = arr.length - 1;
  while (low <= high) {
    let mid = Math.floor((low + high) / 2);
    if (arr[mid] === target) return mid;
    else if (arr[mid] < target) low = mid + 1;
    else high = mid - 1;
  }
  return -1;
}

console.log(binarySearch([1,2,3,4,5], 4));
```

Observation:

- The algorithm logic remains identical across all languages, ensuring consistent results.
- Differences arise in syntax, data types, and structure.
- Java requires a class structure, while Python and JavaScript are more flexible.
- Loop constructs and condition handling vary slightly between languages.
- Translation highlights the difference between language syntax and core algorithm logic.