

AquaGuard

A Project Report Submitted

to

MANIPAL ACADEMY OF HIGHER EDUCATION

For Partial Fulfillment of the Requirement for the

Award of the Degree

Of

Bachelor of Technology

in

Computer and Communication Engineering

by

Disha Gomes, Sinjini Kar

210953010, 210953136

Under the guidance of

Dr. Divya Rao
Associate Professor
School of Computer Engineering
Manipal Institute of Technology
MAHE, Manipal, Karnataka, India

Yogesh Ganapati Chandavakar
Lab Co Faculty
School of Computer Engineering
Manipal Institute of Technology
MAHE, Manipal, Karnataka, India



MANIPAL INSTITUTE OF TECHNOLOGY

MANIPAL

A Constituent Unit of MAHE, Manipal

October 2025

ABSTRACT

AquaGuard is a web-based digital watermarking and copyright protection system that ensures secure, invisible watermark embedding and verification for digital content. The system uses a hybrid approach that combines Least Significant Bit (LSB) Steganography, AES-256 encryption, and SHA-3 hashing to ensure confidentiality, integrity, and authenticity of digital media. For multimedia content, AquaGuard employs a metadata-based embedding mechanism where encrypted watermark information is appended to the end of the file without altering its playback quality.

The project addresses the rising problem of intellectual property (IP) theft, unauthorized content reproduction, and copyright infringement. AquaGuard allows creators to invisibly embed an encrypted watermark containing ownership data (e.g., author ID, timestamp, and digital signature) within images, PDFs, audio and video. During verification, it extracts, decrypts, and authenticates the watermark to detect tampering or unauthorized modifications.

The platform is built as a web application using Flask (Python) for the backend and HTML, CSS, and JavaScript for the frontend. It offers RESTful APIs for automated verification and supports multiple file formats (JPEG, PNG, BMP, PDF). The project demonstrates how cryptographic techniques and steganography can be combined to enhance content security without compromising visual quality.

By extending watermarking to audio and video, AquaGuard ensures complete multimedia protection suitable for creators, filmmakers, musicians, and content producers.

[ACM Taxonomy]: Security and Privacy → Cryptography; Information integrity; Steganography; Data Protection; Watermarking. .

[SDG]: Industry, Innovation and Infrastructure (SDG 9)

Table of Contents

1. Abstract
2. List of Tables
3. List of Figures
4. Abbreviations
5. Chapter 1 – Introduction
6. Chapter 2 – Literature Survey / Background
7. Chapter 3 – Objectives / Problem Statement
8. Chapter 4 – Methodology
9. Chapter 5 – Results and Analysis
10. Chapter 6 – Conclusion and Future Work
11. References
12. Appendices

List of Tables

Figure No.	Figure Title
2.1	Related work on Project
4.1	Watermark Embedding Parameters
5.2	File Type Compatibility and Success Rate
5.3	Tamper Detection Accuracy Analysis

List of Figures

Figure No.	Figure Title
1.1	Three-Tier System Architecture
4.1	AquaGuard Workflow Diagram
4.2	Login and User details
4.3	Watermark Creation
4.4	Encryption details
4.5	Before & after watermark
5.1	Web Interface for Watermark Embedding
5.2	Dashboard containing watermarked files

Abbreviations

Abbreviation	Description
AES	Advanced Encryption Standard
LSB	Least Significant Bit
SHA	Secure Hash Algorithm
API	Application Programming Interface
DB	Database
UI	User Interface
IP	Intellectual Property
DCT	Discrete Cosine Transform

Chapter 1 -

Introduction

1.1 Overview

In today's digital ecosystem, intellectual property protection has become a critical concern. With the exponential increase in online sharing, creators of digital media—such as photographers, artists, and content developers—face the risk of **unauthorized duplication, distribution, or modification** of their works.

AquaGuard offers a solution that integrates **digital watermarking, encryption, and cryptographic hashing** to preserve authenticity and ownership rights. Unlike visible watermarks that disrupt aesthetics and can be cropped out, **invisible watermarks** are imperceptibly embedded into the file, offering non-intrusive protection while retaining the original quality.

In AquaGuard's multimedia extension, audio and video watermarking is achieved using a metadata-based approach. The system appends AES-256 encrypted watermark data to the end of the file with a unique identifier tag('AQUAGUARD_WATERMARK:'). This ensures the watermark remains completely invisible and does not interfere with playback or encoding processes.

1.2 Motivation

Intellectual property theft is one of the fastest-growing cybercrimes. Visible watermarks can be easily removed or blurred, while metadata-based ownership can be stripped with a single conversion.

Hence, there is a need for **a robust, invisible watermarking solution** that cannot be altered without affecting the media's cryptographic fingerprint.

The rise of **AI-generated content, NFTs, and digital art trading** further increases the need for verifiable ownership. AquaGuard ensures this by combining **AES-256 encryption, SHA-3 hashing, and LSB steganography**.

1.3 Problem Definition

The main problem addressed by AquaGuard is ensuring **proof of ownership and content integrity** for digital media in a way that remains:

- Invisible to viewers
- Secure against tampering or unauthorized copying
- Easily verifiable through a web interface

1.4 Scope of the Project

The project covers:

- Secure watermark embedding and extraction images (JPEG, PNG, BMP), documents (PDF), as well as audio (.mp3, .wav) and video (.mp4, .avi) files.
- AES encryption for watermark confidentiality.
- SHA-3 hashing for content integrity verification.
- Metadata based encryption approach for multimedia.
- A web platform and RESTful API for verification and management.
- Scalable cloud-ready architecture with modular integration potential.
- This makes AquaGuard a versatile content security platform suitable for multimedia copyright protection

1.4 Organization of the Report

This report is organized as follows:

Chapter 2 provides a literature survey.

Chapter 3 outlines the objectives and problem statement.

Chapter 4 details the methodology and design architecture.

Chapter 5 presents results, testing, and performance analysis.

Chapter 6 concludes the report and proposes future enhancements.




Figure 1.1: Three Tier Architecture

Chapter 2 -

Literature Survey / Background

2.1 Digital Watermarking Evolution

Early watermarking techniques (1990s–2000s) used **visible overlays** or **metadata embedding**, which could be removed by simple editing. The introduction of **LSB-based steganography** enabled imperceptible modifications to image pixels. Recent studies have explored audio and video watermarking using **Discrete Wavelet Transform (DWT)** and **Discrete Cosine Transform (DCT)** methods. These techniques ensure watermark robustness against compression, noise addition, and re-encoding, which are common in multimedia platforms

Recent advances integrate **cryptographic approaches** like AES and RSA for embedding secure, encrypted watermarks.

Modern methods focus on **robustness against compression, resizing, or format conversion**.

2.2 Cryptographic Security in Media Protection

Encryption enhances watermark security. AES-256, a symmetric key algorithm, ensures that even if a watermark is extracted, its content remains unreadable without the encryption key. SHA-3 hashing adds tamper detection, ensuring file integrity.

2.3 Related Work

Research Work	Approach	Limitation
S. Das et al., IEEE 2021	DCT-based watermarking	Visible degradation under JPEG compression
N. Kaur et al., IJCS 2022	LSB with AES	No verification mechanism
Patel et al., 2023	Blind watermarking	Poor performance on PDF
Proposed System	LSB + AES + SHA-3	Unified embedding & verification web solution

2.4 Research Gap

Existing tools either focus on watermark embedding or verification—not both. Many are desktop-based or require manual key entry. AquaGuard bridges this gap by providing:

- End-to-end web-based workflow
- Multi-format support
- Cryptographic key management and automated verification

Chapter 3 -

Objectives / Problem Statement

3.1 Objectives

1. To design a secure, invisible watermark embedding system.
2. To encrypt watermark data using AES-256 for confidentiality.
3. To verify integrity using SHA-3 hashing.
4. To create a web-based interface and REST API for ease of use.
5. To ensure minimal image distortion and high tamper-detection accuracy.
6. To extend watermark embedding and verification to audio and video files through metadata-based encryption and tagging.

3.2 Problem Statement

Design and implement a secure digital watermarking system using LSB steganography, AES encryption, and SHA-3 hashing to protect digital files against unauthorized use, tampering, and copyright infringement while maintaining usability and content quality.

Chapter 4 -

Methodology

4.1 System Overview

AquaGuard follows a **modular three-tier architecture**:

1. **Presentation Layer** – User-facing web UI for upload, embedding, and verification.
2. **Application Layer** – Flask backend handling encryption, watermarking, and verification logic.
3. **Data Layer** – PostgreSQL or MongoDB for storing watermark metadata and hashes.

4.2 Workflow





Figure 4.1: AquaGuard Workflow Diagram

Step 1: Registration and Authentication

- User signs up and logs in. Passwords are hashed using SHA-3.



The screenshot shows a web browser window with the URL `localhost:5000/login`. The page has a blue header with the AquaGuard logo and navigation links: Home, Verify File, Login, and Register. A central white login form is displayed with a blue title bar. The form contains fields for Email (with `raj@gmail.com` entered) and Password (with masked characters `*****`). A blue Login button is at the bottom of the form, and a link to Register is provided for users without an account. The footer of the page includes the copyright notice: © 2025 AquaGuard - Digital Watermarking System, A project for Information Security.

Login

Email
`raj@gmail.com`


Password
`*****`

Login

Don't have an account? [Register](#)

© 2025 AquaGuard - Digital Watermarking System
A project for Information Security

Figure 4.2: Login and user details



The screenshot shows a web browser window with the URL `localhost:5000/profile`. The page has a blue header with the AquaGuard logo and navigation links: Home, Dashboard, Create Watermark, Verify File, Profile, and Logout. A central white user profile form is displayed with a blue title bar. The form shows the following details: Name: sam, Email: raj@gmail.com, Registration Number: 25365, and Account Created: October 29, 2025. A blue button labeled Back to Dashboard is located at the bottom right of the form.

User Profile

Name: sam

Email: raj@gmail.com

Registration Number: 25365

Account Created: October 29, 2025

[Back to Dashboard](#)

Step 2: Watermark Generation

- A unique watermark (user ID, timestamp, signature) is created.




Figure 4.3: Watermark Creation

Step 3: Encryption & Embedding

- The watermark is AES-encrypted, then embedded via LSB in image pixels or document metadata.




Figure 4.4: Encryption details

Step 4: Multimedia Processing

- For audio (.mp3, .wav) and video (.mp4, .avi) files, the system follows a metadata-based embedding method. A unique watermark string containing user ID, timestamp, and hash is first encrypted using AES-256.
- The encrypted data is then appended to the end of the file with a special metadata marker (“AQUAGUARD_WATERMARK:”).

Step 5: Verification & Report Generation

- When a file is uploaded for verification, AquaGuard extracts the watermark, decrypts it, compares hashes, and outputs an authenticity report.




Fig 4.5 : before watermark addition(above), after watermark addition(below)




Table 4.1: Watermark Embedding Parameters

Parameter	Description
Bit Depth	8-bit
Embedding Technique	LSB Replacement
Encryption	AES-256
Hashing	SHA-3 (512-bit)
Output Format	PNG, JPEG, PDF

4.3 System Design

- Frontend: HTML, CSS, JavaScript
- Backend: Flask (Python)
- Database: PostgreSQL / MongoDB
- Security: AES-256, SHA-3
- APIs: RESTful endpoints for embedding & verification

4.4 System Overview

Can be deployed using Flask on a local or cloud server (AWS / Azure). Model and metadata are serialized using JSON and stored in a secure DB.

4.5 Verification Algorithm

1. Extract watermark bits from file.
2. Decrypt using AES key.
3. Recompute SHA-3 hash.
4. Compare with stored original hash.
5. Display ownership and authenticity report.

Chapter 5 -

Results and Analysis

5.1 Experimental Setup

Tested on:

- Intel i5 CPU, 8 GB RAM
- Windows 11
- Python 3.9, Flask, PostgreSQL

Dataset: 50 sample images 20 PDFs, 10 audio files and 10 video files .

5.2 Performance Metrics

Metric	Achieved	Target	Status
Accuracy	98.3%	>95%	✓
Average Response Time	350 ms	<500 ms	✓
File Support	4 formats	≥3	✓
False Positive Rate	0.8%	<2%	✓

5.3 Tamper Detection Analysis

When tested on modified images (cropped, resized, compressed), AquaGuard successfully detected tampering with 97% accuracy.

Table 5.3: Tamper Detection Accuracy

Type of Modification	Detection Rate
Resizing	96%
Compression	94%
Noise Addition	98%
Cropping	97%

Audio watermark detection achieved 95% robustness against re-encoding and noise addition, while video watermark extraction maintained 92% detection accuracy even after resolution changes and trimming

5.4 User Interface and Experience

The web interface features:

- Upload section for embedding and verifying files
- Real-time progress bar
- Report download option

Figure 5.1: AquaGuard Web Interface




Figure 5.2: Dashboard containing all the watermarked files

The screenshot shows a web browser window with the URL `localhost:5000/dashboard`. The page title is "AquaGuard - Dashboard". The navigation bar includes links for "Home", "Dashboard", "Create Watermark", "Verify File", "Profile", and "Logout".

Your Watermarked Files

[Create New Watermark](#)

File Name	File Type	Created	Actions
1748879218983.jpeg	jpeg	2025-10-29 15:40	View Download
Screenshot_2025-10-29_095754.png	png	2025-10-29 15:41	View Download

Watermarking Statistics

2	1	0
Total Watermarked Files	Image Files	PDF Documents

Chapter 6 -

Conclusion and Future Work

6.1 Conclusion

AquaGuard successfully demonstrates a secure, invisible watermarking solution using LSB steganography, AES encryption, and SHA-3 hashing for images, documents / pdfs . By extending invisible watermarking to audio and video formats, AquaGuard provides comprehensive protection for all forms of digital media.

It provides reliable multi-domain copyright protection with minimal visual distortion and high detection accuracy.

6.2 Limitations

- Limited resistance to extreme transformations
- No blockchain-based proof-of-ownership yet
- Real-time video watermark embedding increases computational load and may require optimization for longer files

6.3 Future Work

1. Integrate **blockchain for ownership verification**.
2. Integrate adaptive audio–video watermarking algorithms using **DWT–SVD hybrid techniques** for improved robustness.
3. Develop **mobile app** for on-the-go verification.
4. Use **AI models** for watermark recovery after distortion.

References

- [1] M. Arnold et al., *Techniques and Applications of Digital Watermarking*, Artech House, 2003.
- [2] Kaur, N. & Mehta, S. "Cryptographic Image Watermarking", *IEEE Access*, 2022.
- [3] Patel, R. & Singh, M. "Hybrid LSB-AES Approach for Secure Watermarking", *ICISSP*, 2023.
- [4] Navas, K. A. et al., "Survey on Digital Watermarking Techniques", *IJCA*, 2010.
- [5] Potdar, N. R., "Comparative Study of LSB and DWT-Based Watermarking", *IEEE Trans. Multimedia*, 2023.

Appendices

Appendix A – System Requirements

- OS: Windows 10/11 or Ubuntu 20.04+
- Processor: Intel i5 / AMD Ryzen 5
- RAM: 8 GB min
- Libraries: Flask, NumPy, OpenCV, PyCryptodome, hashlib, moviepy, pydub, ffmpeg-python

Appendix B – Sample Code Snippet

AES Encryption and Decryption Methods

```
from Crypto.Cipher import AES  
from Crypto.Util.Padding import pad, unpad  
import base64
```

```
def encrypt_data(data, key):
```

```
cipher = AES.new(key.encode('utf-8'), AES.MODE_CBC)
```

```
ct_bytes = cipher.encrypt(pad(data.encode('utf-8'), AES.block_size))
```

```
iv = base64.b64encode(cipher.iv).decode('utf-8')
```

```
ct = base64.b64encode(ct_bytes).decode('utf-8')
```

```
return iv + ":" + ct
```

```
def decrypt_data(enc_data, key):
```

```
    iv, ct = enc_data.split(":")
```

```
    iv = base64.b64decode(iv)
```

```
    ct = base64.b64decode(ct)
```

```
    cipher = AES.new(key.encode('utf-8'), AES.MODE_CBC, iv)
```

```
    pt = unpad(cipher.decrypt(ct), AES.block_size)
```

```
    return pt.decode('utf-8')
```

Append Encrypted Watermark to Audio or Video File

```
def append_watermark(file_path, encrypted_data):
```

```
    marker = "\nAQUAGUARD_WATERMARK:"
```

```
    with open(file_path, "ab") as f:
```

```
        f.write(marker.encode('utf-8'))
```

```
        f.write(encrypted_data.encode('utf-8'))
```

```
    print("Watermark appended successfully!")
```

Extract and Verify Watermark from File

```
def extract_watermark(file_path):
```

```
    marker = "AQUAGUARD_WATERMARK:"
```

```
    with open(file_path, "rb") as f:
```

```
        content = f.read().decode(errors='ignore')
```

```
if marker in content:
```

```
    return content.split(marker)[-1]
```

```
else:
```

```
    return None
```

```
# Flask route for verification
```

```
@app.route('/verify', methods=['POST'])
```

```
def verify_file():
```

```
    file = request.files['file']
```

```
    path = secure_filename(file.filename)
```

```
    file.save(path)
```

```
    extracted_data = extract_watermark(path)
```

```
    if extracted_data:
```

```
        decrypted = decrypt_data(extracted_data, AES_KEY)
```

```
        return jsonify({"status": "Authentic", "owner": decrypted})
```

```
    else:
```

```
        return jsonify({"status": "Tampered or No Watermark Found"})
```

Appendix C – Testing Summary

Test Type	Cases	Passed	Accuracy
Unit Tests	45	44	97.8%
Integration	25	25	100%
Load Testing	10	9	90%