

Smart Helmet for Soldier Safety Using Embedded Systems

Disha Gomes

Reg.No: 230953010

School of Comp. Engineering

Manipal Institute of Technology

Manipal Academy of Higher Education

Manipal- 576104, Karnataka, India

disha4.mitmpl2023@learner.manipal.edu

P Durai Naveen

Reg.No: 230953012

School of Comp. Engineering

Manipal Institute of Technology

Manipal Academy of Higher Education

Manipal- 576104, Karnataka, India

durai.mitmpl2023@learner.manipal.edu

Mugdha Chatterjee

Reg.No: 230953050

School of Comp. Engineering

Manipal Institute of Technology

Manipal Academy of Higher Education

Manipal- 576104, Karnataka, India

mugdha.mitmpl2023@learner.manipal.edu

Abstract—Defense operations often involve soldiers working in extreme environments where manual monitoring of health and location is challenging. This paper presents a Smart Helmet system integrated with embedded sensors for real-time monitoring of soldier health parameters and location. The system measures body temperature, heart rate, and motion activity using sensors such as DHT11, MAX30102, and an accelerometer (MPU6050). GPS and wireless modules (GSM/LoRa) transmit data to a control center for timely response. The system also includes local processing via Arduino UNO or ESP32 for low-latency filtering and event detection. The aim is to enhance safety, improve decision-making, and reduce casualties during missions.

Keywords— Smart helmet, Embedded system, Soldier safety, IoT, Health monitoring, Defense technology.

I. INTRODUCTION

Defense and military technology has evolved dramatically over the last few decades, driven by the demand for automation, real-time intelligence, and human safety in hostile environments. Soldiers on the battlefield operate in physically and mentally demanding conditions, often isolated from immediate medical support. In such circumstances, even a minor delay in identifying health deterioration or loss of consciousness can lead to severe consequences [1]. Traditional monitoring methods depend on verbal or visual communication, which is not reliable under stress or when the soldier is incapacitated. Therefore, the introduction of embedded and IoT-based wearable systems offers a transformative approach to maintaining continuous awareness of soldier health and safety.

Embedded systems serve as the foundation of modern smart devices. They integrate microcontrollers, sensors, and communication interfaces into a compact, reliable architecture capable of operating autonomously. In the defense context, such systems can continuously record physiological and environmental parameters, process data locally, and transmit vital information to remote command centers. This reduces human error and ensures faster decision-making, especially in time-sensitive combat or rescue operations [3].

Recent developments in the Internet of Things (IoT) have made it feasible to create connected networks of soldiers, vehicles, and equipment that communicate in real time. These

systems transform a conventional combat zone into an intelligent, data-driven environment. The concept of the “Smart Soldier” integrates IoT-enabled wearables such as helmets, vests, and gloves that collect data on health, stress, fatigue, posture, and geographical location. Among these, a Smart Helmet is particularly valuable because it provides constant contact with the soldier’s head—ideal for measuring physiological parameters and detecting impacts or injuries [2].

The Smart Helmet proposed in this study combines multiple sensing and communication modules into a single embedded unit. The DHT11 sensor monitors both ambient and body temperature, the MAX30102 pulse sensor tracks heart rate and blood oxygen saturation, and the MPU6050 accelerometer detects head movement, tilt, or impact. The system also includes a Neo-6M GPS module for tracking the soldier’s precise coordinates and a GSM or LoRa communication module for wireless data transmission. All components are managed by a microcontroller, such as Arduino UNO or ESP32, which ensures reliable, low-latency data handling. When abnormal readings—such as elevated body temperature, loss of pulse, or sudden impacts—are detected, the system automatically generates an alert message that includes the soldier’s vital signs and location.

This design has multiple advantages over existing manual or semi-automated monitoring systems. First, it eliminates dependence on external supervision, allowing each soldier to function as a self-monitoring node in a distributed defense network. Second, the real-time transmission of health and location data allows commanders to make informed tactical decisions. Third, the collected data can later be analyzed using machine learning algorithms to predict potential health risks, identify fatigue patterns, and optimize mission planning.

The use of long-range communication protocols such as LoRa makes this system suitable for environments where conventional GSM coverage is weak. LoRa enables data transmission over several kilometers using minimal power, addressing one of the biggest limitations in field operations—energy efficiency. Similarly, GPS integration ensures the continuous availability of geolocation data, crucial for locating soldiers in case of emergencies or during search-and-rescue missions.

Additionally, the Smart Helmet concept aligns with broader defense modernization initiatives that emphasize human-machine collaboration. By acting as an IoT node in a defense network, the helmet can communicate with drones, medical units, and autonomous systems to create a smart, coordinated battlefield. Such systems promote predictive situational awareness—where real-time data is analyzed continuously to anticipate risks before they occur.

In conclusion, the Smart Helmet represents a step toward the next generation of defense technology where embedded systems, wireless communication, and IoT analytics converge to protect and empower soldiers. Fig. 1 shows the block diagram representing the interaction of various modules integrated within the proposed system.




Fig. 1. Block diagram of Smart Helmet for Soldier Safety.

A. Hardware choices: Arduino UNO vs ESP32

Arduino UNO provides an accessible entry point for prototyping sensor-read and control loops; however, for production-like IoT needs the ESP32 is preferable due to integrated Wi-Fi/BLE, greater RAM flash and hardware crypto modules (useful for secure soldier telemetry). The ESP32 also supports deeper sleep modes and multiple power/peripheral configurations that help meet battery life targets. Our design notes both options and provides example firmware skeletons adaptable to either platform.

B. Detailed system block (sensor-network view)

Figure 2 shows the sensor-level connections (sensors wired to MCU, local power regulation and transmitter modules). This figure clarifies wiring, power rails and the local data-aggregation concept.

II. LITERATURE SURVEY

A wide range of research has explored the integration of embedded systems and IoT technologies into soldier safety equipment. The evolution of these systems demonstrates the growing emphasis on reliability, energy efficiency, and advanced communication protocols.

Sensor Network




Fig. 2. Sensor network inside the helmet: sensors → MCU → comms module.

Kodam et al. (2020) provide a broad survey of wearable soldier monitoring, discussing hardware choices, WSN topologies, and major limitations such as power and ruggedization. The survey emphasises the need for event-driven reporting, on-node filtering and secure uplink for sensitive information [1].

Lee (2022) explores multimodal sensing in helmets (physiological and kinematic cues) and the use of lightweight machine learning models on-device for event detection and classification (e.g. distinguishing between intentional head movement and blunt trauma). The review suggests that sensor fusion reduces false positive rates dramatically when compared to single-sensor decision logic [2].

Rao and Desai (2022) demonstrated a practical ESP8266-based IoT prototype (pulse, temperature, location) for soldier health telemetry. Their use of MQTT for lightweight messaging reduced latency and network overhead; however, they reported practical limitations in cellular-only deployments in remote terrain [3].

Patil and Fernandes (2023) implemented a helmet prototype focusing on impact detection, using IMU event windows and a simple threshold + time-window filter to trigger emergency messages over GSM. They reported end-to-end alert latencies under 2 seconds under good signal conditions, but also called out battery drain as a limiting operational factor [4].

Zhang and Liu (2024) evaluated LoRaWAN in a soldier tracking context, demonstrating multi-kilometre uplinks for small telemetry packets and proposing gateway-based security mechanisms to preserve confidentiality of soldier vitals. Their results influenced our decision to include LoRa as a primary or fallback link for remote operations [5].

Sharma et al. (2022) and Gupta & Mehta (2023) focused on edge AI and power optimization respectively, proposing hybrid analytics (threshold pre-checks followed by lightweight classifiers) and duty-cycling strategies that multiply battery life while preserving event-detection sensitivity [6], [7].

To make the literature actionable for this project, we summarise practical design takeaways:

- Use multimodal fusion (DHT11 / MAX30102 /

MPU6050) to reduce false alarms.

- Perform local pre-processing and event detection to avoid constant uplinks.
- Use LoRa/LoRaWAN for long-range low-power uplink; use GSM/LTE as secondary or for high-bandwidth updates when available.
- Design firmware with adaptive sampling and power modes; consider hot-swappable batteries or solar trickle in extended missions.

Figure 3 illustrates the end-to-end data flow from sensors to cloud/dashboard, including local buffering, encryption, and gateway relay.

Smart Helmet System – Data Flow Architecture




Fig. 3. Data flow architecture: sensor → MCU → comms → IoT cloud → Command Center.

TABLE I
COMPARISON OF MAJOR SOLDIER SAFETY SYSTEMS

Author (Year)	Sensors / Modules	Tech Used	Limitations
Kodam (2020)	Survey: IMU, HR, Temp	WSN, GSM	Gaps: power, ruggedization
Lee (2022)	Multimodal sensors	Wi-Fi / BLE	ML on-device needs optimized power
Rao (2022)	HR, Temp, GPS	MQTT / GSM	Cellular coverage limits
Patil (2023)	IMU impact detection	GSM	Power, false positives
Zhang (2024)	HR, GPS, IMU	LoRaWAN	Gateway availability, security

The collective literature shows how soldier safety technology has advanced from simple GSM-based alert systems to complex multi-sensor IoT frameworks with integrated cloud connectivity. Yet, consistent issues like energy consumption, signal reliability, and system synchronization remain unsolved. The proposed Smart Helmet aims to address these limitations

by combining multiple embedded sensors, long-range communication, and efficient power management into a unified, field-deployable device.

REFERENCES

- [1] S. Kodam and R. Patel, "A review on smart wearable devices for soldier safety using wireless sensor networks," 2020.
- [2] P. Lee, "Trends in Smart Helmets With Multimodal Sensing for Health Monitoring," JMIR mHealth and uHealth, 2022.
- [3] V. Rao and P. Desai, "IoT based smart soldier safety system with real-time data communication," Sensors and Systems, 2022.
- [4] N. Patil and M. Fernandes, "Smart Helmet for Defense Applications Using Embedded IoT Devices," Proc. 2023 IEEE Intl. Conf. on IoT Systems, 2023.
- [5] T. Zhang and Q. Liu, "LoRaWAN-based soldier safety monitoring with secure communication," IEEE Access, 2024.
- [6] A. Sharma, V. Iyer and S. Ghosh, "AI-driven Wearable IoT Systems for Predictive Health Analytics," IEEE Access, 2022.
- [7] N. Gupta and A. Mehta, "Low-Power LoRa-based Soldier Tracking and Monitoring System," IEEE Sensors Journal, 2023.