





| | | | |
|--|---|---------------------|--|
| Regulatory Compliance: | IMO MODU 2009, SOLAS 2001, MARPOL 1973/78, ILO 92/133, all with latest amendments. | | |
| Classification: | ABS - A1 Drillship, AMS, OP , OE, CRC, UWILD, BWE, HELIDK | | |
| Enviromental Operating Limits: | ABS - A1 Drillship, AMS, OP , OE, CRC, UWILD, BWE, HELIDK | | |
| Bandera / Flag: |  | Bahamas | |
| <div><div></div><div>Main Specifications</div></div> | | | |
| Length Overall (LOA): | 170.3 m (559') | | |
| Moulded Breadth: | 32 m (105') | | |
| Scantling Draught: | 10.5 m (34') | | |
| Moon Pool Dimentions: | 19.6 m x 11.8 m (64' x 39') | | |
| Dinamic Position: | DP2 | | |
| Storage Capacities | | | |
| Bulk Barite/Bentonite: | 8 x 4 m3 (11,800 ft3) | Bulk Cement | |
| Potable Water: | 1,170 m3 (7,370 bbls) | Drill Water | |
| Sack Material: | 10,000 sacks | Open Pipe Deck Area | |

| | | |
|--------------------|------------------------|----------------------|
| Base Oil: | 850 m3 (5,340 bbls) | Brine |
| Diesel Fuel (MDO): | 2,590 m3 (16,300 bbls) | Liquid Mud (active) |
| Variable Load: | 18,000 tonnes | Liquid Mud (reserve) |

Accomodation Office

Max POB - 150. Ample office space for owner, client and 3rd party service companies.

Materials Handling

| | |
|-------------------|--|
| Pedestal Mounted: | 2 x 80 tonnes SWL c/w 15 tonnes whip line. |
| Deck Cranes: | Boom length 43 m (140') |

Marine Systems

| | |
|-----------------------------|--|
| Main Power: | 5 x 2700 kW (3600 HP) HIMSEN diesel engines driving 2,600 kW alternators. |
| Power Distribution: | 6.6 kV / 600 v / 440 v / 208 v / 110 v / 60 Hz |
| Propulsion / Service Speed: | Electric / 9.5 knots |
| Mooring System: | 8 point mooring system – each leg comprising 12t Stevpris Mk6 anchor, up to 3000m (9,840') of 3½" wire and up to 450m (1,475") of 3" chain. Suitable for wire/chain combination and pre-lay systems. |
| Mooring Winches: | 4 x double drum winches - 180 tonnes braked line pull. |

Drilling Systems

- Drilling Rig:** 50'x45' Bottleneck Derrick for 3x Range 2 tubulars / 2x Range 3 tubulars (90' stands), 2,000 KIP rated. Max. 580st Set Back. Equipped for offline stand building & casing racking.
- Rotary Table:** 1 x 60 1/2" Rotary with hydraulic drive. 750st capacity.
- Top Drive:** AKER 750st AC top drive with Raised Back Up and Block Retract capability.
- Heave Compensation:** 1 x Crown-Mounted Drill String Heave Compensator, 25ft Max. Stroke 800 KIP.
- Draw Works:** 5,300 HP (AC) Gear driven.
- BOP and Riser:** Cameron EVO 2 x 18 3/4" Annular Preventers, 5 x 18 3/4" Ram Preventers. 15K psi system. 5,000' of 21" Marine Riser in 75' lengths c/w Choke, Kill & Booster Lines. 2 x 55' stroke Telescopic Joints
- Diverter Sytem:** Cameron CSO
- BOP Control System:** Cameron Mark III Multiplex - Yellow and Blue Pods/Hoses. 1 x Hot Line.
- Drill String** 5 7/8" / 6 5/8" / 5" Drill String c/w Subs, Driller Collars and HWDP.

Drilling Fluid Systems

- Mud Pumps and Tratment System:** 4 x 2,400HP electric quintaplex mud pumps-7,500psi max work pressure. MISwaco 4 x Triple Deck Shale Shakers, 2400 GPM each. 1 x Mud Gas Separator. 1 x Vacuum Degasser. 2 x 25bbbls Trip Tanks.

Miscellaneous

- Helicopter Deck Capacity:** RSN80-340/2C 24/61 m X 116/58 cub m/h
- Life Saving Equipment:** 4 x Lifeboats, 80 persons each. 1 x Fast Rescue Craft. 12 x 25p life rafts

