Session 02 — D3·D1 Consolidation (16 questions, 32 min)

날짜 _____ 시작 _____ 종료 _____ 점수 _____

1회차 결과(13/15, 추정 846)를 반영했습니다. D3 5 · D1 5 · D2 2 · D4 2 · D5 2. 초점: **Claude Code 확장 기능 구분 (skill·subagent·hook·settings)**, 1회차에 확신도 1~2로 맞힌 개념 재확인, 한 번만 나온 D5 개념 보강. **NOT** 이 들어간 문항이 2개 있습니다. 질문을 끝까지 읽고 고르세요.

풀이 방법: 답과 확신도(1=찍음 … 5=확실)를 답안표에 표시. 다 풀 때까지 `keys/` 는 열지 않는다.

Q1

A team wants a `/deploy-check` workflow that developers invoke by name before a release. It needs a 25-item checklist plus a helper script that validates environment variables. It should not consume context in sessions where nobody is deploying. What is the best fit?

A. A `PreToolUse` hook that runs the checklist on every command

B. A subagent that runs automatically at the start of every session

C. A skill in `.claude/skills/deploy-check/` with a `SKILL.md` and the helper script bundled alongside it

D. The checklist and script contents pasted into `CLAUDE.md`

내 답 _____ 확신도 ① ② ③ ④ ⑤

판단 근거 메모

Q2

Which of the following is **NOT** a good use of a Claude Code hook?

A. Blocking any write to `config/production.yaml` with a `PreToolUse` hook

B. Running the code formatter after Claude edits a file

C. Injecting the current branch and open issue number into context when a session starts

D. Teaching Claude the team's architectural conventions for designing new services

내 답 _____ 확신도 ① ② ③ ④ ⑤

판단 근거 메모

Q3

During a large refactor, Claude needs to find out how a deprecated library is used across 500 files. Reading them all in the main session would flood its context. What is the best approach?

A. Read all 500 files in the main session, then compact

B. Delegate the investigation to a subagent that explores in its own context and returns a concise summary of usage patterns

C. Create a skill that lists the 500 files

D. Switch to plan mode so the files are not modified

내 답 _____ 확신도 ① ② ③ ④ ⑤

판단 근거 메모

Q4

A developer wants Claude Code to run `npm run lint` without asking, but only for themselves and only in this project. Teammates should not be affected. Where should the allow rule go?

- **A.** `.claude/settings.local.json` in the project
- **B.** `.claude/settings.json` in the project
- **C.** `~/.claude/settings.json`
- **D.** A line in `CLAUDE.md` saying lint may be run freely

내 답 _____ 확신도 ① ② ③ ④ ⑤

판단 근거 메모

Q5

A CI job runs Claude Code and a downstream step must parse a result that conforms to a specific JSON Schema. Which invocation is most appropriate?

- **A.** `claude "<prompt>"` interactively, then copy the output
- **B.** `claude -p "<prompt>"` and parse the plain text with regex
- **C.** `claude -p "<prompt>" --output-format json --json-schema '<schema>'`, then read the `structured_output` field
- **D.** `claude -p "<prompt>" --output-format stream-json` and take the first line

내 답 _____ 확신도 ① ② ③ ④ ⑤

판단 근거 메모

Q6

Which of the following is **NOT** a good reason to introduce subagents?

- **A.** Isolating a large exploration so its raw material does not fill the main context
- **B.** Making a simple, fixed three-step sequential pipeline more robust
- **C.** Running independent research tasks in parallel
- **D.** Giving different roles different, narrower tool permissions

내 답 _____ 확신도 ① ② ③ ④ ⑤

판단 근거 메모

Q7

Incoming documents must first be identified as a contract, an invoice, or a resume. Each type then goes through its own fixed sequence of processing steps, which never vary. What design fits best?

A. One autonomous agent with every tool for all three types

B. A coordinator agent that improvises a new plan for each document

C. Three agents that each process every document and vote on the result

D. A routing workflow: a classification step, then a fixed, specialized pipeline for each document type

내 답 _____ 확신도 1 2 3 4 5

판단 근거 메모

Q8

In Claude Code you want the project's code formatter to run automatically on every file Claude edits or creates. What is the right mechanism?

A. A `PostToolUse` hook matching `Edit|Write` that runs the formatter on the changed file

B. A `PreToolUse` hook matching `Edit|Write` that runs the formatter

C. A `Stop` hook that formats the entire repository

D. An instruction in `CLAUDE.md` to always format files

내 답 _____ 확신도 1 2 3 4 5

판단 근거 메모

Q9

In a Messages API agentic loop, the model returns a response with `stop_reason: "tool_use"`. Before sending the tool results, what must the conversation history contain?

A. Only the original user message; the tool results replace the assistant turn

B. A system-prompt update describing which tool was called

C. The assistant's response appended as-is (including its `tool_use` blocks), followed by a new user message with the matching `tool_result` blocks

D. A summary of the assistant's response in place of the original blocks

내 답 _____ 확신도 1 2 3 4 5

판단 근거 메모

Q10

A coordinator delegates a task to a subagent. The subagent starts with a fresh context and does not see the coordinator's conversation. What should the delegation message contain?

A. Only a short task title; the subagent will ask follow-up questions

B. A self-contained brief: the goal, the specific inputs and constraints it needs, and the expected output format

C. The coordinator's entire conversation history

D. Nothing beyond the tool list, since the subagent can discover everything itself

내 답 _____ 확신도 ① ② ③ ④ ⑤

판단 근거 메모

Q11

Which capability is the best candidate for a custom MCP server?

A. The company's internal pricing engine, which applies contract-specific discount rules

B. Reading files in the local repository

C. Running shell commands in the project

D. A general web search that the platform already provides

내 답 _____ 확신도 ① ② ③ ④ ⑤

판단 근거 메모

Q12

A `schedule_meeting` tool takes a `start_time` string. The model often passes values like `"next Friday afternoon"`, which the backend rejects. What is the best first fix?

A. Add an NLP service to parse natural-language dates before the backend

B. Switch to a larger model

C. Let the backend accept any string and guess the date

D. In the input schema and description, specify ISO 8601 format with an example and state that relative dates must be resolved first (e.g., using a provided current date)

내 답 _____ 확신도 ① ② ③ ④ ⑤

판단 근거 메모

Q13

A summarizer's prompt includes three few-shot examples, all of short news articles with one-sentence summaries. On long technical reports, it now produces summaries that are far too short. What is the most likely cause and fix?

A. The model is too small; upgrade it

B. The examples are not representative; add examples covering varied lengths and document types, including long reports with appropriately longer summaries

C. Temperature is too low; raise it

D. Remove all examples and rely on instructions alone

내 답 _____ 확신도 ① ② ③ ④ ⑤

판단 근거 메모

Q14

A prompt says "NEVER use ellipses." The model still uses them occasionally. According to Anthropic's prompting guidance, which change is most likely to help?

A. Repeat the rule three times in capital letters

B. Move the rule to the very end of the conversation

C. Explain why: the output will be read aloud by a text-to-speech engine that cannot pronounce ellipses

D. Add a reviewer model that strips ellipses

내 답 _____ 확신도 ① ② ③ ④ ⑤

판단 근거 메모

Q15

A team enabled prompt caching on a large, unchanging system prompt, but the cache hit rate is near zero. The system prompt starts with `Current time: 2026-10-11T17:57:03Z`. What is the fix?

A. Move the timestamp out of the cached prefix (after the cache breakpoint, e.g., into the user message) so the stable prefix is identical across requests

B. Switch to the 1-hour cache TTL

C. Add more cache breakpoints inside the system prompt

D. Cache the user message instead

내 답 _____ 확신도 ① ② ③ ④ ⑤

판단 근거 메모

Q16

A support agent handles conversations of 200+ turns. Key facts given early (the customer's account ID, the agreed refund amount, a promised deadline) get lost or distorted after the history is summarized. What is the best fix?

A. Disable summarization and keep the full history

B. Switch to a model with a larger context window

C. Ask the customer to repeat key facts every 20 turns

D. Maintain a structured "case facts" record outside the transcript, update it as facts are confirmed, and include it in every request

내 답 _____ 확신도 ① ② ③ ④ ⑤

판단 근거 메모

답안표

★ = 복수 정답(2개). 다 푼 뒤 이 표를 보고 `results/` 답안지를 채우거나 채팅으로 전달.

문항	답	확신도	O/X
Q1	Ⓐ Ⓑ Ⓒ Ⓓ	① ② ③ ④ ⑤	
Q2	Ⓐ Ⓑ Ⓒ Ⓓ	① ② ③ ④ ⑤	
Q3	Ⓐ Ⓑ Ⓒ Ⓓ	① ② ③ ④ ⑤	
Q4	Ⓐ Ⓑ Ⓒ Ⓓ	① ② ③ ④ ⑤	
Q5	Ⓐ Ⓑ Ⓒ Ⓓ	① ② ③ ④ ⑤	
Q6	Ⓐ Ⓑ Ⓒ Ⓓ	① ② ③ ④ ⑤	
Q7	Ⓐ Ⓑ Ⓒ Ⓓ	① ② ③ ④ ⑤	
Q8	Ⓐ Ⓑ Ⓒ Ⓓ	① ② ③ ④ ⑤	
Q9	Ⓐ Ⓑ Ⓒ Ⓓ	① ② ③ ④ ⑤	
Q10	Ⓐ Ⓑ Ⓒ Ⓓ	① ② ③ ④ ⑤	
Q11	Ⓐ Ⓑ Ⓒ Ⓓ	① ② ③ ④ ⑤	
Q12	Ⓐ Ⓑ Ⓒ Ⓓ	① ② ③ ④ ⑤	
Q13	Ⓐ Ⓑ Ⓒ Ⓓ	① ② ③ ④ ⑤	
Q14	Ⓐ Ⓑ Ⓒ Ⓓ	① ② ③ ④ ⑤	
Q15	Ⓐ Ⓑ Ⓒ Ⓓ	① ② ③ ④ ⑤	
Q16	Ⓐ Ⓑ Ⓒ Ⓓ	① ② ③ ④ ⑤	