
COMP 7640 Written Assignment #3

Due: 11:59 PM April 24 (Friday), 2025


Question 1. Given an extendible hashing index as shown in the figure below, where each bucket can contain 4 data entries,

- (1) If we are given a query with the condition key=11, how many I/Os are needed for this query? (6 marks)
- (2) Draw the resulting index after inserting 2* and then 8*. (16 marks)



Solution:

- (1) 2 I/Os. 1 I/O for reading Bucket D (3 marks). 1 I/O for reading the data page. (3 marks)
- (2) Below see the updated index



Question 2. We are given two relations S and E, which contain 10,000 records and 1,000 records, respectively. Each disk page can hold 100 S records and 5 E records, respectively. Consider the relational operation S $\bowtie_{S.sid=E.sid}$ E and estimate the I/O costs of the following access paths.

- (a) What is the lowest cost of using a page-oriented nested loop join? (10 marks)
- (b) What is the lowest cost of using a simple-nested loop join? (12 marks)

[**Remark**: There is no I/O cost for writing the result back to the disk.]

Solution:

```
#Pages for S: 10,000/100 = 100 pages (4 marks)

#Pages for E: 1,000/5 = 200 pages (4 marks)

(a) 100 + 100 * 200 = 20,100 I/Os (4 marks)

(b) When S is the outer relation: 100 + 10,000 * 200 = 2,000,100 I/Os (4 marks)


When E is the outer relation: 200 + 1,000 * 100 = 100,200 I/Os (4 marks)

So the lowest I/O cost is 100,200 I/Os. (2 marks)
```

Question 3. Consider the query $\pi_{a,b,c,d}$ ($R \bowtie_{a=c} S$) with the following information:

- a) Relation R(a, b, e) (a is the key) has 10 pages, and each R record needs 300 bytes;
- b) Relation $S(\underline{c}, d, f, g)$ (c is the key) has 100 pages, and each S record needs 500 bytes;
- c) Attributes a, b, c, and d take 100, 50, 100, and 150 bytes, respectively;
- d) The page size is 1024 bytes;
- e) Each S record joins with exactly one R record.

Estimate the total I/O cost for the following two query evaluation plans:



(10 marks)

(22 marks)

Solution:


```
(1) Cost of join = 10 + 10 * 100 = 1010 page I/Os
                                                            (5 marks)
   Total cost = Cost of join = 1010 page I/Os
                                                             (5 marks)
(2)
   Cost of \pi_{a,b}(R)
    = Cost to scan R + cost to write T1
    = 10 \text{ pages} + \text{size}(T1)
    = 10 pages + (150 bytes/300 bytes) * 10 pages
    = 10 \text{ pages} + 5 \text{ pages}
    = 15 pages
                                        (7 marks)
    Cost of \pi_{c,d}(S)
    = Cost to scan S + cost to write T2
    = 100 \text{ pages} + \text{size}(T2)
    = 100 pages + (250 bytes/500 bytes)*100 pages
    = 100 \text{ pages} + 50 \text{ pages}
    = 150 pages
                                     (7 marks)
Cost of join = 5 + (5*50) = 255 pages
                                               (4 marks)
Total cost = Cost of projection + Cost of join = 165 + 255 = 420 I/Os
                                                                                 (4 marks)
(The following is also correct:
#records in R = 10*|1024/300| = 30
||T1-records per page = |1024/150| = 6
Size(T1) = 30/6 = 5 pages
 Cost of \pi_{a,b}(R)
    = Cost to scan R + cost to write T1
    = 10 \text{ pages} + 5 \text{ pages}
    = 15 pages
                                       (7 marks)
#records in S = 100*|1024/500| = 200
||T2-records per page = |1024/250| = 4
Size(T2) = 200/4 = 50 pages
    Cost of \pi_{c,d}(S)
    = Cost to scan S + cost to write T2
    = 100 \text{ pages} + 50 \text{ pages}
    = 150  pages
                                     (7 marks)
Cost of join = 5 + (5*50) = 255 pages
                                               (4 marks)
Total cost = Cost of projection + Cost of join = 165 + 255 = 420 I/Os
                                                                                 (4 marks)
```

Question 4. Given two relations S(SID, Name, GPA, age) and E(CID, SID, Date), and the following SQL query:

SELECT S.Name, S.GPA
FROM S, E
WHERE S.GPA>3.5 AND S.SID=E.SID

Draw three query evaluation plans for this SQL query. (24 marks)

Solution: Other appropriate access paths are also correct. (No access paths. Reduce 3 marks for each QEP.)



Late Penalty: Late assignments will be marked down 50% for each day it is late. Any

exceptions to this rule must be made prior to when the assignment is due and the excuse needs to be a good one - just too busy won't cut it. Individual exceptions are unfair to other students and hence they won't be made unless the circumstances are truly exceptional.

Plagiarism: All work submitted by you should be your own. Copying or sharing of

assignments would constitute plagiarism. Penalty will be given to those involved in plagiarism. This will be no exception once plagiarism is caught – being copied without notice won't excuse it; you should simply keep your

assignment well.

Submission: Please submit your assignment via BUMoodle