

Generalized Hebbian algorithm

The **generalized Hebbian algorithm** (**GHA**), also known in the literature as **Sanger's rule**, is a linear feedforward neural network model for unsupervised learning with applications primarily in principal components analysis. First defined in 1989,^[1] it is similar to Oja's rule in its formulation and stability, except it can be applied to networks with multiple outputs. The name originates because of the similarity between the algorithm and a hypothesis made by Donald Hebb^[2] about the way in which synaptic strengths in the brain are modified in response to experience, i.e., that changes are proportional to the correlation between the firing of pre- and post-synaptic neurons.^[3]

Contents

Theory

Derivation

Stability and PCA

Applications

See also

References

Theory

The GHA combines Oja's rule with the Gram-Schmidt process to produce a learning rule of the form

$$\Delta w_{ij} = \eta \left(y_i x_j - y_i \sum_{k=1}^i w_{kj} y_k \right),^{[4]}$$

where w_{ij} defines the synaptic weight or connection strength between the j th input and i th output neurons, x and y are the input and output vectors, respectively, and η is the learning rate parameter.

Derivation

In matrix form, Oja's rule can be written

$$\frac{dw(t)}{dt} = w(t)Q - \text{diag}[w(t)Qw(t)^T]w(t),$$

and the Gram-Schmidt algorithm is

$$\Delta w(t) = -\text{lower}[w(t)w(t)^T]w(t),$$

where $w(t)$ is any matrix, in this case representing synaptic weights, $Q = \eta \mathbf{x} \mathbf{x}^T$ is the autocorrelation matrix, simply the outer product of inputs, **diag** is the function that diagonalizes a matrix, and **lower** is the function that sets all matrix elements on or above the diagonal equal to 0. We can combine these equations

to get our original rule in matrix form,

$$\Delta w(t) = \eta(t) (\mathbf{y}(t)\mathbf{x}(t)^T - \text{LT}[\mathbf{y}(t)\mathbf{y}(t)^T]w(t)),$$

where the function LT sets all matrix elements above the diagonal equal to 0, and note that our output $\mathbf{y}(t) = w(t) \mathbf{x}(t)$ is a linear neuron.^[1]

Stability and PCA

[5] [6]

Applications

The GHA is used in applications where a self-organizing map is necessary, or where a feature or principal components analysis can be used. Examples of such cases include artificial intelligence and speech and image processing.

Its importance comes from the fact that learning is a single-layer process—that is, a synaptic weight changes only depending on the response of the inputs and outputs of that layer, thus avoiding the multi-layer dependence associated with the backpropagation algorithm. It also has a simple and predictable trade-off between learning speed and accuracy of convergence as set by the learning rate parameter η .^[5]

See also

- Hebbian learning
- Factor analysis
- Contrastive Hebbian learning
- Oja's rule

References

1. Sanger, Terence D. (1989). "Optimal unsupervised learning in a single-layer linear feedforward neural network" (http://courses.cs.washington.edu/courses/cse528/09sp/sanger_pca_nn.pdf) (PDF). *Neural Networks*. **2** (6): 459–473. CiteSeerX 10.1.1.128.6893 (<https://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.128.6893>). doi:10.1016/0893-6080(89)90044-0 (<https://doi.org/10.1016%2F0893-6080%2889%2990044-0>). Retrieved 2007-11-24.
2. Hebb, D.O. (1949). *The Organization of Behavior* (<https://books.google.com/books?id=uyV5AgAAQBAJ>). New York: Wiley & Sons. ISBN 9781135631918.
3. Hertz, John; Anders Krough; Richard G. Palmer (1991). *Introduction to the Theory of Neural Computation*. Redwood City, CA: Addison-Wesley Publishing Company. ISBN 978-0201515602.
4. Gorrell, Genevieve (2006), "Generalized Hebbian Algorithm for Incremental Singular Value Decomposition in Natural Language Processing.", *EACL*, CiteSeerX 10.1.1.102.2084 (<http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.102.2084>)
5. Haykin, Simon (1998). *Neural Networks: A Comprehensive Foundation* (2 ed.). Prentice Hall. ISBN 978-0-13-273350-2.
6. Oja, Erkki (November 1982). "Simplified neuron model as a principal component analyzer". *Journal of Mathematical Biology*. **15** (3): 267–273. doi:10.1007/BF00275687 (<https://doi.org/>

10.1007%2FBF00275687). PMID 7153672 (<https://pubmed.ncbi.nlm.nih.gov/7153672>).
S2CID 16577977 (<https://api.semanticscholar.org/CorpusID:16577977>). BF00275687.

Retrieved from "https://en.wikipedia.org/w/index.php?title=Generalized_Hebbian_algorithm&oldid=1016476670"

This page was last edited on 7 April 2021, at 11:28 (UTC).

Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.