MIREX ONSET DETECTION TASK

Sebastian Böck
Department of Computational Perception
Johannes Kepler University, Linz, Austria
sebastian.boeck@jku.at

ABSTRACT

This extended abstract describes the MIREX submission `OnsetDetector.2012` and it's online variant `OnsetDetectorLL` for the onset detection task.

1. INTRODUCTION

For the technical details of the systems, please see [3] and [1].

2. RESULTS

Both `OnsetDetector.2012` and `OnsetDetectorLL` mark the current state-of-the-art in onset detection in offline and online settings.

Algorithm	F-measure	Precision	Recall
OnsetDetector.2012	**0.8538**	0.8518	0.8835
OnsetDetectorLL *	**0.8309**	0.8450	0.8484
LogFiltSpecFlux [2].	0.8224	0.8172	0.8572
LogFiltSpecFlux [2]. *	0.8180	0.8167	0.8477
Röbel (2011)	0.8065	0.7831	0.8788
Zhou (2007)	0.8080	0.8570	0.7820

Table 1. MIREX onset detection results. Asterisks mark online results. Years other than 2012 are indicated accordingly.

3. REFERENCES

[1] S. Böck, A. Arzt, F. Krebs, and M. Schedl. Online real-time onset detection with recurrent neural networks. In *Proceedings of the 15th International Conference on Digital Audio Effects (DAFx-12)*, York, UK, September 2012.

[2] S. Böck, F. Krebs, and M. Schedl. Evaluating the online capabilities of onset detection methods. In *Proceedings of the 13th International Society for Music Information Retrieval Conference (ISMIR 2012)*, Porto, Portugal, October 2012.

[3] F. Eyben, S. Böck, B. Schuller, and A. Graves. Universal onset detection with bidirectional long short-term memory neural networks. In *Proceedings of the 11th International Society for Music Information Retrieval Conference (ISMIR 2010)*, pages 589–594, 2010.