USB-C INPUT / POWER

CC1 and CC2 each have their own 5.1k Rd, so USB-C to USB-C hosts enable VBUS.

STATUS LEDS (same GPIOs as the official Debug Probe)

LEVEL-SHIFTED IO0..IO7

A = 3V3 side, B = VIO side
DIR high = probe drives the pin

VIO (target reference): INT = 3V3 from the probe, EXT = VTREF from the target

TRANSLATOR 3V3-SIDE DECOUPLING

TARGET CONNECTOR (2x8, 2.54 mm)

TARGET-SIDE ESD

RP2040 — pin map of the Raspberry Pi Debug Probe firmware

+5 V TO THE TARGET (USB VBUS through Schottky + polyfuse)

MOUNTING HOLES / ERC POWER FLAGS

ANALOG INPUTS (clamped to 0..3.3 V) / VIO SENSE

Pin map compatible with Raspberry Pi Debug Probe (debugprobe) firmware
Generated from gen/design.py + gen/sch_layout.py — edit the generator, not this file
www.eetree.cn

EETree Info & Tech	
Sheet: /	
File: LA_RP2040_V2.kicad_sch	
Title: LA_RP2040 V2 — Multi-function Debug Probe	
Size: A2	Date: 2026-11-12
KiCad E.D.A. 9.0.9	**Rev: V2.0**
	Id: 1/1