# Sentimental Analysis on IMDB


Gonsoo Moon
Post Master Student of Computer Science
University of Texas at Dallas,
gonsoomoon@gmail.com

#### 1. Introduction

Using Dropout LSTM (Long Short Term Memory), sentimental prediction on the IMDB movie reviews is implemented. The movie reviews handled is 22,500 as a train data set and 2,500 as a test data set. The 25,000 movie reviews already have a label of either positive or negative. <The Figure 1> shows an overview of the sentimental prediction neural network, technically having embedding and dropout LSTM layer.

### <Figure1>

#### Sentimental Prediction Neural Network Outline



#### 2. Network Architecture

The input data is downloaded from http://www.iro.umontreal.ca/~lisa/deep/data/imdb.pkl. I only used 25,000 reviews. With 32 of batch size, 703 minibatches are made out of 22,500 reviews. Each minibatch, which is 32 \* 500, is fed into the following network: embedding layer generating 32 \* 500 \* 512 embeddings, dropout LSTM layer with 0.5 dropout rate and 512 sequence length producing 32 \* 512 outputs, sigmoid layer with the batch normalization resulting in 32 \* 2 predictions. For the input 32 \* 500 minibatches, if a review is more than 500 indices, the rest of them after 500 indices are truncated. In the case of being less than 500 indices, 0 is padded into the empty slots until the 500 index. Thus, every review has a length of 500. Through the

intermediate layers, the final prediction is given in the form of either positive as 1 or negative as 0.


## 3. Experiment & Result

The <Figure2> shows the training cost only after one epoch and test accuracy using the test data set that are not good because of the first epoch.

host/replica:0/task:0/cpu:0
data.train.num\_examples: 22500
Total of 703 minbatches in epoch 0
minibatch\_x: (32, 500) minibatch\_y: (32, 2)
embedding shape: (32, 500, 512)
lstm output shape: (32, 5)12)
output shape: (32, 2)
Training cost for batch 0 in epoch 0 was: 0.693879
Epoch: 0001 Minibatch: 0001 cost = 0.69387810
Validation Accuracy: 0.48

However, as the epoch increases, the training cost and validation cost decrease, shown in <Figure3> that is coming from the book [1], resulting in 86% accuracy.

<Figure 3>



The Passion Project in Sep 2017 <Source code: https://gonsoomoon.github.io/RNN/>

# 4. References

[1] Nikhil Buduma (2017). Fundamentals of deep learning. Sebastopol, CA: O'Reilly Media