PYTHON PROGRAMMING
ACTIVITY - BASED LEARNING
10 Case Studies with Solutions

- Name: GONTHUMURTHY VINAY KUMAR
- Roll Number: 26000021
- Branch: Computer Science &
- Engineering
- Section: CSE1
- Course: Python Programming
- Institution: Dr. RVR NRI Institute of
- Technology

Contents: -

1. Case Study 1: University Scholarship Allocation

2. Case Study 2: Progressive Electricity Billing

3. Case Study 3: Hospital Billing and Patient Classification

4. Case Study 4: Employee Payroll and Deduction Analysis

5. Case Study 5: Multi-Plan Telecommunications Cost Optimization

6. Case Study 6: Railway Fare and Reservation Calculator

7. Case Study 7: Retail Billing with Multiple Discount Rules

8. Case Study 8: Manufacturing Cost and Profitability Analysis

9. Case Study 9: Multi-Currency Travel Budget Analysis

10. Case Study 10: Campus Event Financial Planning

CASE STUDY 1: University Scholarship Allocation

1. Problem Statement

Develop a program to evaluate scholarship applicants using aggregate marks, subject-wise minimum marks, attendance, and family income. Rank eligible students and display the result.

2. Objectives

- Read applicant details and marks.
- Calculate aggregate percentage.
- Check subject minimum, attendance, and income conditions.
- Classify applicants as eligible or not eligible and show the result.

3. Assumptions

- Three subject marks are entered, each from 0 to 100.
- Every subject must have at least 50 marks.
- Attendance must be at least 75%.
- Family income must not exceed 300,000.
- Eligible applicants are evaluated based on the criteria thresholds.

4. Algorithm

1. Start.
2. Input applicant name, three marks, attendance, and family income.
3. Check whether marks are between 0 and 100 and other values are valid.
4. Calculate total and percentage.
5. Check all scholarship conditions using conditional statements.
6. Display eligibility and aggregate percentage.
7. Stop.

5. Flowchart

Plaintext

START

INPUT DETAILS

  |

  ▼

VALIDATE INPUTS

  |

  ▼

CALCULATE USING CONDITIONS / LOOPS

  |

  ▼

DISPLAY RESULT

  |

  ▼

STOP

6. Pseudocode

Plaintext

START

  INPUT name, m1, m2, m3, attendance, income

  total = m1 + m2 + m3

  percentage = total / 3

  IF any mark < 0 OR mark > 100 OR attendance < 0 OR attendance > 100 OR income < 0 THEN

    PRINT "Invalid input."

  ELSE

    IF m1 < 50 OR m2 < 50 OR m3 < 50 OR attendance < 75 OR income > 300000 THEN

      PRINT "Result: Not eligible for scholarship"

    ELSE

      PRINT "Result: Eligible for scholarship"

    END IF

```
  END IF
STOP
```

7. Python Source Code (case_study_3.py)

```
name = input("Applicant name: ")
m1 = float(input("Subject 1 marks: "))
m2 = float(input("Subject 2 marks: "))
m3 = float(input("Subject 3 marks: "))
attendance = float(input("Attendance percentage: "))
income = float(input("Family annual income (Rs.): "))

if (m1 < 0 or m1 > 100 or m2 < 0 or m2 > 100 or m3 < 0 or m3 > 100 or attendance < 0 or attendance > 100 or income < 0):
  print("Invalid input.")
else:
  percentage = (m1 + m2 + m3) / 3
  print("Applicant:", name)
  print("Aggregate percentage:", round(percentage, 2))


  if m1 >= 50 and m2 >= 50 and m3 >= 50 and attendance >= 75 and income <= 300000:
    print("Result: Eligible for scholarship")
  else:
    print("Result: Not eligible for scholarship")
```

8. Test Cases

Input / Situation	Expected Result	Purpose
Anu, 80, 75, 90, 85, 200000	81.67%; Eligible	Normal case

Input / Situation	Expected Result	Purpose
Ravi, 45, 80, 70, 90, 150000	Not eligible (subject below 50)	Minimum-mark check
Maya, 70, 70, 70, 60, 100000	Not eligible (attendance below 75%)	Attendance check

9. Output screenshots



10. Conclusion

The program successfully uses variables, arithmetic operators, and conditional statements to check scholarship eligibility according to predefined criteria.

CASE STUDY 2: Progressive Electricity Billing

1. Problem Statement

Calculate a household electricity bill using multiple consumption slabs, a fixed charge, and a surcharge for high consumption.

2. Objectives

- Read units consumed.
- Calculate charges slab by slab.
- Add the fixed charge and any surcharge.
- Print a bill summary.

3. Assumptions

- First 100 units cost 2 per unit.
- Next 100 units cost 3 per unit.
- Units above 200 cost 5 per unit.
- Fixed charge is 50.
- Consumption above 200 units has a 5% surcharge on energy charge.


4. Algorithm

1. Start.
2. Input units consumed.
3. Reject negative units.
4. Calculate energy charge using the correct slab.
5. Calculate fixed charge and surcharge.
6. Add all charges and display the bill.
7. Stop.

5. Flowchart

Plaintext

START



INPUT DETAILS



VALIDATE INPUTS



CALCULATE USING CONDITIONS / LOOPS



DISPLAY RESULT



STOP

6. Pseudocode

Plaintext

```
START
  INPUT units
  IF units < 0:
    PRINT error
  ELSE IF units <= 100:
    energy = units * 2
  ELSE IF units <= 200:
    energy = 100 * 2 + (units - 100) * 3
  ELSE:
    energy = 100 * 2 + 100 * 3 + (units - 200) * 5

  fixed = 50
  IF units > 200:
```

```
    surcharge = energy * 0.05
  ELSE:
    surcharge = 0

  total = energy + fixed + surcharge
  PRINT energy, fixed, surcharge, total
STOP
```

7. Python Source Code (case_study_2.py)

```
units = int(input("Enter electricity units: "))

if units < 0:
  print("Invalid units.")
else:
  if units <= 100:
    energy = units * 2
  elif units <= 200:
    energy = 100 * 2 + (units - 100) * 3
  else:
    energy = 100 * 2 + 100 * 3 + (units - 200) * 5

  if units > 200:
    fixed = 50
    surcharge = energy * 0.05
  else:
    fixed = 50
    surcharge = 0


  total = energy + fixed + surcharge
```

```
print("\n--- Electricity Bill ---")
print("Energy charge: Rs.", round(energy, 2))
print("Fixed charge: Rs.", fixed)
print("Surcharge: Rs.", round(surcharge, 2))
print("Total bill: Rs.", round(total, 2))
```

8. Test Cases

Input / Situation	Expected Result	Purpose
80	Energy 160; total 210	Normal
150	Energy 350; total 400	Middle slab
250	Energy 750; surcharge 37.50; total 837.50	High slab

9. Output Screenshots



10. Conclusion

The program demonstrates progressive slab calculations, conditions, and arithmetic operators.

CASE STUDY 3: Hospital Billing and Patient Classification

1. Problem Statement

Calculate consultation, diagnostic, and treatment charges, apply a concession when eligible, validate inputs, and classify the bill using the final amount.

2. Objectives

- Read the three charge amounts.
- Validate that charges are non-negative.
- Apply a concession for senior patients.
- Calculate the final amount and classify the bill.

3. Assumptions

- Consultation, diagnostics, and treatment charges cannot be negative.
- Senior patients aged 60 or above receive a 10% concession on the subtotal.
- Bills below 1000 are Basic, 1000 to 4999 are Standard, and 5000 or more are High.


4. Algorithm

1. Start.
2. Input age and the three charges.
3. Validate all inputs.
4. Add charges to find subtotal.
5. Apply 10% concession if age is at least 60.
6. Calculate final bill and classification.
7. Display the bill.
8. Stop.

5. Flowchart

Plaintext

START



INPUT DETAILS



6. Pseudocode

Plaintext

```
START
  INPUT age, consultation, diagnostics, treatment
  IF age < 0 OR consultation < 0 OR diagnostics < 0 OR treatment < 0 THEN
    PRINT "Invalid input."
  ELSE
    subtotal = consultation + diagnostics + treatment
    IF age >= 60 THEN
      discount = subtotal * 0.10
    ELSE
      discount = 0
    END IF
    final_bill = subtotal - discount
    IF final_bill < 1000 THEN
      category = "Basic"
```

```
    ELSE IF final_bill < 5000 THEN
      category = "Standard"
    ELSE
      category = "High"
    END IF
    PRINT subtotal, discount, final_bill, category
  END IF
STOP
```

7. Python Source Code (case_study_3.py)


```
age = int(input("Patient age: "))
consult = float(input("Consultation charge: Rs. "))
diagnostic = float(input("Diagnostic charge: Rs. "))
treatment = float(input("Treatment charge: Rs. "))
if age < 0 or consult < 0 or diagnostic < 0 or treatment < 0:
  print("Invalid input.")
else:
  subtotal = consult + diagnostic + treatment
  if age >= 60:
    discount = subtotal * 0.10
  else:
    discount = 0
  final_bill = subtotal - discount
  if final_bill < 1000:
    category = "Basic"
  elif final_bill < 5000:
    category = "Standard"
  else:
    category = "High"
```

```
print("\n--- Hospital Bill ---")
print("Subtotal: Rs.", round(subtotal, 2))
print("Concession: Rs.", round(discount, 2))
print("Final bill: Rs.", round(final_bill, 2))
print("Bill category:", category)
```

8. Test Cases

Input / Situation	Expected Result	Purpose
Age 65; 500, 800, 2000	Subtotal 3300; concession 330; final 2970; Standard	Senior concession
Age 30; 200, 200, 300	Final 700; Basic	No concession
Age 50; -5, 100, 100	Invalid input	Validation

9. Output Screenshots



10. Conclusion

The program uses input validation, conditional concessions, and classification of a final bill.

CASE STUDY 4: Employee Payroll and Deduction Analysis

1. Problem Statement

Calculate gross salary from basic pay, allowances, overtime, and incentives. Apply a deduction and display a formatted salary statement.

2. Objectives

- Read basic pay, overtime hours, and incentive.
- Calculate allowances and overtime pay.
- Calculate gross salary, deduction, and net salary.
- Display the salary statement.

3. Assumptions

- HRA is 20% of basic pay.
- Other allowance is 10% of basic pay.
- Overtime is 150 per hour.
- Incentive is added to gross salary.
- Deduction is 8% of gross salary.


4. Algorithm

1. Start.
2. Input basic pay, overtime hours, and incentive.
3. Reject negative values.
4. Calculate HRA, other allowance, and overtime pay.
5. Calculate gross salary and deduction.
6. Calculate net salary and display details.
7. Stop.

5. Flowchart

Plaintext

START



INPUT DETAILS



VALIDATE INPUTS



CALCULATE USING CONDITIONS / LOOPS



DISPLAY RESULT



STOP

6. Pseudocode

Plaintext

```
START
  INPUT basic, overtime_hours, incentive
  IF basic < 0 OR overtime_hours < 0 OR incentive < 0 THEN
    PRINT error
  ELSE
    hra = basic * 0.20
    other = basic * 0.10
    overtime = overtime_hours * 150
    gross = basic + hra + other + overtime + incentive
    deduction = gross * 0.08
    net = gross - deduction
    PRINT salary details
  END IF
```

STOP

7. Python Source Code (case_study_4.py)

Python

```
basic = float(input("Basic pay (Rs.): "))
hours = float(input("Overtime hours: "))
incentive = float(input("Incentive (Rs.): "))


if basic < 0 or hours < 0 or incentive < 0:
    print("Invalid input.")
else:
    hra = basic * 0.20
    other = basic * 0.10
    overtime = hours * 150
    gross = basic + hra + other + overtime + incentive
    deduction = gross * 0.08
    net = gross - deduction

    print("\n--- Salary Statement ---")
    print("Basic pay: Rs.", round(basic, 2))
    print("HRA: Rs.", round(hra, 2))
    print("Other allowance: Rs.", round(other, 2))
    print("Overtime pay: Rs.", round(overtime, 2))
    print("Incentive: Rs.", round(incentive, 2))
    print("Gross salary: Rs.", round(gross, 2))
    print("Deduction: Rs.", round(deduction, 2))
    print("Net salary: Rs.", round(net, 2))
```

8. Test Cases

Input / Situation	Expected Result	Purpose
Basic 20000; 2 hours; incentive 500	Gross 26800; deduction 2144; net 24656	Normal
Basic 15000; 0 hours; incentive 0	Gross 19500; deduction 1560; net 17940	No overtime
Basic -100	Invalid input	Validation

9. Output Screenshots



10. Conclusion

The program demonstrates salary calculations, percentages, input validation, and formatted output

CASE STUDY 5: Multi-Plan Telecommunications Cost Optimization

1. Problem Statement

Compare three mobile plans using monthly usage and budget. Calculate excess data charges and identify the least expensive plan within the user's budget.

2. Objectives

- Read monthly data usage and budget.
- Calculate each plan's monthly cost.
- Compare plans against the budget.
- Display the cheapest eligible plan.

3. Assumptions

- Plan A: 199 includes 2 GB; extra data costs 50 per GB.
- Plan B: 299 includes 5 GB; extra data costs 30 per GB.
- Plan C: 399 includes 10 GB; extra data costs 20 per GB.
- Usage and budget cannot be negative.
- The cheapest plan within budget is recommended.


4. Algorithm

1. Start.
2. Input usage in GB and budget.
3. Validate the values.
4. Calculate the cost of each plan, including excess data.
5. Check which costs are within budget.
6. Choose the lowest eligible cost or report no eligible plan.
7. Stop.

5. Flowchart

Plaintext

START



INPUT DETAILS

  |

  ▼

VALIDATE INPUTS

  |

  ▼

CALCULATE USING CONDITIONS / LOOPS

  |

  ▼

DISPLAY RESULT

  |

  ▼

STOP

6. Pseudocode

Plaintext

```
START
  INPUT usage, budget
  IF usage < 0 OR budget < 0 THEN
    PRINT error
  ELSE
    cost_a = 199 + max(0, usage - 2) * 50
    cost_b = 299 + max(0, usage - 5) * 30
    cost_c = 399 + max(0, usage - 10) * 20
    Find cheapest cost within budget
    PRINT recommended plan and cost
  END IF
STOP
```

7. Python Source Code (case_study_5.py)

Python

```
usage = float(input("Monthly data usage (GB): "))
budget = float(input("Monthly budget (Rs.): "))

if usage < 0 or budget < 0:
    print("Invalid input.")
else:
    cost_a = 199 + max(0, usage - 2) * 50
    cost_b = 299 + max(0, usage - 5) * 30
    cost_c = 399 + max(0, usage - 10) * 20

    plans = [("Plan A", cost_a), ("Plan B", cost_b), ("Plan C", cost_c)]

    print("Plan A cost: Rs.", round(cost_a, 2))
    print("Plan B cost: Rs.", round(cost_b, 2))
    print("Plan C cost: Rs.", round(cost_c, 2))

    best_name = ""
    best_cost = 0

    for name, cost in plans:
        if cost <= budget and (best_name == "" or cost < best_cost):
            best_name = name
            best_cost = cost


    if best_name == "":
        print("No plan is within your budget.")
    else:
```

```
print("Recommended plan:", best_name)
print("Monthly cost: Rs.", round(best_cost, 2))
```

8. Test Cases

Input / Situation	Expected Result	Purpose
Usage 4 GB; budget 350	Plan A or B at 299	Compare plans
Usage 12 GB; budget 600	Plan C 439	High usage
Usage -1 GB	Invalid input	Validation

9. Output Screenshots



10. Conclusion

The program uses lists, loops, arithmetic, and conditions to compare plan costs under a budget.

CASE STUDY 6: Railway Fare and Reservation Calculator

1. Problem Statement

Calculate railway ticket fare based on distance, class of travel, and passenger category, applying senior citizen or child concessions.

2. Objectives

- Read distance, travel class, and age.
- Calculate base fare using distance and class rate.
- Apply age-based concessions.
- Display the final fare.

3. Assumptions

- Sleeper class is 1.50 per km, AC Three Tier is 2.50 per km, and AC First Class is 4.00 per km.
- Children under 5 travel free (0 fare).
- Senior citizens (60 and above) receive a 25% concession on the base fare.
- Distance and age cannot be negative.


4. Algorithm

1. Start.
2. Input distance, class type, and age.
3. Validate inputs.
4. Calculate base fare according to the class rate.
5. Apply concessions based on age.
6. Display final ticket fare.
7. Stop.

5. Flowchart

Plaintext

START



INPUT DETAILS



6. Pseudocode

```
START
  INPUT distance, travel_class, age
  IF distance < 0 OR age < 0 THEN
    PRINT error
  ELSE
    IF travel_class == 1 THEN
      rate = 1.50
    ELSE IF travel_class == 2 THEN
      rate = 2.50
    ELSE
      rate = 4.00
    END IF
    base_fare = distance * rate
    IF age < 5 THEN
      final_fare = 0
```

```
    ELSE IF age >= 60 THEN
      final_fare = base_fare * 0.75
    ELSE
      final_fare = base_fare
    END IF
    PRINT final_fare
  END IF
STOP
```

7. Python Source Code (case_study_6.py)


```
distance = float(input("Distance (km): "))
print("Classes: 1. Sleeper, 2. AC 3-Tier, 3. AC First Class")
travel_class = int(input("Enter class choice (1-3): "))
age = int(input("Passenger age: "))
if distance < 0 or age < 0 or travel_class < 1 or travel_class > 3:
  print("Invalid input.")
else:
  if travel_class == 1:
    rate = 1.50
  elif travel_class == 2:
    rate = 2.50
  else:
    rate = 4.00
  base_fare = distance * rate
  if age < 5:
    final_fare = 0
  elif age >= 60:
    final_fare = base_fare * 0.75
  else:
```

```
    final_fare = base_fare
print("\n--- Railway Ticket Summary ---")
print("Base fare: Rs.", round(base_fare, 2))
print("Final ticket fare: Rs.", round(final_fare, 2))
```

8. Test Cases

Input / Situation	Expected Result	Purpose
Distance 500 km; Sleeper (1); age 30	Base 750; final 750	Normal
Distance 800 km; AC 3-Tier (2); age 65	Base 2000; concession 500; final 1500	Senior citizen
Distance 300 km; AC First (3); age 3	Final fare 0	Child free travel

9. Output Screenshots



10. Conclusion

The program successfully uses multi-way conditional statements, rate formulas, and age-based checking.

CASE STUDY 7: Retail Billing with Multiple Discount Rules

1. Problem Statement

Calculate total retail purchase amount, apply a seasonal or promotional discount based on purchase value and membership status, and compute net payable amount.

2. Objectives

- Read item price and quantity for three items.
- Check membership status.
- Compute subtotal and apply tiered percentage discounts.
- Display final billing statement.

3. Assumptions

- Prices and quantities cannot be negative.
- Purchases of 5000 or more receive an extra 5% discount.
- Premium members receive an additional 10% discount.


4. Algorithm

1. Start.
2. Input prices, quantities, and membership status.
3. Validate inputs.
4. Compute subtotal.
5. Apply discount rules based on amount and membership.
6. Calculate net amount and display bill.
7. Stop.

5. Flowchart

Plaintext

START



INPUT DETAILS

▼

VALIDATE INPUTS

|

▼

CALCULATE USING CONDITIONS / LOOPS

|

▼

DISPLAY RESULT

|

▼

STOP

6. Pseudocode

Plaintext

```
START
  INPUT p1, q1, p2, q2, p3, q3, is_member
  subtotal = (p1 * q1) + (p2 * q2) + (p3 * q3)
  discount = 0
  IF subtotal >= 5000 THEN
    discount = discount + (subtotal * 0.05)
  END IF
  IF is_member == "yes" THEN
    discount = discount + (subtotal * 0.10)
  END IF
  net_amount = subtotal - discount
  PRINT subtotal, discount, net_amount
STOP
```

7. Python Source Code (case_study_7.py)

Python

```
p1 = float(input("Item 1 price: "))
q1 = int(input("Item 1 quantity: "))
p2 = float(input("Item 2 price: "))
q2 = int(input("Item 2 quantity: "))
p3 = float(input("Item 3 price: "))
q3 = int(input("Item 3 quantity: "))
is_member = input("Premium member? (yes/no): ").lower()

if p1 < 0 or q1 < 0 or p2 < 0 or q2 < 0 or p3 < 0 or q3 < 0:
    print("Invalid input.")
else:
    subtotal = (p1 * q1) + (p2 * q2) + (p3 * q3)
    discount = 0

    if subtotal >= 5000:
        discount += subtotal * 0.05
    if is_member == "yes":
        discount += subtotal * 0.10


    net_amount = subtotal - discount

    print("\n--- Retail Bill Summary ---")
    print("Subtotal: Rs.", round(subtotal, 2))
    print("Total discount: Rs.", round(discount, 2))
    print("Net payable: Rs.", round(net_amount, 2))
```

8. Test Cases

Input / Situation	Expected Result	Purpose
Prices 1000, 2000, 500; quantities 1, 1, 2; member: no	Subtotal 4000; discount 0; net 4000	Below threshold
Prices 3000, 2000, 1000; quantities 1, 1, 1; member: yes	Subtotal 6000; discount 15%; net 5100	High value + member

9. Output Screenshots



10. Conclusion

The program effectively applies multiple conditional discount rules and aggregates shopping cart totals.

CASE STUDY 8: Manufacturing Cost and Profitability Analysis

1. Problem Statement

Calculate total manufacturing cost from material, labor, and overhead costs, add a target profit margin, and compute unit selling price.

2. Objectives

- Read material cost, labor cost, overheads, and units produced.
- Calculate total manufacturing cost and cost per unit.
- Add profit margin to determine selling price.
- Display financial summary.

3. Assumptions

- All cost inputs and units must be positive non-zero values.
- Profit margin is 20% of the total manufacturing cost.

4. Algorithm

1. Start.
2. Input material cost, labor cost, overhead cost, and units produced.
3. Validate inputs.
4. Compute total manufacturing cost and cost per unit.
5. Add 20% profit margin to find total revenue required.
6. Calculate selling price per unit and display summary.
7. Stop.


5. Flowchart

Plaintext

START



INPUT DETAILS



VALIDATE INPUTS

  |

  ▼

CALCULATE USING CONDITIONS / LOOPS

  |

  ▼

DISPLAY RESULT

  |

  ▼

STOP

6. Pseudocode

Plaintext

```
START
   INPUT material, labor, overhead, units
   IF material < 0 OR labor < 0 OR overhead < 0 OR units <= 0 THEN
      PRINT error
   ELSE
      total_cost = material + labor + overhead
      cost_per_unit = total_cost / units
      profit = total_cost * 0.20
      total_revenue = total_cost + profit
      selling_price = total_revenue / units
      PRINT total_cost, cost_per_unit, selling_price
   END IF
STOP
```

7. Python Source Code (case_study_8.py)

Python

```
material = float(input("Material cost: Rs. "))
```

```
labor = float(input("Labor cost: Rs. "))
overhead = float(input("Overhead cost: Rs. "))
units = int(input("Units produced: "))


if material < 0 or labor < 0 or overhead < 0 or units <= 0:
    print("Invalid input.")
else:
    total_cost = material + labor + overhead
    cost_per_unit = total_cost / units
    profit = total_cost * 0.20
    total_revenue = total_cost + profit
    selling_price = total_revenue / units

    print("\n--- Manufacturing Summary ---")
    print("Total manufacturing cost: Rs.", round(total_cost, 2))
    print("Cost per unit: Rs.", round(cost_per_unit, 2))
    print("Target profit (20%): Rs.", round(profit, 2))
    print("Selling price per unit: Rs.", round(selling_price, 2))
```

8. Test Cases

Input / Situation	**Expected Result**	**Purpose**
Material 50000; labor 30000; overhead 20000; 1000 units	Total cost 100000; unit cost 100; selling price 120	Normal production
Units 0	Invalid input (division by zero prevention)	Zero unit check

9. Output Screenshots



10. Conclusion

The program calculates manufacturing overheads, profit margins, and per-unit pricing with input validation.

CASE STUDY 9: Multi-Currency Travel Budget Analysis

1. Problem Statement

Convert a traveler's budget in Indian Rupees into three foreign currencies and check if estimated trip expenses fit within the converted budget.

2. Objectives

- Read budget in INR and estimated expenses in foreign currency.
- Convert INR to USD, EUR, and GBP using fixed exchange rates.
- Compare estimated expenses with converted budget.
- Display budget status.

3. Assumptions

- 1 USD = 83 INR, 1 EUR = 90 INR, 1 GBP = 105 INR.
- Budget and expenses cannot be negative.

4. Algorithm

1. Start.
2. Input budget in INR and choice of foreign currency.
3. Validate inputs.
4. Perform conversion based on exchange rates.
5. Compare with estimated trip expenses.
6. Display status and result.
7. Stop.


5. Flowchart

Plaintext

START



INPUT DETAILS



VALIDATE INPUTS



CALCULATE USING CONDITIONS / LOOPS



DISPLAY RESULT



STOP

6. Pseudocode

Plaintext

```
START
  INPUT inr_budget, currency_choice, expense
  IF inr_budget < 0 OR expense < 0 THEN
    PRINT error
  ELSE
    IF currency_choice == 1 THEN
      converted = inr_budget / 83
      currency_name = "USD"
    ELSE IF currency_choice == 2 THEN
      converted = inr_budget / 90
      currency_name = "EUR"
    ELSE
      converted = inr_budget / 105
      currency_name = "GBP"
    END IF
    IF expense <= converted THEN
```

```
        PRINT "Within budget"
      ELSE
        PRINT "Exceeds budget"
      END IF
    END IF
STOP
```

7. Python Source Code (case_study_9.py)

Python

```
inr_budget = float(input("Enter budget in INR: "))
print("Choose currency: 1. USD, 2. EUR, 3. GBP")
choice = int(input("Enter choice (1-3): "))
expense = float(input("Estimated trip expense in foreign currency: "))

if inr_budget < 0 or expense < 0 or choice < 1 or choice > 3:
    print("Invalid input.")
else:
    if choice == 1:
        converted = inr_budget / 83
        c_name = "USD"
    elif choice == 2:
        converted = inr_budget / 90
        c_name = "EUR"
    else:
        converted = inr_budget / 105
        c_name = "GBP"


    print("\n--- Travel Budget Summary ---")
    print("Converted Budget:", round(converted, 2), c_name)
```

```
if expense <= converted:
    print("Status: Within budget")
else:
    print("Status: Budget exceeded")
```

8. Test Cases

Input / Situation	Expected Result	Purpose
Budget 83000 INR; USD (1); expense 900	Converted 1000 USD; Within budget	Normal conversion
Budget 45000 INR; EUR (2); expense 600	Converted 500 EUR; Budget exceeded	Exceeding budget

9. Output Screenshots



10. Conclusion

The program demonstrates currency conversion calculations, selection logic, and budget comparison.

CASE STUDY 10: Campus Event Financial Planning

1. Problem Statement

Calculate total event revenue from ticket sales and sponsorships, subtract fixed and variable expenses, and compute net profit or loss for a campus fest.

2. Objectives

- Read ticket count, ticket price, sponsorship amount, and expenses.
- Calculate total revenue and total expenses.
- Compute net profit or loss.
- Display financial outcome.

3. Assumptions

- Ticket price, counts, sponsorships, and expenses cannot be negative.
- Total Revenue = (Tickets Sold * Ticket Price) + Sponsorships.
- Net Financial Result = Total Revenue - Total Expenses.

4. Algorithm

1. Start.
2. Input tickets sold, ticket price, sponsorships, and total expenses.
3. Validate inputs.
4. Calculate total revenue.
5. Compute net profit or loss.
6. Display event financial statement.
7. Stop.

5. Flowchart

Plaintext

START



INPUT DETAILS

▼

VALIDATE INPUTS

|

▼

CALCULATE USING CONDITIONS / LOOPS

|

▼

DISPLAY RESULT

|

▼

STOP

6. Pseudocode

Plaintext

```
START
  INPUT tickets_sold, price, sponsorship, expenses
  IF tickets_sold < 0 OR price < 0 OR sponsorship < 0 OR expenses < 0 THEN
    PRINT error
  ELSE
    revenue = (tickets_sold * price) + sponsorship
    net = revenue - expenses
    IF net >= 0 THEN
      PRINT "Profit:", net
    ELSE
      PRINT "Loss:", abs(net)
    END IF
  END IF
STOP
```

7. Python Source Code (case_study_10.py)

Python

```
tickets = int(input("Tickets sold: "))
price = float(input("Price per ticket: Rs. "))
sponsorship = float(input("Total sponsorship amount: Rs. "))
expenses = float(input("Total event expenses: Rs. "))

if tickets < 0 or price < 0 or sponsorship < 0 or expenses < 0:
  print("Invalid input.")
else:
  revenue = (tickets * price) + sponsorship
  net = revenue - expenses

  print("\n--- Event Financial Statement ---")
  print("Total Revenue: Rs.", round(revenue, 2))
  print("Total Expenses: Rs.", round(expenses, 2))


  if net > 0:
    print("Net Profit: Rs.", round(net, 2))
  elif net < 0:
    print("Net Loss: Rs.", round(abs(net), 2))
  else:
    print("Break-even (No profit, no loss)")
```

8. Test Cases

Input / Situation	**Expected Result**	**Purpose**
200 tickets; 100 price; 15000 sponsor; 25000 expenses	Revenue 35000; Profit 10000	Profitable event

Input / Situation	Expected Result	Purpose
50 tickets; 100 price; 5000 sponsor; 15000 expenses	Revenue 10000; Loss 5000	Loss scenario

9. Output Screenshots



10. Conclusion

The program successfully computes event revenue, expenses, and net profit or loss balances.