RESONANCE COMPENSATION STUDIES AT THE FNAL RECYCLER RING

By

Cristhian Gonzalez-Ortiz

A DISSERTATION

Submitted to
Michigan State University
in partial fulfillment of the requirements
for the degree of

Physics—Doctor of Philosophy

2024

ABSTRACT

ACKNOWLEDGEMENTS

Your acknowledgements here.

TABLE OF CONTENTS

LIST OF ABBREVIATIONS

MSU Michigan State University

FNAL Fermilab National Accelerator Laboratory

RR Recycler Ring

MI Main Injector

RDTs Resonance Driving Terms

CHAPTER 1

SINGLE PARTICLE DYNAMICS

The most basic element of a particle accelerator can be thought of as a black box. This black box takes some initial transverse coordinates x_0, x_0', y_0, y_0', as defined in a Frenet-Serret coordinate system, and maps them to some final coordinates x_f, x_f', y_f, y_f'. For simplicity, any longitudinal effect will not be taken into account for this analysis [1] [2] [3] [4].

1.1 Basic Accelerator Elements

1.2 Normal Form

1.3 Resonances in Circular Accelerators

1.4 Resonance Driving Terms

CHAPTER 2

THE FNAL RECYCLER RING

The Fermilab Recycler Ring (RR) is one of the circular accelerators located .

2.1 General Specifications

2.2 Tune Diagram and Resonances

2.3 High Intensity and Tune Footprint

CHAPTER 3

COMPENSATION OF THIRD-ORDER RESONANCES AT LOW INTENSITIES

3.1 Global RDTs and Lattice Model

3.2 Measurement of Third Order RDTs

3.3 Compensation of RDTs

3.4 Optimization of Compensation Currents

3.5 Experimental Verification of Compensation

3.5.1 Dynamic Loss Map

3.5.2 Static Tune Scans

CHAPTER 4

RESONANCE COMPENSATION STUDIES AT THE CERN PS BOOSTER

4.1 General specifications

4.2 Tune Diagram and Operation

4.3 Optimization Algorithms for Resonance Compensation

4.4 Experimental Verification of Compensation

CHAPTER 5

HIGH INTENSITY STUDIES

5.1 Global RDTs and Intensity-Dependent Effects

5.2 Space Charge Tune Shift

5.3 Measurement of Tune Shift

5.4 Static Tune Scans at Different Intensities

CHAPTER 6

CONCLUSIONS AND FUTURE WORK

BIBLIOGRAPHY

[1] Robert Ainsworth et al. "High intensity operation using proton stacking in the Fermilab Recycler to deliver 700 kW of 120 GeV proton beam". In: *Phys. Rev. Accel. Beams* 23 (12 Dec. 2020), p. 121002. DOI: 10.1103/PhysRevAccelBeams.23.121002. URL: https://link.aps.org/doi/10.1103/PhysRevAccelBeams.23.121002.

[2] R. Ainsworth et al. "High intensity space charge effects on slip stacked beam in the Fermilab Recycler". In: *Phys. Rev. Accel. Beams* 22 (2 Feb. 2019), p. 020404. DOI: 10.1103/PhysRevAccelBeams.22.020404. URL: https://link.aps.org/doi/10.1103/PhysRevAccelBeams.22.020404.

[3] Andrzej Wolski. *Beam Dynamics in High Energy Particle Accelerators*. 2nd. WORLD SCIENTIFIC, 2023. DOI: 10.1142/13333. eprint: https://www.worldscientific.com/doi/pdf/10.1142/13333. URL: https://www.worldscientific.com/doi/abs/10.1142/13333.

[4] M. Ball et al. *The PIP-II Conceptual Design Report*. Tech. rep. FERMILAB-TM-2649-AD-APC1516858. Fermilab, Mar. 2017. DOI: 10.2172/1346823. URL: https://www.osti.gov/biblio/1346823.

APPENDIX

YOUR APPENDIX