
Roof plan slices · grid B

horizontal cuts through the roof, looking down


- (1) Inner layer 1, 80 printed, room side, then layer 2 (printed, thinner towards the crown).
- (2) Air zone, open between the ribs, for insulation (dotted).
- (3) Cast ribs cut by the plane (crossed hatch): the two diagonal families of grid B; each 160 wide across the rib and 240 deep. The cut is longer than 160 and sheared where the rib is inclined in the face; 4 Ø16 and stirrups as in the rib section.
- (4) Corner blocks: the four hip ribs, cut across the corners (cast).
- (5) Outer layer 80, printed.
- (6) Insulation 100 (very thin line), then the outer layer 30 (dark).

● from your sketches
○ assumed by me, to confirm


cut at +5.90 (1:50)



cut at +7.00 (1:100)



cut at +8.00 (1:100)



Notes

Large slice at +5.90 (3400 above the eave, just below the middle horizontal rib of option A), 1:50; small slices at +7.00 and +8.00, 1:100.

Option B: the same two diagonal families at every height; the cut ribs move towards the corners as the roof narrows, the diamonds are clipped by the hips.

Layer 2 thins towards the crown (the leaf is 160 at the base, 80 at the crown). Ribs use the same geometry as the roof-grid sheets; bars and stirrups are assumed.



Scale 1:50 at A3 · dimensions in mm · draft 1, 2026-10-11
pyramid-roof · hand estimates, not engineered