

Powermatic_1200_Retrofit_BOM

NO	CAT	QUA	PACK	ITEM	VENDOR	PART NO	UNIT COST	LINE COST
1	Drive	1	1	VFD — 2 HP, 230 V, 3-ph input (STO, over-torque)	AD	GS23-22P0	\$ 247.00	\$ 247.00
	Drive	1	1	DURApulse GS20 DIN rail adapter	AD	GS20A-DR-AB	\$ 6.00	\$ 6.00
	Drive	1	1	Weidmüller KLBUE 10-20 SC, 360° shield clamp, direct backpanel mount, Mfr. 1712321001	DK	281-4688-ND	\$ 20.32	\$ 20.32
2	Drive	1	1	Dynamic braking resistor — 50 Ω / 280 W, thermal switch	AD	BR-N1-280W50	\$ 156.00	\$ 156.00
	Motor	2	1	SPUCE LEVER 24-12AWG 3POS	DK	2946-221-413-ND	\$ 0.76	\$ 1.52
3	Contact	1	1	Contact A (line/safety) — TeSys D, 3P, 18 A AC-3 / 32 A AC-1, 24 VDC coil, 1 N.O. mechanically linked + 1 N.C. mirror	DK	4008-LC1D18BD-ND	\$ 168.30	\$ 168.30
4	Contact	1	1	Contact B (theater/chunk) — vintage Furnas, 240 V tap	GBB	D2936_32	\$ 0.00	\$ 0.00
6	Power	1	1	ABB Disconnect Switches, SWITCHLINE Series, 3P 30A UL98 NF SW	Galco	OT30F3	\$ 174.82	\$ 174.82
	Power	1	1	Handle for OT30F3	TBD	TBD	\$ 0.00	\$ 0.00
	Power	1	1	Shaft for OT30F3	TBD	TBD	\$ 0.00	\$ 0.00
8	Fuse	1	1	300 V, 60 A, three-pole, DIN-rail Class T block	DK	LFT300603C-ND	\$ 61.35	\$ 61.35
9	Fuse	3	1	dead-front cover system for LFT300603C	DK	5666-LFT30060FBC-ND	\$ 9.31	\$ 27.93
10	Fuse	5	1	Edison fuse, TJN series, Class T, current-limiting, extremely fast-acting, 35A, 300 VAC	AD	TJN35-1	\$ 38.00	\$ 190.00
11	Fuse	1	10	fuse block, wire size 24-10 AWG, 6.3A, 35mm DIN rail mount, 10kA SCCR	AD	DN-F10MN	\$ 58.00	\$ 58.00
12	Fuse	2	5	Bussmann fuse, GMC series, small dimension, medium time-delay, 3A, 250 VAC	AD	GMC3	\$ 13.00	\$ 26.00
13	Fuse	1	5	Bussmann fuse, GMC series, small dimension, medium time-delay, 5A, 250 VAC	AD	GMC5	\$ 13.00	\$ 13.00
	Fuse	1	5	DB-FU — Bussmann GMC series, 1 A medium time-delay, 5 × 20 mm glass fuse	AD	GMC1	\$ 13.00	\$ 13.00
14	PLC	1	1	PLC CPU — CLICK PLUS, 2 option slots, Ethernet	AD	C2-01CPU-2	\$ 154.00	\$ 154.00
15	PLC	2	1	Option-slot I/O — 8 DC in / 6 DC out	AD	C2-14D1	\$ 66.00	\$ 132.00
16	Power	1	1	Power supply — 24 VDC, 10 A / 240 W	GBB	NDR-240-24	\$ 0.00	\$ 0.00
17	Relay	1	1	Interface relay, 24 VDC coil voltage, DPDT, (2) N.O., (2) N.C., 6A contact rating, 250 VAC/VDC load voltage	AD	52102	\$ 22.00	\$ 22.00
18	Relay	3	1	CR-S1 / CR-S2 / CR-DB — Phoenix Contact PLC-RSC-24DC/21AU, 24 VDC SPDT hard-gold signal relay module, screw terminals	Mouser	651-2966265	\$ 19.64	\$ 58.92
	Relay	1	1	Programmable (Multi-Function) Time Delay Relay SPDT (1 Form C) 0.1 Sec ~ 300 Min Delay 6.3A @ 250VAC DIN Rail	DK	277-2910140-ND	\$ 81.40	\$ 81.40
19	PLC	1	1	CPU backup battery	AD	DO-MC-BAT	\$ 4.00	\$ 4.00
20	PLC	1	1	Programming cable — USB A -> microB	AD	USB-CBL-AMICB6	\$ 6.00	\$ 6.00
21	Relay	1	1	release delay, 0.1 to 1 sec, 2-channel, 24 VAC/VDC, (3) N.O. time delay and (2) N.O. safety output(s), (1) N.C. monitoring output(s)	AD	BH5928-92-61-24-1	\$ 319.00	\$ 319.00
22	Operator	1	1	E-stop — mushroom + 2x N.C., M12 4-pin, yellow CM12 enclosure	GBB	ZB2_BE102 x2	\$ 0.00	\$ 0.00
23	Operator	1	1	DRILL/TAP selector — 2-position maintained, 2x N.O. blocks installed	GBB	XB4BD21	\$ 0.00	\$ 0.00
24	Operator	1	1	Reset pushbutton — black flush, spring-return, 1 N.O.	DK	4008-XB4BA21-ND	\$ 28.00	\$ 28.00
25	Operator	1	1	Pilot light, Harmony XB4,metal, green, 22mm, universal LED, plain lens, 24V AC DC	DK	4008-XB4BV3-ND	\$ 52.92	\$ 52.92
26	Operator	2	1	Pilot light, Harmony XB4,metal, red, 22mm, universal LED, plain lens, 24V AC DC	DK	4008-XB4BV4-ND	\$ 52.92	\$ 105.84
27	Operator	1	1	Pilot light, Harmony XB4,metal, white, 22mm, universal LED, plain lens, 24V AC DC	RS	70008070	\$ 54.51	\$ 54.51
28	Sensor	1	1	Feed-lever prox — M12, 8 mm non-flush, PNP-NO, 10-30 V	DK	1864-ICF12L45N08M1IO-ND	\$ 61.00	\$ 61.00
29	Operator	1	1	Drum switch (OFF/LOW/HIGH) — speed select X008/X009	GBB	365_TAV2111	\$ 0.00	\$ 0.00
30	Operator	1	1	Button pendant (FWD/STOP/REV) — X003/X004/X005	GBB	800S_3SA	\$ 0.00	\$ 0.00
31	Sensor	2	1	Travel limits, bottom/top — X006/X007	GBB	1LS1_J	\$ 0.00	\$ 0.00
32	Terminals	1	100	Konnect-It 26-12 AWG, 20 A, 600 V (UL), 100 kA SCCR, gray	AD	KN-T12GRY-100	\$ 37.00	\$ 37.00
33	Terminals	1	25	Konnect-It 26-12 AWG, 20 A, 600 V (UL), 100 kA SCCR, blue	AD	KN-T12BLU-25	\$ 10.00	\$ 10.00
34	Terminals	2	10	Konnect-It screw-down end bracket, 8mm wide	AD	KN-EB3-10	\$ 8.00	\$ 16.00
35	Terminals	1	25	Konnect-It terminal block end cover, gray	AD	KN-ECT6GRY-25	\$ 7.00	\$ 7.00
36	Terminals	1	10	Konnect-It terminal block end cover, blue	AD	KN-ECT6BLU	\$ 4.00	\$ 4.00
37	Terminals	1	5	Konnect-It terminal block jumper, screw-down type, 10-pole, 24A, 750V	AD	KN-10J12	\$ 14.00	\$ 14.00
38	Terminals	1	15	Konnect-It terminal block jumper, screw-down type, 4-pole, 24A, 750V	AD	KN-4J12	\$ 22.00	\$ 22.00
39	Terminals	1	25	Konnect-It terminal block jumper, screw-down type, 2-pole, 24A, 750V	AD	KN-2J12	\$ 14.00	\$ 14.00
40	Terminals	2	10	Konnect-It screw grounding block, single-level, size 26-10 AWG, yellow/green	AD	KN-G10-10	\$ 35.00	\$ 70.00
41	Wire	100	1	12 AWG, black, stranded copper, MTW or THHN/THWN-2, 600 V, 90 °C	MCM	9874T14	\$ 0.57	\$ 57.00
42	Wire	100	1	12 AWG, gn/y, stranded copper, MTW or THHN/THWN-2, 600 V, 90 °C	MCM	6513T6	\$ 1.93	\$ 192.65
43	Wire	100	1	12 AWG, 3/C + ground, continuous shielded VFD cable	MCM	7777T22	\$ 7.64	\$ 76.40
45	Wire	100	1	14 AWG, gn/y, stranded copper, MTW or THHN/THWN-2, 600 V, 90 °C	MCM	6513T5	\$ 0.39	\$ 39.00
46	Wire	100	1	16 AWG, black, stranded copper, MTW or THHN/THWN-2, 600 V, 90 °C	MCM	9874T12	\$ 0.33	\$ 33.00
47	Wire	25	1	16 AWG, blue, stranded copper, MTW or THHN/THWN-2, 600 V, 90 °C	MCM	9874T12	\$ 0.33	\$ 8.25
48	Wire	250	1	18 AWG, blue, stranded copper, MTW or THHN/THWN-2, 600 V, 90 °C	MCM	9874T11	\$ 0.33	\$ 82.50
49	Wire	2	1	M12 4/C cordsets	GBB	-	\$ 0.00	\$ 0.00
50	Wire	2	1	M12 4/C female panel mount receptacle	GBB	-	\$ 0.00	\$ 0.00
51	Wire	1	100	12AWG ferrule 0.47" grey	MCM	7950K32	\$ 17.33	\$ 17.33
52	Wire	1	100	14AWG ferrule 0.47" blue	MCM	7950K28	\$ 16.47	\$ 16.47
53	Wire	1	100	16AWG ferrule 0.39" black	MCM	7950K24	\$ 15.89	\$ 15.89
54	Wire	5	100	18AWG ferrule 0.31" white	MCM	7950K164	\$ 3.91	\$ 19.55
55	Wire	1	100	18AWG twin-ferrule 0.39" yellow	MCM	9703K63	\$ 9.03	\$ 9.03
56	Misc	1	1	24V 80-92mm stirring fan off of bus	TBD	TBD	\$ 0.00	\$ 0.00
57	Misc	1	1	Enclosure — NEMA 12, dimensions TBD	TBD	TBD	\$ 0.00	\$ 0.00
58	Misc	1	1	DIN rail, duct	TBD	TBD	\$ 0.00	\$ 0.00
								\$ 3,003.90