

## Powermatic\_1200\_Retrofit\_BOM

| NO | CAT       | QUA | PACK | ITEM                                                                                                                                 | VENDOR | PART NO                 | UNIT COST | LINE COST   |
|----|-----------|-----|------|--------------------------------------------------------------------------------------------------------------------------------------|--------|-------------------------|-----------|-------------|
| 1  | Drive     | 1   | 1    | VFD — 2 HP, 230 V, 3-ph input (STO, over-torque)                                                                                     | AD     | GS23-22P0               | \$ 247.00 | \$ 247.00   |
| 2  | Drive     | 1   | 1    | DURApulse GS20 DIN rail adapter                                                                                                      | AD     | GS20A-DR-AB             | \$ 6.00   | \$ 6.00     |
| 3  | Drive     | 1   | 1    | Weidmüller KLBUE 10-20 SC, 360° shield clamp, direct backpanel mount, Mfr. 1712321001                                                | DK     | 281-4688-ND             | \$ 20.32  | \$ 20.32    |
| 4  | Drive     | 1   | 1    | Dynamic braking resistor — 50 Ω / 280 W, thermal switch                                                                              | AD     | BR-N1-280W50            | \$ 156.00 | \$ 156.00   |
| 5  | Motor     | 2   | 1    | SPUCE LEVER 24-12AWG 3POS                                                                                                            | DK     | 2946-221-413-ND         | \$ 0.76   | \$ 1.52     |
| 6  | Contact   | 1   | 1    | Contact A (line/safety) — TeSys D, 3P, 18 A AC-3 / 32 A AC-1, 24 VDC coil, 1 N.O. mechanically linked + 1 N.C. mirror                | DK     | 4008-LC1D18BD-ND        | \$ 168.30 | \$ 168.30   |
| 7  | Contact   | 1   | 1    | Contact B (theater/chunk) — vintage Furnas, 240 V tap                                                                                | GBB    | D2936_32                | \$ 0.00   | \$ 0.00     |
| 8  | Power     | 1   | 1    | ABB Disconnect Switches, SWITCHLINE Series, 3P 30A UL98 NF SW                                                                        | Galco  | OT30F3                  | \$ 174.82 | \$ 174.82   |
| 9  | Power     | 1   | 1    | Handle for OT30F3                                                                                                                    | TBD    | TBD                     | \$ 0.00   | \$ 0.00     |
| 10 | Power     | 1   | 1    | Shaft for OT30F3                                                                                                                     | TBD    | TBD                     | \$ 0.00   | \$ 0.00     |
| 11 | Fuse      | 1   | 1    | 300 V, 60 A, three-pole, DIN-rail Class T block                                                                                      | DK     | LFT300603C-ND           | \$ 61.35  | \$ 61.35    |
| 12 | Fuse      | 3   | 1    | dead-front cover system for LFT300603C                                                                                               | DK     | 5666-LFT30060FBC-ND     | \$ 9.31   | \$ 27.93    |
| 13 | Fuse      | 5   | 1    | Edison fuse, TJN series, Class T, current-limiting, extremely fast-acting, 35A, 300 VAC                                              | AD     | TJN35-1                 | \$ 38.00  | \$ 190.00   |
| 14 | Fuse      | 1   | 10   | fuse block, wire size 24-10 AWG, 6.3A, 35mm DIN rail mount, 10kA SCCR                                                                | AD     | DN-F10MN                | \$ 58.00  | \$ 58.00    |
| 15 | Fuse      | 2   | 5    | Bussmann fuse, GMC series, small dimension, medium time-delay, 3A, 250 VAC                                                           | AD     | GMC3                    | \$ 13.00  | \$ 26.00    |
| 16 | Fuse      | 1   | 5    | Bussmann fuse, GMC series, small dimension, medium time-delay, 5A, 250 VAC                                                           | AD     | GMC5                    | \$ 13.00  | \$ 13.00    |
| 17 | Fuse      | 1   | 5    | DB-FU — Bussmann GMC series, 1 A medium time-delay, 5 × 20 mm glass fuse                                                             | AD     | GMC1                    | \$ 13.00  | \$ 13.00    |
| 18 | PLC       | 1   | 1    | PLC CPU — CLICK PLUS, 2 option slots, Ethernet                                                                                       | AD     | C2-01CPU-2              | \$ 154.00 | \$ 154.00   |
| 19 | PLC       | 2   | 1    | CLICK PLUS option-slot I/O module — 8 × 24 VDC sink/source inputs, 6 × 24 VDC sourcing outputs                                       | AD     | C2-14D2                 | \$ 66.00  | \$ 132.00   |
| 20 | Power     | 1   | 1    | Power supply — 24 VDC, 10 A / 240 W                                                                                                  | GBB    | NDR-240-24              | \$ 0.00   | \$ 0.00     |
| 21 | Relay     | 1   | 1    | Interface relay, 24 VDC coil voltage, DPDT, (2) N.O., (2) N.C., 6A contact rating, 250 VAC/VDC load voltage                          | AD     | 52102                   | \$ 22.00  | \$ 22.00    |
| 22 | Relay     | 3   | 1    | CR-S1 / CR-S2 / CR-DB — Phoenix Contact PLC-RSC-24DC/21AU, 24 VDC SPDT hard-gold signal relay module, screw terminals                | Mouser | 651-2966265             | \$ 19.64  | \$ 58.92    |
| 23 | Relay     | 1   | 1    | Programmable (Multi-Function) Time Delay Relay SPDT (1 Form C) 0.1 Sec ~ 300 Min Delay 6.3A @ 250VAC DIN Rail                        | DK     | 277-2910140-ND          | \$ 81.40  | \$ 81.40    |
| 24 | PLC       | 1   | 1    | CPU backup battery                                                                                                                   | AD     | DO-MC-BAT               | \$ 4.00   | \$ 4.00     |
| 25 | PLC       | 1   | 1    | Programming cable — USB A -> microB                                                                                                  | AD     | USB-CBL-AMICB6          | \$ 6.00   | \$ 6.00     |
| 26 | Relay     | 1   | 1    | release delay, 0.1 to 1 sec, 2-channel, 24 VAC/VDC, (3) N.O. time delay and (2) N.O. safety output(s), (1) N.C. monitoring output(s) | AD     | BH5928-92-61-24-1       | \$ 319.00 | \$ 319.00   |
| 27 | Operator  | 1   | 1    | E-stop — mushroom + 2x N.C., M12 4-pin, yellow CM12 enclosure                                                                        | GBB    | ZB2_BE102 x2            | \$ 0.00   | \$ 0.00     |
| 28 | Operator  | 1   | 1    | DRILL/TAP selector — 2-position maintained, 2x N.O. blocks installed                                                                 | GBB    | XB4BD21                 | \$ 0.00   | \$ 0.00     |
| 29 | Operator  | 1   | 1    | Reset pushbutton — black flush, spring-return, 1 N.O.                                                                                | DK     | 4008-XB4BA21-ND         | \$ 28.00  | \$ 28.00    |
| 30 | Operator  | 1   | 1    | Pilot light, Harmony XB4,metal, green, 22mm, universal LED, plain lens, 24V AC DC                                                    | DK     | 4008-XB4BV3-ND          | \$ 52.92  | \$ 52.92    |
| 31 | Operator  | 2   | 1    | Pilot light, Harmony XB4,metal, red, 22mm, universal LED, plain lens, 24V AC DC                                                      | DK     | 4008-XB4BV4-ND          | \$ 52.92  | \$ 105.84   |
| 32 | Operator  | 1   | 1    | Pilot light, Harmony XB4,metal, white, 22mm, universal LED, plain lens, 24V AC DC                                                    | RS     | 70008070                | \$ 54.51  | \$ 54.51    |
| 33 | Sensor    | 1   | 1    | Feed-lever prox — M12, 8 mm non-flush, PNP-NO, 10-30 V                                                                               | DK     | 1864-ICF12L45N08M1IO-ND | \$ 61.00  | \$ 61.00    |
| 34 | Operator  | 1   | 1    | Drum switch (OFF/LOW/HIGH) — speed select X008/X009                                                                                  | GBB    | 365_TAV2111             | \$ 0.00   | \$ 0.00     |
| 35 | Operator  | 1   | 1    | Button pendant (FWD/STOP/REV) — X003/X004/X005                                                                                       | GBB    | 800S_3SA                | \$ 0.00   | \$ 0.00     |
| 36 | Sensor    | 2   | 1    | Travel limits, bottom/top — X006/X007                                                                                                | GBB    | 1LS1_J                  | \$ 0.00   | \$ 0.00     |
| 37 | Terminals | 1   | 100  | Konnect-It 26-12 AWG, 20 A, 600 V (UL), 100 kA SCCR, gray                                                                            | AD     | KN-T12GRY-100           | \$ 37.00  | \$ 37.00    |
| 38 | Terminals | 1   | 25   | Konnect-It 26-12 AWG, 20 A, 600 V (UL), 100 kA SCCR, blue                                                                            | AD     | KN-T12BLU-25            | \$ 10.00  | \$ 10.00    |
| 39 | Terminals | 2   | 10   | Konnect-It screw-down end bracket, 8mm wide                                                                                          | AD     | KN-EB3-10               | \$ 8.00   | \$ 16.00    |
| 40 | Terminals | 1   | 25   | Konnect-It terminal block end cover, gray                                                                                            | AD     | KN-ECT6GRY-25           | \$ 7.00   | \$ 7.00     |
| 41 | Terminals | 1   | 10   | Konnect-It terminal block end cover, blue                                                                                            | AD     | KN-ECT6BLU              | \$ 4.00   | \$ 4.00     |
| 42 | Terminals | 1   | 5    | Konnect-It terminal block jumper, screw-down type, 10-pole, 24A, 750V                                                                | AD     | KN-10J12                | \$ 14.00  | \$ 14.00    |
| 43 | Terminals | 1   | 15   | Konnect-It terminal block jumper, screw-down type, 4-pole, 24A, 750V                                                                 | AD     | KN-4J12                 | \$ 22.00  | \$ 22.00    |
| 44 | Terminals | 1   | 25   | Konnect-It terminal block jumper, screw-down type, 2-pole, 24A, 750V                                                                 | AD     | KN-2J12                 | \$ 14.00  | \$ 14.00    |
| 45 | Terminals | 2   | 10   | Konnect-It screw grounding block, single-level, size 26-10 AWG, yellow/green                                                         | AD     | KN-G10-10               | \$ 35.00  | \$ 70.00    |
| 46 | Wire      | 75  | 1    | 12 AWG, black, stranded copper, MTW or THHN/THWN-2, 600 V, 90°C                                                                      | MCM    | 9874T14                 | \$ 0.57   | \$ 42.75    |
| 47 | Wire      | 50  | 1    | 12 AWG, gn/y, stranded copper, MTW or THHN/THWN-2, 600 V, 90°C                                                                       | MCM    | 6513T6                  | \$ 1.93   | \$ 96.33    |
| 48 | Wire      | 10  | 1    | 12 AWG, 3/C + ground, continuous shielded VFD cable                                                                                  | MCM    | 7777T22                 | \$ 7.64   | \$ 76.40    |
| 49 | Wire      | 25  | 1    | 14 AWG, gn/y, stranded copper, MTW or THHN/THWN-2, 600 V, 90°C                                                                       | MCM    | 6513T5                  | \$ 0.39   | \$ 9.75     |
| 50 | Wire      | 25  | 1    | 16 AWG, black, stranded copper, MTW or THHN/THWN-2, 600 V, 90°C                                                                      | MCM    | 9874T12                 | \$ 0.33   | \$ 8.25     |
| 51 | Wire      | 25  | 1    | 16 AWG, blue, stranded copper, MTW or THHN/THWN-2, 600 V, 90°C                                                                       | MCM    | 9874T12                 | \$ 0.33   | \$ 8.25     |
| 52 | Wire      | 25  | 1    | 16 AWG, red, stranded copper, MTW or THHN/THWN-2, 600 V, 90°C                                                                        | MCM    | 9874T12                 | \$ 0.33   | \$ 8.25     |
| 53 | Wire      | 25  | 1    | 16 AWG, white, stranded copper, MTW or THHN/THWN-2, 600 V, 90°C. add a blue heat shrink at both ends                                 | MCM    | 9874T12                 | \$ 0.33   | \$ 8.25     |
| 54 | Wire      | 250 | 1    | 18 AWG, blue, stranded copper, MTW or THHN/THWN-2, 600 V, 90°C                                                                       | MCM    | 9874T11                 | \$ 0.24   | \$ 60.00    |
| 55 | Wire      | 100 | 1    | 18 AWG, white, stranded copper, MTW or THHN/THWN-2, 600 V, 90°C. add a blue heat shrink at both ends                                 | MCM    | 9874T11                 | \$ 0.24   | \$ 24.00    |
| 56 | Wire      | 2   | 1    | M12 4/C cordsets                                                                                                                     | GBB    | -                       | \$ 0.00   | \$ 0.00     |
| 57 | Wire      | 2   | 1    | M12 4/C female panel mount receptacle                                                                                                | GBB    | -                       | \$ 0.00   | \$ 0.00     |
| 58 | Wire      | 1   | 100  | 12AWG ferrule 0.47" grey                                                                                                             | MCM    | 7950K32                 | \$ 17.33  | \$ 17.33    |
| 59 | Wire      | 1   | 100  | 14AWG ferrule 0.47" blue                                                                                                             | MCM    | 7950K28                 | \$ 16.47  | \$ 16.47    |
| 60 | Wire      | 1   | 100  | 16AWG ferrule 0.39" black                                                                                                            | MCM    | 7950K24                 | \$ 15.89  | \$ 15.89    |
| 61 | Wire      | 5   | 100  | 18AWG ferrule 0.31" white                                                                                                            | MCM    | 7950K164                | \$ 3.91   | \$ 19.55    |
| 62 | Wire      | 1   | 100  | 18AWG twin-ferrule 0.39" yellow                                                                                                      | MCM    | 9703K63                 | \$ 9.03   | \$ 9.03     |
| 63 | Misc      | 1   | 1    | 24V 80-92mm stirring fan off of bus                                                                                                  | TBD    | TBD                     | \$ 0.00   | \$ 0.00     |
| 64 | Misc      | 1   | 1    | Enclosure — NEMA 12, dimensions TBD                                                                                                  | TBD    | TBD                     | \$ 0.00   | \$ 0.00     |
| 65 | Misc      | 1   | 1    | DIN rail, duct                                                                                                                       | TBD    | TBD                     | \$ 0.00   | \$ 0.00     |
|    |           |     |      |                                                                                                                                      |        |                         |           | \$ 2,857.33 |