VISUAL RECOGNITION

ANUSH SANKARAN
IBM RESEARCH

Most of the slide content are borrowed from CS231n. Thanks to the original authors

RECAP: WHAT IS THE PROBLEM?

- You are a genius …
- Only if a machine or an algorithm could do it …

- Make a computer understand the image …
- Understand the background & environment …
- Classify various objects in the image …

RECAP: WHAT IS THE SOLUTION PIPELINE





RECAP: MULTI LAYER PERECEPTRON



RECAP: UNSUPERVISED FEATURE LEARNING



Deep Learning is one technique to perform Unsupervised Feature Learning

RECAP: STACKED AUTOENCODER



RECAP: DIFFERENT TYPES OF DEEP LEARNING

- Input data is a vector Stacked
  - Autoencoder
  - Restricted Boltzmann Machines
  - Deep Belief Networks

- Input data is multi-dimensional
  - Convolutional Neural Network
  - Example: Image analysis, Object recognition

- Input data is time-series
  - Recurrent Neural Network
  - Example: Language Modelling, Speech recognition

RECAP: CONVOLUTIONAL NEURAL NETWORK

Where we are now...



CONVOLUTIONAL LAYER



Convolve the filter with the image
i.e. “slide over the image spatially,
computing dot products”

CONVOLUTIONAL LAYER



1 number:
the result of taking a dot product between the filter and a small 5x5x3 chunk of the image (i.e. 5*5*3 = 75-dimensional dot product + bias)

$$w^T x + b$$

CONVOLUTIONAL LAYER



CONVOLUTIONAL LAYER



CONVOLUTIONAL LAYER

For example, if we had 6 5x5 filters, we'll get 6 separate activation maps:



We stack these up to get a "new image" of size 28x28x6!

CONVOLUTIONAL LAYER

Preview: ConvNet is a sequence of Convolution Layers, interspersed with activation functions



CONVOLUTIONAL NEURAL NETWORK

Preview: ConvNet is a sequence of Convolution Layers, interspersed with activation functions



CONVOLUTIONAL NERUAL NETWORK



CNN: LEARNT FILTERS



We call the layer convolutional because it is related to convolution of two signals:

$$f[x,y] * g[x,y] = \sum_{n_1=-\infty}^{\infty} \sum_{n_2=-\infty}^{\infty} f[n_1,n_2] \cdot g[x-n_1, y-n_2]$$

elementwise multiplication and sum of a filter and the signal (image)

DATASET: MNIST



- 28*28 grayscale images
- 10 classes (0-9)
- 60000 images
  - 50000 training images
  - 10000 holdout test images
- SOTA: easily achieving more than 99.5% accuracy

DATASET: CIFAR10



- 32*32*3 color images
- 10 classes
- 60000 images
  - 50000 training images
  - 10000 holdout test images
- SOTA: easily achieving more than 95% accuracy
- Extended to CIFAR-100

DATASETS: IMAGENET



- 256*256*3 color images
- More than 1000 classes
- Manually annotated in a crowdsource manner

WHAT IS THE TRAINING PROCESS

1. **One time setup**
   activation functions, preprocessing, weight initialization, regularization, gradient checking
2. **Training dynamics**
   babysitting the learning process, parameter updates, hyperparameter optimization
3. **Evaluation**
   model ensembles

ONE-TIME SETUP

- Activation Functions
- Data Preprocessing
- Weight Initialization
- Batch Normalization
- Babysitting the Learning Process
- Hyperparameter Optimization

ACTIVATION FUNCTION



DIFFERENT ACTIVATION FUNCTIONS

Sigmoid

$$\sigma(x) = \frac{1}{1+e^{-x}}$$



tanh

$$\tanh(x)$$



ReLU

$$\max(0, x)$$



Leaky ReLU

$$\max(0.1x, x)$$



Maxout

$$\max(w_1^T x + b_1, w_2^T x + b_2)$$

ELU

$$\begin{cases} x & x \geq 0 \\ \alpha(e^x - 1) & x < 0 \end{cases}$$



ACTIVATION FUNCTION: BEST PRACTICES

- Use ReLU. Be careful with your learning rates
- Try out Leaky ReLU / Maxout / ELU
- Try out tanh but don’t expect much
- Don’t use sigmoid

DATA PREPROCESSING




```
X -= np.mean(X, axis = 0)
```

```
X /= np.std(X, axis = 0)
```

DATA PREPROCESSING: BEST PRACTICES

e.g. consider CIFAR-10 example with [32,32,3] images

- Subtract the mean image (e.g. AlexNet)
  (mean image = [32,32,3] array)
- Subtract per-channel mean (e.g. VGGNet)
  (mean along each channel = 3 numbers)

Not common to normalize variance, to do PCA or whitening

WEIGHT INITIALIZATION

- First idea: **Small random numbers**
(gaussian with zero mean and 1e-2 standard deviation)

```
W = 0.01* np.random.randn(D,H)
```

Works ~okay for small networks, but problems with deeper networks.

WEIGHT INITIALIZATION

Lets look at some activation statistics

E.g. 10-layer net with 500 neurons on each layer, using tanh non-linearities, and initializing as described in last slide.

```
# assume some unit gaussian 10-D input data
D = np.random.randn(1000, 500)
hidden_layer_sizes = [500]*10
nonlinearities = ['tanh']*len(hidden_layer_sizes)
```

```
act = {'relu':lambda x:np.maximum(0,x), 'tanh':lambda x:np.tanh(x)}
Hs = {}
for i in xrange(len(hidden_layer_sizes)):
    X = D if i == 0 else Hs[i-1] # input at this layer
    fan_in = X.shape[1]
    fan_out = hidden_layer_sizes[i]
    W = np.random.randn(fan_in, fan_out) * 0.01 # layer initialization

    H = np.dot(X, W) # matrix multiply
    H = act[nonlinearities[i]](H) # nonlinearity
    Hs[i] = H # cache result on this layer
```

```
# look at distributions at each layer
print 'input layer had mean %f and std %f' % (np.mean(D), np.std(D))
layer_means = [np.mean(H) for i,H in Hs.iteritems()]
layer_stds = [np.std(H) for i,H in Hs.iteritems()]
for i,H in Hs.iteritems():
    print 'hidden layer %d had mean %f and std %f' % (i+1, layer_means[i], layer_stds[i])

# plot the means and standard deviations
plt.figure()
plt.subplot(121)
plt.plot(Hs.keys(), layer_means, 'ob-')
plt.title('layer mean')
plt.subplot(122)
plt.plot(Hs.keys(), layer_stds, 'or-')
plt.title('layer std')

# plot the raw distributions
plt.figure()
for i,H in Hs.iteritems():
    plt.subplot(1,len(Hs),i+1)
    plt.hist(H.ravel(), 30, range=(-1,1))
```

WEIGHT INITIALIZATION

```
input layer had mean 0.000927 and std 0.998388
hidden layer 1 had mean -0.000117 and std 0.213081
hidden layer 2 had mean -0.000001 and std 0.047551
hidden layer 3 had mean -0.000002 and std 0.010630
hidden layer 4 had mean 0.000001 and std 0.002378
hidden layer 5 had mean 0.000002 and std 0.000532
hidden layer 6 had mean -0.000000 and std 0.000119
hidden layer 7 had mean 0.000000 and std 0.000026
hidden layer 8 had mean -0.000000 and std 0.000006
hidden layer 9 had mean 0.000000 and std 0.000001
hidden layer 10 had mean -0.000000 and std 0.000000
```



All activations become zero!

Q: think about the backward pass. What do the gradients look like?

Hint: think about backward pass for a W*X gate.

WEIGHT INITIALIZATION

```
W = np.random.randn(fan_in, fan_out) * 1.0 # layer initialization
```

```
input layer had mean 0.001800 and std 1.001311
hidden layer 1 had mean -0.000430 and std 0.981879
hidden layer 2 had mean -0.000849 and std 0.981649
hidden layer 3 had mean 0.000566 and std 0.981601
hidden layer 4 had mean 0.000483 and std 0.981755
hidden layer 5 had mean -0.000682 and std 0.981614
hidden layer 6 had mean -0.000401 and std 0.981560
hidden layer 7 had mean -0.000237 and std 0.981520
hidden layer 8 had mean -0.000448 and std 0.981913
hidden layer 9 had mean -0.000899 and std 0.981728
hidden layer 10 had mean 0.000584 and std 0.981736
```

*1.0 instead of *0.01







Almost all neurons completely saturated, either -1 and 1. Gradients will be all zero.

WEIGHT INITIALIZATION: BEST PRACTICES

```
input layer had mean 0.001800 and std 1.001311
hidden layer 1 had mean 0.001198 and std 0.627953
hidden layer 2 had mean -0.000175 and std 0.486051
hidden layer 3 had mean 0.000055 and std 0.407723
hidden layer 4 had mean -0.000306 and std 0.357108
hidden layer 5 had mean 0.000142 and std 0.320917
hidden layer 6 had mean -0.000389 and std 0.292116
hidden layer 7 had mean -0.000228 and std 0.273387
hidden layer 8 had mean -0.000291 and std 0.254935
hidden layer 9 had mean 0.000361 and std 0.239266
hidden layer 10 had mean 0.000139 and std 0.228008
```

```
W = np.random.randn(fan_in, fan_out) / np.sqrt(fan_in) # layer initialization
```

"Xavier initialization"
[Glorot et al., 2010]







Reasonable initialization.
(Mathematical derivation assumes linear activations)

WEIGHT INITIALIZATION: AN ACTIVE RESEARCH AREA

Proper initialization is an active area of research…

Understanding the difficulty of training deep feedforward neural networks by Glorot and Bengio, 2010

Exact solutions to the nonlinear dynamics of learning in deep linear neural networks by Saxe et al, 2013

Random walk initialization for training very deep feedforward networks by Sussillo and Abbott, 2014

Delving deep into rectifiers: Surpassing human-level performance on ImageNet classification by He et al., 2015

Data-dependent Initializations of Convolutional Neural Networks by Krähenbühl et al., 2015

All you need is a good init, Mishkin and Matas, 2015

…

LEARNING RATE



LEARNING RATE: BEST PRACTICES

- Do not use fixed (static) learning rate
- Use dynamic learning rate
  - Exponential decay learning rate
  - Step decay based on number of epochs
- Use momentum to speed up the learning

LEARNING RATE: LEARN WITH MOMENTUM

SGD+Momentum

$$v_{t+1} = \rho v_t - \alpha \nabla f(x_t)$$
$$x_{t+1} = x_t + v_{t+1}$$

```
vx = 0
while True:
  dx = compute_gradient(x)
  vx = rho * vx - learning_rate * dx
  x += vx
```

SGD+Momentum

$$v_{t+1} = \rho v_t + \nabla f(x_t)$$
$$x_{t+1} = x_t - \alpha v_{t+1}$$

```
vx = 0
while True:
  dx = compute_gradient(x)
  vx = rho * vx + dx
  x -= learning_rate * vx
```

You may see SGD+Momentum formulated different ways, but they are equivalent - give same sequence of x

OVERFITTING PROBLEM: WHICH MODEL TO CHOOSE



Prefer simpler models …

OVERFITTING PROBLEM: WHICH WEIGHTS TO CHOSE?

$$x = [1, 1, 1, 1]$$

$$w_1 = [1, 0, 0, 0]$$

$$w_2 = [0.25, 0.25, 0.25, 0.25]$$

$$w_1^T x = w_2^T x = 1$$

Prefer distributed “spread out weights” …

OVERFITTING: WHAT IS THE LOSS FUNCTION

$$L(W) = \underbrace{\frac{1}{N}\sum_{i=1}^{N} L_i(f(x_i, W), y_i)}$$

Data loss: Model predictions should match training data

OVERFITTING: SOLUTION IS REGULARIZATION

Regularization

λ = regularization strength (hyperparameter)

$$L(W) = \underbrace{\frac{1}{N}\sum_{i=1}^{N} L_i(f(x_i, W), y_i)}_{} + \underbrace{\lambda R(W)}_{}$$

Data loss: Model predictions should match training data

Regularization: Prevent the model from doing *too* well on training data

Simple examples

<u>L2 regularization:</u> $R(W) = \sum_k \sum_l W_{k,l}^2$

L1 regularization: $R(W) = \sum_k \sum_l |W_{k,l}|$

Elastic net (L1 + L2): $R(W) = \sum_k \sum_l \beta W_{k,l}^2 + |W_{k,l}|$

More complex:

Dropout

Batch normalization

Stochastic depth, fractional pooling, etc

BATCH NORMALIZATION

"you want zero-mean unit-variance activations? just make them so."



1. compute the empirical mean and variance independently for each dimension.

2. Normalize

$$\widehat{x}^{(k)} = \frac{x^{(k)} - \mathrm{E}[x^{(k)}]}{\sqrt{\mathrm{Var}[x^{(k)}]}}$$

BATCH NORMALIZATION



Usually inserted after Fully Connected or Convolutional layers, and before nonlinearity.

$$\widehat{x}^{(k)} = \frac{x^{(k)} - \mathrm{E}[x^{(k)}]}{\sqrt{\mathrm{Var}[x^{(k)}]}}$$

BATCH NORMALIZATION

Input: Values of x over a mini-batch: $\mathcal{B} = \{x_{1\ldots m}\}$;
Parameters to be learned: γ, β

Output: $\{y_i = \mathrm{BN}_{\gamma,\beta}(x_i)\}$

$$\mu_\mathcal{B} \leftarrow \frac{1}{m}\sum_{i=1}^{m} x_i \qquad \text{// mini-batch mean}$$

$$\sigma_\mathcal{B}^2 \leftarrow \frac{1}{m}\sum_{i=1}^{m} (x_i - \mu_\mathcal{B})^2 \qquad \text{// mini-batch variance}$$

$$\widehat{x}_i \leftarrow \frac{x_i - \mu_\mathcal{B}}{\sqrt{\sigma_\mathcal{B}^2 + \epsilon}} \qquad \text{// normalize}$$

$$y_i \leftarrow \gamma \widehat{x}_i + \beta \equiv \mathrm{BN}_{\gamma,\beta}(x_i) \qquad \text{// scale and shift}$$

- Improves gradient flow through the network
- Allows higher learning rates
- Reduces the strong dependence on initialization
- Acts as a form of regularization in a funny way, and slightly reduces the need for dropout, maybe

DIFFERENT TYPES OF NORMS



WHAT IS DROPOUT: LEARNING AN ENSEMBLE



WHAT IS DROPOUT



Forces the network to have a redundant representation;
Prevents co-adaptation of features

WHAT IS DROPOUT



Another interpretation:

Dropout is training a large **ensemble** of models (that share parameters).

Each binary mask is one model

An FC layer with 4096 units has
$2^{4096} \sim 10^{1233}$ possible masks!
Only $\sim 10^{82}$ atoms in the universe...

WELL, DON'T USE DROPOUT IN CNN; USE BATCHNORM INSTEAD





BABY SITTING THE TRAINING PROCESS

STEP1: PREPROCESS THE DATA




```
X -= np.mean(X, axis = 0)
```

```
X /= np.std(X, axis = 0)
```

(Assume X [NxD] is data matrix,
each example in a row)

STEP 2: CHOOSE THE ARCHITECTURE

say we start with one hidden layer of 50 neurons:



STEP 2: TRAIN THE NETWORK AND OBSERVE THE LOSS

```
def init_two_layer_model(input_size, hidden_size, output_size):
  # initialize a model
  model = {}
  model['W1'] = 0.0001 * np.random.randn(input_size, hidden_size)
  model['b1'] = np.zeros(hidden_size)
  model['W2'] = 0.0001 * np.random.randn(hidden_size, output_size)
  model['b2'] = np.zeros(output_size)
  return model
```

```
model = init_two_layer_model(32*32*3, 50, 10) # input size, hidden size, number of classes
loss, grad = two_layer_net(X_train, model, y_train, 0.0)
print loss
```

disable regularization

```
2.30261216167
```

loss ~2.3.
"correct" for
10 classes

returns the loss and the
gradient for all parameters

STEP 2: PLAY WITH THE REGULARISATION

Double check that the loss is reasonable:

```
def init_two_layer_model(input_size, hidden_size, output_size):
  # initialize a model
  model = {}
  model['W1'] = 0.0001 * np.random.randn(input_size, hidden_size)
  model['b1'] = np.zeros(hidden_size)
  model['W2'] = 0.0001 * np.random.randn(hidden_size, output_size)
  model['b2'] = np.zeros(output_size)
  return model
```

```
model = init_two_layer_model(32*32*3, 50, 10) # input size, hidden size, number of classes
loss, grad = two_layer_net(X_train, model, y_train, 1e3)
print loss
```

crank up regularization

```
3.06859716482
```

loss went up, good. (sanity check)

STEP 3: WORK WITH A VERY SMALL DATA

Lets try to train now…

Tip: Make sure that you can overfit very small portion of the training data

```
model = init_two_layer_model(32*32*3, 50, 10) # input size, hidden size, number of classes
trainer = ClassifierTrainer()
X_tiny = X_train[:20] # take 20 examples
y_tiny = y_train[:20]
best_model, stats = trainer.train(X_tiny, y_tiny, X_tiny, y_tiny,
                                  model, two_layer_net,
                                  num_epochs=200, reg=0.0,
                                  update='sgd', learning_rate_decay=1,
                                  sample_batches = False,
                                  learning_rate=1e-3, verbose=True)
```

```
Finished epoch 1 / 200: cost 2.302603, train: 0.400000, val 0.400000, lr 1.000000e-03
Finished epoch 2 / 200: cost 2.302258, train: 0.450000, val 0.450000, lr 1.000000e-03
Finished epoch 3 / 200: cost 2.301849, train: 0.600000, val 0.600000, lr 1.000000e-03
Finished epoch 4 / 200: cost 2.301196, train: 0.650000, val 0.650000, lr 1.000000e-03
Finished epoch 5 / 200: cost 2.300044, train: 0.650000, val 0.650000, lr 1.000000e-03
Finished epoch 6 / 200: cost 2.297864, train: 0.550000, val 0.550000, lr 1.000000e-03
Finished epoch 7 / 200: cost 2.293595, train: 0.600000, val 0.600000, lr 1.000000e-03
Finished epoch 8 / 200: cost 2.285096, train: 0.550000, val 0.550000, lr 1.000000e-03
Finished epoch 9 / 200: cost 2.268094, train: 0.550000, val 0.550000, lr 1.000000e-03
Finished epoch 10 / 200: cost 2.234787, train: 0.500000, val 0.500000, lr 1.000000e-03
Finished epoch 11 / 200: cost 2.173187, train: 0.500000, val 0.500000, lr 1.000000e-03
Finished epoch 12 / 200: cost 2.076862, train: 0.500000, val 0.500000, lr 1.000000e-03
Finished epoch 13 / 200: cost 1.974090, train: 0.400000, val 0.400000, lr 1.000000e-03
Finished epoch 14 / 200: cost 1.895885, train: 0.400000, val 0.400000, lr 1.000000e-03
Finished epoch 15 / 200: cost 1.820876, train: 0.450000, val 0.450000, lr 1.000000e-03
Finished epoch 16 / 200: cost 1.737430, train: 0.450000, val 0.450000, lr 1.000000e-03
Finished epoch 17 / 200: cost 1.642356, train: 0.500000, val 0.500000, lr 1.000000e-03
Finished epoch 18 / 200: cost 1.535239, train: 0.600000, val 0.600000, lr 1.000000e-03
Finished epoch 19 / 200: cost 1.421527, train: 0.600000, val 0.600000, lr 1.000000e-03
```

```
Finished epoch 195 / 200: cost 0.002694, train: 1.000000, val 1.000000, lr 1.000000e-03
Finished epoch 196 / 200: cost 0.002674, train: 1.000000, val 1.000000, lr 1.000000e-03
Finished epoch 197 / 200: cost 0.002655, train: 1.000000, val 1.000000, lr 1.000000e-03
Finished epoch 198 / 200: cost 0.002635, train: 1.000000, val 1.000000, lr 1.000000e-03
Finished epoch 199 / 200: cost 0.002617, train: 1.000000, val 1.000000, lr 1.000000e-03
Finished epoch 200 / 200: cost 0.002597, train: 1.000000, val 1.000000, lr 1.000000e-03
finished optimization. best validation accuracy: 1.000000
```

Very small loss, train accuracy 1.00, nice!

STEP 3: FIND A GOOD LEARNING RATE AND REGULARIZER

Lets try to train now…

Start with small regularization and find learning rate that makes the loss go down.

loss not going down: learning rate too low

```
model = init_two_layer_model(32*32*3, 50, 10) # input size, hidden size, number of classes
trainer = ClassifierTrainer()
best_model, stats = trainer.train(X_train, y_train, X_val, y_val,
                                  model, two_layer_net,
                                  num_epochs=10, reg=0.000001,
                                  update='sgd', learning_rate_decay=1,
                                  sample_batches = True,
                                  learning_rate=1e-6, verbose=True)
```

```
Finished epoch 1 / 10: cost 2.302576, train: 0.080000, val 0.103000, lr 1.000000e-06
Finished epoch 2 / 10: cost 2.302582, train: 0.121000, val 0.124000, lr 1.000000e-06
Finished epoch 3 / 10: cost 2.302558, train: 0.119000, val 0.138000, lr 1.000000e-06
Finished epoch 4 / 10: cost 2.302519, train: 0.127000, val 0.151000, lr 1.000000e-06
Finished epoch 5 / 10: cost 2.302517, train: 0.158000, val 0.171000, lr 1.000000e-06
Finished epoch 6 / 10: cost 2.302518, train: 0.179000, val 0.172000, lr 1.000000e-06
Finished epoch 7 / 10: cost 2.302466, train: 0.180000, val 0.176000, lr 1.000000e-06
Finished epoch 8 / 10: cost 2.302452, train: 0.175000, val 0.185000, lr 1.000000e-06
Finished epoch 9 / 10: cost 2.302459, train: 0.206000, val 0.192000, lr 1.000000e-06
Finished epoch 10 / 10: cost 2.302420, train: 0.190000, val 0.192000, lr 1.000000e-06
finished optimization. best validation accuracy: 0.192000
```

Loss barely changing: Learning rate is probably too low

STEP 3: FIND A GOOD LEARNING RATE AND REGULARIZER

Lets try to train now…

Start with small regularization and find learning rate that makes the loss go down.

```
model = init_two_layer_model(32*32*3, 50, 10) # input size, hidden size, number of classes
trainer = ClassifierTrainer()
best_model, stats = trainer.train(X_train, y_train, X_val, y_val,
                                  model, two_layer_net,
                                  num_epochs=10, reg=0.000001,
                                  update='sgd', learning_rate_decay=1,
                                  sample_batches = True,
                                  learning_rate=1e6, verbose=True)
```

```
/home/karpathy/cs231n/code/cs231n/classifiers/neural_net.py:50: RuntimeWarning: divide by zero en
countered in log
  data_loss = -np.sum(np.log(probs[range(N), y])) / N
/home/karpathy/cs231n/code/cs231n/classifiers/neural_net.py:48: RuntimeWarning: invalid value enc
ountered in subtract
  probs = np.exp(scores - np.max(scores, axis=1, keepdims=True))
Finished epoch 1 / 10: cost nan, train: 0.091000, val 0.087000, lr 1.000000e+06
Finished epoch 2 / 10: cost nan, train: 0.095000, val 0.087000, lr 1.000000e+06
Finished epoch 3 / 10: cost nan, train: 0.100000, val 0.087000, lr 1.000000e+06
```

cost: NaN almost always means high learning rate...

loss not going down: learning rate too low
loss exploding: learning rate too high

STEP 3: FIND A GOOD LEARNING RATE AND REGULARIZER

Lets try to train now…

Start with small regularization and find learning rate that makes the loss go down.

loss not going down:
learning rate too low
loss exploding:
learning rate too high

```
model = init_two_layer_model(32*32*3, 50, 10) # input size, hidden size, number of classes
trainer = ClassifierTrainer()
best_model, stats = trainer.train(X_train, y_train, X_val, y_val,
                                  model, two_layer_net,
                                  num_epochs=10, reg=0.000001,
                                  update='sgd', learning_rate_decay=1,
                                  sample_batches = True,
                                  learning_rate=3e-3, verbose=True)
```

```
Finished epoch 1 / 10: cost 2.186654, train: 0.308000, val 0.306000, lr 3.000000e-03
Finished epoch 2 / 10: cost 2.176230, train: 0.330000, val 0.350000, lr 3.000000e-03
Finished epoch 3 / 10: cost 1.942257, train: 0.376000, val 0.352000, lr 3.000000e-03
Finished epoch 4 / 10: cost 1.827868, train: 0.329000, val 0.310000, lr 3.000000e-03
Finished epoch 5 / 10: cost inf, train: 0.128000, val 0.128000, lr 3.000000e-03
Finished epoch 6 / 10: cost inf, train: 0.144000, val 0.147000, lr 3.000000e-03
```

3e-3 is still too high. Cost explodes….

=> Rough range for learning rate we should be cross-validating is somewhere [1e-3 … 1e-5]

HYPER-PARAMETER SEARCH: CROSS VALIDATION

coarse -> fine cross-validation in stages

First stage: only a few epochs to get rough idea of what params work
Second stage: longer running time, finer search
… (repeat as necessary)

Tip for detecting explosions in the solver:
If the cost is ever > 3 * original cost, break out early

HYPER-PARAMETER SEARCH: CROSS VALIDATION

For example: run coarse search for 5 epochs

```
max_count = 100
for count in xrange(max_count):
      reg = 10**uniform(-5, 5)
      lr = 10**uniform(-3, -6)

      trainer = ClassifierTrainer()
      model = init_two_layer_model(32*32*3, 50, 10) # input size, hidden size, number of classes
      trainer = ClassifierTrainer()
      best_model_local, stats = trainer.train(X_train, y_train, X_val, y_val,
                                              model, two_layer_net,
                                              num_epochs=5, reg=reg,
                                              update='momentum', learning_rate_decay=0.9,
                                              sample_batches = True, batch_size = 100,
                                              learning_rate=lr, verbose=False)
```

note it's best to optimize in log space!

```
val_acc: 0.412000, lr: 1.405206e-04, reg: 4.793564e-01, (1 / 100)
val_acc: 0.214000, lr: 7.231888e-06, reg: 2.321281e-04, (2 / 100)
val_acc: 0.208000, lr: 2.119571e-06, reg: 8.011857e+01, (3 / 100)
val_acc: 0.196000, lr: 1.551131e-05, reg: 4.374936e-05, (4 / 100)
val_acc: 0.079000, lr: 1.753300e-05, reg: 1.200424e+03, (5 / 100)
val_acc: 0.223000, lr: 4.215128e-05, reg: 4.196174e+01, (6 / 100)
val_acc: 0.441000, lr: 1.750259e-04, reg: 2.110807e-04, (7 / 100)
val_acc: 0.241000, lr: 6.749231e-05, reg: 4.226413e+01, (8 / 100)
val_acc: 0.482000, lr: 4.296863e-04, reg: 6.642555e-01, (9 / 100)
val_acc: 0.079000, lr: 5.401602e-06, reg: 1.599828e+04, (10 / 100)
val_acc: 0.154000, lr: 1.618508e-06, reg: 4.925252e-01, (11 / 100)
```

nice

HYPER-PARAMETER SEARCH: CROSS VALIDATION

Now run finer search...

```
max_count = 100
for count in xrange(max_count):
      reg = 10**uniform(-5, 5)
      lr = 10**uniform(-3, -6)
```

adjust range →

```
max_count = 100
for count in xrange(max_count):
      reg = 10**uniform(-4, 0)
      lr = 10**uniform(-3, -4)
```

```
val_acc: 0.527000, lr: 5.340517e-04, reg: 4.097824e-01, (0 / 100)
val_acc: 0.492000, lr: 2.279484e-04, reg: 9.991345e-04, (1 / 100)
val_acc: 0.512000, lr: 8.680827e-04, reg: 1.349727e-02, (2 / 100)
val_acc: 0.461000, lr: 1.028377e-04, reg: 1.220193e-02, (3 / 100)
val_acc: 0.460000, lr: 1.113730e-04, reg: 5.244309e-02, (4 / 100)
val_acc: 0.498000, lr: 9.477776e-04, reg: 2.001293e-03, (5 / 100)
val_acc: 0.469000, lr: 1.484369e-04, reg: 4.328313e-01, (6 / 100)
val_acc: 0.522000, lr: 5.586261e-04, reg: 2.312685e-04, (7 / 100)
val_acc: 0.530000, lr: 5.808183e-04, reg: 8.259964e-02, (8 / 100)
val_acc: 0.489000, lr: 1.979168e-04, reg: 1.010889e-04, (9 / 100)
val_acc: 0.490000, lr: 2.036031e-04, reg: 2.406271e-03, (10 / 100)
val_acc: 0.475000, lr: 2.021162e-04, reg: 2.287807e-01, (11 / 100)
val_acc: 0.460000, lr: 1.135527e-04, reg: 3.905040e-02, (12 / 100)
val_acc: 0.515000, lr: 6.947668e-04, reg: 1.562808e-02, (13 / 100)
val_acc: 0.531000, lr: 9.471549e-04, reg: 1.433895e-03, (14 / 100)
val_acc: 0.509000, lr: 3.140888e-04, reg: 2.857518e-01, (15 / 100)
val_acc: 0.514000, lr: 6.438349e-04, reg: 3.033781e-01, (16 / 100)
val_acc: 0.502000, lr: 3.921784e-04, reg: 2.707126e-04, (17 / 100)
val_acc: 0.509000, lr: 9.752279e-04, reg: 2.850865e-03, (18 / 100)
val_acc: 0.500000, lr: 2.412048e-04, reg: 4.997821e-04, (19 / 100)
val_acc: 0.466000, lr: 1.319314e-04, reg: 1.189915e-02, (20 / 100)
val_acc: 0.516000, lr: 8.039527e-04, reg: 1.528291e-02, (21 / 100)
```

53% - relatively good for a 2-layer neural net with 50 hidden neurons.

WHAT HYPER-PARAMETERS TO PLAY WITH?

- Network architecture
  - How many layers?
  - What sequence of layers?
  - What is the depth of the model?
- Learning rate
  - Decay rate
  - Update strategy
- Regularization
  - L2 / Dropout strength
- Which loss function?
  - hinge/ L2/ Cross-entropy
- Which optimization?
  - SGD/ adam/ RMSPROP

EVENTUAL CROSS VALIDATION BE LIKE . . .



MONITOR AND LEARN FROM THE LOSS CURVE





LESSON 1: BAD INITIALISATION



LESSON 2: OVERFITTING/ UNDERFITTING



big gap = overfitting

=> increase regularization strength?

no gap

=> increase model capacity?

SUMMARY

- Activation Functions (use ReLU)
- Data Preprocessing (images: subtract mean)
- Weight Initialization (use Xavier/He init)
- Batch Normalization (use)
- Babysitting the Learning process
- Hyperparameter Optimization
  (random sample hyperparams, in log space when appropriate)

TIPS & TRICKS (MAY NOT WORK ALWAYS)

CHOICE OF OPTIMIZATION

- **Adam** is a good default choice in many cases
- **SGD+Momentum** with learning rate decay often outperforms Adam by a bit, but requires more tuning

- If you can afford to do full batch updates then try out **L-BFGS** (and don't forget to disable all sources of noise)

EARLY STOPPING





Stop training the model when accuracy on the validation set decreases
Or train for a long time, but always keep track of the model snapshot that worked best on val

MODEL ENSEMBLE

1. Train multiple independent models
2. At test time average their results
   (Take average of predicted probability distributions, then choose argmax)

Enjoy 2% extra performance

Instead of training independent models, use multiple snapshots of a single model during training!

HANDS-ON

- Convolutional Neural Network
- How to read the training loss & validation loss
- Write a learning rate strategy for better learning the ConvNet

ASSIGNMENT #2 (DEADLINE: 21 APRIL) TEAM SIZE (2–3)

- Consider InceptionV3 model, CIFAR-10 dataset
- Hyperparameters to explore:
  - Layer activation function
  - Data preprocessing, normalisation
  - Dropout (where to apply, what is the strength)
  - BatchNorm (where to apply)
  - Loss function
  - Learning rate and learning strategy
- Report the final best set of hyper parameters set that gave you the best accuracy.
- You will be evaluated on what values you explored for each of the parameter and in what order? Please do explain how you baby-sit the learning process.
- Please note that there is no single correct answer to this questions.