

3GPP TS 26.131 V6.0.0 (2004-09)

Technical Specification

3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Terminal acoustic characteristics for telephony; Requirements (Release 6)



The present document has been developed within the 3rd Generation Partnership Project (3GPPTM) and may be further elaborated for the purposes of 3GPP

The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification Specifications and reports for implementation of the 3GPPTM system should be obtained via the 3GPP Organizational Partners' Publications Offices.

Keywords

UMTS, terminal, telephony, acoustic

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2004, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TTA, TTC).
All rights reserved.

Contents

Foreword.....	5
Introduction	5
1 Scope	6
2 References.....	6
3 Definitions, symbols and abbreviations	7
3.1 Definitions.....	7
3.2 Abbreviations.....	7
4 Interfaces	7
5 Narrow-band telephony transmission performance.....	8
5.1 Applicability.....	8
5.2 Overall loss/loudness ratings.....	8
5.2.1 General.....	8
5.2.2 Connections with handset UE.....	8
5.2.3 Connections with Desktop and Vehicle-mounted hands-free UE.....	9
5.2.4 Connections with handheld hands-free UE.....	9
5.2.5 Connections with headset UE.....	9
5.3 Idle channel noise (handset and headset UE)	9
5.3.1 Sending	9
5.3.2 Receiving.....	10
5.4 Sensitivity/frequency characteristics	10
5.4.1 Handset and headset UE sending	10
5.4.2 Handset and headset UE receiving	10
5.4.3 Desktop and Vehicle-mounted hands-free UE sending	11
5.4.4 Desktop and Vehicle-mounted hands-free UE receiving.....	11
5.4.5 Handheld hands-free UE sending.....	12
5.4.6 Handheld hands-free UE receiving.....	12
5.5 Sidetone characteristics (handset and headset UE)	13
5.5.1 Sidetone loss.....	13
5.6 Stability loss.....	13
5.7 Acoustic echo control.....	13
5.7.1 General.....	13
5.7.2 Acoustic echo control in an Desktop and Vehicle-mounted hands-free UE.....	14
5.7.3 Acoustic echo control in an handheld hands-free UE.....	14
5.7.4 Acoustic echo control in a handset UE	14
5.7.5 Acoustic echo control in a headset UE.....	14
5.8 Distortion.....	14
5.8.1 Sending Distortion	14
5.8.2 Receiving.....	15
5.9 Ambient Noise Rejection	15
5.10 Information on other Parameters (not normative)	16
6 Wideband telephony transmission performance	17
6.1 Applicability.....	17
6.2 Overall loss/loudness ratings.....	17
6.2.1 General.....	17
6.2.2 Connections with handset UE.....	17
6.2.3 Connections with Desktop and Vehicle-mounted hands-free UE.....	17
6.2.4 Connections with handheld hands-free UE.....	18
6.2.5 Connections with headset UE.....	18
6.3 Idle channel noise (handset and headset UE)	18
6.3.1 Sending	18
6.3.2 Receiving.....	18
6.4 Sensitivity/frequency characteristics	19
6.4.1 Handset and headset UE sending.....	19

6.4.2	Handset and headset UE receiving	19
6.4.3	Desktop and Vehicle-mounted hands-free UE sending	20
6.4.4	Desktop and Vehicle-mounted hands-free UE receiving.....	20
6.4.5	Handheld hands-free UE sending.....	21
6.4.6	Handheld hands-free UE receiving.....	21
6.5	Sidetone characteristics (handset and headset UE)	22
6.5.1	Sidetone loss.....	22
6.6	Stability loss.....	22
6.7	Acoustic echo control.....	22
6.7.1	General.....	22
6.7.2	Acoustic echo control in an Desktop and Vehicle-mounted hands-free UE	23
6.7.3	Acoustic echo control in an handheld hands-free UE	23
6.7.4	Acoustic echo control in a handset UE	23
6.7.5	Acoustic echo control in a headset UE.....	23
6.8	Distortion.....	23
6.8.1	Sending Distortion	23
6.8.2	Receiving.....	24
6.9	Ambient Noise rejection	24
Annex A (informative):	Change history	25

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document specifies minimum performance requirements for the acoustic characteristics of 3G terminals when used to provide narrow-band or wideband telephony.

The objective for narrow-band services is to reach a quality as close as possible to ITU-T standards for PSTN circuits. However, due to technical and economic factors, there cannot be full compliance with the general characteristics of international telephone connections and circuits recommended by the ITU-T.

The performance requirements are specified the main body of the text; the test methods and considerations are described in [TS 26.132](#).

1 Scope

The present document is applicable to any terminal capable of supporting ~~narrow-band~~ or wideband telephony, either as a stand-alone service or as the telephony component of a multimedia service. The present document specifies minimum performance requirements for the acoustic characteristics of 3G terminals when used to provide narrow-band or wideband telephony.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 26.132: "Narrow-band speech telephony terminal acoustic characteristics - test methods".
- [2] ITU-T Recommendation B.12 (1988): "Use of the decibel and the neper in telecommunications".
- [3] ITU-T Recommendation G.103 (1998): "Hypothetical reference connections".
- [4] ITU-T Recommendation G.111 (1993): "Loudness ratings (LRs) in an international connection".
- [5] ITU-T Recommendation G.121 (1993): "Loudness ratings (LRs) of national systems".
- [6] ITU-T Recommendation G.122 (1993): "Influence of national systems on stability, talker echo, and listener echo in international connections".
- [7] ITU-T Recommendation G.711 (1988): "Pulse code modulation (PCM) of voice frequencies".
- [8] ITU-T Recommendation P.11 (1993): "Effect of transmission impairments".
- [9] ITU-T Recommendation P.38 (1993): "Transmission characteristics of operator telephone systems (OTS)".
- [10] ITU-T Recommendation P.50 (1993): "Artificial voices".
- [11] ITU-T Recommendation P.79 (1999): "Calculation of loudness ratings for telephone sets".
- [12] ITU-T Recommendation G.223: "Assumptions for the calculation of noise on hypothetical reference circuits for telephony".
- [13] ITU-T Recommendations P.340: "Transmission characteristics of hands-free telephones".
- [14] ITU-T Recommendation P.501: "Test signals for use in telephonometry".
- [15] ITU-T Recommendation P.502: "Objective test methods for speech communication systems using complex test signals".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document the term *narrow-band* shall refer to signals sampled at 8kHz; *wideband* shall refer to signals sampled at 16kHz.

For the purposes of the present document, the following terms: dB, dBr, dBm0, dBm0p and dBA, shall be interpreted as defined in ITU-T Recommendation B.12; the term dBPa shall be interpreted as the sound pressure level relative to 1 Pascal expressed in dB (0dBPa is equivalent to 94dB SPL).

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ADC	Analogue to Digital Converter
DAC	Digital to Analogue Converter
DAI	Digital Audio Interface
DTX	Discontinuous Transmission
EEC	Electrical Echo Control
EL	Echo Loss
ERP	Ear Reference Point
HATS	Head and Torso Simulator
LSTR	Listener Sidetone Rating
LRGP	Loudness Rating Guardring Position
MRP	Mouth Reference Point
OLR	Overall Loudness Rating
PCM	Pulse Code Modulation
POI	Point of Interconnection (with PSTN)
PSTN	Public Switched Telephone Network
RLR	Receive Loudness Rating
SLR	Send Loudness Rating
STMR	Sidetone Masking Rating
SS	System Simulator
TX	Transmission
UE	User Equipment
UPCMI	13-bit Uniform PCM Interface

4 Interfaces

The interfaces required to define terminal acoustic characteristics are shown in figure 1. These are the air interface and the point of interconnect (POI).

The Air Interface is specified by the 3G 25 series specifications and is required to achieve user equipment (UE) transportability. Analogue measurements can be made at this point using a system simulator (SS) comprising the appropriate radio terminal equipment and speech transcoder. The losses and gains introduced by the test speech transcoder will need to be specified.

The POI with the public switched telephone network (PSTN) is considered to have a relative level of 0 dBr, where signals will be represented by 8-bit A-law, according to ITU-T Recommendation G.711. Analogue measurements may be made at this point using a standard send and receive side, as defined in ITU-T Recommendations.

Five classes of acoustic interface are considered in this specification:

Handset UE;

Headset UE;

Desktop-mounted hands-free UE;

Vehicle-mounted hands-free UE;

Handheld hands-free UE.

5 Narrow-band telephony transmission performance

5.1 Applicability

The performance requirements in this sub-clause shall apply when UE is used to provide narrow-band telephony, either as a stand-alone service, or as part of a multimedia service.

5.2 Overall loss/loudness ratings

5.2.1 General

An international connection involving a 3G network and the PSTN should meet the overall loudness rating (OLR) limits in ITU-T Recommendation G.111. The national parts of the connection should therefore meet the send and receive loudness rating (SLR, RLR) limits in ITU-T Recommendation G.121.

For the case where digital routings are used to connect the 3G network to the international chain of circuits, the SLR and RLR of the national extension will be largely determined by the SLR and RLR of the 3G network. The limits given below are consistent with the national extension limits and long term objectives in ITU-T Recommendation G.121.

The SLR and RLR values for the 3G network apply up to the POI. However, the main determining factors are the characteristics of the UE, including the analogue to digital conversion (ADC) and digital to analogue conversion (DAC). In practice, it is convenient to specify loudness ratings to the Air Interface. For the normal case, where the 3G network introduces no additional loss between the Air Interface and the POI, the loudness ratings to the PSTN boundary (POI) will be the same as the loudness ratings measured at the Air Interface. However, in some cases loss adjustment may be needed for interworking situations in individual countries.

5.2.2 Connections with handset UE

The nominal values of SLR/RLR to the POI shall be:

SLR = 8 +/- 3 dB;

RLR = 2 +/- 3 dB.

Where a user controlled receiving volume control is provided, the RLR shall meet the selected nominal value for at least one setting of the control. When the control is set to maximum, the RLR shall not be less than (louder than) -13 dB.

With the volume control set to the minimum position the RLR shall not be greater than (quieter than) 18 dB.

Compliance shall be checked by the relevant tests described in TS 26.132.

NOTE: The mechanical design of some UE may make it impossible to seal the ear-piece to the knife edge of the ITU-T artificial ear. Minimal additional methods may be used to provide the seal provided that they do not affect the mounting position of the UE with respect to the Mouth Reference Point and the Ear Reference Point.

5.2.3 Connections with Desktop and Vehicle-mounted hands-free UE

The nominal values of SLR/RLR to/from the POI shall be:

$$\text{SLR} = 13 \pm 4 \text{ dB};$$

$$\text{RLR} = 2 \pm 4 \text{ dB}.$$

Compliance shall be checked by the relevant tests described in TS 26.132.

Where a user controlled volume control is provided, the RLR shall meet the nominal value at one setting of the control. It is recommended that a volume control giving at least 15 dB increase from the nominal RLR (louder) is provided for hands-free units intended to work in the vehicle environment. This is to allow for the increased noise volume in a moving vehicle.

5.2.4 Connections with handheld hands-free UE

The nominal values of SLR/RLR to/from the POI shall be:

$$\text{SLR} = 13 \pm 4 \text{ dB};$$

$$\text{RLR} = 6 + 12 / - 4 \text{ dB}.$$

Compliance shall be checked by the relevant tests described in TS 26.132.

Where a user controlled volume control is provided, the RLR shall meet the nominal value at one setting of the control.

5.2.5 Connections with headset UE

The SLR and RLR should be measured and computed using methods given in ITU-T Recommendation P.38. This Recommendation currently gives a measuring technique for supra-aural earphone and insert type receivers. Study is continuing on other types of ear-pieces in ITU-T Study Group 12

The nominal values of SLR/RLR to/from the POI shall be:

$$\text{SLR} = 8 \pm 3 \text{ dB};$$

$$\text{RLR} = 2 \pm 3 \text{ dB with any volume control set to mid position}.$$

Where a user controlled receiving volume control is provided, the RLR shall meet the selected nominal value for at least one setting of the control. When the control is set to maximum, the RLR shall not be less than (louder than) -13 dB.

With the volume control set to the minimum position the RLR shall not be greater than (quieter than) 18 dB.

Compliance shall be checked by the relevant tests described in 3GPP TS 26.132.

5.3 Idle channel noise (handset and headset UE)

5.3.1 Sending

The maximum noise level produced by the apparatus at the output of the SS under silent conditions in the sending direction shall not exceed -64 dBm0p.

NOTE 1: This level includes the eventual noise contribution of an acoustic echo canceller under the condition that no signal is received.

NOTE 2: This figure applies to the wideband noise signal. It is recommended that the level of single frequency disturbances should be 10 dB lower (ITU-T Recommendation P.11).

Compliance shall be checked by the relevant test described in TS 26.132.

5.3.2 Receiving

The maximum (acoustic) noise level at the handset and headset UE when no signal is applied to the input of the SS shall be as follows:

If no user-controlled receiving volume control is provided, or, if it is provided, at the setting of the user-controlled receiving volume control at which the RLR is equal to the nominal value, the noise measured at the ear reference point (ERP) contributed by the receiving equipment alone shall not exceed -57 dB Pa(A).

Where a volume control is provided, the measured noise shall also not exceed -54 dB Pa(A) at the maximum setting of the volume control.

NOTE: In a connection with the PSTN, noise conditions as described in ITU-T Recommendation G.103 can be expected at the input (POI) of the 3G network. The characteristics of this noise may be influenced by the speech transcoding process (for further study).

Compliance shall be checked by the relevant test described in 3GPP TS 26.132.

5.4 Sensitivity/frequency characteristics

5.4.1 Handset and headset UE sending

The sensitivity/frequency characteristics shall be as follows:

The sending sensitivity frequency response, measured either from the mouth reference point (MRP) to digital interface or from the MRP to the SS audio output (digital output of the reference speech decoder of the SS), shall be within a mask, which can be drawn between the points given in table 1. The mask is drawn with straight lines between the breaking points in table 1 on a logarithmic (frequency) - linear (dB sensitivity) scale.

Table 1: Sending sensitivity/frequency mask

Frequency (Hz)	Upper limit	Lower limit
100	-12	-
200	0	-
300	0	-12
1 000	0	-6
2 000	4	-6
3 000	4	-6
3 400	4	-9
4 000	0	

NOTE: All sensitivity values are expressed in dB on an arbitrary scale.

Compliance shall be checked by the relevant test described in TS 26.132.

5.4.2 Handset and headset UE receiving

The sensitivity/frequency characteristics shall be as follows:

The receiving sensitivity frequency response, measured either from the digital interface to the ERP or from the SS audio input (analogue or digital input of the reference speech encoder of the SS) to the ERP, shall be within a mask, which can be drawn with straight lines between the breaking points in table 2 on a logarithmic (frequency) - linear (dB sensitivity) scale. The values in table 2 are provisional and are for further study.

Table 2: Receiving sensitivity/frequency mask

Frequency (Hz)	Upper limit	Lower limit
70	-10	-
200	[2	-
300		-9
500		(see note 2)
1 000	(see note 2)	-7
3 000		(see note 2)
3 400		-12
4 000	2	-

NOTE 1: All sensitivity values are expressed in dB on an arbitrary scale.

NOTE 2: The limit at intermediate frequencies lies on a straight line drawn between the given values on a log (frequency) - linear (dB) scale.

Compliance shall be checked by the relevant test described in TS 26.132.

5.4.3 Desktop and Vehicle-mounted hands-free UE sending

The sending sensitivity frequency response from the MRP to the SS audio output (digital output of the reference speech decoder of the SS) shall be as follows:

The sending sensitivity frequency response shall be within the mask which can be drawn with straight lines between the breaking points in table 3 on a logarithmic (frequency) - linear (dB sensitivity) scale.

Table 3: Hands-free sending sensitivity/frequency response

Frequency (Hz)	Upper limit	Lower limit
200	0	
250	0	
315	0	-14
400	0	-13
500	0	-12
630	0	-11
800	0	-10
1 000	0	-8
1 300	2	-8
1 600	3	-8
2 000	4	-8
2 500	4	-8
3 100	4	-8
4 000	0	

NOTE: All sensitivity values are expressed in dB on an arbitrary scale.

Compliance shall be checked by the relevant test described in TS 26.132.

5.4.4 Desktop and Vehicle-mounted hands-free UE receiving

The receiving sensitivity frequency response from the SS audio input (analogue or digital input of the reference speech encoder of the SS) to the ERP shall be as follows:

The receiving sensitivity frequency response shall be within the mask which can be drawn with straight lines between the breaking points in table 4 on a logarithmic (frequency) - linear (dB sensitivity) scale.

Table 4: Hands-free receiving sensitivity/frequency response

Frequency (Hz)	Upper limit	Lower limit
200	0	
250	0	
315	0	-15
400	0	-12
500	0	-12
630	0	-12
800	0	-12
1 000	0	-12
1 300	0	-12
1 600	0	-12
2 000	0	-12
2 500	0	-12
3 100	0	-12
4 000	0	

NOTE: All sensitivity values are expressed in dB on an arbitrary scale.

Compliance shall be checked by the relevant test described in TS 26.132.

5.4.5 Handheld hands-free UE sending

The sending sensitivity frequency response from the MRP to the SS audio output (digital output of the reference speech decoder of the SS) shall be as follows:

The sending sensitivity frequency response shall be within the mask which can be drawn with straight lines between the breaking points in table 5 on a logarithmic (frequency) - linear (dB sensitivity) scale.

Table 5: Hands-free sending sensitivity/frequency response

Frequency (Hz)	Upper limit	Lower limit
200	0	
250	0	
315	0	-14
400	0	-13
500	0	-12
630	0	-11
800	0	-10
1 000	0	-8
1 300	2	-8
1 600	3	-8
2 000	4	-8
2 500	4	-8
3 100	4	-8
4 000	0	

NOTE: All sensitivity values are expressed in dB on an arbitrary scale.

Compliance shall be checked by the relevant test described in TS 26.132.

5.4.6 Handheld hands-free UE receiving

The receiving sensitivity frequency response from the SS audio input (analogue or digital input of the reference speech encoder of the SS) to the ERP shall be as follows:

The receiving sensitivity frequency response shall be within the mask which can be drawn with straight lines between the breaking points in table 6 on a logarithmic (frequency) - linear (dB sensitivity) scale.

Table 6: Hands-free receiving sensitivity/frequency response

Frequency (Hz)	Upper limit	Lower limit
200	0	
250	0	
315	0	
400	0	
500	0	
630	0	
800	0	-12
1 000	0	-12
1 300	0	-12
1 600	0	-12
2 000	0	-12
2 500	0	-12
3 100	0	-12
4 000	0	

NOTE: All sensitivity values are expressed in dB on an arbitrary scale.

Compliance shall be checked by the relevant test described in TS 26.132.

5.5 Sidetone characteristics (handset and headset UE)

5.5.1 Sidetone loss

The talker sidetone masking rating (STMR) shall be 18 ± 5 dB.

Compliance shall be checked by the relevant test described in 3GPP TS 26.132.

5.6 Stability loss

The stability loss presented to the PSTN by the 3G network at the POI should meet the principles of the requirements in clauses 2 and 3 of ITU-T Recommendation G.122. These requirements will be met if the attenuation between the digital input and digital output at the POI is at least 6 dB at all frequencies in the range 200 Hz to 4 kHz under the worst case acoustic conditions at the UE (any acoustic echo control should be enabled). For the normal case of digital connection between the Air Interface and the POI, the stability requirement can be applied at the Air Interface.

The worst case acoustic conditions will be as follows (with any volume control set to maximum):

Handset UE: the handset lying on, and the transducers facing, a hard surface with the ear-piece uncapped.

Headset UE: for further study

Handsfree UE: no requirement other than echo loss.

NOTE: The test procedure must take into account the switching effects of echo control and discontinuous transmission (DTX).

5.7 Acoustic echo control

5.7.1 General

The echo loss (EL) presented by the 3G network at the POI should be at least 46 dB during single talk. This value takes into account the fact that UE is likely to be used in a wide range of noise environments.

The use of acoustic echo control is not mandated for 3G networks and the connection between the UE and the POI is zero loss. Therefore the acoustic echo control provided in UE should provide a TCLw of at least 46 dB at the POI over the likely range of acoustic end delays.

If acoustic echo control is provided by voice switching, comfort noise should be injected. This comfort noise shall operate in the same way to that used in DTX.

5.7.2 Acoustic echo control in an Desktop and Vehicle-mounted hands-free UE

The TCLw for the handsfree UE shall be 40 dB at the nominal setting of the volume control in quiet background conditions and 33 dB at the maximum user selectable volume control setting. If acoustic echo control is provided using some form of echo cancellation technique, the cancellation algorithm should be designed to cope with the expected reverberation and dispersion. In the case of the hands-free UE, this reverberation and dispersion may be time variant. Compliance with this requirement shall be checked by the relevant test described in TS 26.132.

5.7.3 Acoustic echo control in an handheld hands-free UE

The TCLw for the hands-free UE shall be 40 dB at the nominal setting of the volume control in quiet background conditions and 33 dB at the maximum user selectable volume control setting. If acoustic echo control is provided using some form of echo cancellation technique, the cancellation algorithm should be designed to cope with the expected reverberation and dispersion. In the case of the hands-free UE, this reverberation and dispersion may be time variant. Compliance with this requirement shall be checked by the relevant test described in TS 26.132.

5.7.4 Acoustic echo control in a handset UE

The TCLw for the handset UE shall be 46 dB. Careful acoustic design of the handset body and selection of the mouth and ear piece transducers may facilitate the required acoustic echo loss without the need for active echo control techniques. However, should echo cancellation be employed the echo canceller should be capable of dealing with the variations in handset positions when in normal use. The implications of this are under study. Compliance with this requirement shall be checked by the relevant test described in TS 26.132.

5.7.5 Acoustic echo control in a headset UE

The TCLw for a headset UE shall be 46 dB. Due to the obstacle effect of the head in this type of terminal, careful design might mean that no active echo control is necessary.

5.8 Distortion

5.8.1 Sending Distortion

The sending part shall meet the following distortion requirements:

NOTE: Digital signal processing other than the transcoder itself is included in this requirement (e.g. echo cancelling).

Distortion shall be measured between MRP and the SS audio output (output of the reference speech decoder of the SS). The ratio of signal-to-total distortion power measured with the proper noise weighting (see table 3 of ITU-T Recommendation G.223) shall be above the limits given in table 7 unless the sound pressure at MRP exceeds +10 dBPa.

Table 7: Limits for signal-to-total distortion ratio

Sending level dB relative to ARL	Sending Ratio (dB)
-25	26,6
-20	30,7
-10	33,3
0	33,7
+7	31,7
+10	25,5

Limits for intermediate levels are found by drawing straight lines between the breaking points in the table on a linear (dB signal level) - linear (dB ratio) scale.

Compliance of the sending distortion shall be checked by the test described in TS 26.132.

5.8.2 Receiving

The receiving part between the SS audio input (input of the reference speech encoder of the SS) and ERP shall meet the requirements at the nominal setting of the volume control:

The ratio of signal-to-total distortion power measured with the proper noise weighting (see table 4 of CCITT Recommendation G.223) shall be above the limits given in table 8 when the sound pressure at ERP is up to +10 dBPa. For sound pressures exceeding +10 dBPa at the ERP there is no distortion requirement.

Table 8: Limits for signal-to-total distortion ratio

Receiving level at the digital interface (dBm0)	Receiving Ratio (dB)
-45	17,5
-40	22,5
-30	30,5
-20	33,0
-10	33,5
-3	31,2
0	25,5

Limits for intermediate levels are found by drawing straight lines between the breaking points in the table on a linear (dB signal level) - linear (dB ratio) scale.

Compliance of the receiving distortion shall be checked by the appropriate test method in TS 26.132.

5.9 Ambient Noise Rejection

Handset and Headset UE:

The nature of mobile telephony is such that the UE will typically be operated in ~~high ambient acoustic noise~~. Due to the adverse interaction of noise signals with speech codecs operating at lower rates, for example 8kbit/s or less, a minimum noise rejection specification is required.


The UE ambient noise rejection ANR, calculated as a Single Figure DELSM (SFDELSM) shall be greater than or equal to the nominal value of 0dB. Due to the uncertainty inherent in the measurement method for ANR, a 3dB tolerance is allowed on the nominal value.

For good performance, it is recommended that a figure of +3 dB should be achieved.

Compliance shall be checked by the relevant test described in 3GPP TS 26.132.

Hands-free UE (all categories):

No requirement in hands-free operations.



NOTE 1: Includes DTX functionality.

NOTE 2: Connection to PSTN should include electrical echo control (EEC).

Figure 1: 3G Interfaces for specification and testing of terminal narrow-band acoustic characteristics

5.10 Information on other Parameters (not normative)

Information about additional parameters relevant to speech quality e.g. for terminals where signal processing is used can be found in ITU-T Recommendations P.340, P.501 and P.502.

6 Wideband telephony transmission performance

6.1 Applicability

The performance requirements in this sub-clause shall apply when UE is used to provide wideband telephony, either as a stand-alone service, or as part of a multimedia service. The requirements in the clause apply only when the far-end terminal is also providing wideband, and not narrow-band telephony. When a wideband-enabled terminal is providing narrow-band telephony, the requirements in clause 5, 'narrow-band telephony transmission performance' shall apply.

6.2 Overall loss/loudness ratings

6.2.1 General

An international connection involving a 3G network and the PSTN should meet the overall loudness rating (OLR) limits in ITU-T Recommendation G.111. The national parts of the connection should therefore meet the send and receive loudness rating (SLR, RLR) limits in ITU-T Recommendation G.121.

For the case where digital routings are used to connect the 3G network to the international chain of circuits, the SLR and RLR of the national extension will be largely determined by the SLR and RLR of the 3G network. The limits given below are consistent with the national extension limits and long term objectives in ITU-T Recommendation G.121. The SLR and RLR values for the 3G network apply up to the POI. However, the main determining factors are the characteristics of the UE, including the analogue to digital conversion (ADC) and digital to analogue conversion (DAC). In practice, it is convenient to specify loudness ratings to the Air Interface. For the normal case, where the 3G network introduces no additional loss between the Air Interface and the POI, the loudness ratings to the PSTN boundary (POI) will be the same as the loudness ratings measured at the Air Interface. However, in some cases loss adjustment may be needed for interworking situations in individual countries.

Requirements for wideband telephony are based on ITU-T Recommendations P. 311, for handset user-equipment, and ITU-T Recommendation P. 341 for hands-free user-equipment.

6.2.2 Connections with handset UE

The nominal values of SLR/RLR to the POI shall be:

SLR = 8 +/- 3 dB;

RLR = 5 +/- 3 dB.

Where a user controlled receiving volume control is provided, the RLR shall meet the selected nominal value for at least one setting of the control. When the control is set to maximum, the RLR shall not be less than (louder than) - 10 dB.

The loudness rating is 3dB higher (quieter) than for narrow-band telephony, due to the increased loudness of the wider bandwidth.

With the volume control set to the minimum position the RLR shall not be greater than (quieter than) 18 dB.

Compliance shall be checked by the relevant tests described in TS 26.132.

6.2.3 Connections with Desktop and Vehicle-mounted hands-free UE

The nominal values of SLR/RLR to/from the POI shall be:

SLR = 13 +/- 4 dB;

RLR = 5 +/- 4 dB.

Compliance shall be checked by the relevant tests described in TS 26.132.

The loudness rating is 3dB high (quieter) than for narrow-band telephony, due to the increased loudness of the wider bandwidth. Where a user controlled volume control is provided, the RLR shall meet the nominal value at one setting of the control. It is recommended that a volume control giving at least 15 dB increase from the nominal RLR (louder) is provided for hands-free units intended to work in the vehicle environment. This is to allow for the increased noise volume in a moving vehicle.

6.2.4 Connections with handheld hands-free UE

The nominal values of SLR/RLR to/from the POI shall be:

$$\text{SLR} = 13 \pm 4 \text{ dB};$$

$$\text{RLR} = 9 \pm 4 \text{ dB}.$$

Compliance shall be checked by the relevant tests described in TS 26.132.

The loudness rating is 3dB higher (quieter) than for narrow-band telephony, due to the increased loudness of the wider bandwidth.

Where a user controlled volume control is provided, the RLR shall meet the nominal value at one setting of the control.

6.2.5 Connections with headset UE

The SLR and RLR should be measured and computed using methods given in ITU-T Recommendation P.38. This Recommendation currently gives a measuring technique for supra-aural earphone and insert type receivers. Study is continuing on other types of ear-pieces in ITU-T Study Group 12.

The nominal values of SLR/RLR to/from the POI shall be:

$$\text{SLR} = 8 \pm 3 \text{ dB};$$

$$\text{RLR} = 5 \pm 3 \text{ dB}$$

Where a user controlled receiving volume control is provided, the RLR shall meet the selected nominal value for at least one setting of the control. When the control is set to maximum, the RLR shall not be less than (louder than) -13 dB. With the volume control set to the minimum position the RLR shall not be greater than (quieter than) 18 dB.

The loudness rating is 3dB high (quieter) than for narrow-band telephony, due to the increased loudness of the wider bandwidth.

6.3 Idle channel noise (handset and headset UE)

6.3.1 Sending

The maximum noise level produced by the apparatus at the output of the SS under silent conditions in the sending direction shall not exceed -64 dBm0(A).

NOTE 1: This level includes the eventual noise contribution of an acoustic echo canceller under the condition that no signal is received.

NOTE 2: This figure applies to the wideband noise signal. It is recommended that the level of single frequency disturbances should be 10 dB lower (ITU-T Recommendation P.11).

Compliance shall be checked by the relevant test described in TS 26.132.

6.3.2 Receiving

The maximum (acoustic) noise level at the handset and headset UE when no signal is transmitted to the input of the SS shall be as follows:

If no user-controlled receiving volume control is provided, or, if it is provided, at the setting of the user-controlled receiving volume control at which the RLR is equal to the nominal value, the noise measured at the ear reference point (ERP) contributed by the receiving equipment alone shall not exceed -57 dBPa(A).

Where a volume control is provided, the measured noise shall also not exceed -54 dBPa(A) at the maximum setting of the volume control.

NOTE: In a connection with the PSTN, noise conditions as described in ITU-T Recommendation G.103 can be expected at the input (POI) of the 3G network. The characteristics of this noise may be influenced by the speech transcoding process (for further study).

Compliance shall be checked by the relevant test described in TS 26.132.

6.4 Sensitivity/frequency characteristics

6.4.1 Handset and headset UE sending

The sensitivity/frequency characteristics shall be as follows:

The sending sensitivity frequency response, measured either from the mouth reference point (MRP) to digital interface or from the MRP to the SS audio output (digital output of the reference speech decoder of the SS), shall be within a mask, which can be drawn between the points given in table 9. The mask is drawn with straight lines between the breaking points in table 1 on a logarithmic (frequency) - linear (dB sensitivity) scale.

Table 9: Sending sensitivity/frequency mask

Frequency (Hz)	Upper limit	Lower limit
100	-12	-
200	0	-
300	0	-12
1 000	0	-6
2 000	4	-6
5000	4	-6
6300	4	-9
8000	0	-

NOTE: All sensitivity values are expressed in dB on an arbitrary scale.

Compliance shall be checked by the relevant test described in TS 26.132.

6.4.2 Handset and headset UE receiving

The sensitivity/frequency characteristics shall be as follows:

The receiving sensitivity frequency response, measured either from the digital interface to the ERP or from the SS audio input (analogue or digital input of the reference speech encoder of the SS) to the ERP, shall be within a mask, which can be drawn with straight lines between the breaking points in table 10 on a logarithmic (frequency) - linear (dB sensitivity) scale.

Table 10: Receiving sensitivity/frequency mask

Frequency (Hz)	Upper limit	Lower limit
70	-10	-
200	2	-
300	2	-9
500	2	(see note 2)
1 000	2	-7
3 000	2	(see note 2)
3 400	2	(see note 2)
6300	2	-14
8000	2	-

NOTE 1: All sensitivity values are expressed in dB on an arbitrary scale.

NOTE 2: The limit at intermediate frequencies lies on a straight line drawn between the given values on a log (frequency) - linear (dB) scale.

Compliance shall be checked by the relevant test described in TS 26.132.

6.4.3 Desktop and Vehicle-mounted hands-free UE sending

The sending sensitivity frequency response from the MRP to the SS audio output (digital output of the reference speech decoder of the SS) shall be as follows:

The sending sensitivity frequency response shall be within the mask which can be drawn with straight lines between the breaking points in table 11 on a logarithmic (frequency) - linear (dB sensitivity) scale.

Table 11: Desktop and Vehicle-mounted hands-free sending sensitivity/frequency response

Frequency (Hz)	Upper limit	Lower limit
100	-12	-
200	0	-
315	0	-14
400	0	-13
500	0	-12
630	0	-11
800	0	-10
1 000	0	-8
1 300	2	-8
1 600	3	-8
2 000	4	-8
2 500	4	-8
6 300	4	-8
8 000	0	-

NOTE: All sensitivity values are expressed in dB on an arbitrary scale.

Compliance shall be checked by the relevant test described in TS 26.132.

6.4.4 Desktop and Vehicle-mounted hands-free UE receiving

The receiving sensitivity frequency response from the SS audio input (analogue or digital input of the reference speech encoder of the SS) to the ERP shall be as follows:

The receiving sensitivity frequency response shall be within the mask which can be drawn with straight lines between the breaking points in table 12 on a logarithmic (frequency) - linear (dB sensitivity) scale.

Table 12: Hands-free receiving sensitivity/frequency response

Frequency (Hz)	Upper limit	Lower limit
200	0	
315	0	-15
400	0	-12
500	0	-12
630	0	-12
800	0	-12
1 000	0	-12
1 300	0	-12
1 600	0	-12
2 000	0	-12
2 500	0	-12
6 300	0	-12
8 000	0	

NOTE: All sensitivity values are expressed in dB on an arbitrary scale.

Compliance shall be checked by the relevant test described in TS 26.132.

6.4.5 Handheld hands-free UE sending

The sending sensitivity frequency response from the MRP to the SS audio output (digital output of the reference speech decoder of the SS) shall be as follows:

The sending sensitivity frequency response shall be within the mask which can be drawn with straight lines between the breaking points in table 13 on a logarithmic (frequency) - linear (dB sensitivity) scale.

Table 13: Handheld hands-free sending sensitivity/frequency response

Frequency (Hz)	Upper limit	Lower limit
100	-12	
200	0	
250	0	
315	0	-14
400	0	-13
500	0	-12
630	0	-11
800	0	-10
1 000	0	-8
1 300	2	-8
1 600	3	-8
2 000	4	-8
2 500	4	-8
6 300	4	-8
8 000	0	

NOTE: All sensitivity values are expressed in dB on an arbitrary scale.

Compliance shall be checked by the relevant test described in TS 26.132.

6.4.6 Handheld hands-free UE receiving

The receiving sensitivity frequency response from the SS audio input (analogue or digital input of the reference speech encoder of the SS) to the ERP shall be as follows:

The receiving sensitivity frequency response shall be within the mask which can be drawn with straight lines between the breaking points in table 14 on a logarithmic (frequency) - linear (dB sensitivity) scale.

Table 14: Hands-free receiving sensitivity/frequency response

Frequency (Hz)	Upper limit	Lower limit
200	0	
250	0	
315	0	
400	0	
500	0	
630	0	
800	0	-12
1 000	0	-12
1 300	0	-12
1 600	0	-12
2 000	0	-12
2 500	0	-12
6 300	0	-12
8 000	0	

NOTE: All sensitivity values are expressed in dB on an arbitrary scale.

Compliance shall be checked by the relevant test described in TS 26.132.

6.5 Sidetone characteristics (handset and headset UE)

6.5.1 Sidetone loss

The talker sidetone masking rating (STMR) shall be 18dB \pm 5. Compliance shall be checked by the relevant test described in TS 26.132

6.6 Stability loss

The stability loss presented to the PSTN by the 3G network at the POI should meet the principles of the requirements in clauses 2 and 3 of ITU-T Recommendation G.122. These requirements will be met if the attenuation between the digital input and digital output at the POI is at least 6 dB at all frequencies in the range 100 Hz to 8 kHz under the worst case acoustic conditions at the UE (any acoustic echo control should be enabled). For the normal case of digital connection between the Air Interface and the POI, the stability requirement can be applied at the Air Interface.

The worst case acoustic conditions will be as follows (with any volume control set to maximum):

Handset UE: the handset lying on, and the transducers facing, a hard surface with the ear-piece uncapped.

Handset UE: for further study

Handsfree UE: no requirement other than echo loss.

NOTE: The test procedure must take into account the switching effects of echo control and discontinuous transmission (DTX).

6.7 Acoustic echo control

6.7.1 General

The echo loss (EL) presented by the 3G network at the POI should be at least 46 dB during single talk. This value takes into account the fact that UE is likely to be used in a wide range of noise environments.

The use of acoustic echo control is not mandated for 3G networks and the connection between the UE and the POI is zero loss. Therefore the acoustic echo control provided in UE should provide a TCLw of at least 46 dB at the POI over the likely range of acoustic end delays.

If acoustic echo control is provided by voice switching, comfort noise should be injected. This comfort noise shall operate in the same way to that used in DTX.

6.7.2 Acoustic echo control in an Desktop and Vehicle-mounted hands-free UE

The TCLw for the handsfree UE shall be 40 dB at the nominal setting of the volume control in quiet background conditions and 33 dB at the maximum user selectable volume control setting. If acoustic echo control is provided using some form of echo cancellation technique, the cancellation algorithm should be designed to cope with the expected reverberation and dispersion. In the case of the hands-free UE, this reverberation and dispersion may be time variant. Compliance with this requirement shall be checked by the relevant test described in TS 26.132.

6.7.3 Acoustic echo control in an handheld hands-free UE

The TCLw for the hands-free UE shall be 40 dB at the nominal setting of the volume control in quiet background conditions and 33 dB at the maximum user selectable volume control setting. If acoustic echo control is provided using some form of echo cancellation technique, the cancellation algorithm should be designed to cope with the expected reverberation and dispersion. In the case of the hands-free UE, this reverberation and dispersion may be time variant. Compliance with this requirement shall be checked by the relevant test described in TS 26.132.

6.7.4 Acoustic echo control in a handset UE

The TCLw for the handset UE shall be 46 dB. Careful acoustic design of the handset body and selection of the mouth and ear piece transducers may facilitate the required acoustic echo loss without the need for active echo control techniques. However, should echo cancellation be employed the echo canceller should be capable of dealing with the variations in handset positions when in normal use. The implications of this are under study. Compliance with this requirement shall be checked by the relevant test described in TS 26.132.

6.7.5 Acoustic echo control in a headset UE

The TCLw for a headset UE shall be 46 dB. Due to the obstacle effect of the head in this type of terminal, careful design might mean that no active echo control is necessary.

6.8 Distortion

6.8.1 Sending Distortion

The sending part shall meet the following distortion requirements:

NOTE: Digital signal processing other than the transcoder itself is included in this requirement (e.g. echo cancelling).

Distortion shall be measured between MRP and the SS audio output (output of the reference speech decoder of the SS). The ratio of signal-to-total distortion power measured with the proper noise weighting (see table 3 of ITU-T Recommendation G.223) shall be above the limits given in table 15 unless the sound pressure at MRP exceeds +10 dBPa.

Table 15: Limits for signal-to-total distortion ratio

Sending level dB relative to ARL	Sending Ratio (dB)
-35	17,5
-30	22,5
-20	30,7
-10	33,3
0	33,7
+7	31,7
+10	25,5

Limits for intermediate levels are found by drawing straight lines between the breaking points in the table on a linear (dB signal level) - linear (dB ratio) scale.

Compliance of the sending distortion shall be checked by the test described in TS 26.132.

6.8.2 Receiving

The receiving part between the SS audio input (input of the reference speech encoder of the SS) and ERP shall meet the requirements in this clause at the nominal setting of the volume control:

The ratio of signal-to-total distortion power measured with the proper noise weighting (see table 4 of CCITT Recommendation G.223) shall be above the limits given in table 16 when the sound pressure at ERP is up to +10 dBPa. For sound pressures exceeding +10 dBPa at the ERP there is no distortion requirement.

Table 16: Limits for signal-to-total distortion ratio

Receiving level at the digital interface (dBm0)	Receiving Ratio (dB)
-45	17,5
-40	22,5
-30	30,5
-20	33,0
-10	33,5
-3	31,2
0	25,5

Limits for intermediate levels are found by drawing straight lines between the breaking points in the table on a linear (dB signal level) - linear (dB ratio) scale.

Compliance of the receiving distortion shall be checked by the appropriate method in TS 26.132.

6.9 Ambient Noise rejection

Handset and Headset UE:

The nature of mobile telephony is such that the UE will typically be operated in high ambient acoustic noise. Due to the adverse interaction of noise signals with speech codecs operating at lower rates, for example 8kbit/s or less, a minimum noise rejection specification is required.

The UE ambient noise rejection ANR, calculated as a Single Figure DELSM (SFDELSM) shall be greater than or equal to 0 dB. For good performance, it is recommended that a figure of +3 dB should be achieved.

Compliance shall be checked by the relevant test described in TS 26.132.

Hands -free UE (all categories):

For further study.

Annex A (informative): Change history

3.0.0	December 1999	Approved at TSG-SA#6 Plenary
-------	---------------	------------------------------

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2000-06	8	SP-000264	001	2	CR on Addition of a chapter pointing to ITU-T Recommendations for extended parameters	3.0.0	3.1.0
2000-06	8	SP-000264	002		CR on Listener side tone (LSTR) and talker side tone (STMR) requirements	3.0.0	3.1.0
2000-06	8	SP-000264	003	1	CR on Change of Handset and headset UE receiving sensitivity/frequency characteristic mask	3.0.0	3.1.0
2000-06	8	SP-000264	004	1	CR on Acoustic requirements for Handheld-type hands-free user equipment	3.0.0	3.1.0
2001-03	11	SP-010106	005	1	Harmonisation of narrow-band acoustic requirements between 3GPP and GSM	3.1.0	3.2.0
2001-03	11				Release 4		4.0.0
2001-03	11	SP-010106	006	3	Wideband acoustic requirements	4.0.0	5.0.0
2001-09	13	SP-010453	009		Introduction of ANR tolerance of 3 dB	5.0.0	5.1.0
2002-09	17	SP-020435	014		Correction on the ANR requirement for hands-free Ues	5.1.0	5.2.0
2004-09	25	SP-040649	022		Change of sending distortion requirement	5.2.0	6.0.0