Which Stem Carries the Era of a Song, and Can a Generator Be Steered to It?

Stem-wise probes of release decade and release market, and era-targeted accompaniment regeneration on Discogs-VI clips

James Christian* Angel Hsia† Jefferson Sy Dionisio‡

Abstract

We ask two connected questions on a subset of Discogs-VI clips: which part of a recording (vocal stem, accompaniment stem, or the mix) lets frozen audio encoders recognise the release *decade* and the release *market*, and can a generator that keeps the original vocal and melody regenerate the accompaniment in a requested decade. With linear probes, stem recombination, concept erasure and signal-level controls we find that decade information is carried by the accompaniment at least as much as by the vocal, whereas market information follows the vocal stem and is largely, but not entirely, explained by sung language. For generation we keep the original vocal, condition MusicGen-Melody on the chroma of the original mix, fine-tune a low-rank adapter on decade-labelled accompaniment and add a three-branch guidance rule that keeps the melody term and adds an era-contrast term. With codec-matched probes of two encoders, an independent third encoder, and distribution and pairing metrics, the system orders six prompted decades monotonically in expected decade and largely keeps song identity (chroma song-identification top-1 0.875 against 0.944 for neutral generations of the same adapter), while the unmodified model moves only the 1980s and 2010s. We also report where the evidence is weak: probes respond to bandwidth cues, the 1990s prompt is wording-dependent, and no listening test was run.

1 Introduction

Release decade and release market are weak, edition-level labels: in the full Discogs-VI metadata a composition has on average 2.42 distinct release countries and 1.99 distinct release decades (Sec. 3). Still, models trained on them are used as "era" or "region" detectors, and generators are asked to produce music "in the style of the 1980s". Two questions follow. (i) Which *part* of a recording, and which *cue* (sung language, genre, recording bandwidth), does a detector actually use? (ii) If a stable cue exists, can it be used to steer a cover that keeps the original melody and vocal?

*UT Austin (MS in AI)

†Graduate Institute of Communication Engineering, NTU (MS)

‡Graduate Institute of Communication Engineering, NTU (Ph.D.)

Related work is reviewed in Sec. 2. This is mainly an empirical study: the adapter and the guidance rule combine existing techniques, and we claim no new architecture.

Contributions. (1) A stem-wise analysis with causal-style interventions (stem swap, linear erasure with random-rank controls, retrained-probe cue ablations) on two tasks. (2) An era-controllable cover system built from a public generator, an adapter and a guidance rule, evaluated with codec-matched probes, an independent encoder, a zero-shot audio-language judge, distribution and pairing metrics, and content-preservation metrics. (3) Controls that show what the probes also respond to (bandwidth, spectral balance, wording), reported with the main result rather than separately.

2 Related work

Era recognition. Year prediction from audio was introduced as the showcase task of the Million Song Dataset [1]; He et al. [2] frame era recognition as classification into year ranges with supervised contrastive learning and artist information; Lee et al. [3] classify the first-entry era of US and Korean pop from audio and name as their main limitation that models cannot separate compositional style from recording technology. None of these separates stems or tests which cue a detector uses by intervention, which our analysis does; none uses release era as a control signal for generation.

Cues and confounds. Hsieh et al. [4] remix vocals with accompaniments of other songs to study confounds in singer identification; we use the same intervention. LEACE [5] gives a closed-form linear eraser, which we use with random-rank controls.

Controllable and melody-preserving generation. MusicGen-Melody [6] conditions on chroma and text, which is the mechanism we use. Music ControlNet [7], JASCO [8], ControlNet for Stable Audio Open [9] (top-k CQT melody control, motivated by the ambiguity of chroma) and MuseControlLite [10] add time-varying melody, rhythm or dynamics control, and are stronger melody-control baselines than ours; we compare only with MuseControlLite (Sec. 5). Our conditioning is full-mix chroma, which is not the vocal melody; we did not ablate richer representations.

Covers. SongEcho [11] conditions on the vocal melody and text and generates new vocals and accompaniment; Demerlé et al. [12] transfer genre style while carrying over rhythm and melody. Both target style or text control, not a release-decade axis, and we did not evaluate their systems. To our knowledge we did not find prior work that evaluates release decade as a controlled attribute of a melody-preserving cover; this is the result of a search and not a proof of absence.

Our delta. Relative to MusicGen-Melody: (i) an adapter trained on decade-labelled accompaniment; (ii) a three-branch guidance rule that keeps the melody term and adds an era-contrast term; (iii) an evaluation of decade control with nuisance controls. The probes used to evaluate are proxies for era, not human judgments.

3 Data and protocol

Clips. We use 30 s mono 24 kHz excerpts from Discogs-VI recordings [13] with artist-disjoint splits. Dataset A (decade, six classes 1960s–2010s): 1026 train, 132 validation clips with labels. Dataset B (market: US, UK, Brazil, Spain, Germany, Italy; all released in the 1980s): 798 train, 102 validation. Test labels are hidden, so all accuracies are on the validation split (chance .167). The audio is YouTube-sourced and may not be redistributed; we release code and result tables, not audio.

Stems. HT Demucs [14] separates vocals from drums+bass+other (accompaniment); BS-RoFormer is used as a second separator. Stems are loudness-normalised to −23 LUFS.

Probes. Frozen MERT-v2-30s [15] and MuQ [16] hidden states, mean-pooled over time; standardised logistic regression, layer and C chosen by cross-validation on train only, scored once on validation; 95% bootstrap intervals over clips; exact McNemar tests with Holm correction. Single-split differences below about .05 are within layer-selection noise (a 3-fold choice gives mix .523 instead of .477 on A), and intervals span about ±.09.

Label semantics. In the full Discogs-VI metadata (1.91 M versions, 348,796 cliques), 62.1% of cliques have ≥ 2 release countries and 60.0% have ≥ 2 release decades; 44.1% of 1980s versions in the six market countries sit in a clique with a 1980s version in another of the six. A release-market or release-decade label is therefore a property of an edition, not necessarily of the recording: a 1978 recording reissued in 1992 can carry a 1990s label although no acoustic property changed. We therefore speak of *release decade* and treat probe and steering results as statements about decade-correlated audio properties, not recording era. (Our clips carry no Discogs ids, so these statistics describe the full metadata, not our subset.)

Table 1: Validation accuracy of linear probes (A: n=132, B: n=102; chance .167).

Task	Encoder	Mix	Vocals	Accomp.	Recomb.
A decade	MERT	.477	.394	.485	.485
	MuQ	.477	.318	.424	–
B market	MERT	.588	.608	.422	.608
	MuQ	.471	.471	.392	–

Table 2: Interventions on what the probes use (MERT, validation).

Intervention	Result
Shuffle-and-remix: vocal of clip i + accompaniment of clip j, other label (A: 396 pairs, B: 306)	A: prediction = accompaniment label 34.8% [29.5, 39.9] vs. vocal label 16.4% [12.1, 21.0]. B: vocal label 50.0% [42.2, 58.2] vs. accompaniment label 18.3% [13.1, 23.5]. Same with BS-RoFormer.
LEACE erasure of the language subspace (B, rank 5)	mix .588 → .353, vocals .608 → .402, accomp. .422 → .314; random same-rank erasure: .591, .606, .413. A (85% English): no change.
English-sung clips only (B, pooled out-of-fold)	mix .397 (majority share .274) vs. .591 on all clips.
LEACE erasure of style PCs (Discogs-EffNet tags; k=10)	A mix .477 → .409 (random .49); B accomp. .422 → .294.

4 Which stem carries the cue

Table 1 shows the pattern: for decade the accompaniment is as informative as the mix, the vocal stem is lower; for market the vocal stem is as informative as the mix and the accompaniment is lower. After Holm correction, the significant contrasts are mix vs. vocals on A with MuQ (adjusted p=.012) and, on B with MERT, mix vs. accompaniment (.038) and vocals vs. accompaniment (.022); MERT vocals vs. accompaniment on A (p=.073 before correction) is not significant. Re-summing the separated stems reproduces the mix accuracy (.485, .608), so separation itself does not change the result. BS-RoFormer reproduces the ordering (MERT, A: vocals .386, accompaniment .515; B: .549 vs. .392), but vocal-stem probes lose .08–.13 accuracy when the separator at test time differs from the one at training time, so absolute stem accuracies depend on the separator. Richer probes (MLP, SVM, layer concatenation, stem or encoder fusion), other pooling statistics, a layer-weighted sum, and five encoders (MERT, MuQ, Whisper, AST, CLAP) do not change the ordering; MERT is best or tied on every condition. Accuracy has not saturated with training size for A.

Table 2 separates cues. Swapping stems shows that the *decade* label follows the accompaniment and the *market* label follows the vocal (cluster bootstrap over

vocal clips). Erasing the linear subspace of Whisper-LID language [17] groups, with a same-rank random control [5], removes most of the market accuracy while random erasure costs nothing; the result is unchanged when the language groups come from Whisper-large-v3 instead of Whisper-small (.382, .392, .314). Language labels are a proxy (no ground truth exists for these clips; the two LID models agree on 87.6% of B clips after grouping). For decade, erasing style directions lowers accuracy more than random erasure, so part of the decade signal is entangled with genre/style, but accuracy stays far above chance. Retrained-probe cue ablations indicate that decade information in the accompaniment survives band-limiting, compression, noise and segment shuffling at .36–.49 and loses most from removing content below 500 Hz (.485 → .364, p=.007), while market information in the vocal stem is unchanged by band-limiting and compression and falls only under time reversal (.608 → .480, p=.029), the pattern expected from phonetic content. Erasure bounds linear reliance from above; it does not prove that the remainder is musical [5].

Language held fixed. Restricting dataset B to English-sung clips (n=489; pooled train and validation, five-fold out-of-fold, not artist-grouped) leaves a market signal that is much smaller than with all languages: five-way without Brazil reaches .398 [.360, .437] (majority .281; balanced accuracy .349, macro-F1 .351), and US vs. UK (n=266) reaches .713 [.665, .762] with mix, .642 with vocals and .673 with accompaniment (chance .500). Once language is fixed, the accompaniment carries about as much as the vocal. Without artist ids these pooled values may include artist leakage and are likely optimistic.

Genre held out. Clustering the pooled dataset-A clips into six style clusters (Discogs-EffNet embedding) and training the decade probe on five clusters to predict the sixth gives .430 [.402, .459] (mean error 0.90 decades) for the mix versus .472 for ordinary out-of-fold prediction, and .436 vs. .467 for the accompaniment: decade information is not only within-genre, but the cluster split is a proxy for genre and is not artist-grouped.

5 Era-targeted cover generation

System. For each of 24 validation songs of dataset A we keep the original vocal stem and regenerate the accompaniment with MusicGen-Melody 1.5B [6] (text prompt for the era, chroma of the original mix), then remix at the original accompaniment level. A LoRA adapter [18] (r=16 on decoder attention, 3000 steps, batch 8, lr 10^{-4}, 10% neutral-prompt dropout) is trained on the accompaniment stems of the 1026 training clips with the clip's decade prompt as text. At inference we use three branches per codebook, with log-softmaxed logits

$$\ell = \ell_{\text{null}} + g_m(\ell_{\text{neut}} - \ell_{\text{null}}) + g_e(\ell_{\text{era}} - \ell_{\text{neut}}),$$

Table 3: ΔP (MERT / MuQ) for the 1960s, 1980s and 2010s prompts; song-identification top-1 (neutral LoRA generations: .944). 24 songs × 3 seeds. The LoRA row is the mean over three adapter training seeds. Intervals include 0 only for the base 1960s cells; the three-branch rows are positive in 20–24 of 24 songs ($p < .001$) at g_e=7, 10.

System	1960s	1980s	2010s	top-1
Base, std. guidance	−.001/+.006	+.593/+.414	+.328/+.094	.892
LoRA (3 train seeds)	+.392/+.255	+.253/+.207	+.120/+.077	.86–.88
+3-branch g_e=7	+.618/+.478	+.517/+.351	+.353/+.286	.875
+3-branch g_e=10	+.698/+.588	+.648/+.475	+.424/+.370	.875
+3-branch g_e=20	+.759/+.761	+.826/+.637	+.649/+.650	.840

where "neut" is the neutral prompt with chroma, "era" the era prompt with chroma, g_m=3 the standard melody-guidance scale [19] and g_e the era scale; g_e=g_m recovers standard guidance. Keeping the melody term at g_m=3 preserves song identity; contrast-only variants (negative-prompt, delta guidance) lower song-identification top-1 to .67–.68 (vs. .875).

Evaluation. Each song, prompt and generation seed gives one clip (24 songs × 3 seeds). *Era score:* decade probes (MERT layer 22, MuQ layer 9) trained on real accompaniment stems after an EnCodec [20] round trip ("codec-matched"), because probes trained on original stems barely register generated audio. The statistic is $\Delta P = P(\text{target decade} \mid \text{era prompt}) - P(\text{target decade} \mid \text{neutral prompt})$ per song, with 95% song-bootstrap intervals; E is the mean expected decade index (0 = 1960s). *Independent evaluators:* a Discogs-EffNet decade probe (own training, validation accuracy .523), zero-shot CLAP [21], and an audio-language judge [22]. *Identity:* chroma song-identification top-1 among the 24 originals (chance .042), chord agreement, tempo difference, and Discogs-VINet. *Quality and distribution:* Audiobox Aesthetics [23], a KAD-style MMD margin [24] (own implementation), FD-VGG against 171 real train clips of the prompted decade, and per-clip KL-PaSST to the original clip. COCOLA [25] measures vocal–accompaniment fit.

Main result. Table 3 shows that the unmodified model follows the 1980s prompt strongly and the 2010s prompt moderately but does not follow the 1960s prompt. The adapter makes the 1960s prompt-able; the three-branch rule adds to every decade and both encoders, and for the 1960s, 1970s, 1980s, 1990s and 2010s the gain keeps growing with g_e up to 20 (the MERT 1960s value plateaus between 15 and 20). The gain over the adapter alone replicates on two further adapter training seeds at g_e=7 and 10 (e.g. MERT 1960s: seed 1 +.658 and +.709, seed 2 +.601 and +.661). Across training seeds the adapter alone has MERT standard deviations of .024 (1960s), .015 (1980s) and .052 (2010s), so the 2010s effect is the least reproducible.

Six decades. Table 4 and Fig. 1 extend the prompts to the 1970s, 1990s and 2000s. With the adapter, E increases monotonically with the prompted decade in both encoders and in the independent EffNet




Figure 1: Expected probe decade per prompted decade (11 configurations: base, LoRA at $g_e \in \{7, 10, 15, 20\}$, and seed adapters as thin dashed lines).

Table 4: Six prompted decades, +3-branch g_e=10: ΔP and expected decade E (neutral E: MERT 3.05, MuQ 2.94). Base model g_e=7 in the last row.

		60s	70s	80s	90s	00s	10s
MERT	ΔP	.70	.60	.65	.26	.26	.42
	E	0.26	1.15	2.25	3.31	4.05	4.49
MuQ	ΔP	.59	.56	.48	.18	.32	.37
	E	0.65	1.43	2.38	3.08	3.91	4.30
EffNet	ΔP	.54	.28	.42	.26	.09	.18
	E	0.74	1.79	2.46	2.90	3.33	3.73
Base MERT	E	2.80	4.46	2.47	3.50	4.12	4.62

probe, and every ΔP interval excludes 0 in all configurations. The base model does not: its 1970s prompt gives E=4.46 and a negative ΔP ($-.036$, interval excludes 0). The 1990s prompt is the weakest (MERT top-1 target share .46 at g_e=10, .58 at 15 and 20). For the 2000s prompt the primary adapter's ΔP falls from +.257 (g_e=10) to +.181 (20) while E drifts toward the 2010s (4.05 → 4.19); the two seed adapters do not show this (+.335/+.362 at 10, +.377/+.347 at 20), and a pop-punk wording of the 2000s prompt keeps its effect from g_e=10 to 15 (MERT +.240 at both), so the decline is specific to an adapter and a wording. Wording matters strongly for the 1990s: a grunge wording gives MERT ΔP=+.098 and E=3.86, a eurodance wording +.413 at g_e=15, and no wording beats the default prompt in both encoders.

Content and quality. Song-identification top-1 stays .84–.88 for the main decades at g_e=7–20 (.944 neutral), chord agreement .33–.36 (rotation floor .02). For the extra decades it falls with g_e (1970s .833 at 10, .764 at 20) and chord agreement drops to .317–.337. Audiobox production quality does not drop (3-branch: 7.50–7.52 vs. 7.31 neutral); the 2000s prompt loses 0.27 PQ only at g_e=20. KAD-style margins rise with g_e (same encoder family as the probe, so not independent). FD-VGG against real clips of the prompted decade is lower than neutral for the 1980s and 2010s in both seed adapters at g_e=7 and 10 (interval excludes 0 in 7 of 8 cells; 2010s: -1.9 to -2.1) but not for the 1960s; for $g_e \geq 15$ the 2010s gain stays significant and the 1980s gain no longer is, and 72 clips per cell keep intervals wide ($\approx \pm 1$). For the seed adapters at every guidance level and all six decades, the mean KL-PaSST to the original clip is lower than neutral (-0.18 to -0.42) and the mean CLAP text score higher (+.04 to +.26), i.e. era-prompted clips remain classified like their originals (not so for every base-model cell, e.g. 2010s KL +.025). We therefore recommend g_e=7–10, where the probes, FD, quality and identity agree (interpretation).

Other generators. MuseControlLite (Stable Audio Open with melody adapter) preserves the melody more strictly (top-1 1.000) but the same prompts barely move the probes (MERT 2010s +.171, others $\leq$ +.015); ACE-Step 1.5 in cover mode moves the 1960s and 1980s probes (+.05–+.08, +.13–+.22 in MERT) but keeps much less of the song (top-1 .27–.35 at every strength). Text-only MusicGen keeps .188 song-identification, showing that the chroma condition, not the kept vocal, preserves identity.

6 What else moves the probes

Probe training set. Training on original stems, codec-resynthesised stems, their union, and double-codec stems gives the same sign and similar size for 1980s and 2010s (differences $\leq$ .09 for double-codec); a probe trained only on original stems barely registers the generated 1980s (MERT +.01 to +.23 vs. +.25 to +.83 codec-matched), which is why we use codec-matched probes.

Bandwidth. Band-limiting the real accompaniment moves the probes toward earlier decades (MuQ $-.61$, MERT $-.30$ expected decades) and so does added hiss; soft clipping, limiting and a high shelf do not. Era prompts change high-frequency content in every system (+4 to +12 dB above 7 kHz for the 1980s prompt), with weak-to-moderate correlation between spectral change and probe change (Spearman up to .44). Matching each era clip's long-term spectrum to its neutral clip leaves MERT 1980s and 2010s ef-

Table 5: MERT ΔP (1960s / 1980s / 2010s) before and after erasing style and bandwidth nuisance directions (rank 19).

System	No erasure	Erased
Base, std. guidance	−.001 / +.593 / +.328	+.069 / +.608 / −.020
LoRA alone	+.396 / +.246 / +.171	+.179 / +.165 / +.050
+3-branch g_e=10	+.698 / +.648 / +.424	+.489 / +.503 / +.249
+3-branch g_e=20	+.759 / +.826 / +.649	+.613 / +.747 / +.476

fects positive (three-branch g_e=10: +.648 → +.553, +.424 → +.406) and the 1960s effect unchanged; the MuQ 2010s effect halves (+.370 → +.187) and the base-model MuQ 2010s effect disappears (+.094 → −.044, interval includes 0). Finally, prompts that name no decade but only bandwidth change the expected decade of the same generator: "dull, band-limited, tape hiss" shifts it by −1.34 (MERT) and −0.98 (MuQ) at g_e=10 (the 1960s prompt shifts it by −2.79 and −2.29), and "bright, full-bandwidth" by +0.42 and +0.97. Part of the era effect is thus carried by bandwidth; the spectrum-matching control shows it is not all of it. A hard decoder-level bandwidth constraint was not run.

Nuisance removal. We fit a LEACE eraser on the training embeddings of codec-resynthesised accompaniment for two nuisance concepts, ten principal components of Discogs-EffNet style tags of the original mix (genre proxy) and nine signal statistics of the accompaniment stem (bandwidth and noise-floor proxy), retrain the era probe on the erased features, and apply the same eraser to the generated clips. Table 5 shows that every adapter-plus-guidance effect stays positive with intervals excluding 0 in both encoders, at g_e=7, 10, 20 and for both seed adapters, but shrinks by .07 to .27; a random projection of the same rank changes nothing (within .004). The base model's 2010s effect disappears (MERT +.328 → −.020, MuQ +.094 → +.010) while its 1980s effect does not (+.593 → +.608), so the base 2010s effect is carried by these nuisance directions and its 1980s effect is not. The erased probes are weaker on real audio (MuQ accuracy .432 → .295), so some shrinkage may reflect a weaker probe, and erasure also moves the neutral reference.

Evaluator disagreement. The zero-shot audio-language judge is weak on real clips (exact-decade accuracy near chance, Spearman .45–.67 with the true decade); it confirms the 1980s effect of the base model but not the adapter's 1980s and 2010s effects. CLAP and the probes agree on the sign of 2010s shifts for guidance variants but disagree for the 1960s of some adapters. We treat the probes as proxies, not as measures of perceived era.

7 Limitations

Release decade is not recording era (reissues, Sec. 3); we could not recover Discogs ids for our clips, so splits are artist-disjoint but not guaranteed clique-disjoint (covers or reissues of one composition could cross partitions) and no clean original-release subset could be built. 24 validation songs, 3 seeds, one validation split per task whose results also guided choices such as layer and guidance scale, no artist ids (so no artist-grouped intervals; pooled out-of-fold analyses are not artist-disjoint), hidden test labels. Language and genre are proxies (Whisper LID, Discogs-EffNet tags). Probe-based era scores are proxies trained on the same real clips whose labels they predict; each conclusion is reported with at least two encoders and a third family where possible. One generator family carries the main result and the only external baselines are MuseControlLite and ACE-Step, not the stronger controllers above; the melody condition is full-mix chroma; the learned adapter is generic (decade-labelled), and the nuisance-erasure analysis is a diagnostic: the discovered cues are not used to steer generation; a single training recipe has three adapter seeds, and several comparisons are single runs. The wording of the 1990s and 2000s prompts changes results. No listening test has been run, so we make no claim about perceived era or audio quality beyond automatic metrics.

8 Conclusion

Release decade is mostly read from the accompaniment and release market from the vocal, largely through sung language (a smaller signal remains for English-sung clips); both are properties of editions, and part of the decade signal travels with genre and recording bandwidth. A melody-preserving cover can be pushed along the decade axis by an adapter plus a melody-preserving era-contrast guidance rule, with probe-measured effects that replicate across adapter seeds and encoders and no measured loss of song identity at moderate guidance, but the effect partly rides on bandwidth cues and is wording-dependent for the 1990s and 2000s.

Reproducibility. Code, every result file and a worklog with each run's configuration are in https://github.com/goog-msft-fb-nflx-nvda-aapl/musicgen-steering-eval (folder `topics/era_market_cover`); `src/99_make_all_tables.sh` regenerates all tables from stored results and was run from a fresh clone with identical output. Generated audio, embeddings and the source clips are not in the repository.

References

[1] Thierry Bertin-Mahieux, Daniel P. W. Ellis, Brian Whitman, and Paul Lamere. The million song dataset. In *ISMIR*, 2011.

[2] Qiqi He, Xuchen Song, Weituo Hao, Ju-Chiang Wang, Wei-Tsung Lu, and Wei Li. Music era

recognition using supervised contrastive learning and artist information. *arXiv preprint arXiv:2407.05368*, 2024.

[3] Lee, Lee, Ju, Kim, Lee, and Jeong. Measuring cross-cultural style diffusion through era classification: US and Korean popular music. *arXiv preprint arXiv:2608.10980*, 2026. ISMIR 2026.

[4] Hsieh, Cheng, Fan, Yang, and Yang. Addressing the confounds of accompaniments in singer identification. *arXiv preprint arXiv:2002.06817*, 2020.

[5] Belrose et al. LEACE: Perfect linear concept erasure in closed form. *arXiv preprint arXiv:2306.03819*, 2023.

[6] Jade Copet, Felix Kreuk, Itai Gat, Tal Remez, David Kant, Gabriel Synnaeve, Yossi Adi, and Alexandre Défossez. Simple and controllable music generation. In *NeurIPS*, 2023.

[7] Shih-Lun Wu, Chris Donahue, Shinji Watanabe, and Nicholas J. Bryan. Music ControlNet: Multiple time-varying controls for music generation. *arXiv preprint arXiv:2311.07069*, 2023.

[8] Or Tal, Alon Ziv, Itai Gat, Felix Kreuk, and Yossi Adi. Joint audio and symbolic conditioning for temporally controlled text-to-music generation. In *ISMIR*, 2024. arXiv:2406.10970.

[9] Hou et al. Editing music with melody and text: Using ControlNet for diffusion transformer. *arXiv preprint arXiv:2410.05151*, 2024.

[10] Fang-Duo Tsai et al. MuseControlLite: Multifunctional music generation with lightweight conditioners. In *ICML*, 2025. arXiv:2506.18729.

[11] SongEcho authors. SongEcho. *arXiv preprint arXiv:2602.19976*, 2026. ICLR 2026; title and authors not re-checked.

[12] Demerlé, Esling, Doras, and Genova. Combining audio control and style transfer using latent diffusion. *arXiv preprint arXiv:2408.00196*, 2024. ISMIR 2024.

[13] Recep Oguz Araz, Xavier Serra, and Dmitry Bogdanov. Discogs-VI: A musical version identification dataset based on public editorial metadata. *arXiv preprint arXiv:2410.17400*, 2024. ISMIR 2024.

[14] Simon Rouard, Francisco Massa, and Alexandre Défossez. Hybrid transformers for music source separation. *arXiv preprint arXiv:2211.08553*, 2022.

[15] Yizhi Li, Ruibin Yuan, Ge Zhang, et al. MERT: Acoustic music understanding model with large-scale self-supervised training. *arXiv preprint arXiv:2306.00107*, 2023. ICLR 2024.

[16] Haina Zhu, Yizhi Zhou, Hangting Chen, Jianwei Yu, Ziyang Ma, Rongzhi Gu, Yi Luo, Wei Tan, and Xie Chen. MuQ: Self-supervised music representation learning with mel residual vector quantization. *arXiv preprint arXiv:2501.01108*, 2025.

[17] Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. Robust speech recognition via large-scale weak supervision. *arXiv preprint arXiv:2212.04356*, 2022.

[18] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021.

[19] Jonathan Ho and Tim Salimans. Classifier-free diffusion guidance. *arXiv preprint arXiv:2207.12598*, 2022.

[20] Alexandre Défossez, Jade Copet, Gabriel Synnaeve, and Yossi Adi. High fidelity neural audio compression. *arXiv preprint arXiv:2210.13438*, 2022.

[21] Yusong Wu, Ke Chen, Tianyu Zhang, Yuchen Hui, Marianna Nezhurina, Taylor Berg-Kirkpatrick, and Shlomo Dubnov. Large-scale contrastive language-audio pretraining with feature fusion and keyword-to-caption augmentation. *arXiv preprint arXiv:2211.06687*, 2022.

[22] Yunfei Chu, Jin Xu, Qian Yang, et al. Qwen2-audio technical report. *arXiv preprint arXiv:2407.10759*, 2024.

[23] Andros Tjandra et al. Meta audiobox aesthetics: Unified automatic quality assessment for speech, music, and sound. *arXiv preprint arXiv:2502.05139*, 2025.

[24] Yoonjin Chung, Pilsun Eu, Junwon Lee, Keunwoo Choi, Juhan Nam, and Ben Sangbae Chon. KAD: No more FAD! an effective and efficient evaluation metric for audio generation. *arXiv preprint arXiv:2502.15602*, 2025.

[25] Ruben Ciranni, Giorgio Mariani, Michele Mancusi, Emilian Postolache, Giorgio Fabbro, Emanuele Rodolà, and Luca Cosmo. COCOLA: Coherence-oriented contrastive learning of musical audio representations. *arXiv preprint arXiv:2404.16969*, 2024. ICASSP 2025.