gf180mcu_9T_TT_3P3_25C.ccs Library

Cell Groups
GF180MCU_OSU_SC_9T_ADDF_1
GF180MCU_OSU_SC_9T_ADDH_1
GF180MCU_OSU_SC_9T_AND2_1
GF180MCU_OSU_SC_9T_AOI21_1
GF180MCU_OSU_SC_9T_AOI22_1
GF180MCU_OSU_SC_9T_AOI31_1
GF180MCU_OSU_SC_9T_BUF_16
GF180MCU_OSU_SC_9T_BUF_1
GF180MCU_OSU_SC_9T_BUF_2
GF180MCU_OSU_SC_9T_BUF_4
GF180MCU_OSU_SC_9T_BUF_8
GF180MCU_OSU_SC_9T_CLKBUF_16
GF180MCU_OSU_SC_9T_CLKBUF_1
GF180MCU_OSU_SC_9T_CLKBUF_2
GF180MCU_OSU_SC_9T_CLKBUF_4
GF180MCU_OSU_SC_9T_CLKBUF_8
GF180MCU_OSU_SC_9T_CLKINV_16
GF180MCU_OSU_SC_9T_CLKINV_1
GF180MCU_OSU_SC_9T_CLKINV_2
GF180MCU_OSU_SC_9T_CLKINV_4
GF180MCU_OSU_SC_9T_CLKINV_8
GF180MCU_OSU_SC_9T_DFFN_1
GF180MCU_OSU_SC_9T_DFFSR_1

GF180MCU_OSU_SC_9T_DFF_1
GF180MCU_OSU_SC_9T_DLATN_1
GF180MCU_OSU_SC_9T_DLAT_1
GF180MCU_OSU_SC_9T_INV_16
GF180MCU_OSU_SC_9T_INV_1
GF180MCU_OSU_SC_9T_INV_2
GF180MCU_OSU_SC_9T_INV_4
GF180MCU_OSU_SC_9T_INV_8
GF180MCU_OSU_SC_9T_LSHIFDOWN
GF180MCU_OSU_SC_9T_LSHIFUP
GF180MCU_OSU_SC_9T_MUX2_1
GF180MCU_OSU_SC_9T_NAND2_1
GF180MCU_OSU_SC_9T_NOR2_1
GF180MCU_OSU_SC_9T_OAI21_1
GF180MCU_OSU_SC_9T_OAI22_1
GF180MCU_OSU_SC_9T_OAI31_1
GF180MCU_OSU_SC_9T_OR2_1
GF180MCU_OSU_SC_9T_TBUF_16
GF180MCU_OSU_SC_9T_TBUF_1
GF180MCU_OSU_SC_9T_TBUF_2
GF180MCU_OSU_SC_9T_TBUF_4
GF180MCU_OSU_SC_9T_TBUF_8
GF180MCU_OSU_SC_9T_TIEHI
GF180MCU_OSU_SC_9T_TIELO
GF180MCU_OSU_SC_9T_TINV_16
GF180MCU_OSU_SC_9T_TINV_1

GF180MCU_OSU_SC_9T_TINV_2
GF180MCU_OSU_SC_9T_TINV_4
GF180MCU_OSU_SC_9T_TINV_8
GF180MCU_OSU_SC_9T_XNOR2_1
GF180MCU_OSU_SC_9T_XOR2_1

GF180MCU_OSU_SC_9T_ADDF_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT			OUTPUT	
A	В	CI	CO	S
0	0	0	0	0
0	0	1	0	1
0	1	0	0	1
0	1	1	1	0
1	0	0	0	1
1	0	1	1	0
1	1	0	1	0
1	1	1	1	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_addf_1	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)			Max Cap(pf)	
Cell Name	A	В	CI	со	S
gf180mcu_osu_sc_9T_addf_1	0.01543	0.01458	0.01139	1.55550	1.54990

Coll Name		Leakage(nW)	
Cell Name	Min.	Avg	Max.
gf180mcu_osu_sc_9T_addf_1	0.00000	0.00434	0.00459

Delay Information Delay(ns) to CO rising:

Cell Name	Timing Ang(Div)	Delay(ns)		
	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_addf_1	A->CO (RR)	0.20585	0.69708	7.28378
	B->CO (RR)	0.21739	0.80653	7.77409
	CI->CO (RR)	0.19557	0.74488	7.27903

Delay(ns) to CO falling:

Cell Name	Timin Am (Din)	Delay(ns)		
	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_addf_1	A->CO (FF)	0.23716	0.87562	8.06347
	B->CO (FF)	0.22283	0.98240	8.62006
	CI->CO (FF)	0.18799	0.95206	8.30552

Delay(ns) to S rising:

Cell Name	Timing Ang(Din)	Delay(ns)		
	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_addf_1	A->S (-R)	0.41926	1.03203	8.51167
	B->S (-R)	0.40253	1.16425	9.24794
	CI->S (-R)	0.36765	1.08439	8.80527

Delay(ns) to S falling:

Call Name	Timing Ana(Din)	Delay(ns)		
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_addf_1	A->S (-F)	0.24727	1.06331	9.07279
	B->S (-F)	0.29334	1.01143	8.75645
	CI->S (-F)	0.31546	0.93878	8.32990

Internal switching power(pJ) to CO rising:

Cell Name	I	Power(pJ)			
	Input	first	mid	last	
gf180mcu_osu_sc_9T_addf_1	A	0.04887	0.07881	0.36336	
	A	0.08870	0.11843	0.40215	
	В	0.04926	0.07537	0.32982	
	В	0.08995	0.11667	0.37156	
	CI	0.03598	0.06575	0.28970	
	CI	0.07624	0.10309	0.32645	

Internal switching power(pJ) to CO falling:

Call Name	I4	Power(pJ)			
Cell Name	Input	first	mid	last	
gf180mcu_osu_sc_9T_addf_1	A	0.10044	0.13016	0.41358	
	A	0.06316	0.09294	0.37677	
	В	0.08219	0.10990	0.36674	
	В	0.04008	0.06796	0.32534	
	CI	0.07598	0.10643	0.33568	
	CI	0.04283	0.07338	0.30256	

Internal switching power(pJ) to S rising:

Call Name	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
gf180mcu_osu_sc_9T_addf_1	A	0.02661	0.06920	0.48450	
	A	0.11051	0.15362	0.56919	
	В	0.03099	0.08080	0.53364	
	В	0.11235	0.16171	0.61364	
	CI	0.04272	0.09607	0.60594	
	CI	0.11962	0.17269	0.68256	

Internal switching power(pJ) to S falling:

Call Name	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
gf180mcu_osu_sc_9T_addf_1	A	0.10615	0.15186	0.57105	
	A	0.01921	0.06505	0.48432	
	В	0.10833	0.15763	0.61211	
	В	0.03144	0.08092	0.53586	
	CI	0.11726	0.17157	0.68970	
	CI	0.05203	0.10650	0.62457	

GF180MCU_OSU_SC_9T_ADDH_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INP	UT	OUTPUT		
A	В	CO	S	
0	0	0	0	
0	1	0	1	
1	0	0	1	
1	1	1	0	

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_addh_1	0.00000

Pin Capacitance Information

Call Nama	Pin C	ap(pf)	Max Cap(pf)	
Cell Name	A	В	CO	S
gf180mcu_osu_sc_9T_addh_1	0.00767	0.00696	1.55628	1.55391

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_addh_1	0.00000	0.00347	0.00375	

Delay Information Delay(ns) to CO rising:

Call Name	Timing Ana(Div)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
000 000 111 4	A->CO (RR)	0.15467	0.64985	7.36131	
gf180mcu_osu_sc_9T_addh_1	B->CO (RR)	0.14895	0.72422	7.77768	

Delay(ns) to CO falling:

Call Name	Timing Ang(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
	A->CO (FF)	0.13279	0.75995	7.69113
gf180mcu_osu_sc_9T_addh_1	B->CO (FF)	0.12077	0.69463	7.25277

Delay(ns) to S rising (conditional):

Call Name	Timing Ang(Dir)	XX/1	Delay(ns)		
Cell Name	I Name Timing Arc(Dir) Whe	When	First	Mid	Last
gf180mcu_osu_sc_9T_addh_1	A->S (RR)	!B	0.16270	0.71195	7.61725
	A->S (FR)	В	0.23655	0.87707	8.21953
	B->S (RR)	!A	0.13015	0.60051	6.99760
	B->S (FR)	A	0.25391	0.83110	7.75742

Delay(ns) to S falling (conditional):

Call Name	Timing Ang(Din)	When	Delay(ns)			
Cell Name T	Timing Arc(Dir)	When	First	Mid	Last	
gf180mcu_osu_sc_9T_addh_1	A->S (FF)	!B	0.17120	0.73500	7.50836	
	A->S (RF)	В	0.25202	0.67477	6.32892	
	B->S (FF)	!A	0.14725	0.81531	8.02549	
	B->S (RF)	A	0.24585	0.75724	6.87189	

Internal switching power(pJ) to CO rising:

Call Name	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
gf180mcu_osu_sc_9T_addh_1	A	0.04299	0.08223	0.37997	
	A	0.06130	0.10052	0.39863	
	В	0.04770	0.08520	0.35633	
	В	0.05977	0.09719	0.36744	

Internal switching power(pJ) to CO falling:

Cell Name	T4	Power(pJ)			
	Input	first	mid	last	
gf180mcu_osu_sc_9T_addh_1	A	0.06008	0.10355	0.40474	
	A	0.04178	0.08525	0.38649	
	В	0.05943	0.09650	0.36742	
	В	0.04816	0.08534	0.35620	

Internal switching power(pJ) to S rising (conditional):

Cell Name	T4	When	Power(pJ)			
Cen Name	Input	input when	first	mid	last	
	A	В	0.06012	0.10349	0.40495	
	A	В	0.04182	0.08524	0.38660	
	A	!B	0.02997	0.09205	0.56649	
of100mon agu ga 0T addh 1	A	!B	0.08213	0.14414	0.61727	
gf180mcu_osu_sc_9T_addh_1	В	A	0.05948	0.09652	0.36619	
	В	A	0.04820	0.08530	0.35514	
	В	!A	0.02096	0.07904	0.49045	
	В	!A	0.05887	0.11686	0.52826	

Internal switching power(pJ) to S falling (conditional):

Cell Name	T4	Input When	Power(pJ)			
Ceii Name	Input		first	mid	last	
	A	В	0.04297	0.08214	0.37910	
	A	В	0.06128	0.10039	0.39736	
	A	!B	0.07202	0.13255	0.60704	
of 190 man age of oddle 1	A	!B	0.01999	0.08077	0.55544	
gf180mcu_osu_sc_9T_addh_1	В	A	0.04768	0.08502	0.35523	
	В	A	0.05975	0.09696	0.36673	
	В	!A	0.06365	0.12211	0.53310	
	В	!A	0.02516	0.08378	0.49494	

GF180MCU_OSU_SC_9T_AND2_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INP	UT	OUTPUT
A	В	Y
0	x	0
1	0	0
1	1	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_and2_1	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)		Max Cap(pf)	
Cell Name	A	В	Y	
gf180mcu_osu_sc_9T_and2_1	0.00404	0.00402	1.54145	

Call Name	Leakage(nW)				
Cell Name	Min.	Avg	Max.		
gf180mcu_osu_sc_9T_and2_1	0.00000	0.00146	0.00208		

Delay Information Delay(ns) to Y rising:

Cell Name	Timing Ana(Din)	Delay(ns)			
	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_and2_1	A->Y (RR)	0.12091	0.65220	7.57945	
	B->Y (RR)	0.12636	0.58968	7.19291	

Delay(ns) to Y falling:

Call Name	Timing Ana(Din)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_and2_1	A->Y (FF)	0.10143	0.62890	7.06634	
	B->Y (FF)	0.11392	0.70107	7.52062	

Internal switching power(pJ) to Y rising:

Cell Name	Toward	Power(pJ)			
	Input	first	mid	last	
gf180mcu_osu_sc_9T_and2_1	A	0.02791	0.10203	0.60267	
	A	0.05101	0.12515	0.62581	
	В	0.02663	0.10507	0.66141	
	В	0.05501	0.13318	0.68909	

Internal switching power(pJ) to Y falling:

Cell Name	Immud	Power(pJ)			
	Input	first	mid	last	
gf180mcu_osu_sc_9T_and2_1	A	0.04428	0.11969	0.62096	
	A	0.02100	0.09659	0.60403	
	В	0.05603	0.13811	0.69514	
	В	0.02773	0.11005	0.66733	

Passive power(pJ) for A rising (conditional):

Call Name	When		Power(pJ)	
Cell Name		first	mid	last
gf180mcu_osu_sc_9T_and2_1	(!B * !Y)	-0.01400	-0.01412	-0.01413
	(!B * !Y)	0.00187	0.00189	0.00178

Passive power(pJ) for A falling (conditional):

Call Name	Wilson	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_and2_1	(!B * !Y)	0.01420	0.01431	0.01418	
	(!B * !Y)	-0.00176	-0.00177	-0.00175	

Passive power(pJ) for B rising (conditional):

Call Name	Where	Power(pJ)			
Cell Name	When	first	mid	last	
M00	(!A * !Y)	-0.01352	-0.01360	-0.01352	
gf180mcu_osu_sc_9T_and2_1	(!A * !Y)	0.00648	0.00654	0.00646	

Passive power(pJ) for B falling (conditional):

Call Name	Wilson	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_and2_1	(!A * !Y)	0.01358	0.01367	0.01355	
	(!A * !Y)	-0.00640	-0.00652	-0.00646	

GF180MCU_OSU_SC_9T_AOI21_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

IN	INPUT		OUTPUT
A0	A1	В	Y
0	X	0	1
x	X	1	0
1	0	0	1
1	1	x	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_aoi21_1	0.00000

Pin Capacitance Information

Call Name		Pin Cap(pf)	Max Cap(pf)	
Cell Name	A0	A1	В	Y
gf180mcu_osu_sc_9T_aoi21_1	0.00395	0.00398	0.00404	0.78130

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_aoi21_1	0.00000	0.00095	0.00180	

Delay Information Delay(ns) to Y rising:

C.II V	Timin Am (Din)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_aoi21_1	A0->Y (FR)	0.12548	0.84857	8.60718	
	A1->Y (FR)	0.10104	0.81316	8.52901	
	B->Y (FR)	0.09169	1.00457	9.87220	

Delay(ns) to Y falling:

C.II V	Timin Am (Din)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_aoi21_1	A0->Y (RF)	0.09477	0.58210	6.15213	
	A1->Y (RF)	0.08832	0.72225	7.33025	
	B->Y (RF)	0.04221	0.47554	5.35620	

Internal switching power(pJ) to Y rising:

Cell Name	T4	Power(pJ)			
Ceii Name	Input	first	mid	last	
	A0	0.04812	0.08538	0.28720	
	A0	0.01017	0.04724	0.24915	
of100mon ogn av 0T opi21 1	A1	0.03578	0.07111	0.25783	
gf180mcu_osu_sc_9T_aoi21_1	A1	0.00294	0.03791	0.22455	
	В	0.02638	0.07697	0.30014	
	В	0.00387	0.05445	0.27768	

Internal switching power(pJ) to Y falling:

Cell Name	T4	Power(pJ)			
Cen Name	Input	first	mid	last	
gf180mcu_osu_sc_9T_aoi21_1	A0	0.01571	0.05307	0.23767	
	A0	0.05345	0.09097	0.27532	
	A1	0.01624	0.05172	0.21206	
	A1	0.04889	0.08447	0.24502	
	В	0.00014	0.04677	0.25198	
	В	0.02266	0.06934	0.27849	

Passive power(pJ) for A0 rising (conditional):

Cell Name	XX/b ore	Power(pJ)			
	When	first	mid	last	
	(A1 * B * !Y)	-0.01313	-0.01339	-0.01331	
	(A1 * B * !Y)	0.00659	0.00658	0.00651	
-£100 OT -: 21 1	(!A1 * B * !Y)	-0.01352	-0.01358	-0.01352	
gf180mcu_osu_sc_9T_aoi21_1	(!A1 * B * !Y)	0.00649	0.00654	0.00647	
	(!A1 * !B * Y)	-0.01351	-0.01352	-0.01352	
	(!A1 * !B * Y)	0.00649	0.00646	0.00646	

Passive power(pJ) for A0 falling (conditional):

Cell Name	XX/h o r	Power(pJ)			
	When	first	mid	last	
gf180mcu_osu_sc_9T_aoi21_1	(A1 * B * !Y)	0.01337	0.01339	0.01331	
	(A1 * B * !Y)	-0.00648	-0.00652	-0.00649	
	(!A1 * B * !Y)	0.01367	0.01367	0.01355	
	(!A1 * B * !Y)	-0.00639	-0.00652	-0.00647	
	(!A1 * !B * Y)	0.01358	0.01366	0.01355	
	(!A1 * !B * Y)	-0.00639	-0.00646	-0.00646	

Passive power(pJ) for A1 rising (conditional):

Cell Name	W/h on	Power(pJ)			
	When	first	mid	last	
gf180mcu_osu_sc_9T_aoi21_1	(B * !Y)	-0.01315	-0.01339	-0.01333	
	(B * !Y)	0.00656	0.00658	0.00651	
	(!A0 * !B * Y)	-0.01399	-0.01412	-0.01413	
	(!A0 * !B * Y)	0.00187	0.00188	0.00178	

Passive power(pJ) for A1 falling (conditional):

Call Name	W/h or	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_aoi21_1	(B * !Y)	0.01337	0.01339	0.01333	
	(B * !Y)	-0.00649	-0.00651	-0.00649	
	(!A0 * !B * Y)	0.01424	0.01430	0.01418	
	(!A0 * !B * Y)	-0.00176	-0.00177	-0.00175	

Passive power(pJ) for B rising (conditional):

Call Name	W/h ove	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_aoi21_1	(A0 * A1 * !Y)	-0.00461	-0.00456	-0.00451	
	(A0 * A1 * !Y)	0.00790	0.00786	0.00780	

Passive power(pJ) for B falling (conditional):

Call Name	Wilesan	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_aoi21_1	(A0 * A1 * !Y)	0.00495	0.00497	0.00463	
	(A0 * A1 * !Y)	-0.00734	-0.00745	-0.00779	

GF180MCU_OSU_SC_9T_AOI22_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT			OUTPUT	
A0	A1	В0	B1	Y
0	X	0	x	1
0	x	1	0	1
х	x	1	1	0
1	0	0	x	1
1	0	1	0	1
1	1	x	x	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_aoi22_1	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)				Max Cap(pf)
Cell Name	A0	A1	В0	B1	Y
gf180mcu_osu_sc_9T_aoi22_1	0.00395	0.00398	0.00404	0.00402	0.77202

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_aoi22_1	0.00000	0.00123	0.00180	

Delay Information Delay(ns) to Y rising:

Call Name	Timing Ang(Din)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_aoi22_1	A0->Y (FR)	0.17213	0.89100	8.57616	
	A1->Y (FR)	0.14831	0.85632	8.49813	
	B0->Y (FR)	0.10389	0.98572	9.65346	
	B1->Y (FR)	0.12623	1.01964	9.71440	

Delay(ns) to Y falling:

Call Name	Timing Ang(Dir)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_aoi22_1	A0->Y (RF)	0.13668	0.63055	6.18231	
	A1->Y (RF)	0.12991	0.77413	7.35755	
	B0->Y (RF)	0.06829	0.68232	7.25666	
	B1->Y (RF)	0.07320	0.54700	6.07316	

Internal switching power(pJ) to Y rising:

Cell Name	T4	Power(pJ)			
Cen Name	Input	first	mid	last	
	A0	0.05781	0.09406	0.30180	
	A0	0.01022	0.04639	0.25415	
	A1	0.04575	0.07997	0.27119	
of190man age as 0T asi22 1	A1	0.00309	0.03698	0.22854	
gf180mcu_osu_sc_9T_aoi22_1	ВО	0.02810	0.06829	0.24370	
	ВО	0.00430	0.04440	0.21941	
	B1	0.03957	0.08293	0.27062	
	B1	0.01079	0.05417	0.24150	

Internal switching power(pJ) to Y falling:

Call Name	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
	A0	0.03098	0.06975	0.27357	
	A0	0.07847	0.11725	0.32086	
	A1	0.03154	0.06898	0.24727	
of190man age as 0T asi22 1	A1	0.07376	0.11141	0.28950	
gf180mcu_osu_sc_9T_aoi22_1	В0	0.00664	0.04533	0.21440	
	В0	0.03044	0.06925	0.24098	
	B1	0.00547	0.04572	0.23691	
	B1	0.03429	0.07470	0.26575	

Passive power(pJ) for A0 rising (conditional):

C.II V	Call Name		Power(pJ)			
Cell Name	When	first	mid	last		
	(A1 * B0 * B1 * !Y)	-0.01304	-0.01331	-0.01331		
	(A1 * B0 * B1 * !Y)	0.00654	0.00658	0.00651		
	(!A1 * B0 * B1 * !Y)	-0.01354	-0.01355	-0.01352		
of 190 may any so OT asi22 1	(!A1 * B0 * B1 * !Y)	0.00649	0.00647	0.00646		
gf180mcu_osu_sc_9T_aoi22_1	(!A1 * B0 * !B1 * Y)	-0.01353	-0.01356	-0.01352		
	(!A1 * B0 * !B1 * Y)	0.00650	0.00650	0.00648		
	(!A1 * !B0 * Y)	-0.01353	-0.01356	-0.01352		
	(!A1 * !B0 * Y)	0.00650	0.00650	0.00648		

Passive power(pJ) for A0 falling (conditional):

Cell Name	When	Power(pJ)			
Cen Name	vvnen	first	mid	last	
	(A1 * B0 * B1 * !Y)	0.01333	0.01331	0.01331	
	(A1 * B0 * B1 * !Y)	-0.00648	-0.00649	-0.00649	
	(!A1 * B0 * B1 * !Y)	0.01358	0.01367	0.01355	
of180may ogy sa 0T agi22 1	(!A1 * B0 * B1 * !Y)	-0.00639	-0.00647	-0.00646	
gf180mcu_osu_sc_9T_aoi22_1	(!A1 * B0 * !B1 * Y)	0.01358	0.01366	0.01355	
	(!A1 * B0 * !B1 * Y)	-0.00641	-0.00650	-0.00647	
	(!A1 * !B0 * Y)	0.01358	0.01366	0.01355	
	(!A1 * !B0 * Y)	-0.00641	-0.00650	-0.00647	

Passive power(pJ) for A1 rising (conditional):

Call Name	W/h ore	Power(pJ)			
Cell Name	When	first	mid	last	
	(B0 * B1 * !Y)	-0.01310	-0.01337	-0.01331	
	(B0 * B1 * !Y)	0.00654	0.00658	0.00651	
26190mon ozu za 0T oci22 1	(!A0 * B0 * !B1 * Y)	-0.01410	-0.01412	-0.01413	
gf180mcu_osu_sc_9T_aoi22_1	(!A0 * B0 * !B1 * Y)	0.00190	0.00188	0.00178	
	(!A0 * !B0 * Y)	-0.01410	-0.01412	-0.01413	
	(!A0 * !B0 * Y)	0.00190	0.00188	0.00178	

Passive power(pJ) for A1 falling (conditional):

C.II N	XX/L	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_aoi22_1	(B0 * B1 * !Y)	0.01335	0.01337	0.01331	
	(B0 * B1 * !Y)	-0.00649	-0.00650	-0.00649	
	(!A0 * B0 * !B1 * Y)	0.01422	0.01430	0.01418	
	(!A0 * B0 * !B1 * Y)	-0.00175	-0.00177	-0.00175	
	(!A0 * !B0 * Y)	0.01422	0.01430	0.01418	
	(!A0 * !B0 * Y)	-0.00175	-0.00177	-0.00175	

Passive power(pJ) for B0 rising (conditional):

Call Name	W/h ove	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_aoi22_1	(A0 * A1 * !Y)	-0.00456	-0.00456	-0.00451	
	(A0 * A1 * !Y)	0.00780	0.00786	0.00780	
	(!A1 * !B1 * Y)	-0.01407	-0.01403	-0.01414	
	(!A1 * !B1 * Y)	0.00189	0.00187	0.00178	
	(!A0 * A1 * !B1 * Y)	-0.01407	-0.01403	-0.01414	
	(!A0 * A1 * !B1 * Y)	0.00189	0.00187	0.00178	

Passive power(pJ) for B0 falling (conditional):

Call Name	W/h ove	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_aoi22_1	(A0 * A1 * !Y)	0.00509	0.00511	0.00465	
	(A0 * A1 * !Y)	-0.00719	-0.00730	-0.00777	
	(!A1 * !B1 * Y)	0.01422	0.01428	0.01417	
	(!A1 * !B1 * Y)	-0.00178	-0.00177	-0.00175	
	(!A0 * A1 * !B1 * Y)	0.01421	0.01428	0.01417	
	(!A0 * A1 * !B1 * Y)	-0.00178	-0.00177	-0.00175	

Passive power(pJ) for B1 rising (conditional):

C.II N	XX/I	Power(pJ)			
Cell Name	When	first	mid	last	
	(A0 * A1 * !Y)	-0.00453	-0.00456	-0.00451	
	(A0 * A1 * !Y)	0.00782	0.00785	0.00780	
-£100 OT - 222 1	(!A1 * !B0 * Y)	-0.01351	-0.01359	-0.01352	
gf180mcu_osu_sc_9T_aoi22_1	(!A1 * !B0 * Y)	0.00645	0.00651	0.00644	
	(!A0 * A1 * !B0 * Y)	-0.01351	-0.01359	-0.01352	
	(!A0 * A1 * !B0 * Y)	0.00645	0.00651	0.00644	

Passive power(pJ) for B1 falling (conditional):

Call Name	VV/In ove	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_aoi22_1	(A0 * A1 * !Y)	0.00509	0.00510	0.00465	
	(A0 * A1 * !Y)	-0.00718	-0.00730	-0.00777	
	(!A1 * !B0 * Y)	0.01355	0.01364	0.01354	
	(!A1 * !B0 * Y)	-0.00642	-0.00651	-0.00644	
	(!A0 * A1 * !B0 * Y)	0.01355	0.01364	0.01354	
	(!A0 * A1 * !B0 * Y)	-0.00642	-0.00651	-0.00644	

GF180MCU_OSU_SC_9T_AOI31_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT				OUTPUT
A0	A1	A2	В	Y
0	x	x	0	1
x	x	x	1	0
1	0	x	0	1
1	1	0	0	1
1	1	1	x	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_aoi31_1	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)				Max Cap(pf)
Cell Name	A0	A1	A2	В	Y
gf180mcu_osu_sc_9T_aoi31_1	0.00395	0.00398	0.00395	0.00405	0.74982

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_aoi31_1	0.00000	0.00098	0.00194	

Delay Information Delay(ns) to Y rising:

Cell Name	T:: A(D:)			
	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_aoi31_1	A0->Y (FR)	0.13465	0.82305	8.22635
	A1->Y (FR)	0.10934	0.78987	8.16413
	A2->Y (FR)	0.15251	0.85519	8.29414
	B->Y (FR)	0.10807	1.01662	9.64281

Delay(ns) to Y falling:

Cell Name	Timin - A (Din)			
	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_aoi31_1	A0->Y (RF)	0.13934	0.79311	7.96315
	A1->Y (RF)	0.12166	0.89351	8.81714
	A2->Y (RF)	0.14960	0.68000	7.06367
	B->Y (RF)	0.04182	0.47221	5.22496

Internal switching power(pJ) to Y rising:

C.II N	T4		Power(pJ)		
Cell Name	Input	first	mid	last	
	A0	0.04951	0.07862	0.24580	
	A0	0.01072	0.03955	0.20679	
	A1	0.03710	0.06525	0.22237	
of100man agn as 0T as:21 1	A1	0.00327	0.03119	0.18823	
gf180mcu_osu_sc_9T_aoi31_1	A2	0.06127	0.09203	0.27109	
	A2	0.01757	0.04813	0.22732	
	В	0.02646	0.08031	0.32062	
	В	0.00400	0.05747	0.29742	

Internal switching power(pJ) to Y falling:

Call Name	T4		Power(pJ)	ower(pJ)		
Cell Name	Input	first	mid	last		
	A0	0.02082	0.05091	0.20281		
	A0	0.05953	0.08978	0.24203		
	A1	0.02138	0.05084	0.19068		
of100mon ogn av 0T oci21 1	A1	0.05494	0.08446	0.22443		
gf180mcu_osu_sc_9T_aoi31_1	A2	0.02073	0.05400	0.23770		
	A2	0.06436	0.09780	0.28142		
	В	-0.00007	0.04923	0.27075		
	В	0.02244	0.07186	0.29658		

Passive power(pJ) for A0 rising (conditional):

Cell Name	W/le ove	Power(pJ)		
Cell Name	When	first	mid	last
	(A1 * B * !Y)	-0.01307	-0.01337	-0.01330
	(A1 * B * !Y)	0.00656	0.00658	0.00651
	(A1 * !A2 * !B * Y) + (!A1 * !B * Y)	-0.01359	-0.01360	-0.01350
gf180mcu_osu_sc_9T_aoi31_1	(A1 * !A2 * !B * Y) + (!A1 * !B * Y)	0.00238	0.00237	0.00235
	(!A1 * B * !Y)	-0.01352	-0.01353	-0.01352
	(!A1 * B * !Y)	0.00645	0.00648	0.00644

Passive power(pJ) for A0 falling (conditional):

Call Name	XX/In our)	
Cell Name When		first	mid	last
	(A1 * B * !Y)	0.01331	0.01337	0.01330
	(A1 * B * !Y)	-0.00649	-0.00651	-0.00649
	(A1 * !A2 * !B * Y) + (!A1 * !B * Y)	0.01373	0.01378	0.01359
gf180mcu_osu_sc_9T_aoi31_1	(A1 * !A2 * !B * Y) + (!A1 * !B * Y)	-0.00223	-0.00225	-0.00229
	(!A1 * B * !Y)	0.01352	0.01353	0.01355
	(!A1 * B * !Y)	-0.00636	-0.00645	-0.00644

Passive power(pJ) for A1 rising (conditional):

Call Massa	XX /I ₂			
Cell Name	When	first	mid	last
	(A0 * B * !Y)	-0.01304	-0.01338	-0.01330
	(A0 * B * !Y)	0.00652	0.00658	0.00651
	(A0 * !A2 * !B * Y)	-0.01393	-0.01397	-0.01411
af190may agy ag 0T agi21 1	(A0 * !A2 * !B * Y)	0.00198	0.00196	0.00175
gf180mcu_osu_sc_9T_aoi31_1	(!A0 * B * !Y)	-0.01355	-0.01362	-0.01352
	(!A0 * B * !Y)	0.00645	0.00650	0.00644
	(!A0 * !B * Y)	-0.01409	-0.01412	-0.01413
	(!A0 * !B * Y)	0.00190	0.00188	0.00178

Passive power(pJ) for A1 falling (conditional):

Cell Name	XX/la ara			
Cen Name	When	first	mid	last
	(A0 * B * !Y)	0.01349	0.01338	0.01330
	(A0 * B * !Y)	-0.00650	-0.00652	-0.00649
	(A0 * !A2 * !B * Y)	0.01423	0.01430	0.01418
of 190 may acre so OT asi21 1	(A0 * !A2 * !B * Y)	-0.00173	-0.00174	-0.00172
gf180mcu_osu_sc_9T_aoi31_1	(!A0 * B * !Y)	0.01371	0.01369	0.01355
	(!A0 * B * !Y)	-0.00639	-0.00648	-0.00644
	(!A0 * !B * Y)	0.01423	0.01430	0.01418
	(!A0 * !B * Y)	-0.00175	-0.00177	-0.00175

Passive power(pJ) for A2 rising (conditional):

Call Name	XX/I	Power(pJ)			
Cell Name	When	first	mid	last	
	(A0 * A1 * B * !Y)	-0.01303	-0.01333	-0.01329	
	(A0 * A1 * B * !Y)	0.00654	0.00658	0.00651	
	(A0 * !A1 * B * !Y)	-0.01352	-0.01361	-0.01352	
gf180mcu_osu_sc_9T_aoi31_1	(A0 * !A1 * B * !Y)	0.00640	0.00644	0.00638	
	(A0 * !A1 * !B * Y) + (!A0 * A1 * !B * Y)	-0.01350	-0.01361	-0.01352	
	(A0 * !A1 * !B * Y) + (!A0 * A1 * !B * Y)	0.00641	0.00646	0.00640	
	(!A0 * B * !Y)	-0.01354	-0.01355	-0.01352	
	(!A0 * B * !Y)	0.00649	0.00647	0.00646	
	(!A0 * !A1 * !B * Y)	-0.01353	-0.01358	-0.01352	
	(!A0 * !A1 * !B * Y)	0.00649	0.00656	0.00648	

Passive power(pJ) for A2 falling (conditional):

Call Name	W/h ore	Power(pJ)			
Cell Name	When	first	mid	last	
	(A0 * A1 * B * !Y)	0.01331	0.01333	0.01329	
	(A0 * A1 * B * !Y)	-0.00649	-0.00650	-0.00649	
	(A0 * !A1 * B * !Y)	0.01356	0.01367	0.01355	
gf180mcu_osu_sc_9T_aoi31_1	(A0 * !A1 * B * !Y)	-0.00622	-0.00644	-0.00638	
	(A0 * !A1 * !B * Y) + (!A0 * A1 * !B * Y)	0.01372	0.01366	0.01355	
	(A0 * !A1 * !B * Y) + (!A0 * A1 * !B * Y)	-0.00623	-0.00646	-0.00640	
	(!A0 * B * !Y)	0.01358	0.01367	0.01355	
	(!A0 * B * !Y)	-0.00639	-0.00647	-0.00646	
	(!A0 * !A1 * !B * Y)	0.01354	0.01366	0.01355	
	(!A0 * !A1 * !B * Y)	-0.00640	-0.00652	-0.00647	

Passive power(pJ) for B rising (conditional):

Call Name	Wilson	Power(pJ)		
Cell Name	When	first	mid	last
gf180mcu_osu_sc_9T_aoi31_1	(A0 * A1 * A2 * !Y)	-0.00454	-0.00457	-0.00451
	(A0 * A1 * A2 * !Y)	0.00781	0.00786	0.00780

Passive power(pJ) for B falling (conditional):

Cell Name	Whore	Power(pJ)		
	When	first mid last		last
gf180mcu_osu_sc_9T_aoi31_1	(A0 * A1 * A2 * !Y)	0.00509	0.00510	0.00465
	(A0 * A1 * A2 * !Y)	-0.00719	-0.00730	-0.00777

GF180MCU_OSU_SC_9T_BUF_16

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	0
1	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_buf_16	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)	
Cell Name	A	Y	
gf180mcu_osu_sc_9T_buf_16	0.00404	24.76612	

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_buf_16	0.00000	0.01267	0.01499	

Delay Information Delay(ns) to Y rising:

Cell Name	Timing Aug(Div)		Delay(ns)	Delay(ns)	
	Timing Arc(Dir)	First	Last		
gf180mcu_osu_sc_9T_buf_16	A->Y (RR)	0.33754	0.79801	7.91918	

Delay(ns) to Y falling:

Cell Name	Timing Aug(Din)	Delay(ns)		
	Timing Arc(Dir)	First	Last	
gf180mcu_osu_sc_9T_buf_16	A->Y (FF)	0.36409	0.97238	8.58056

Internal switching power(pJ) to Y rising:

Cell Name	T4	Power(pJ)			
	Input	first mi	mid	last	
gf180mcu_osu_sc_9T_buf_16	A	0.71260	0.73169	1.14194	
	A	0.73444	0.75355	1.14522	

Internal switching power(pJ) to \boldsymbol{Y} falling:

Cell Name	T4	Power(pJ)			
	Input	first	mid	last	
gf180mcu_osu_sc_9T_buf_16	A	0.78739	0.77302	1.12733	
	A	0.76551	0.75116	1.10816	

GF180MCU_OSU_SC_9T_BUF_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	0
1	1

Footprint

Cell Name	Area	
gf180mcu_osu_sc_9T_buf_1	0.00000	

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)
Cell Name	A	Y
gf180mcu_osu_sc_9T_buf_1	0.00405	1.55566

Cell Name	Leakage(nW)		
	Min.	Avg	Max.
gf180mcu_osu_sc_9T_buf_1	0.00000	0.00149	0.00149

Call Name	Timing Aug(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_buf_1	A->Y (RR)	0.08426	0.50781	6.93348

Call Name	Timing Aug(Din)	Delay(ns)		
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_buf_1	A->Y (FF)	0.09264	0.66519	7.59185

Internal switching power(pJ) to Y rising:

Cell Name	Input -	Power(pJ)		
		first	mid	last
gf180mcu_osu_sc_9T_buf_1	A	0.02013	0.10920	0.69832
	A	0.04198	0.13108	0.72018

Call Name	Immut	Power(pJ)		
Cell Name	Input	first	mid	last
gf180mcu_osu_sc_9T_buf_1	A	0.04221	0.13434	0.72073
	A	0.02040	0.11249	0.69903

GF180MCU_OSU_SC_9T_BUF_2

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	0
1	1

Footprint

Cell Name	Area	
gf180mcu_osu_sc_9T_buf_2	0.00000	

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)	
Cell Name	A	Y	
gf180mcu_osu_sc_9T_buf_2	0.00404	3.10294	

Cell Name	Leakage(nW)		
	Min.	Avg	Max.
gf180mcu_osu_sc_9T_buf_2	0.00000	0.00224	0.00239

Call Name	Timing Aug(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_buf_2	A->Y (RR)	0.10055	0.47431	7.01509

Call Name	There's A and (Disc)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_buf_2	A->Y (FF)	0.10963	0.64043	7.67275

Internal switching power(pJ) to Y rising:

C.II N.	I4		Power(pJ)	
Cell Name	Input	first	mid	last
-6100 OT 16 2	A	0.04221	0.13201	0.71774
gf180mcu_osu_sc_9T_buf_2	A	0.06414	0.15388	0.73960

CHN	T4		Power(pJ)	
Cell Name	Input	<u> </u>	last	
of 190 men on an OT harf 2	A	0.06406	0.15612	0.73814
gf180mcu_osu_sc_9T_buf_2	A	0.04206	0.13431	0.71640

GF180MCU_OSU_SC_9T_BUF_4

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	0
1	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_buf_4	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)
Cell Name	A	Y
gf180mcu_osu_sc_9T_buf_4	0.00404	6.15334

Coll Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_buf_4	0.00000	0.00373	0.00419	

Call Name	Timing Aug(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_buf_4	A->Y (RR)	0.13464	0.50150	7.13109

Call Name	Timing Aug(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_buf_4	A->Y (FF)	0.14592	0.67397	7.79491

Internal switching power(pJ) to Y rising:

Call Name	Innut	Power(pJ)		
Cell Name	Input	first	mid	last
-6100 OT L6 4	A	0.09366	0.18701	0.76428
gf180mcu_osu_sc_9T_buf_4	A	0.11572	0.20872	0.78373

CHN	T4		Power(pJ)	
Cell Name	Input	first	mid	last
of 190 men on an OT has 4	A	0.11749	0.21027	0.78112
gf180mcu_osu_sc_9T_buf_4	A	0.09536	0.18852	0.76264

GF180MCU_OSU_SC_9T_BUF_8

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	0
1	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_buf_8	0.00000

Pin Capacitance Information

Coll Nama	Pin Cap(pf)	Max Cap(pf)
Cell Name	A	Y
gf180mcu_osu_sc_9T_buf_8	0.00404	12.28096

Call Name	Leakage(nW)		
Cell Name	Min. Avg Ma		Max.
gf180mcu_osu_sc_9T_buf_8	0.00000	0.00671	0.00779

Call Name	Timing Ang(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_buf_8	A->Y (RR)	0.20308	0.60328	7.39814

Call Name			Delay(ns)	(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_buf_8	A->Y (FF)	0.21924	0.78004	8.06740	

Internal switching power(pJ) to Y rising:

Call Name	T4		Power(pJ)	
Cell Name	Input	first	mid	last
-6100 OT L6 0	A	0.23904	0.33421	0.87603
gf180mcu_osu_sc_9T_buf_8	A	0.26101	0.35591	0.88880

Call Name			Power(pJ)	Power(pJ)	
Cell Name	Input	first	mid	last	
of 100 mon one of OT harf 0	A	0.27241	0.35418	0.87944	
gf180mcu_osu_sc_9T_buf_8	A	0.25041	0.33282	0.86069	

GF180MCU_OSU_SC_9T_CLKBUF_16

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	0
1	1

Footprint

Cell Name	Area	
gf180mcu_osu_sc_9T_clkbuf_16	0.00000	

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)	
Cell Name	A	Y	
gf180mcu_osu_sc_9T_clkbuf_16	0.00404	24.76612	

Call Name	Leakage(nW)		
Cell Name	Min.	Avg	Max.
gf180mcu_osu_sc_9T_clkbuf_16	0.00000	0.01267	0.01499

Call Name	Timing Arc(Dir)		Delay(ns)	
Cell Name		First	Mid	Last
gf180mcu_osu_sc_9T_clkbuf_16	A->Y (RR)	0.33754	0.79801	7.91918

Call Name	Timing Ang(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkbuf_16	A->Y (FF)	0.36409	0.97238	8.58056

Internal switching power(pJ) to Y rising:

Call Name	I4	Power(pJ)			
Cell Name	Input	first	mid	last	
M00 0T NV 0.46	A	0.71260	0.73169	1.14194	
gf180mcu_osu_sc_9T_clkbuf_16	A	0.73444	0.75355	1.14522	

Call Name	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
0T 11 0 16	A	0.78739	0.77302	1.12733	
gf180mcu_osu_sc_9T_clkbuf_16	A	0.76551	0.75116	1.10816	

GF180MCU_OSU_SC_9T_CLKBUF_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	0
1	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_clkbuf_1	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)
Cell Name	A	Y
gf180mcu_osu_sc_9T_clkbuf_1	0.00405	1.55566

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_clkbuf_1	0.00000	0.00149	0.00149	

Call Name	Timing Arc(Dir)		Delay(ns)	
Cell Name		First	Mid	Last
gf180mcu_osu_sc_9T_clkbuf_1	A->Y (RR)	0.08426	0.50781	6.93348

Call Name	Timing Aug(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkbuf_1	A->Y (FF)	0.09264	0.66519	7.59185

Internal switching power(pJ) to Y rising:

Call Name	T4		Power(pJ)	
Cell Name	Input	first	mid	last
	A	0.02013	0.10920	0.69832
gf180mcu_osu_sc_9T_clkbuf_1	A	0.04198	0.13108	0.72018

Internal switching power(pJ) to Y falling :

Call Name	T4		Power(pJ)	
Cell Name	Input	first	mid	last
	A	0.04221	0.13434	0.72073
gf180mcu_osu_sc_9T_clkbuf_1	A	0.02040	0.11249	0.69903

GF180MCU_OSU_SC_9T_CLKBUF_2

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	0
1	1

Footprint

Cell Name	Area	
gf180mcu_osu_sc_9T_clkbuf_2	0.00000	

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)	
Cell Name	A	Y	
gf180mcu_osu_sc_9T_clkbuf_2	0.00404	3.10294	

Cell Name	Leakage(nW)		
	Min.	Avg	Max.
gf180mcu_osu_sc_9T_clkbuf_2	0.00000	0.00224	0.00239

Cell Name Delay(ns)				
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkbuf_2	A->Y (RR)	0.10055	0.47431	7.01509

Call Name	Timing Ana(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkbuf_2	A->Y (FF)	0.10963	0.64043	7.67275

Internal switching power(pJ) to Y rising:

Cell Name	Input	Power(pJ)		
		first	mid	last
gf180mcu_osu_sc_9T_clkbuf_2	A	0.04221	0.13201	0.71774
	A	0.06414	0.15388	0.73960

Cell Name	Input	Power(pJ)		
		first	mid	last
gf180mcu_osu_sc_9T_clkbuf_2	A	0.06406	0.15612	0.73814
	A	0.04206	0.13431	0.71640

GF180MCU_OSU_SC_9T_CLKBUF_4

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	0
1	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_clkbuf_4	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)	
Cell Name	A	Y	
gf180mcu_osu_sc_9T_clkbuf_4	0.00404	6.15334	

Cell Name	Leakage(nW)		
	Min.	Avg	Max.
gf180mcu_osu_sc_9T_clkbuf_4	0.00000	0.00373	0.00419

Call Name	T:: A(D:)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkbuf_4	A->Y (RR)	0.13464	0.50150	7.13109

Call Name	Timing Ana(Div)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkbuf_4	A->Y (FF)	0.14592	0.67397	7.79491

Internal switching power(pJ) to Y rising:

Call Name	T4		Power(pJ)	
Cell Name	Input	first	mid	last
	A	0.09366	0.18701	0.76428
gf180mcu_osu_sc_9T_clkbuf_4	A	0.11572	0.20872	0.78373

Internal switching power(pJ) to Y falling :

Call Name	T4		Power(pJ)	
Cell Name	Input	first	mid	last
	A	0.11749	0.21027	0.78112
gf180mcu_osu_sc_9T_clkbuf_4	A	0.09536	0.18852	0.76264

GF180MCU_OSU_SC_9T_CLKBUF_8

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	0
1	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_clkbuf_8	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)
Cell Name	A	Y
gf180mcu_osu_sc_9T_clkbuf_8	0.00404	12.28096

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_clkbuf_8	0.00000	0.00671	0.00779	

Call Name	Timing Ang(Dir)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkbuf_8	A->Y (RR)	0.20308	0.60328	7.39814

Call Name	Timing Ama(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkbuf_8	A->Y (FF)	0.21924	0.78004	8.06740

Internal switching power(pJ) to Y rising:

Call Name	T4		Power(pJ)	
Cell Name	Input	first	mid	last
2100 OT N. A.O.	A	0.23904	0.33421	0.87603
gf180mcu_osu_sc_9T_clkbuf_8	A	0.26101	0.35591	0.88880

CHN	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
4400 OT N. 4.0	A	0.27241	0.35418	0.87944	
gf180mcu_osu_sc_9T_clkbuf_8	A	0.25041	0.33282	0.86069	

GF180MCU_OSU_SC_9T_CLKINV_16

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	1
1	0

Footprint

Cell Name	Area	
gf180mcu_osu_sc_9T_clkinv_16	0.00000	

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)	
Cell Name	A	Y	
gf180mcu_osu_sc_9T_clkinv_16	0.06466	23.87903	

Cell Name	Leakage(nW)		
	Min.	Avg	Max.
gf180mcu_osu_sc_9T_clkinv_16	0.00000	0.01192	0.01439

Call Name	Timing Aug(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkinv_16	A->Y (FR)	0.03956	0.49677	9.96266

Call Name	Timing Ang(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkinv_16	A->Y (RF)	0.03092	0.29391	8.47767

Internal switching power(pJ) to Y rising:

Call Name	Immut	Power(pJ)		
Cell Name	Input	first	mid	last
gf180mcu_osu_sc_9T_clkinv_16	A	0.35769	1.48564	4.08772
	A	0.00871	1.13458	3.73679

Internal switching power(pJ) to Y falling :

Call Name	Input	Power(pJ)		
Cell Name		first	mid	last
gf180mcu_osu_sc_9T_clkinv_16	A	0.00389	1.07024	3.39414
	A	0.35277	1.42158	3.74746

GF180MCU_OSU_SC_9T_CLKINV_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	1
1	0

Footprint

Cell Name	Area	
gf180mcu_osu_sc_9T_clkinv_1	0.00000	

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)	
Cell Name	A	Y	
gf180mcu_osu_sc_9T_clkinv_1	0.00404	1.50748	

Cell Name	Leakage(nW)		
	Min.	Avg	Max.
gf180mcu_osu_sc_9T_clkinv_1	0.00000	0.00075	0.00090

Call Name	Timing Ana(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkinv_1	A->Y (FR)	0.04498	0.84197	10.02570

Call Name	Timing Ang(Div)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkinv_1	A->Y (RF)	0.03639	0.64312	8.53517

Internal switching power(pJ) to Y rising:

Call Name	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
MO0 0T N. 1	A	0.02226	0.07404	0.25366	
gf180mcu_osu_sc_9T_clkinv_1	A	0.00038	0.05208	0.23179	

CHN	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
07. U. 1	A	-0.00053	0.04771	0.21052	
gf180mcu_osu_sc_9T_clkinv_1	A	0.02128	0.06976	0.23249	

GF180MCU_OSU_SC_9T_CLKINV_2

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	1
1	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_clkinv_2	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)
Cell Name	A	Y
gf180mcu_osu_sc_9T_clkinv_2	0.00808	2.98498

C.II N	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_clkinv_2	0.00000	0.00149	0.00180	

Call Name	Timing Ana(Div)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkinv_2	A->Y (FR)	0.04172	0.72858	9.96233

Call Name	Timing Ang(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkinv_2	A->Y (RF)	0.03307	0.52906	8.47738

Internal switching power(pJ) to Y rising:

C.II N	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
MO0 0T W	A	0.04475	0.15897	0.51097	
gf180mcu_osu_sc_9T_clkinv_2	A	0.00091	0.11480	0.46711	

CHN	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
MO0 0T 11.	A	-0.00109	0.10609	0.42288	
gf180mcu_osu_sc_9T_clkinv_2	A	0.04270	0.15004	0.46704	

GF180MCU_OSU_SC_9T_CLKINV_4

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	1
1	0

Footprint

Cell Name	Area	
gf180mcu_osu_sc_9T_clkinv_4	0.00000	

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)	
Cell Name	A	Y	
gf180mcu_osu_sc_9T_clkinv_4	0.01616	5.97048	

Cell Name	Leakage(nW)		
	Min.	Avg	Max.
gf180mcu_osu_sc_9T_clkinv_4	0.00000	0.00298	0.00360

Delay Information Delay(ns) to Y rising:

Call Name	Timing Ana(Div)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkinv_4	A->Y (FR)	0.04000	0.63574	9.96289

Delay(ns) to Y falling:

Call Name	Timing Ana(Div)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkinv_4	A->Y (RF)	0.03137	0.43650	8.47788

Power Information

Internal switching power(pJ) to Y rising:

Call Name	T4	Power(pJ)		
Cell Name	Input	first	mid	last
gf180mcu_osu_sc_9T_clkinv_4	A	0.08959	0.33578	1.02191
	A	0.00205	0.24768	0.93418

Internal switching power(pJ) to \boldsymbol{Y} falling:

Call Name	T4	Power(pJ)		
Cell Name	Input	first	mid	last
gf180mcu_osu_sc_9T_clkinv_4	A	-0.00200	0.23109	0.84572
	A	0.08550	0.31888	0.93405

GF180MCU_OSU_SC_9T_CLKINV_8

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	1
1	0

Footprint

Cell Name	Area	
gf180mcu_osu_sc_9T_clkinv_8	0.00000	

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)	
Cell Name	A	Y	
gf180mcu_osu_sc_9T_clkinv_8	0.03232	11.94140	

Cell Name	Leakage(nW)		
	Min.	Avg	Max.
gf180mcu_osu_sc_9T_clkinv_8	0.00000	0.00596	0.00720

Delay Information Delay(ns) to Y rising:

Call Name	Timing Arg(Dir)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkinv_8	A->Y (FR)	0.03912	0.55929	9.96313

Delay(ns) to Y falling:

Call Name	Timing Ang(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_clkinv_8	A->Y (RF)	0.03045	0.35837	8.47809

Power Information

Internal switching power(pJ) to Y rising:

Cell Name	T4	Power(pJ)			
	Input	first	mid	last	
gf180mcu_osu_sc_9T_clkinv_8	A	0.17894	0.70851	2.04380	
	A	0.00445	0.53241	1.86833	

Internal switching power(pJ) to \boldsymbol{Y} falling:

Cell Name	T4	Power(pJ)			
	Input	first	mid	last	
gf180mcu_osu_sc_9T_clkinv_8	A	-0.00375	0.49690	1.69140	
	A	0.17077	0.67287	1.86807	

GF180MCU_OSU_SC_9T_DFFN_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT		OUTPUT		
D	CLKN	Q	QN	
0	R	0	1	
1	R	1	0	
X	X	IQ	IQN	

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_dffn_1	0.00000

Pin Capacitance Information

Cell Name	Pin Cap(pf) Max			Cap(pf)	
	D	CLKN	Q	QN	
gf180mcu_osu_sc_9T_dffn_1	0.00393	0.01039	1.56141	1.56075	

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_dffn_1	0.00000	0.00595	0.00661	

Delay Information Delay(ns) to Q rising:

Cell Name	Timing Ana(Div)	Delay(ns)			
	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_dffn_1	CLKN->Q (RR)	0.26942	1.25620	16.48390	
	QN->Q (FR)	0.04498	0.85148	10.25460	

Delay(ns) to Q falling:

Coll Name Timing Ana(Din)		Delay(ns)		
Cell Name	Timing Arc(Dir)	First	Mid	Last
0400 OT 100 4	CLKN->Q (RF)	0.35742	1.28545	16.29670
gf180mcu_osu_sc_9T_dffn_1	QN->Q (RF)	0.03639	0.65226	8.74007

Delay(ns) to QN rising:

Call Name	Coll Name Timing Ana(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_dffn_1	CLKN->QN (RR)	0.32250	0.75813	6.99720

Delay(ns) to QN falling:

Cell Name	Timing Ang(Din)	Delay(ns)			
	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_dffn_1	CLKN->QN (RF)	0.23125	0.67320	6.16788	

Constraint Information

Constraints(ns) for D rising:

Call Name	Timing Chask	Ref Pin(trans)	Reference Slew Rate(ns)			
Cell Name	Timing Check		first	mid	last	
-6100 OT 166 1	hold	CLKN (R)	-0.10101	-0.09519	0.57241	
gf180mcu_osu_sc_9T_dffn_1	setup	CLKN (R)	0.19078	0.25850	0.88708	

Constraints(ns) for D falling:

Call Name	Timing Chook	Dof Din(trong)	Reference Slew Rate(ns)		
Cen Name	Cell Name Timing Check	Ref Pin(trans)	first	mid	last
-6100 OT 166- 1	hold	CLKN (R)	-0.20420	-0.60089	-4.76816
gf180mcu_osu_sc_9T_dffn_1 setup	setup	CLKN (R)	0.22179	0.61438	5.15952

Constraints(ns) for CLKN rising (conditional):

Call Name	Timing Check	Ref Pin(trans)	Reference Slew Rate(ns)			
Cell Name Timing Check	Kei Fill(trails)	first	mid	last		
of 190 man age of OT Jeffer 1	min_pulse_width	CLKN ()	0.15531	1.45630	16.50020	
gf180mcu_osu_sc_9T_dffn_1	min_pulse_width	CLKN ()	0.18900	1.45630	16.50020	

$Constraints (ns) \ for \ CLKN \ falling \ (conditional):$

Call Name	Timing Chask	Ref Pin(trans)	Reference Slew Rate(ns)			
Cell Name Timing Check	Tilling Check	Kei Fill(trails)	first	mid	last	
of 100 more on a OT defer 1	min_pulse_width	CLKN ()	0.25379	1.45630	16.50020	
gf180mcu_osu_sc_9T_dffn_1	min_pulse_width	CLKN ()	0.18123	1.45630	16.50020	

Power Information

Internal switching power(pJ) to Q rising:

Call Name	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
gf180mcu_osu_sc_9T_dffn_1	CLKN	0.04946	0.12984	0.64377	
	CLKN	0.07753	0.15803	0.67514	

Internal switching power(pJ) to Q falling:

Call Name	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
gf180mcu_osu_sc_9T_dffn_1	CLKN	0.05842	0.10745	0.50368	
	CLKN	0.07991	0.12830	0.52377	

Internal switching power(pJ) to QN rising:

Call Name	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
gf180mcu_osu_sc_9T_dffn_1	CLKN	0.05840	0.10719	0.50270	
	CLKN	0.07989	0.12852	0.52401	

Internal switching power(pJ) to QN falling:

Call Name	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
gf180mcu_osu_sc_9T_dffn_1	CLKN	0.04937	0.12979	0.64122	
	CLKN	0.07744	0.15791	0.67139	

Passive power(pJ) for D rising (conditional):

Call Name	W/le ore	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_dffn_1	CLKN	-0.01322	-0.01338	-0.01335	
	CLKN	0.00655	0.00647	0.00649	
	(!CLKN * Q * !QN) + (!CLKN * !Q * QN)	0.05982	0.13524	0.71342	
	(!CLKN * Q * !QN) + (!CLKN * !Q * QN)	0.09138	0.16690	0.74479	

Passive power(pJ) for D falling (conditional):

C-II N	XX/I	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_dffn_1	CLKN	0.01350	0.01350	0.01335	
	CLKN	-0.00644	-0.00647	-0.00648	
	(!CLKN * Q * !QN) + (!CLKN * !Q * QN)	0.09185	0.16885	0.74724	
	(!CLKN * Q * !QN) + (!CLKN * !Q * QN)	0.06027	0.13728	0.71567	

Passive power(pJ) for CLKN rising (conditional):

Call Name	Whom	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_dffn_1	(D * Q * !QN)	-0.00022	0.08422	0.66646	
	(D * Q * !QN)	0.04664	0.13102	0.71314	
	(!D * !Q * QN)	-0.00083	0.08453	0.66610	
	(!D * !Q * QN)	0.05312	0.13836	0.71997	

Passive power(pJ) for CLKN falling (conditional):

C-II N	XX/1	Power(pJ)			
Cell Name	When	first	mid	last	
	(D * Q * !QN)	0.04730	0.13539	0.71738	
	(D * Q * !QN)	0.00048	0.08841	0.67051	
	(D * !Q * QN)	0.12427	0.21430	0.99209	
of 100 man and a OT Affr. 1	(D * !Q * QN)	0.08251	0.17233	0.94983	
gf180mcu_osu_sc_9T_dffn_1	(!D * Q * !QN)	0.12089	0.27488	1.16805	
	(!D * Q * !QN)	0.06421	0.21785	1.11108	
	(!D * !Q * QN)	0.05375	0.13922	0.72024	
	(!D * !Q * QN)	-0.00032	0.08498	0.66630	

GF180MCU_OSU_SC_9T_DFFSR_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT				OUTPUT		
D	RN	SN	CLK	Q	QN	
0	1	1	R	0	1	
1	1	1	R	1	0	
x	0	X	x	0	1	
x	1	0	x	1	0	
x	1	1	X	IQ	IQN	

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_dffsr_1	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)				Max Cap(pf)	
Cell Name	D	RN	SN	CLK	Q	QN
gf180mcu_osu_sc_9T_dffsr_1	0.00393	0.00405	0.00802	0.01039	1.54794	1.55977

Call Name	Leakage(nW)				
Cell Name	Min. Avg		Max.		
gf180mcu_osu_sc_9T_dffsr_1	0.00000	0.00708	0.00862		

Delay Information Delay(ns) to Q rising:

Call Name	Timing Ang(Din)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_dffsr_1	CLK->Q (RR)	0.39152	1.36998	16.45910	
	QN->Q (FR)	0.04498	0.84959	10.19690	
	RN->Q (RR)	0.28691	1.26458	16.47060	
	SN->Q (FR)	0.26970	1.36489	17.32290	

Delay(ns) to Q falling:

Call Name	T: A (D:)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_dffsr_1	CLK->Q (RF)	0.44884	1.38495	16.25880	
	QN->Q (RF)	0.03639	0.65027	8.68858	
	RN->Q (FF)	0.25479	1.37924	17.40650	

Delay(ns) to QN rising:

Call Name	Timing Ang(Div)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_dffsr_1	CLK->QN (RR)	0.41343	0.86099	7.09321	
	RN->QN (FR)	0.21980	0.85598	8.24101	

Delay(ns) to QN falling:

Call Name	Timing Ana(Din)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_dffsr_1	CLK->QN (RF)	0.34947	0.79178	6.28325	
	RN->QN (RF)	0.24559	0.68577	6.29256	
	SN->QN (FF)	0.22847	0.78577	7.14017	

Constraint Information

Constraints(ns) for D rising:

Cell Name	Timing Chash	Dof Din(tuons)	Reference Slew Rate(ns)			
	Timing Check	Ref Pin(trans)	first	mid	last	
gf180mcu_osu_sc_9T_dffsr_1	hold	CLK (R)	-0.14469	-0.12515	0.54748	
	setup	CLK (R)	0.29476	0.37169	0.69818	

Constraints(ns) for D falling:

Cell Name	Timing Chash	Dof Dire(tropes)	Reference Slew Rate(ns)			
	Timing Check	Ref Pin(trans)	first	mid	last	
gf180mcu_osu_sc_9T_dffsr_1	hold	CLK (R)	-0.23016	-0.60573	-5.00636	
	setup	CLK (R)	0.26622	0.62665	5.14907	

Constraints(ns) for D rising (conditional):

Cell Name	Timing Chook	Ref Pin(trans)	Reference Slew Rate(ns)			
	Timing Check	Kei Fill(trails)	first	mid	last	
gf180mcu_osu_sc_9T_dffsr_1	hold	CLK (R)	-0.14469	-0.12515	0.54748	
	setup	CLK (R)	0.29476	0.37169	0.69818	

Constraints(ns) for D falling (conditional):

Cell Name	Timing Chask	Ref Pin(trans)	Reference Slew Rate(ns)			
	Timing Check	Kei Fill(trails)	first	mid	last	
gf180mcu_osu_sc_9T_dffsr_1	hold	CLK (R)	-0.23016	-0.60573	-5.00636	
	setup	CLK (R)	0.26622	0.62665	5.14907	

Constraints(ns) for RN rising:

Cell Name	Tii Chh	D - f D: (4)	Reference Slew Rate(ns)			
	Timing Check	Ref Pin(trans)	first	mid	last	
gf180mcu_osu_sc_9T_dffsr_1	recovery	CLK (R)	0.17521	0.29401	1.45846	
	removal	CLK (R)	-0.01563	-0.01947	-0.04919	
	hold	SN (R)	-0.21059	-0.41752	-0.83190	
	setup	SN (R)	0.24903	0.56181	5.27872	

Constraints(ns) for RN rising (conditional):

Cell Name	Timing Check	D - f D' (4)	Reference Slew Rate(ns)			
		Ref Pin(trans)	first	mid	last	
gf180mcu_osu_sc_9T_dffsr_1	recovery	CLK (R)	0.17521	0.29401	1.45846	
	removal	CLK (R)	-0.01563	-0.01947	-0.04919	
	hold	SN (R)	-0.21059	-0.41752	-0.83192	
	hold	SN (R)	-0.21242	-0.41968	-0.83190	
	setup	SN (R)	0.24614	0.55781	5.20954	
	setup	SN (R)	0.24903	0.56181	5.27872	

Constraints(ns) for RN falling (conditional):

Call Name	Timing Charle	Dof Dire(Arrang)	Reference Slew Rate(ns)		
Cen Name	Cell Name Timing Check	Ref Pin(trans)	first	mid	last
gf180mcu_osu_sc_9T_dffsr_1	min_pulse_width	RN ()	0.16568	1.45630	16.50020
	min_pulse_width	RN ()	0.16568	1.45630	16.50020

Constraints(ns) for SN rising:

Call Name	Timing Chash	Dof Din (4mans)	Reference Slew Rate(ns)			
Cell Name Tim	1 iming Check	Ref Pin(trans)	first	mid	last	
gf180mcu_osu_sc_9T_dffsr_1	recovery	CLK (R)	0.07717	0.17001	5.62369	
	removal	CLK (R)	-0.03673	-0.08870	-0.61887	

Constraints(ns) for SN rising (conditional):

Call Name	Timing Chash	Dof Din (4mans)	Reference Slew Rate(ns)			
Cell Name T	Timing Check	Ref Pin(trans)	first	mid	last	
gf180mcu_osu_sc_9T_dffsr_1	recovery	CLK (R)	0.07717	0.17001	5.62369	
	removal	CLK (R)	-0.03673	-0.08870	-0.61887	

Constraints(ns) for SN falling (conditional):

Call Name	Timing Charle	Dof Dire(Arrows)	Reference Slew Rate(ns)		
Cell Name	Timing Check	Ref Pin(trans)	first	mid	last
gf180mcu_osu_sc_9T_dffsr_1	min_pulse_width	SN ()	0.22788	1.45630	16.50020
	min_pulse_width	SN ()	0.23047	1.45630	16.50020

Constraints(ns) for CLK rising (conditional):

Call Name	Timing Chook	Ref Pin(trans)	Reference Slew Rate(ns)		
Cell Name	Timing Check	Kei Fill(trails)	first	mid	last
celonum on an or defau 1	min_pulse_width	CLK ()	0.20714	1.45630	16.50020
gf180mcu_osu_sc_9T_dffsr_1	min_pulse_width	CLK ()	0.23047	1.45630	16.50020

Constraints(ns) for CLK falling (conditional):

Call Nama	Timing Cheek	Ref Pin(trans)	Reference Slew Rate(ns)		
Cell Name	Timing Check	Kei Fini(trans)	first	mid	last
gf180mcu_osu_sc_9T_dffsr_1	min_pulse_width	CLK ()	0.35746	1.45630	16.50020
	min_pulse_width	CLK ()	0.22788	1.45630	16.50020

Power Information

Internal switching power(pJ) to Q rising:

Call Name	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
	CLK	0.06467	0.13937	0.65038	
	CLK	0.08972	0.16530	0.67768	
-6100 OT Jee- 1	RN	0.10502	0.15566	0.55926	
gf180mcu_osu_sc_9T_dffsr_1	RN	0.12178	0.17262	0.57788	
	SN	0.09520	0.15571	0.62174	
	SN	0.07891	0.14051	0.60644	

Internal switching power(pJ) to Q falling:

Cell Name	T4	Power(pJ)			
	Input	first	mid	last	
	CLK	0.06770	0.11451	0.50899	
_£100 OT 1£6 1	CLK	0.09222	0.13887	0.53172	
gf180mcu_osu_sc_9T_dffsr_1	RN	0.11637	0.17244	0.59300	
	RN	0.09957	0.15467	0.57629	

Internal switching power(pJ) to QN rising:

Cell Name	Immut	Power(pJ)			
	Input	first	mid	last	
	CLK	0.06763	0.11443	0.50805	
of 190 may ago as OT defan 1	CLK	0.09215	0.13878	0.53208	
gf180mcu_osu_sc_9T_dffsr_1	RN	0.11635	0.17181	0.59143	
	RN	0.09955	0.15509	0.57434	

Internal switching power(pJ) to QN falling:

Call Name	I4	Power(pJ)			
Cell Name	Input	first	mid	last	
	CLK	0.06458	0.13962	0.64790	
	CLK	0.08963	0.16459	0.67511	
-6100 OT Jee 1	RN	0.10495	0.15575	0.55607	
gf180mcu_osu_sc_9T_dffsr_1	RN	0.12171	0.17250	0.57349	
	SN	0.09512	0.15609	0.61949	
	SN	0.07882	0.13985	0.60344	

Passive power(pJ) for D rising (conditional):

Call Name	W/le our	Power(pJ)			
Cell Name	When	first	mid	last	
	CLK	-0.01322	-0.01337	-0.01335	
	CLK	0.00655	0.00647	0.00649	
	(!CLK * RN * SN * Q * !QN) + (!CLK * RN * SN * !Q * QN)	0.08460	0.15229	0.71637	
	(!CLK * RN * SN * Q * !QN) + (!CLK * RN * SN * !Q * QN)	0.11017	0.17788	0.74184	
gf180mcu_osu_sc_9T_dffsr_1	(!CLK * RN * !SN * Q * !QN)	0.03740	0.10128	0.62199	
	(!CLK * RN * !SN * Q * !QN)	0.06908	0.13307	0.65351	
	(!CLK * !RN * SN * !Q * QN)	0.03715	0.10059	0.62211	
	(!CLK * !RN * SN * !Q * QN)	0.06896	0.13235	0.65366	
	(!CLK * !RN * !SN * !Q * QN)	0.03740	0.10128	0.62199	
	(!CLK * !RN * !SN * !Q * QN)	0.06908	0.13307	0.65351	

Passive power(pJ) for D falling (conditional):

Call Name	XX/leave	Power(pJ)			
Cell Name	When	first	mid	last	
	CLK	0.01350	0.01350	0.01335	
	CLK	-0.00644	-0.00647	-0.00648	
	(!CLK * RN * SN * Q * !QN) + (!CLK * RN * SN * !Q * QN)	0.10616	0.17651	0.74263	
	(!CLK * RN * SN * Q * !QN) + (!CLK * RN * SN * !Q * QN)	0.08055	0.15087	0.71713	
gf180mcu_osu_sc_9T_dffsr_1	(!CLK * RN * !SN * Q * !QN)	0.04832	0.11362	0.63649	
	(!CLK * RN * !SN * Q * !QN)	0.01674	0.08188	0.60486	
	(!CLK * !RN * SN * !Q * QN)	0.04844	0.11347	0.63632	
	(!CLK * !RN * SN * !Q * QN)	0.01680	0.08179	0.60475	
	(!CLK * !RN * !SN * !Q * QN)	0.04832	0.11362	0.63650	
	(!CLK * !RN * !SN * !Q * QN)	0.01674	0.08186	0.60486	

Passive power(pJ) for RN rising (conditional):

Call Name	Whom	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_dffsr_1	(CLK * SN * !Q * QN) + (!CLK * !D * SN * !Q * QN)	0.00945	0.09340	0.67565	
	(CLK * SN * !Q * QN) + (!CLK * !D * SN * !Q * QN)	0.03159	0.11551	0.69779	
	(!CLK * D * SN * !Q * QN)	0.05546	0.14345	0.75218	
	(!CLK * D * SN * !Q * QN)	0.07230	0.16042	0.76910	

Passive power(pJ) for RN falling (conditional):

Call Name	Whom	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_dffsr_1	(CLK * SN * !Q * QN) + (!CLK * !D * SN * !Q * QN)	0.03774	0.12507	0.70816	
	(CLK * SN * !Q * QN) + (!CLK * !D * SN * !Q * QN)	0.01557	0.10282	0.68608	
	(!CLK * D * SN * !Q * QN)	0.07901	0.17019	0.78403	
	(!CLK * D * SN * !Q * QN)	0.06214	0.15344	0.76718	

Passive power(pJ) for SN rising (conditional):

Call Name	XX/b ove	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_dffsr_1	(CLK * RN * Q * !QN) + (!CLK * D * RN * Q * !QN)	-0.02793	-0.02816	-0.02827	
	(CLK * RN * Q * !QN) + (!CLK * D * RN * Q * !QN)	0.00386	0.00388	0.00366	
	(!RN * !Q * QN)	-0.02694	-0.02702	-0.02698	
	(!RN * !Q * QN)	0.01311	0.01316	0.01302	
	(!CLK * !D * RN * Q * !QN)	0.02956	0.08801	0.55614	
	(!CLK * !D * RN * Q * !QN)	0.06710	0.12577	0.59362	

Passive power(pJ) for SN falling (conditional):

Cell Name	W/le ove	Power(pJ)			
	When	first	mid	last	
gf180mcu_osu_sc_9T_dffsr_1	(CLK * RN * Q * !QN) + (!CLK * D * RN * Q * !QN)	0.02846	0.02860	0.02836	
	(CLK * RN * Q * !QN) + (!CLK * D * RN * Q * !QN)	-0.00361	-0.00364	-0.00359	
	(!RN * !Q * QN)	0.02707	0.02702	0.02698	
	(!RN * !Q * QN)	-0.01298	-0.01298	-0.01298	
	(!CLK * !D * RN * Q * !QN)	0.06258	0.11848	0.58926	
	(!CLK * !D * RN * Q * !QN)	0.02492	0.08071	0.55161	

Passive power(pJ) for CLK rising (conditional):

Cell Name	Whon	Power(pJ)			
	When	first	mid	last	
	(D * RN * Q * !QN)	-0.00022	0.08422	0.66646	
	(D * RN * Q * !QN)	0.04664	0.13103	0.71314	
	(D * !RN * SN * !Q * QN)	0.03593	0.12442	0.73405	
	(D * !RN * SN * !Q * QN)	0.08031	0.16869	0.77671	
	(D * !RN * !SN * !Q * QN)	0.03580	0.12436	0.73378	
gf180mcu_osu_sc_9T_dffsr_1	(D * !RN * !SN * !Q * QN)	0.08025	0.16861	0.77637	
	(!D * RN * SN * !Q * QN) + (!D * !RN * !Q * QN)	-0.00083	0.08455	0.66610	
	(!D * RN * SN * !Q * QN) + (!D * !RN * !Q * QN)	0.05312	0.13834	0.71997	
	(!D * RN * !SN * Q * !QN)	0.02509	0.16620	1.15806	
	(!D * RN * !SN * Q * !QN)	0.08159	0.22280	1.21437	

Passive power(pJ) for CLK falling (conditional):

CHN	***	Power(pJ)			
Cell Name	When	first	mid	last	
	(D*RN*SN*!Q*QN)	0.14915	0.23727	1.00237	
	(D*RN*SN*!Q*QN)	0.10132	0.18958	0.95592	
	(D*RN*Q*!QN)	0.04729	0.13513	0.71738	
	(D*RN*Q*!QN)	0.00048	0.08852	0.67051	
	(D * !RN * SN * !Q * QN)	0.09406	0.18881	0.79676	
	(D * !RN * SN * !Q * QN)	0.04959	0.14470	0.75327	
	(D * !RN * !SN * !Q * QN)	0.09424	0.18910	0.79678	
gf180mcu_osu_sc_9T_dffsr_1	(D * !RN * !SN * !Q * QN)	0.04977	0.14491	0.75318	
	(!D * RN * SN * Q * !QN)	0.13537	0.28452	1.17447	
	(!D * RN * SN * Q * !QN)	0.08472	0.23384	1.12334	
	(!D * RN * SN * !Q * QN) + (!D * !RN * !Q * QN)	0.05373	0.13922	0.72024	
	(!D * RN * SN * !Q * QN) + (!D * !RN * !Q * QN)	-0.00033	0.08498	0.66631	
	(!D * RN * !SN * Q * !QN)	0.06924	0.21479	1.20685	
	(!D * RN * !SN * Q * !QN)	0.01269	0.15837	1.15038	

GF180MCU_OSU_SC_9T_DFF_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

IN	INPUT		ГРUТ
D	CLK	Q	QN
0	R	0	1
1	R	1	0
X	X	IQ	IQN

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_dff_1	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)		Max Cap(pf)	
Cell Name	D	CLK	Q	QN
gf180mcu_osu_sc_9T_dff_1	0.00393	0.01039	1.56141	1.56075

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_dff_1	0.00000	0.00595	0.00661	

Delay Information Delay(ns) to Q rising:

Call Name	Timing Aug(Din)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_dff_1	CLK->Q (RR)	0.26942	1.25620	16.48390	
	QN->Q (FR)	0.04498	0.85148	10.25460	

Delay(ns) to Q falling:

Call Name	Timing Ang(Din)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_dff_1	CLK->Q (RF)	0.35742	1.28545	16.29670	
	QN->Q (RF)	0.03639	0.65226	8.74007	

Delay(ns) to QN rising:

Call Name	Timing Aug(Din)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_dff_1	CLK->QN (RR)	0.32250	0.75813	6.99720	

Delay(ns) to QN falling:

Cell Name	Timing Ang(Din)	Delay(ns)			
	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_dff_1	CLK->QN (RF)	0.23125	0.67320	6.16788	

Constraint Information

Constraints(ns) for D rising:

Call Name	Timing Chash	Dof Dir (trops)	Reference Slew Rate(ns)			
Cell Name	Timing Check	Ref Pin(trans)	first	mid	last	
gf180mcu_osu_sc_9T_dff_1	hold	CLK (R)	-0.10101	-0.09519	0.57241	
	setup	CLK (R)	0.19078	0.25850	0.88708	

Constraints(ns) for D falling:

Call Name	Timing Chook	Dof Din(tuons)	Reference Slew Rate(ns)			
Cen Name	Cell Name Timing Check	Ref Pin(trans)	first	mid	last	
gf180mcu_osu_sc_9T_dff_1	hold	CLK (R)	-0.20420	-0.60089	-4.76816	
	setup	CLK (R)	0.22179	0.61438	5.15952	

Constraints(ns) for CLK rising (conditional):

Cell Name Timing Check	Timing Chook	Ref Pin(trans)	Reference Slew Rate(ns)			
	Kei Fill(trails)	first	mid	last		
gf180mcu_osu_sc_9T_dff_1 min_pulse_width	CLK ()	0.15531	1.45630	16.50020		
	min_pulse_width	CLK ()	0.18900	1.45630	16.50020	

$Constraints (ns) \ for \ CLK \ falling \ (conditional):$

Cell Name	Timing Chook	Ref Pin(trans)	Reference Slew Rate(ns)		
	Timing Check	Kei Fill(trails)	first	mid	last
gf180mcu_osu_sc_9T_dff_1	min_pulse_width	CLK ()	0.25379	1.45630	16.50020
	min_pulse_width	CLK ()	0.18123	1.45630	16.50020

Power Information

Internal switching power(pJ) to Q rising:

Call Name	I4	Power(pJ)			
Cell Name	Input	first	mid	last	
24.00	CLK	0.04946	0.12984	0.64377	
gf180mcu_osu_sc_9T_dff_1	CLK	0.07753	0.15803	0.67514	

Internal switching power(pJ) to Q falling:

Call Name	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
gf180mcu_osu_sc_9T_dff_1	CLK	0.05842	0.10745	0.50368	
	CLK	0.07991	0.12830	0.52377	

Internal switching power(pJ) to QN rising:

Call Nama	Immut	Power(pJ)			
Cell Name	Input	first	mid	last	
gf180mcu_osu_sc_9T_dff_1	CLK	0.05840	0.10719	0.50270	
	CLK	0.07989	0.12852	0.52401	

Internal switching power(pJ) to QN falling:

Cell Name	Innut	Power(pJ)			
	Input	first	mid	last	
gf180mcu_osu_sc_9T_dff_1	CLK	0.04937	0.12979	0.64122	
	CLK	0.07744	0.15791	0.67139	

Passive power(pJ) for D rising (conditional):

Call Name	W/horn	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_dff_1	CLK	-0.01322	-0.01338	-0.01335	
	CLK	0.00655	0.00647	0.00649	
	(!CLK * Q * !QN) + (!CLK * !Q * QN)	0.05982	0.13524	0.71342	
	(!CLK * Q * !QN) + (!CLK * !Q * QN)	0.09138	0.16690	0.74479	

Passive power(pJ) for D falling (conditional):

Cell Name	XVII. o in	Power(pJ)			
	When	first	mid	last	
gf180mcu_osu_sc_9T_dff_1	CLK	0.01350	0.01350	0.01335	
	CLK	-0.00644	-0.00647	-0.00648	
	(!CLK * Q * !QN) + (!CLK * !Q * QN)	0.09185	0.16885	0.74724	
	(!CLK * Q * !QN) + (!CLK * !Q * QN)	0.06027	0.13728	0.71567	

Passive power(pJ) for CLK rising (conditional):

Cell Name	XX/I	Power(pJ)			
	When	first	mid	last	
gf180mcu_osu_sc_9T_dff_1	(D * Q * !QN)	-0.00022	0.08422	0.66646	
	(D * Q * !QN)	0.04664	0.13102	0.71314	
	(!D * !Q * QN)	-0.00083	0.08453	0.66610	
	(!D * !Q * QN)	0.05312	0.13836	0.71997	

Passive power(pJ) for CLK falling (conditional):

Cell Name	¥¥71	Power(pJ)			
Cell Name	When	first	mid	last	
	(D * Q * !QN)	0.04730	0.13539	0.71738	
	(D * Q * !QN)	0.00048	0.08841	0.67051	
	(D * !Q * QN)	0.12427	0.21430	0.99209	
-6100 OT JCC 1	(D * !Q * QN)	0.08251	0.17233	0.94983	
gf180mcu_osu_sc_9T_dff_1	(!D * Q * !QN)	0.12089	0.27488	1.16805	
	(!D * Q * !QN)	0.06421	0.21785	1.11108	
	(!D * !Q * QN)	0.05375	0.13922	0.72024	
	(!D * !Q * QN)	-0.00032	0.08498	0.66630	

GF180MCU_OSU_SC_9T_DLATN_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

I	NPUT	OUTPUT
D	CLKN	Q
X	0	IQ
0	1	0
1	1	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_dlatn_1	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)		Max Cap(pf)	
Cell Name	D	CLKN	Q	
gf180mcu_osu_sc_9T_dlatn_1	0.00395	0.00812	1.56358	

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_dlatn_1	0.00000	0.00418	0.00475	

Delay Information Delay(ns) to Q rising:

Cell Name	Timing Ang(Din)	Delay(ns)			
	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_dlatn_1	CLKN->Q (RR)	0.26321	0.74398	6.94335	
	D->Q (RR)	0.29531	0.73056	6.96558	

Delay(ns) to Q falling:

Call Name	Timing Ana(Din)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_dlatn_1	CLKN->Q (RF)	0.33278	0.70064	6.22097	
	D->Q (FF)	0.32836	0.89642	7.70570	

Constraint Information

Constraints(ns) for D rising:

Cell Name	Timing Chask	Dof Din(tuons)	Reference Slew Rate(ns)			
	1 ming Check	Ref Pin(trans)	first	mid	last	
gf180mcu_osu_sc_9T_dlatn_1	hold	CLKN (F)	-0.17417	-0.36560	-2.23157	
	setup	CLKN (F)	0.18929	0.52757	6.82894	

Constraints(ns) for D falling:

Cell Name	Timing Chash	Dof Dire(tropes)	Reference Slew Rate(ns)			
	1 iming Check	Ref Pin(trans)	first	mid	last	
gf180mcu_osu_sc_9T_dlatn_1	hold	CLKN (F)	-0.15692	-0.19037	0.12822	
	setup	CLKN (F)	0.16945	0.19470	-0.12937	

Constraints(ns) for CLKN rising (conditional):

Call Name Timing		Ref Pin(trans)	Reference Slew Rate(ns)			
Cell Name	Timing Check	Kei i iii(ti alis)	first	mid	last	
of 190 many one of OT district	min_pulse_width	CLKN ()	0.15531	1.45630	16.50020	
gf180mcu_osu_sc_9T_dlatn_1	min_pulse_width	CLKN ()	0.18123	1.45630	16.50020	

Power Information

Internal switching power(pJ) to Q rising:

Cell Name	T4	Power(pJ)			
	Input	first	mid	last	
gf180mcu_osu_sc_9T_dlatn_1	CLKN	0.09253	0.24889	1.13079	
	CLKN	0.13707	0.29348	1.17570	
	D	0.08989	0.16843	0.75443	
	D	0.11759	0.19603	0.78214	

Internal switching power(pJ) to Q falling:

Cell Name	T4	Power(pJ)			
	Input	first	mid	last	
gf180mcu_osu_sc_9T_dlatn_1	CLKN	0.11208	0.20101	0.81578	
	CLKN	0.13878	0.22776	0.84295	
	D	0.12857	0.20696	0.79445	
	D	0.10028	0.17900	0.76670	

Passive power(pJ) for D rising (conditional):

Call Name	VVII- o	Power(pJ)				
Cell Name	When	first	mid last			
gf180mcu_osu_sc_9T_dlatn_1	!CLKN	-0.01334	-0.01350	-0.01346		
	!CLKN	0.00659	0.00649	0.00646		

Passive power(pJ) for D falling (conditional):

Call Name	VVII- o	Power(pJ)				
Cell Name	When	first	mid last			
gf180mcu_osu_sc_9T_dlatn_1	!CLKN	0.01344	0.01354	0.01346		
	!CLKN	-0.00639	-0.00649	-0.00646		

Passive power(pJ) for CLKN rising (conditional):

Cell Name	W/h ore	Power(pJ)			
	When	first	mid	last	
gf180mcu_osu_sc_9T_dlatn_1	(D * Q)	-0.00054	0.08676	0.67099	
	(D * Q)	0.03387	0.12148	0.70541	
	(!D * !Q)	-0.00068	0.08702	0.67094	
	(!D * !Q)	0.03723	0.12494	0.70871	

Passive power(pJ) for CLKN falling (conditional):

Cell Name	Where	Power(pJ)		
	When	first	mid	last
gf180mcu_osu_sc_9T_dlatn_1	(D * Q)	0.03505	0.12500	0.70878
	(D * Q)	0.00046	0.09045	0.67426
	(!D * !Q)	0.03797	0.12641	0.70996
	(!D * !Q)	-0.00001	0.08839	0.67209

GF180MCU_OSU_SC_9T_DLAT_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT		OUTPUT
D	CLK	Q
х	0	IQ
0	1	0
1	1	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_dlat_1	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)		Max Cap(pf)	
Cell Name	D	CLK	Q	
gf180mcu_osu_sc_9T_dlat_1	0.00395	0.00812	1.56358	

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_dlat_1	0.00000	0.00418	0.00475	

Delay Information Delay(ns) to Q rising:

Call Name	Timing Aug(Din)	Delay(ns)		
Cell Name	Timing Arc(Dir)	First	Mid	Last
	CLK->Q (RR)	0.26321	0.74398	6.94335
gf180mcu_osu_sc_9T_dlat_1	D->Q (RR)	0.29531	0.73056	6.96558

Delay(ns) to Q falling:

Cell Name	Timing Arc(Dir)	Delay(ns)		
		First	Mid	Last
gf180mcu_osu_sc_9T_dlat_1	CLK->Q (RF)	0.33278	0.70064	6.22097
	D->Q (FF)	0.32836	0.89642	7.70570

Constraint Information

Constraints(ns) for D rising:

Call Maria	Timing Chash	Dof Dire(trops)	Refere	nce Slew R	ate(ns)
Cell Name	Timing Check	Kei Pin(trans)	first	mid	last
gf180mcu_osu_sc_9T_dlat_1	hold	CLK (F)	-0.17417	-0.36560	-2.23157
	setup	CLK (F)	0.18929	0.52757	6.82894

$Constraints (ns) \ for \ D \ falling:$

Call Name	Timing Check	Dof Din(tuons)	Refere	nce Slew R	ate(ns)
Cell Name		Ref Pin(trans)	first	mid	last
gf180mcu_osu_sc_9T_dlat_1	hold	CLK (F)	-0.15692	-0.19037	0.12822
	setup	CLK (F)	0.16945	0.19470	-0.12937

Constraints(ns) for CLK rising (conditional):

Cell Name	Timing Cheek	Ref Pin(trans)	Refere	nce Slew 1	Rate(ns)
Cen Name	Timing Check	Kei Pin(trans)	first	mid	last
of 190 man age of OT diet 1	min_pulse_width min_pulse_width	CLK ()	0.15531	1.45630	16.50020
gf180mcu_osu_sc_9T_dlat_1		CLK ()	0.18123	1.45630	16.50020

Internal switching power(pJ) to Q rising:

Call Name	I4		Power(pJ)	
Cell Name	Input	first	mid	last
gf180mcu_osu_sc_9T_dlat_1	CLK	0.09253	0.24889	1.13079
	CLK	0.13707	0.29348	1.17570
	D	0.08989	0.16843	0.75443
	D	0.11759	0.19603	0.78214

Internal switching power(pJ) to Q falling:

Call Name	T4		Power(pJ)	
Cell Name	Input	first	mid	last
gf180mcu_osu_sc_9T_dlat_1	CLK	0.11208	0.20101	0.81578
	CLK	0.13878	0.22776	0.84295
	D	0.12857	0.20696	0.79445
	D	0.10028	0.17900	0.76670

Passive power(pJ) for D rising (conditional):

Call Name	XX/la oza		Power(pJ)	
Cell Name	When	first	mid	last
gf180mcu_osu_sc_9T_dlat_1	!CLK	-0.01334	-0.01350	-0.01346
	!CLK	0.00659	0.00649	0.00646

Passive power(pJ) for D falling (conditional):

Call Name	W/le oze		Power(pJ)	
Cell Name	When	first	mid	last
0100 OTT 11 4 4	!CLK	0.01344	0.01354	0.01346
gf180mcu_osu_sc_9T_dlat_1	!CLK	-0.00639	-0.00649	-0.00646

Passive power(pJ) for CLK rising (conditional):

Call Name	Where		Power(pJ)	
Cell Name	When	first	mid	last
gf180mcu_osu_sc_9T_dlat_1	(D * Q)	-0.00054	0.08676	0.67099
	(D * Q)	0.03387	0.12148	0.70541
	(!D * !Q)	-0.00068	0.08702	0.67094
	(!D * !Q)	0.03723	0.12494	0.70871

Passive power(pJ) for CLK falling (conditional):

Call Name	Where		Power(pJ)	
Cell Name	When	first	mid	last
gf180mcu_osu_sc_9T_dlat_1	(D * Q)	0.03505	0.12500	0.70878
	(D * Q)	0.00046	0.09045	0.67426
	(!D * !Q)	0.03797	0.12641	0.70996
	(!D * !Q)	-0.00001	0.08839	0.67209

GF180MCU_OSU_SC_9T_INV_16

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	1
1	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_inv_16	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)	
Cell Name	A	Y	
gf180mcu_osu_sc_9T_inv_16	0.06466	23.87903	

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_inv_16	0.00000	0.01192	0.01439	

Call Name	Timing Aug(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_inv_16	A->Y (FR)	0.03956	0.49677	9.96266

Call Name	Timing Ang(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_inv_16	A->Y (RF)	0.03092	0.29391	8.47767

Internal switching power(pJ) to Y rising:

Call Name	T4		Power(pJ)	
Cell Name	Input	first	mid	last
0100 OTL 1 47	A	0.35769	1.48564	4.08772
gf180mcu_osu_sc_9T_inv_16	A	0.00871	1.13458	3.73679

Internal switching power(pJ) to \boldsymbol{Y} falling:

Call Name	T4		Power(pJ)	
Cell Name	Input	first	mid	last
6100 OT 1 17	A	0.00389	1.07024	3.39414
gf180mcu_osu_sc_9T_inv_16	A	0.35277	1.42158	3.74746

GF180MCU_OSU_SC_9T_INV_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	1
1	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_inv_1	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)
Cell Name	A	Y
gf180mcu_osu_sc_9T_inv_1	0.00404	1.50748

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_inv_1	0.00000	0.00075	0.00090	

Call Name	Timing Ang(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_inv_1	A->Y (FR)	0.04498	0.84197	10.02570

Call Name	Timing Aug (Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_inv_1	A->Y (RF)	0.03639	0.64312	8.53517

Internal switching power(pJ) to Y rising:

Call Name	Innut		Power(pJ)	
Cell Name	Input	first	mid	last
-6100 OT : 1	A	0.02226	0.07404	0.25366
gf180mcu_osu_sc_9T_inv_1	A	0.00038	0.05208	0.23179

Internal switching power(pJ) to \boldsymbol{Y} falling:

Call Name	Input		Power(pJ)	
Cell Name		first	mid	last
gf180mcu_osu_sc_9T_inv_1	A	-0.00053	0.04771	0.21052
	A	0.02128	0.06976	0.23249

GF180MCU_OSU_SC_9T_INV_2

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	1
1	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_inv_2	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)	
Cell Name	A	Y	
gf180mcu_osu_sc_9T_inv_2	0.00808	2.98498	

Call Name	Leakage(nW)			
Cell Name	Min. Avg		Max.	
gf180mcu_osu_sc_9T_inv_2	0.00000	0.00149	0.00180	

Call Name	Timing Aug(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)		Mid	Last
gf180mcu_osu_sc_9T_inv_2	A->Y (FR)	0.04172	0.72858	9.96233

Call Name	Timing Ang(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_inv_2	A->Y (RF)	0.03307	0.52906	8.47738

Internal switching power(pJ) to Y rising:

C.II Nome	Input	Power(pJ)		
Cell Name		first	mid	last
gf180mcu_osu_sc_9T_inv_2	A	0.04475	0.15897	0.51097
	A	0.00091	0.11480	0.46711

Internal switching power(pJ) to \boldsymbol{Y} falling:

Call Name	Input		Power(pJ)	
Cell Name		first	mid	last
gf180mcu_osu_sc_9T_inv_2	A	-0.00109	0.10609	0.42288
	A	0.04270	0.15004	0.46704

GF180MCU_OSU_SC_9T_INV_4

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	1
1	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_inv_4	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)	
Cell Name	A	Y	
gf180mcu_osu_sc_9T_inv_4	0.01616	5.97048	

Call Name	Leakage(nW)			
Cell Name	Min. Avg M		Max.	
gf180mcu_osu_sc_9T_inv_4	0.00000	0.00298	0.00360	

Call Name	Timing Aug(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_inv_4	A->Y (FR)	0.04000	0.63574	9.96289

Call Name	Timing Aug (Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_inv_4	A->Y (RF)	0.03137	0.43650	8.47788

Internal switching power(pJ) to Y rising:

Call Name	I4		Power(pJ)	
Cell Name	Input	first	mid	last
0T) 1 4	A	0.08959	0.33578	1.02191
gf180mcu_osu_sc_9T_inv_4	A	0.00205	0.24768	0.93418

Internal switching power(pJ) to \boldsymbol{Y} falling:

Call Name	T4		Power(pJ)	
Cell Name	Input	first	mid	last
6100 OTT 1 4	A	-0.00200	0.23109	0.84572
gf180mcu_osu_sc_9T_inv_4	A	0.08550	0.31888	0.93405

GF180MCU_OSU_SC_9T_INV_8

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	1
1	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_inv_8	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)
Cell Name	A	Y
gf180mcu_osu_sc_9T_inv_8	0.03232	11.94140

Call Name	Leakage(nW)			
Cell Name	Min. Avg		Max.	
gf180mcu_osu_sc_9T_inv_8	0.00000	0.00596	0.00720	

Call Name	Timing Aug(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_inv_8	A->Y (FR)	0.03912	0.55929	9.96313

Call Name	Timing Aug(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_inv_8	A->Y (RF)	0.03045	0.35837	8.47809

Internal switching power(pJ) to Y rising:

Call Name	Immut		Power(pJ)	
Cell Name	Input	first	mid	last
6400 OT 1 0	A	0.17894	0.70851	2.04380
gf180mcu_osu_sc_9T_inv_8	A	0.00445	0.53241	1.86833

Internal switching power(pJ) to \boldsymbol{Y} falling:

Call Name	T4		Power(pJ)	
Cell Name	Input	first	mid	last
of 100 mon one of OT in the	A	-0.00375	0.49690	1.69140
gf180mcu_osu_sc_9T_inv_8	A	0.17077	0.67287	1.86807

GF180MCU_OSU_SC_9T_LSHIFDOWN

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
0	0
1	HiZ

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_lshifdown	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)	
Cell Name	A	Y	
gf180mcu_osu_sc_9T_lshifdown	0.00404	1.86454	

Call Name		Leakage(nW)	e(nW)	
Cell Name	Min. Avg		Max.	
gf180mcu_osu_sc_9T_lshifdown	0.00000	0.00098	0.00142	

Call Name	Timing Ang(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_lshifdown	A->Y (RR)	0.06895	0.14207	0.25494

Call Name	Timing Ang(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_lshifdown	A->Y (FF)	0.09893	0.70859	8.81878

Internal switching power(pJ) to Y falling:

Call Name	T4	T4		Power(pJ)	Power(pJ) mid last		
Cell Name	Input	first	mid	last			
-6100 OT 1-1-161	A	0.04918	0.13876	0.72690			
gf180mcu_osu_sc_9T_lshifdown	A	0.02721	0.11697	0.70521			

Passive power(pJ) for A rising (conditional):

Call Name	XX/h orr		Power(pJ)	
Cell Name	When	first	mid	last
-6100 OT 1-1-161	!Y	0.00460	0.09160	0.67577
gf180mcu_osu_sc_9T_lshifdown	!Y	0.02640	0.11364	0.69770

Passive power(pJ) for A falling (conditional):

Call Name	When		Power(pJ)	
Cell Name	vvnen	first	mid	last
of 190 man and an OT labifilation	!Y	0.02928	0.11895	0.70365
gf180mcu_osu_sc_9T_lshifdown	!Y	0.00730	0.09684	0.68168

GF180MCU_OSU_SC_9T_LSHIFUP

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT	OUTPUT
A	Y
x	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_lshifup	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)	Max Cap(pf)	
Cell Name	A	Y	
gf180mcu_osu_sc_9T_lshifup	0.00728	0.08462	

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_lshifup	0.00000	0.00000	0.00000	

Call Name	Timing Ana(Din)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
-£100 OT 1-1-12	A->Y (RR)	0.05111	0.94139	6.56566	
gf180mcu_osu_sc_9T_lshifup	A->Y (FR)	0.05111	0.94139	6.56566	

Passive Power Information

Passive power(pJ) for A rising (conditional):

Call Name	Whom	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_lshifup	!Y	0.04031	0.04062	0.03953	

Passive power(pJ) for A falling (conditional):

Call Name	XX/le oze	Power(pJ)			
Cell Name	When	first	mid	last	
-£190 OT 1-1-12	Y	-0.01548	-0.01544	-0.01600	
gf180mcu_osu_sc_9T_lshifup	!Y	-0.02369	-0.02395	-0.02405	

GF180MCU_OSU_SC_9T_MUX2_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

I	INPUT		OUTPUT
A	В	Sel	Y
0	0	X	0
0	1	0	0
x	1	1	1
1	X	0	1
1	0	1	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_mux2_1	0.00000

Pin Capacitance Information

Call Name		Max Cap(pf)		
Cell Name	A	В	Sel	Y
gf180mcu_osu_sc_9T_mux2_1	0.24485	0.24485	0.00808	0.24039

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_mux2_1	0.00000	0.00201	0.00207	

Delay Information Delay(ns) to Y rising (conditional):

Call Name	Timing Ang(Dir)	W/h are	Delay(ns)			
Cell Name	Timing Arc(Dir)	When	First	Mid	Last	
gf180mcu_osu_sc_9T_mux2_1	A->Y (RR)	-	0.02333	0.10898	0.80157	
	B->Y (RR)	-	0.02529	0.10981	0.80245	
	Sel->Y (RR)	(!A * B)	0.07429	0.23298	0.84092	
	Sel->Y (FR)	(A * !B)	0.05563	0.41382	2.58659	

Delay(ns) to Y falling (conditional):

Call Name	Timing Ang(Dir)	W/h are	Delay(ns)			
Cell Name	Timing Arc(Dir)	When	First	Mid	Last	
gf180mcu_osu_sc_9T_mux2_1	A->Y (FF)	-	0.02811	0.11506	0.84003	
	B->Y (FF)	-	0.02571	0.11405	0.83896	
	Sel->Y (FF)	(!A * B)	0.08564	0.41550	2.08689	
	Sel->Y (RF)	(A * !B)	0.04719	0.24437	1.46441	

Internal switching power(pJ) to Y rising (conditional):

C-II N	T4	Input When	Power(pJ)			
Cell Name	Input		first	mid	last	
	A	-	-0.03048	-0.03051	-0.03049	
	A	-	0.01297	0.01301	0.01300	
	В	-	-0.02387	-0.02386	-0.02388	
af100mon ogn av OT mon 2 1	В	-	0.02376	0.02377	0.02378	
gf180mcu_osu_sc_9T_mux2_1	Sel	(A * !B)	0.01192	0.10175	0.68712	
	Sel	(A * !B)	0.00927	0.09899	0.68458	
	Sel	(!A * B)	-0.01752	0.06847	0.65235	
	Sel	(!A * B)	0.05188	0.13862	0.72483	

Internal switching power(pJ) to Y falling (conditional):

Cell Name	I4	When		Power(pJ)			
Cell Name	Input	input when	first	mid	last		
	A	-	0.03048	0.03051	0.03054		
	A	-	-0.01297	-0.01301	-0.01300		
	В	-	0.02387	0.02389	0.02390		
of 190 may ago as OT may 2 1	В	-	-0.02376	-0.02377	-0.02378		
gf180mcu_osu_sc_9T_mux2_1	Sel	(A * !B)	0.01619	0.10391	0.68925		
	Sel	(A * !B)	0.01876	0.10709	0.69450		
	Sel	(!A * B)	0.06024	0.14739	0.73129		
	Sel	(!A * B)	-0.00917	0.07800	0.66226		

Passive power(pJ) for A rising (conditional):

		Power(pJ)		
Cell Name	When	first	mid	last
of 100 mon one of OT money 1	(B * Sel * Y) + (!B * Sel * !Y)	-0.00715	-0.00717	-0.00714
gf180mcu_osu_sc_9T_mux2_1	(B * Sel * Y) + (!B * Sel * !Y)	0.00469	0.00472	0.00470

Passive power(pJ) for A falling (conditional):

Call Name	W/h ove			
Cell Name	When	first	mid	last
-£100	(B * Sel * Y) + (!B * Sel * !Y)	0.00720	0.00717	0.00714
gf180mcu_osu_sc_9T_mux2_1	(B * Sel * Y) + (!B * Sel * !Y)	-0.00469	-0.00472	-0.00470

Passive power(pJ) for B rising (conditional):

Call Name	C.II Nama		Power(pJ)			
Cell Name	When	first	mid	last		
-£190	(A * !Sel * Y) + (!A * !Sel * !Y)	-0.00843	-0.00846	-0.00842		
gf180mcu_osu_sc_9T_mux2_1	(A * !Sel * Y) + (!A * !Sel * !Y)	0.00407	0.00409	0.00407		

Passive power(pJ) for B falling (conditional):

Call Name	W/h ore	Power(pJ)			
Cell Name	When	first	mid	last	
-£190	(A * !Sel * Y) + (!A * !Sel * !Y)	0.00843	0.00846	0.00842	
gf180mcu_osu_sc_9T_mux2_1	(A * !Sel * Y) + (!A * !Sel * !Y)	-0.00407	-0.00409	-0.00407	

Passive power(pJ) for Sel rising (conditional):

Cell Name	W/h or	Power(pJ)		
	When	first	mid	last
gf180mcu_osu_sc_9T_mux2_1	(A * B * Y)	-0.00072	0.08697	0.67095
	(A * B * Y)	0.03710	0.12490	0.70871
	(!A * !B * !Y)	-0.00068	0.08657	0.67087
	(!A * !B * !Y)	0.03358	0.12111	0.70522

Passive power(pJ) for Sel falling (conditional):

Cell Name	W/h ore			
	When	first	mid	last
gf180mcu_osu_sc_9T_mux2_1	(A * B * Y)	0.03787	0.12605	0.70976
	(A * B * Y)	-0.00007	0.08814	0.67191
	(!A * !B * !Y)	0.03459	0.12426	0.70857
	(!A * !B * !Y)	0.00021	0.08986	0.67424

GF180MCU_OSU_SC_9T_NAND2_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INP	UT	OUTPUT
A	В	Y
0	x	1
1	0	1
1	1	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_nand2_1	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)		Max Cap(pf)	
Cell Name	A	В	Y	
gf180mcu_osu_sc_9T_nand2_1	0.00404	0.00402	1.04725	

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_nand2_1	0.00000	0.00079	0.00118	

Call Name	Timing Aug(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First Mid		Last
-0100	A->Y (FR)	0.05391	0.73458	7.95705
gf180mcu_osu_sc_9T_nand2_1	B->Y (FR)	0.06585	0.76115	7.99777

C HN TO A CD: A		Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_nand2_1	A->Y (RF)	0.06150	0.77694	9.03370	
	B->Y (RF)	0.06617	0.63493	7.88183	

Internal switching power(pJ) to Y rising:

Cell Name	T4	Power(pJ)			
	Input	first	mid	last	
gf180mcu_osu_sc_9T_nand2_1	A	0.02371	0.06746	0.23835	
	A	0.00059	0.04432	0.21361	
	В	0.03513	0.08287	0.26647	
	В	0.00703	0.05453	0.23683	

Internal switching power(pJ) to Y falling:

Cell Name	T4	Power(pJ)			
	Input	first	last		
gf180mcu_osu_sc_9T_nand2_1	A	0.00588	0.04849	0.21421	
	A	0.02905	0.07189	0.23791	
	В	0.00459	0.04928	0.23854	
	В	0.03280	0.07788	0.26777	

Passive power(pJ) for A rising (conditional):

Call Name	XX/le ove	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_nand2_1	(!B * Y)	-0.01402	-0.01412	-0.01414	
	(!B * Y)	0.00188	0.00188	0.00178	

Passive power(pJ) for A falling (conditional):

Call Name	XX/le ove	Power(pJ)					
Cell Name	When	first	mid	last			
gf180mcu_osu_sc_9T_nand2_1	(!B * Y)	0.01426	0.01431	0.01418			
	(!B * Y)	-0.00177	-0.00177	-0.00175			

Passive power(pJ) for B rising (conditional):

Call Name	11 /le o re		Power(pJ)	
Cell Name	When	first	mid	last
gf180mcu_osu_sc_9T_nand2_1	(!A * Y)	-0.01352	-0.01358	-0.01352
	(!A * Y)	0.00650	0.00654	0.00648

Passive power(pJ) for B falling (conditional):

Call Name	Whee		Power(pJ)			
Cell Name	When	first	mid	last		
0.00 O.T. 10.4	(!A * Y)	0.01367	0.01367	0.01355		
gf180mcu_osu_sc_9T_nand2_1	(!A * Y)	-0.00639	-0.00652	-0.00647		

GF180MCU_OSU_SC_9T_NOR2_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT		OUTPUT
A	В	Y
0	0	1
x	1	0
1	X	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_nor2_1	0.00000

Pin Capacitance Information

Call Name	Pin C	ap(pf)	Max Cap(pf)	
Cell Name	A	В	Y	
gf180mcu_osu_sc_9T_nor2_1	0.00398	0.00404	0.78121	

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_nor2_1	0.00000	0.00084	0.00180	

Call Name	Timing Ang(Div)	Delay(ns)		
Cell Name	Timing Arc(Dir)	First	Last	
gf180mcu_osu_sc_9T_nor2_1	A->Y (FR)	0.09194	0.83618	8.71519
	B->Y (FR)	0.07001	0.97901	9.85004

Cell Name	Timing Arc(Dir)	Delay(ns)			
		First	Mid	Last	
gf180mcu_osu_sc_9T_nor2_1	A->Y (RF)	0.05934	0.50696	5.37174	
	B->Y (RF)	0.04320	0.46109	5.29400	

Internal switching power(pJ) to Y rising:

Cell Name	Input	Power(pJ)			
		first	mid	last	
gf180mcu_osu_sc_9T_nor2_1	A	0.03440	0.08071	0.32284	
	A	0.00253	0.04853	0.29057	
	В	0.02602	0.07081	0.26848	
	В	0.00354	0.04821	0.24589	

Internal switching power(pJ) to Y falling:

Call Name	Input	Power(pJ)			
Cell Name		first	mid	last	
gf180mcu_osu_sc_9T_nor2_1	A	0.01134	0.05559	0.25578	
	A	0.04303	0.08747	0.29150	
	В	0.00064	0.04168	0.21929	
	В	0.02314	0.06435	0.24590	

Passive power(pJ) for A rising (conditional):

Cell Name	When	Power(pJ)			
		first	mid	last	
gf180mcu_osu_sc_9T_nor2_1	(B * !Y)	-0.01310	-0.01344	-0.01336	
	(B * !Y)	0.00654	0.00659	0.00651	

Passive power(pJ) for A falling (conditional):

Cell Name	When	Power(pJ)			
		first	mid	last	
gf180mcu_osu_sc_9T_nor2_1	(B * !Y)	0.01341	0.01344	0.01336	
	(B * !Y)	-0.00648	-0.00652	-0.00649	

Passive power(pJ) for B rising (conditional):

Call Name	XX/la o ra	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_nor2_1	(A * !Y)	-0.00461	-0.00456	-0.00451	
	(A * !Y)	0.00792	0.00785	0.00780	

Passive power(pJ) for B falling (conditional):

Call Name	11 /1- 0	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_nor2_1	(A * !Y)	0.00488	0.00484	0.00460	
	(A * !Y)	-0.00756	-0.00760	-0.00780	

GF180MCU_OSU_SC_9T_OAI21_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT		OUTPUT	
A0	A1	В	Y
0	0	X	1
x	1	0	1
X	1	1	0
1	X	0	1
1	x	1	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_oai21_1	0.00000

Pin Capacitance Information

Call Name		Pin Cap(pf)	Max Cap(pf)	
Cell Name	A0	A1	В	Y
gf180mcu_osu_sc_9T_oai21_1	0.00395	0.00402	0.00404	0.77902

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_oai21_1	0.00000	0.00097	0.00152	

C.II V	Timin Am (Din)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_oai21_1	A0->Y (FR)	0.12840	0.85377	8.59381	
	A1->Y (FR)	0.10356	0.99678	9.74633	
	B->Y (FR)	0.05358	0.68184	6.75524	

C.II N	Timing Ang(Div)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_oai21_1	A0->Y (RF)	0.10041	0.58269	6.13624	
	A1->Y (RF)	0.07349	0.53463	6.04630	
	B->Y (RF)	0.08984	0.73943	7.41956	

Internal switching power(pJ) to Y rising:

Cell Name	I4	Power(pJ)			
	Input	first	mid	last	
gf180mcu_osu_sc_9T_oai21_1	A0	0.04753	0.08644	0.28834	
	A0	0.00947	0.04817	0.25008	
	A1	0.03846	0.07638	0.23966	
	A1	0.00976	0.04758	0.21166	
	В	0.02356	0.07591	0.30431	
	В	0.00040	0.05241	0.28053	

Internal switching power(pJ) to Y falling:

Cell Name	T4	Power(pJ)			
	Input	first	mid	last	
gf180mcu_osu_sc_9T_oai21_1	A0	0.01748	0.05472	0.23887	
	A0	0.05552	0.09284	0.27682	
	A1	0.00577	0.04052	0.20627	
	A1	0.03445	0.06937	0.23499	
	В	0.00617	0.05579	0.27437	
	В	0.02930	0.07900	0.29751	

Passive power(pJ) for A0 rising (conditional):

Cell Name	VV/h o z	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_oai21_1	(A1 * B * !Y)	-0.01308	-0.01344	-0.01338	
	(A1 * B * !Y)	0.00653	0.00659	0.00651	
	(A1 * !B * Y)	-0.01314	-0.01344	-0.01336	
	(A1 * !B * Y)	0.00651	0.00659	0.00651	
	(!A1 * !B * Y)	-0.01352	-0.01357	-0.01352	
	(!A1 * !B * Y)	0.00652	0.00648	0.00645	

Passive power(pJ) for A0 falling (conditional):

Cell Name	VV/h o re	Power(pJ)			
Cen Name	When	first	mid	last	
gf180mcu_osu_sc_9T_oai21_1	(A1 * B * !Y)	0.01351	0.01344	0.01338	
	(A1 * B * !Y)	-0.00648	-0.00652	-0.00649	
	(A1 * !B * Y)	0.01349	0.01344	0.01336	
	(A1 * !B * Y)	-0.00650	-0.00653	-0.00649	
	(!A1 * !B * Y)	0.01358	0.01366	0.01355	
	(!A1 * !B * Y)	-0.00637	-0.00648	-0.00645	

Passive power(pJ) for A1 rising (conditional):

Cell Name	W/L or			
	When	first mid		last
gf180mcu_osu_sc_9T_oai21_1	(A0 * B * !Y)	-0.00461	-0.00456	-0.00451
	(A0 * B * !Y)	0.00789	0.00785	0.00780
	(!B * Y)	-0.01311	-0.01342	-0.01331
	(!B * Y)	0.00654	0.00652	0.00651

Passive power(pJ) for A1 falling (conditional):

Cell Name	XX/b are			
	When	first mid		last
gf180mcu_osu_sc_9T_oai21_1	(A0 * B * !Y)	0.00488	0.00484	0.00460
	(A0 * B * !Y)	-0.00752	-0.00759	-0.00780
	(!B * Y)	0.01331	0.01344	0.01331
	(!B * Y)	-0.00650	-0.00652	-0.00649

Passive power(pJ) for B rising (conditional):

Call Name	W/h or	Power(pJ)			
Cell Name	When		mid	last	
gf180mcu_osu_sc_9T_oai21_1	(!A0 * !A1 * Y)	-0.01396	-0.01405	-0.01413	
	(!A0 * !A1 * Y)	0.00194	0.00194	0.00179	

Passive power(pJ) for B falling (conditional):

C.II Nama	W/h or		Power(pJ)		
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_oai21_1	(!A0 * !A1 * Y)	0.01413	0.01430	0.01418	
	(!A0 * !A1 * Y)	-0.00174	-0.00177	-0.00175	

GF180MCU_OSU_SC_9T_OAI22_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INF	PUT	OUTPUT
A0	A1	Y
0	0	1
x	1	0
1	x	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_oai22_1	0.00000

Pin Capacitance Information

Call Name	Pin C	ap(pf)	Max Cap(pf)	
Cell Name	A0	A 1	Y	
gf180mcu_osu_sc_9T_oai22_1	0.00398	0.00404	0.74002	

Cell Name	Leakage(nW)			
	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_oai22_1	0.00000	0.00145	0.00180	

C III	Timing Ang(Din)		Delay(ns)	y(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last	
4400	A0->Y (FR)	0.14597	0.86374	8.36791	
gf180mcu_osu_sc_9T_oai22_1	A1->Y (FR)	0.12121	1.00853	9.50550	

Call Name	Timing Ana(Div)	Delay(ns)		
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_oai22_1	A0->Y (RF)	0.17477	0.71890	7.27315
	A1->Y (RF)	0.13099	0.65830	7.15756

Internal switching power(pJ) to Y rising:

Cell Name	T4	Power(pJ)			
	Input	first	mid	last	
gf180mcu_osu_sc_9T_oai22_1	A0	0.05343	0.09465	0.32290	
	A0	0.02142	0.06238	0.28961	
	A1	0.04421	0.08494	0.26988	
	A1	0.02177	0.06233	0.24719	

Internal switching power(pJ) to Y falling:

Cell Name	T4	Power(pJ)			
	Input	first	mid	last	
gf180mcu_osu_sc_9T_oai22_1	A0	2.47139	2.41090	1.73828	
	A0	2.50280	2.44232	1.76983	
	A1	2.45533	2.38805	1.69936	
	A1	2.47758	2.41041	1.72170	

Passive power(pJ) for A0 rising (conditional):

Call Name	Call Name When		Power(pJ)			
Cell Name	When	first	mid	last		
gf180mcu_osu_sc_9T_oai22_1	(A1 * !Y)	-0.01308	-0.01345	-0.01338		
	(A1 * !Y)	0.00653	0.00659	0.00651		

Passive power(pJ) for A0 falling (conditional):

Call Name	Whon	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_oai22_1	(A1 * !Y)	0.01342	0.01345	0.01338	
	(A1 * !Y)	-0.00648	-0.00652	-0.00649	

Passive power(pJ) for A1 rising (conditional):

Call Name	Wilson	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_oai22_1	(A0 * !Y)	-0.00461	-0.00456	-0.00451	
	(A0 * !Y)	0.00790	0.00785	0.00780	

Passive power(pJ) for A1 falling (conditional):

Call Name	Wilson	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_oai22_1	(A0 * !Y)	0.00487	0.00485	0.00460	
	(A0 * !Y)	-0.00750	-0.00759	-0.00780	

GF180MCU_OSU_SC_9T_OAI31_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT			OUTPUT	
A0	A1	A2	В	Y
0	0	0	x	1
0	x	1	0	1
0	x	1	1	0
x	1	X	0	1
x	1	X	1	0
1	X	X	0	1
1	x	X	1	0

Footprint

Cell Name	Area	
gf180mcu_osu_sc_9T_oai31_1	0.00000	

Pin Capacitance Information

Call Name	Pin Cap(pf)				Max Cap(pf)
Cell Name	A0	A1	A2	В	Y
gf180mcu_osu_sc_9T_oai31_1	0.00395	0.00402	0.00395	0.00404	0.52736

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_oai31_1	0.00000	0.00103	0.00216	

Call Name	Timing Ang(Dir.)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_oai31_1	A0->Y (FR)	0.19501	1.03447	8.96826	
	A1->Y (FR)	0.13793	1.11756	9.77263	
	A2->Y (FR)	0.22160	0.94893	8.21896	
	B->Y (FR)	0.05347	0.61238	5.45578	

C.II V	T:: A(D:)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_oai31_1	A0->Y (RF)	0.10829	0.48084	4.34351	
	A1->Y (RF)	0.07891	0.43324	4.25359	
	A2->Y (RF)	0.11836	0.51714	4.44466	
	B->Y (RF)	0.10307	0.68762	5.76240	

Internal switching power(pJ) to Y rising:

Cell Name	T4	Power(pJ)			
Cen Name	Input	first	mid	last	
	A0	0.05132	0.08226	0.27359	
	A0	0.01280	0.04368	0.23486	
	A1	0.04210	0.07622	0.24306	
-£100 OT:21 1	A1	0.01295	0.04697	0.21392	
gf180mcu_osu_sc_9T_oai31_1	A2	0.06079	0.09246	0.33351	
	A2	0.01280	0.04438	0.28543	
	В	0.02351	0.08124	0.36876	
	В	0.00035	0.05802	0.34435	

Internal switching power(pJ) to Y falling:

Cell Name	T4	Power(pJ)			
Cen Name	Input	first	mid	last	
	A0	0.01898	0.04904	0.22780	
	A0	0.05749	0.08768	0.26747	
	A1	0.00610	0.03629	0.19824	
of100man agn ag 0T agi21 1	A1	0.03541	0.06554	0.22852	
gf180mcu_osu_sc_9T_oai31_1	A2	0.03002	0.06156	0.26133	
	A2	0.07745	0.10917	0.31025	
	В	0.00626	0.06127	0.33656	
	В	0.02939	0.08444	0.36027	

Passive power(pJ) for A0 rising (conditional):

Call Name	XX/In our	Power(pJ))
Cell Name	When	first	mid	last
	(A1 * B * !Y) + (!A1 * A2 * B * !Y)	-0.00839	-0.00849	-0.00845
gf180mcu_osu_sc_9T_oai31_1	(A1 * B * !Y) + (!A1 * A2 * B * !Y)	0.00659	0.00653	0.00650
	(A1 * !B * Y)	-0.00961	-0.00972	-0.00964
	(A1 * !B * Y)	0.00658	0.00654	0.00651
	(!A1 * !B * Y)	-0.01309	-0.01339	-0.01327
	(!A1 * !B * Y)	0.00653	0.00655	0.00651

Passive power(pJ) for A0 falling (conditional):

Cell Name	XX/leave	Power(pJ))
Cen Name	When	first	mid	last
gf180mcu_osu_sc_9T_oai31_1	(A1 * B * !Y) + (!A1 * A2 * B * !Y)	0.00839	0.00849	0.00845
	(A1 * B * !Y) + (!A1 * A2 * B * !Y)	-0.00645	-0.00652	-0.00649
	$(\mathbf{A1} * \mathbf{!B} * \mathbf{Y})$	0.00961	0.00972	0.00964
	(A1 * !B * Y)	-0.00646	-0.00654	-0.00649
	(!A1 * !B * Y)	0.01324	0.01339	0.01327
	(!A1 * !B * Y)	-0.00648	-0.00655	-0.00649

Passive power(pJ) for A1 rising (conditional):

Cell Name	XX/I			
Cell Name	When	first	mid	last
	(A0 * B * !Y)	-0.00457	-0.00456	-0.00451
	(A0 * B * !Y)	0.00785	0.00785	0.00780
	(A0 * !B * Y)	-0.01303	-0.01342	-0.01333
2f100man agu ag 0T agi21 1	(A0 * !B * Y)	0.00649	0.00652	0.00651
gf180mcu_osu_sc_9T_oai31_1	(!A0 * A2 * B * !Y)	-0.00454	-0.00449	-0.00442
	(!A0 * A2 * B * !Y)	0.00789	0.00785	0.00780
	(!A0 * !B * Y)	-0.01207	-0.01283	-0.01279
	(!A0 * !B * Y)	0.00652	0.00650	0.00651

Passive power(pJ) for A1 falling (conditional):

Call Name	XX/le ore			
Cell Name	When	first mid		last
	(A0 * B * !Y)	0.00487	0.00484	0.00460
	(A0 * B * !Y)	-0.00751	-0.00759	-0.00780
	(A0 * !B * Y)	0.01327	0.01345	0.01333
af100may agy ag 0T ag;21 1	(A0 * !B * Y)	-0.00646	-0.00652	-0.00649
gf180mcu_osu_sc_9T_oai31_1	(!A0 * A2 * B * !Y)	0.00498	0.00494	0.00442
	(!A0 * A2 * B * !Y)	-0.00698	-0.00709	-0.00775
	(!A0 * !B * Y)	0.01289	0.01283	0.01279
	(!A0 * !B * Y)	-0.00648	-0.00650	-0.00649

Passive power(pJ) for A2 rising (conditional):

Cell Name	XX/In over	Power(pJ)		
	When	first	mid	last
	(A0 * A1 * B * !Y)	-0.01312	-0.01344	-0.01338
	(A0 * A1 * B * !Y)	0.00649	0.00659	0.00651
	(A0 * !B * Y)	-0.01322	-0.01347	-0.01339
	(A0 * !B * Y)	0.00657	0.00659	0.00651
gf180mcu_osu_sc_9T_oai31_1	(A0 * !A1 * B * !Y) + (!A0 * A1 * B * !Y)	-0.01311	-0.01344	-0.01338
	(A0 * !A1 * B * !Y) + (!A0 * A1 * B * !Y)	0.00649	0.00659	0.00651
	(!A0 * A1 * !B * Y)	-0.01254	-0.01316	-0.01302
	(!A0 * A1 * !B * Y)	0.00659	0.00657	0.00651
	(!A0 * !A1 * !B * Y)	-0.01349	-0.01357	-0.01352
	(!A0 * !A1 * !B * Y)	0.00645	0.00646	0.00644

Passive power(pJ) for A2 falling (conditional):

Cell Name	When	Power(pJ)			
Cen Name	when	first	mid	last	
	(A0 * A1 * B * !Y)	0.01351	0.01344	0.01338	
	(A0 * A1 * B * !Y)	-0.00649	-0.00652	-0.00649	
	(A0 * !B * Y)	0.01351	0.01349	0.01339	
gf180mcu_osu_sc_9T_oai31_1	(A0 * !B * Y)	-0.00649	-0.00654	-0.00649	
	(A0 * !A1 * B * !Y) + (!A0 * A1 * B * !Y)	0.01350	0.01344	0.01338	
	(A0 * !A1 * B * !Y) + (!A0 * A1 * B * !Y)	-0.00649	-0.00652	-0.00649	
	(!A0 * A1 * !B * Y)	0.01302	0.01316	0.01302	
	(!A0 * A1 * !B * Y)	-0.00650	-0.00653	-0.00649	
	(!A0 * !A1 * !B * Y)	0.01355	0.01360	0.01355	
	(!A0 * !A1 * !B * Y)	-0.00636	-0.00646	-0.00644	

Passive power(pJ) for B rising (conditional):

Call Name	Where	Power(pJ)		
Cell Name	When	first	mid	last
gf180mcu_osu_sc_9T_oai31_1	(!A0 * !A1 * !A2 * Y)	-0.01389	-0.01398	-0.01412
	(!A0 * !A1 * !A2 * Y)	0.00200	0.00200	0.00180

Passive power(pJ) for B falling (conditional):

Call Name	W/h ore	Power(pJ)		
Cell Name	When	first	mid	last
gf180mcu_osu_sc_9T_oai31_1	(!A0 * !A1 * !A2 * Y)	0.01413	0.01430	0.01418
	(!A0 * !A1 * !A2 * Y)	-0.00174	-0.00177	-0.00175

GF180MCU_OSU_SC_9T_OR2_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT		OUTPUT
A	В	Y
0	0	0
X	1	1
1	X	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_or2_1	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)		Max Cap(pf)	
Cell Name	A	В	Y	
gf180mcu_osu_sc_9T_or2_1	0.00404	0.00398	1.55634	

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_or2_1	0.00000	0.00166	0.00239	

Call Name	Timing Aug(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
9100	A->Y (RR)	0.09111	0.44583	6.27342
gf180mcu_osu_sc_9T_or2_1	B->Y (RR)	0.10926	0.54557	6.87422

Call Name	Timing Aug(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
-£100 OT2 1	A->Y (FF)	0.13197	0.83526	8.44438
gf180mcu_osu_sc_9T_or2_1	B->Y (FF)	0.15549	0.76444	7.98435

Internal switching power(pJ) to Y rising:

Call Name	Input		Power(pJ)	
Cell Name		first	mid	last
gf180mcu_osu_sc_9T_or2_1	A	0.02158	0.08977	0.55597
	A	0.04409	0.11227	0.57669
	В	0.03263	0.10988	0.66201
	В	0.06449	0.14162	0.69352

Internal switching power(pJ) to Y falling:

Call Name	Turnut		Power(pJ)	
Cell Name	Input	first	mid	last
gf180mcu_osu_sc_9T_or2_1	A	0.04804	0.11729	0.57924
	A	0.02543	0.09489	0.55677
	В	0.05681	0.13034	0.68094
	В	0.02480	0.09841	0.64951

Passive power(pJ) for A rising (conditional):

Call Name	When		Power(pJ)	
Cell Name		first	mid	last
gf180mcu_osu_sc_9T_or2_1	(B * Y)	-0.00462	-0.00456	-0.00451
	(B * Y)	0.00789	0.00785	0.00780

Passive power(pJ) for A falling (conditional):

Call Name	When		Power(pJ)	
Cell Name		first	mid	last
gf180mcu_osu_sc_9T_or2_1	(B * Y)	0.00488	0.00485	0.00460
	(B * Y)	-0.00753	-0.00759	-0.00780

Passive power(pJ) for B rising (conditional):

Call Name	XX/la o va		Power(pJ)	
Cell Name	When	first	mid	last
gf180mcu_osu_sc_9T_or2_1	(A * Y)	-0.01308	-0.01345	-0.01338
	(A * Y)	0.00653	0.00659	0.00651

Passive power(pJ) for B falling (conditional):

Call Name	VVII- o		Power(pJ)	
Cell Name	When	first	mid	last
gf180mcu_osu_sc_9T_or2_1	(A * Y)	0.01349	0.01345	0.01338
	(A * Y)	-0.00649	-0.00652	-0.00649

GF180MCU_OSU_SC_9T_TBUF_16

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

	INPUT		OUTPUT
A	EN	EN_BAR	Y
0	x	0	0
0	x	1	1
1	X	X	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_tbuf_16	0.00000

Pin Capacitance Information

Call Name		Max Cap(pf)		
Cell Name	A	EN	EN_BAR	Y
gf180mcu_osu_sc_9T_tbuf_16	0.00395	0.00132	0.00272	24.97480

Call Name	Leakage(nW)				
Cell Name	Min. Avg Max.				
gf180mcu_osu_sc_9T_tbuf_16	0.00000	1583270.00000	4460640.00000		

Call Name	Timing Ana(Div)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_tbuf_16	A->Y (RR)	0.55361	0.92033	8.11300
	EN->Y (RR)	0.53575	0.93744	6.16560

Call Name	Timing Ang(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
6100 OT 41 6 1 C	A->Y (FF)	0.68314	1.17977	8.94805
gf180mcu_osu_sc_9T_tbuf_16	EN_BAR->Y (FF)	0.65180	1.18358	6.77083

Internal switching power(pJ) to Y rising:

Call Name	Input		Power(pJ)	
Cell Name		first	mid	last
gf180mcu_osu_sc_9T_tbuf_16	A	1.10049	0.87371	1.14055
	A	1.13674	0.90772	1.16769
	EN	1.10914	0.93883	0.74067
	EN	1.12681	0.95510	0.72587

Internal switching power(pJ) to Y falling:

Call Name	Input -		Power(pJ)	
Cell Name		first	mid	last
gf180mcu_osu_sc_9T_tbuf_16	A	1.34740	1.04732	1.16581
	A	1.31113	1.00988	1.12983
	EN_BAR	1.33599	1.12754	0.74701
	EN_BAR	1.31557	1.10563	0.74109

Passive power(pJ) for A rising (conditional):

Call Name	XVIII ozo		Power(pJ)	
Cell Name	When	first	mid	last
gf180mcu_osu_sc_9T_tbuf_16	(EN * EN_BAR * Y)	-0.01422	-0.01411	-0.01365
	(EN * EN_BAR * Y)	0.00541	0.00542	0.00536
	(!EN * EN_BAR)	-0.01321	-0.01340	-0.01335
	(!EN * EN_BAR)	0.00653	0.00646	0.00646
	(!EN * !EN_BAR * !Y)	-0.01121	-0.01181	-0.01171
	(!EN * !EN_BAR * !Y)	0.00862	0.00750	0.00702

Passive power(pJ) for A falling (conditional):

Call Name	W/h ozo		Power(pJ)	
Cell Name	When	first	mid	last
gf180mcu_osu_sc_9T_tbuf_16	(EN * EN_BAR * Y)	0.01498	0.01411	0.01365
	(EN * EN_BAR * Y)	-0.00494	-0.00542	-0.00536
	(!EN * EN_BAR)	0.01350	0.01350	0.01335
	(!EN * EN_BAR)	-0.00639	-0.00646	-0.00646
	(!EN * !EN_BAR * !Y)	0.01184	0.01181	0.01171
	(!EN * !EN_BAR * !Y)	-0.00804	-0.00750	-0.00702

Passive power(pJ) for EN rising (conditional):

Call Name	C-II N		Power(pJ)			
Cell Name	When	first	mid	last		
	(EN_BAR * Y)	-0.00210	-0.00089	-0.00035		
	(EN_BAR * Y)	0.00442	0.00446	0.00441		
	(A * !EN_BAR * Y)	-0.00210	-0.00089	-0.00035		
of 190 may say so OT thuf 16	(A * !EN_BAR * Y)	0.00442	0.00445	0.00441		
gf180mcu_osu_sc_9T_tbuf_16	(!A * EN_BAR * !Y)	-0.00022	-0.00022	-0.00027		
	(!A * EN_BAR * !Y)	0.00217	0.00216	0.00212		
	(!A * !EN_BAR * !Y)	-0.00050	-0.00050	-0.00061		
	(!A * !EN_BAR * !Y)	0.00190	0.00188	0.00178		

Passive power(pJ) for EN falling (conditional):

Call Name	When			
Cell Name	vv nen	first	mid	last
	(EN_BAR * Y)	0.00296	0.00089	0.00035
	(EN_BAR * Y)	-0.00354	-0.00446	-0.00441
	(A * !EN_BAR * Y)	0.00296	0.00089	0.00035
-6100 OT 416 16	(A * !EN_BAR * Y)	-0.00354	-0.00445	-0.00441
gf180mcu_osu_sc_9T_tbuf_16	(!A * EN_BAR * !Y)	0.00029	0.00028	0.00028
	(!A * EN_BAR * !Y)	-0.00213	-0.00210	-0.00209
	(!A * !EN_BAR * !Y)	0.00064	0.00063	0.00063
	(!A * !EN_BAR * !Y)	-0.00179	-0.00176	-0.00174

Passive power(pJ) for EN_BAR rising (conditional):

Call Name	W/h or	Power(pJ)			
Cell Name	When	first	mid	last	
	(A * EN * Y)	-0.00458	-0.00454	-0.00451	
	(A * EN * Y)	0.00130	0.00129	0.00129	
	(A * !EN * Y)	-0.00566	-0.00561	-0.00558	
af180may agy so 0T thuf 16	(A * !EN * Y)	0.00021	0.00021	0.00021	
gf180mcu_osu_sc_9T_tbuf_16	(!EN * !Y)	-0.00712	-0.00715	-0.00708	
	(!EN * !Y)	0.00542	0.00598	0.00613	
	(!A * EN * !Y)	-0.00946	-0.01029	-0.01018	
	(!A * EN * !Y)	0.00396	0.00156	0.00066	

Passive power(pJ) for EN_BAR falling (conditional):

C-II N	When	Power(pJ)			
Cell Name		first	mid	last	
	(A * EN * Y)	0.00491	0.00484	0.00460	
	(A * EN * Y)	-0.00100	-0.00102	-0.00129	
	(A * !EN * Y)	0.00574	0.00570	0.00570	
of 100 many ago OT 4huf 16	(A * !EN * Y)	-0.00016	-0.00016	-0.00020	
gf180mcu_osu_sc_9T_tbuf_16	(!EN * !Y)	0.00712	0.00715	0.00708	
	(!EN * !Y)	-0.00542	-0.00571	-0.00565	
	(!A * EN * !Y)	0.01022	0.01029	0.01018	
	(!A * EN * !Y)	-0.00333	-0.00156	-0.00066	

GF180MCU_OSU_SC_9T_TBUF_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

	INPUT		OUTPUT
A	EN	EN_BAR	Y
0	x	0	0
0	x	1	1
1	x	X	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_tbuf_1	0.00000

Pin Capacitance Information

Call Name		Pin Cap(pf	Max Cap(pf)	
Cell Name	A	EN	EN_BAR	Y
gf180mcu_osu_sc_9T_tbuf_1	0.00395	0.00132	0.00275	1.55772

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_tbuf_1	0.00000	98954.60000	278790.00000	

Call Name	Timing Arc(Dir)	Delay(ns)		
Cell Name		First	Mid	Last
gf180mcu_osu_sc_9T_tbuf_1	A->Y (RR)	0.14941	0.59417	7.13501
	EN->Y (RR)	0.13255	0.34109	3.79007

Call Name	Timing Arc(Dir)		Delay(ns)	
Cell Name		First	Mid	Last
0100 OT (1 0 4	A->Y (FF)	0.17413	0.77127	7.90358
gf180mcu_osu_sc_9T_tbuf_1	EN_BAR->Y (FF)	0.14475	0.44159	3.85679

Internal switching power(pJ) to Y rising:

Cell Name	T4	Power(pJ)			
Cen Name	Input	first	mid	last	
gf180mcu_osu_sc_9T_tbuf_1	A	0.03337	0.10287	0.63002	
	A	0.06966	0.13902	0.66557	
	EN	0.04295	0.04598	0.04694	
	EN	0.06065	0.06360	0.06390	

Internal switching power(pJ) to Y falling:

Call Nama	I4	Power(pJ)			
Cell Name	Input	first	mid	last	
gf180mcu_osu_sc_9T_tbuf_1	A	0.06562	0.13353	0.66068	
	A	0.02920	0.09722	0.62505	
	EN_BAR	0.05508	0.05796	0.05791	
	EN_BAR	0.03456	0.03753	0.03753	

Passive power(pJ) for A rising (conditional):

Cell Name	W/h ove	Power(pJ)			
Cen Name	When	first	mid	last	
	(EN * EN_BAR * Y)	-0.01343	-0.01360	-0.01348	
	(EN * EN_BAR * Y)	0.00616	0.00610	0.00610	
of 190 mean earn as OT thruf 1	(!EN * EN_BAR)	-0.01321	-0.01341	-0.01335	
gf180mcu_osu_sc_9T_tbuf_1	(!EN * EN_BAR)	0.00653	0.00646	0.00646	
	(!EN * !EN_BAR * !Y)	-0.01202	-0.01283	-0.01270	
	(!EN * !EN_BAR * !Y)	0.00717	0.00670	0.00660	

Passive power(pJ) for A falling (conditional):

Cell Name	W/h ove	Power(pJ)			
	When	first	mid	last	
	(EN * EN_BAR * Y)	0.01405	0.01360	0.01348	
	(EN * EN_BAR * Y)	-0.00572	-0.00610	-0.00610	
2400	(!EN * EN_BAR)	0.01350	0.01350	0.01335	
gf180mcu_osu_sc_9T_tbuf_1	(!EN * EN_BAR)	-0.00639	-0.00646	-0.00646	
	(!EN * !EN_BAR * !Y)	0.01281	0.01283	0.01270	
	(!EN * !EN_BAR * !Y)	-0.00675	-0.00670	-0.00660	

Passive power(pJ) for EN rising (conditional):

Cell Name	W/h ore	Power(pJ)			
	When	first	mid	last	
	(EN_BAR * Y)	-0.00044	-0.00022	-0.00015	
	(EN_BAR * Y)	0.00612	0.00614	0.00608	
	(A * !EN_BAR * Y)	-0.00044	-0.00022	-0.00015	
of 190 may ago at thuf 1	(A * !EN_BAR * Y)	0.00612	0.00614	0.00607	
gf180mcu_osu_sc_9T_tbuf_1	(!A * EN_BAR * !Y)	-0.00027	-0.00027	-0.00031	
	(!A * EN_BAR * !Y)	0.00214	0.00212	0.00208	
	(!A * !EN_BAR * !Y)	-0.00050	-0.00051	-0.00061	
	(!A * !EN_BAR * !Y)	0.00189	0.00187	0.00178	

Passive power(pJ) for EN falling (conditional):

Cell Name	XX/I	Power(pJ)			
	When	first	mid	last	
	(EN_BAR * Y)	0.00107	0.00022	0.00015	
	(EN_BAR * Y)	-0.00531	-0.00614	-0.00608	
	(A * !EN_BAR * Y)	0.00106	0.00022	0.00015	
of 100 mon on on OT thurs 1	(A * !EN_BAR * Y)	-0.00530	-0.00614	-0.00607	
gf180mcu_osu_sc_9T_tbuf_1	(!A * EN_BAR * !Y)	0.00033	0.00033	0.00033	
	(!A * EN_BAR * !Y)	-0.00205	-0.00202	-0.00200	
	(!A * !EN_BAR * !Y)	0.00063	0.00063	0.00063	
	(!A * !EN_BAR * !Y)	-0.00179	-0.00176	-0.00175	

Passive power(pJ) for EN_BAR rising (conditional):

Cell Name	XX/1	Power(pJ)			
Ceii Name	When	first	mid	last	
	(A * EN * Y)	-0.00452	-0.00454	-0.00451	
	(A * EN * Y)	0.00128	0.00129	0.00129	
	(A * !EN * Y)	-0.00547	-0.00542	-0.00539	
of 100 men and a OT thruf 1	(A * !EN * Y)	0.00033	0.00032	0.00032	
gf180mcu_osu_sc_9T_tbuf_1	(!EN * !Y)	-0.00932	-0.00926	-0.00842	
	(!EN * !Y)	0.00238	0.00239	0.00252	
	(!A * EN * !Y)	-0.01183	-0.01272	-0.01265	
	(!A * EN * !Y)	0.00140	0.00045	0.00027	

Passive power(pJ) for EN_BAR falling (conditional):

Cell Name	XX/I	Power(pJ)			
Cell Name	When	first	mid	last	
	(A * EN * Y)	0.00489	0.00483	0.00460	
	(A * EN * Y)	-0.00101	-0.00103	-0.00129	
	(A * !EN * Y)	0.00729	0.00798	0.01307	
af100man agn ag 0T thuf 1	(A * !EN * Y)	0.00141	0.00215	0.00721	
gf180mcu_osu_sc_9T_tbuf_1	(!EN * !Y)	0.01253	0.01194	0.00842	
	(!EN * !Y)	0.00194	0.00146	-0.00199	
	(!A * EN * !Y)	0.01274	0.01272	0.01265	
	(!A * EN * !Y)	-0.00078	-0.00045	-0.00027	

GF180MCU_OSU_SC_9T_TBUF_2

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

	INPUT		OUTPUT	
A	EN	EN_BAR	Y	
0	x	0	0	
0	x	1	1	
1	X	X	1	

Footprint

Cell Name	Area	
gf180mcu_osu_sc_9T_tbuf_2	0.00000	

Pin Capacitance Information

Call Name		Max Cap(pf)		
Cell Name	A	EN	EN_BAR	Y
gf180mcu_osu_sc_9T_tbuf_2	0.00395	0.00133	0.00273	3.10304

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_tbuf_2	0.00000	197909.00000	557580.00000	

Call Name	Timing Ana(Din)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_tbuf_2	A->Y (RR)	0.17631	0.55897	7.18623	
	EN->Y (RR)	0.15922	0.34684	4.02272	

Call Name	Timing Ang(Din)	Delay(ns)		
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_tbuf_2	A->Y (FF)	0.20650	0.74722	7.96694
	EN_BAR->Y (FF)	0.17653	0.48072	4.17012

Internal switching power(pJ) to Y rising:

Call Name	Input	Power(pJ)			
Cell Name		first	mid	last	
gf180mcu_osu_sc_9T_tbuf_2	A	0.06111	0.12783	0.65344	
	A	0.09740	0.16397	0.68834	
	EN	0.07059	0.07710	0.08152	
	EN	0.08828	0.09466	0.09397	

Internal switching power(pJ) to Y falling:

C.II N	Input	Power(pJ)			
Cell Name		first	mid	last	
gf180mcu_osu_sc_9T_tbuf_2	A	0.09545	0.15983	0.68290	
	A	0.05905	0.12372	0.64778	
	EN_BAR	0.08458	0.09073	0.08654	
	EN_BAR	0.06406	0.07037	0.06614	

Passive power(pJ) for A rising (conditional):

Call Name	W/h ove	Power(pJ)			
Cell Name	When	first	mid	last	
	(EN * EN_BAR * Y)	-0.01352	-0.01366	-0.01350	
	(EN * EN_BAR * Y)	0.00606	0.00608	0.00601	
of 190 mean age of OT that 2	(!EN * EN_BAR)	-0.01321	-0.01341	-0.01335	
gf180mcu_osu_sc_9T_tbuf_2	(!EN * EN_BAR)	0.00653	0.00646	0.00646	
	(!EN * !EN_BAR * !Y)	-0.01185	-0.01265	-0.01253	
	(!EN * !EN_BAR * !Y)	0.00748	0.00685	0.00667	

Passive power(pJ) for A falling (conditional):

Cell Name	W/h ove	Power(pJ)			
	When	first	mid	last	
	(EN * EN_BAR * Y)	0.01427	0.01366	0.01350	
gf180mcu_osu_sc_9T_tbuf_2	(EN * EN_BAR * Y)	-0.00553	-0.00608	-0.00601	
	(!EN * EN_BAR)	0.01350	0.01350	0.01335	
	(!EN * EN_BAR)	-0.00639	-0.00646	-0.00646	
	(!EN * !EN_BAR * !Y)	0.01264	0.01265	0.01253	
	(!EN * !EN_BAR * !Y)	-0.00696	-0.00685	-0.00667	

Passive power(pJ) for EN rising (conditional):

Cell Name	Whom	Power(pJ)			
Cen Name	When	first	mid	last	
	(EN_BAR * Y)	-0.00081	-0.00028	-0.00018	
	(EN_BAR * Y)	0.00570	0.00570	0.00568	
	(A * !EN_BAR * Y)	-0.00081	-0.00028	-0.00018	
of 100 money ages as OT thruf 2	(A * !EN_BAR * Y)	0.00570	0.00570	0.00568	
gf180mcu_osu_sc_9T_tbuf_2	(!A * EN_BAR * !Y)	-0.00025	-0.00025	-0.00030	
	(!A * EN_BAR * !Y)	0.00215	0.00213	0.00209	
	(!A * !EN_BAR * !Y)	-0.00050	-0.00051	-0.00061	
	(!A * !EN_BAR * !Y)	0.00189	0.00188	0.00178	

Passive power(pJ) for EN falling (conditional):

Cell Name	¥¥71	Power(pJ)			
Cell Name	When	first	mid	last	
	(EN_BAR * Y)	0.00143	0.00028	0.00018	
	(EN_BAR * Y)	-0.00497	-0.00570	-0.00568	
	(A * !EN_BAR * Y)	0.00143	0.00028	0.00018	
of 100 mon on on OT thurs 2	(A * !EN_BAR * Y)	-0.00496	-0.00570	-0.00568	
gf180mcu_osu_sc_9T_tbuf_2	(!A * EN_BAR * !Y)	0.00031	0.00031	0.00031	
	(!A * EN_BAR * !Y)	-0.00208	-0.00205	-0.00204	
	(!A * !EN_BAR * !Y)	0.00063	0.00063	0.00063	
	(!A * !EN_BAR * !Y)	-0.00179	-0.00176	-0.00175	

Passive power(pJ) for EN_BAR rising (conditional):

Cell Name	W/h ore	Power(pJ)			
Cell Name	When	first	mid	last	
	(A * EN * Y)	-0.00459	-0.00454	-0.00451	
	(A * EN * Y)	0.00129	0.00129	0.00129	
	(A * !EN * Y)	-0.00555	-0.00550	-0.00547	
af190may agy as OT thuf 2	(A * !EN * Y)	0.00028	0.00028	0.00027	
gf180mcu_osu_sc_9T_tbuf_2	(!EN * !Y)	-0.00830	-0.00831	-0.00784	
	(!EN * !Y)	0.00326	0.00327	0.00345	
	(!A * EN * !Y)	-0.01118	-0.01252	-0.01239	
	(!A * EN * !Y)	0.00209	0.00057	0.00034	

Passive power(pJ) for EN_BAR falling (conditional):

Cell Name	VV/h ove	Power(pJ)			
	When	first	mid	last	
	(A * EN * Y)	0.00490	0.00483	0.00460	
	(A * EN * Y)	-0.00100	-0.00103	-0.00129	
	(A * !EN * Y)	0.00572	0.00568	0.00574	
of 100 men on a OT thirf 2	(A * !EN * Y)	-0.00017	-0.00016	-0.00015	
gf180mcu_osu_sc_9T_tbuf_2	(!EN * !Y)	0.00830	0.00831	0.00784	
	(!EN * !Y)	-0.00267	-0.00277	-0.00313	
	(!A * EN * !Y)	0.01241	0.01252	0.01239	
	(!A * EN * !Y)	-0.00107	-0.00057	-0.00034	

GF180MCU_OSU_SC_9T_TBUF_4

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

	INPUT		OUTPUT
A	EN	EN_BAR	Y
0	x	0	0
0	x	1	1
1	X	X	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_tbuf_4	0.00000

Pin Capacitance Information

Call Name		Max Cap(pf)		
Cell Name	A	EN	EN_BAR	Y
gf180mcu_osu_sc_9T_tbuf_4	0.00395	0.00132	0.00274	6.20353

Call Name	Leakage(nW)			
Cell Name	Min. Avg M		Max.	
gf180mcu_osu_sc_9T_tbuf_4	0.00000	395818.00000	1115160.00000	

Delay Information Delay(ns) to Y rising:

C.II N	Timing Aug(Din)	Delay(ns)		
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_tbuf_4	A->Y (RR)	0.23196	0.58712	7.34413
	EN->Y (RR)	0.21450	0.43768	4.45232

Delay(ns) to Y falling:

CHN	Timing Ang(Din)	Delay(ns)			
Cell Name	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_tbuf_4	A->Y (FF)	0.27479	0.78961	8.13518	
	EN_BAR->Y (FF)	0.24431	0.60733	4.71424	

Internal switching power(pJ) to Y rising:

Call Nama	I4	Power(pJ)			
Cell Name	Input	first	mid	last	
gf180mcu_osu_sc_9T_tbuf_4	A	0.13426	0.19068	0.70528	
	A	0.17051	0.22686	0.73841	
	EN	0.14350	0.15373	0.14906	
	EN	0.16118	0.17124	0.16006	

Internal switching power(pJ) to Y falling:

Call Name	I4	Power(pJ)			
Cell Name	Input	first	mid	last	
gf180mcu_osu_sc_9T_tbuf_4	A	0.17777	0.22302	0.73095	
	A	0.14144	0.18673	0.69586	
	EN_BAR	0.16673	0.17154	0.15544	
	EN_BAR	0.14627	0.15125	0.13812	

Passive power(pJ) for A rising (conditional):

Cell Name	When	Power(pJ)			
Cen Name	when	first	mid	last	
	(EN * EN_BAR * Y)	-0.01371	-0.01379	-0.01352	
	(EN * EN_BAR * Y)	0.00587	0.00589	0.00582	
	(!EN * EN_BAR)	-0.01321	-0.01340	-0.01335	
gf180mcu_osu_sc_9T_tbuf_4	(!EN * EN_BAR)	0.00653	0.00646	0.00646	
	(!EN * !EN_BAR * !Y)	-0.01162	-0.01242	-0.01231	
	(!EN * !EN_BAR * !Y)	0.00788	0.00701	0.00678	

Passive power(pJ) for A falling (conditional):

Cell Name	W/h ove	Power(pJ)			
Cen Name	When	first	mid	last	
gf180mcu_osu_sc_9T_tbuf_4	(EN * EN_BAR * Y)	0.01450	0.01379	0.01352	
	(EN * EN_BAR * Y)	-0.00532	-0.00589	-0.00582	
	(!EN * EN_BAR)	0.01350	0.01350	0.01335	
	(!EN * EN_BAR)	-0.00639	-0.00646	-0.00646	
	(!EN * !EN_BAR * !Y)	0.01242	0.01242	0.01231	
	(!EN * !EN_BAR * !Y)	-0.00726	-0.00701	-0.00678	

Passive power(pJ) for EN rising (conditional):

Cell Name	W/h ore	Power(pJ)			
	When	first	mid	last	
	(EN_BAR * Y)	-0.00109	-0.00040	-0.00022	
	(EN_BAR * Y)	0.00541	0.00542	0.00540	
	(A * !EN_BAR * Y)	-0.00109	-0.00040	-0.00022	
of 190 may ago of thuf 4	(A * !EN_BAR * Y)	0.00541	0.00542	0.00540	
gf180mcu_osu_sc_9T_tbuf_4	(!A * EN_BAR * !Y)	-0.00024	-0.00024	-0.00029	
	(!A * EN_BAR * !Y)	0.00216	0.00215	0.00210	
	(!A * !EN_BAR * !Y)	-0.00050	-0.00051	-0.00061	
	(!A * !EN_BAR * !Y)	0.00190	0.00188	0.00178	

Passive power(pJ) for EN falling (conditional):

Call Name	XX/I	Power(pJ)			
Cell Name	When	first	mid	last	
	(EN_BAR * Y)	0.00199	0.00040	0.00022	
	(EN_BAR * Y)	-0.00447	-0.00542	-0.00540	
	(A * !EN_BAR * Y)	0.00199	0.00040	0.00022	
of 100 mon on on OT thurs 4	(A * !EN_BAR * Y)	-0.00447	-0.00542	-0.00540	
gf180mcu_osu_sc_9T_tbuf_4	(!A * EN_BAR * !Y)	0.00030	0.00030	0.00030	
	(!A * EN_BAR * !Y)	-0.00211	-0.00208	-0.00206	
	(!A * !EN_BAR * !Y)	0.00063	0.00063	0.00063	
	(!A * !EN_BAR * !Y)	-0.00179	-0.00176	-0.00174	

Passive power(pJ) for EN_BAR rising (conditional):

Cell Name	VV/h ove	Power(pJ)			
	When	first	mid	last	
	(A * EN * Y)	-0.00459	-0.00454	-0.00451	
	(A * EN * Y)	0.00129	0.00129	0.00129	
	(A * !EN * Y)	-0.00560	-0.00556	-0.00552	
	(A * !EN * Y)	0.00024	0.00024	0.00024	
gf180mcu_osu_sc_9T_tbuf_4	(!EN * !Y)	-0.00758	-0.00756	-0.00757	
	(!EN * !Y)	0.00443	0.00462	0.00462	
	(!A * EN * !Y)	-0.01068	-0.01173	-0.01175	
	(!A * EN * !Y)	0.00284	0.00073	0.00042	

Passive power(pJ) for EN_BAR falling (conditional):

Cell Name	XX/I	Power(pJ)			
	When	first	mid	last	
	(A * EN * Y)	0.00490	0.00483	0.00460	
	(A * EN * Y)	-0.00100	-0.00103	-0.00129	
	(A * !EN * Y)	0.00571	0.00567	0.00566	
of 190 many age of the f	(A * !EN * Y)	-0.00019	-0.00019	-0.00023	
gf180mcu_osu_sc_9T_tbuf_4	(!EN * !Y)	0.00758	0.00756	0.00757	
	(!EN * !Y)	-0.00402	-0.00402	-0.00405	
	(!A * EN * !Y)	0.01176	0.01173	0.01175	
	(!A * EN * !Y)	-0.00172	-0.00073	-0.00042	

GF180MCU_OSU_SC_9T_TBUF_8

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT		OUTPUT	
A	EN	EN_BAR	Y
0	x	0	0
0	x	1	1
1	X	X	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_tbuf_8	0.00000

Pin Capacitance Information

Call Name		Max Cap(pf)		
Cell Name	A	EN	EN_BAR	Y
gf180mcu_osu_sc_9T_tbuf_8	0.00395	0.00132	0.00273	12.46914

Call Name	Leakage(nW)			
Cell Name	Min. Avg Max.			
gf180mcu_osu_sc_9T_tbuf_8	0.00000	791637.00000	2230320.00000	

Delay Information Delay(ns) to Y rising:

Call Name	Timing Aug(Din)	Delay(ns)		
Cell Name	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_tbuf_8	A->Y (RR)	0.34085	0.69793	7.64557
	EN->Y (RR)	0.32306	0.62597	5.16901

Delay(ns) to Y falling:

Call Name	Timing Ang(Din)		Delay(ns)	
Cell Name	Timing Arc(Dir)	First	Mid	Last
6100 OT (1 6 0	A->Y (FF)	0.41186	0.91656	8.44678
gf180mcu_osu_sc_9T_tbuf_8	EN_BAR->Y (FF)	0.38077	0.83239	5.56958

Internal switching power(pJ) to Y rising:

Cell Name	T4	Power(pJ)			
	Input	first	last		
gf180mcu_osu_sc_9T_tbuf_8	A	0.35506	0.35802	0.83000	
	A	0.39132	0.39419	0.85406	
	EN	0.36387	0.35442	0.29115	
	EN	0.38154	0.37189	0.30878	

Internal switching power(pJ) to Y falling:

Call Nama	I4	Power(pJ)		
Cell Name	Input	first	mid	last
gf180mcu_osu_sc_9T_tbuf_8	A	0.43817	0.40355	0.84749
	A	0.40185	0.36731	0.81181
	EN_BAR	0.42685	0.40337	0.31594
	EN_BAR	0.40641	0.38384	0.29555

Passive power(pJ) for A rising (conditional):

Cell Name	W/h ove	Power(pJ)		
Cen Name	Cell Name When		mid	last
	(EN * EN_BAR * Y)	-0.01395	-0.01394	-0.01359
	(EN * EN_BAR * Y)	0.00566	0.00568	0.00561
	(!EN * EN_BAR)	-0.01321	-0.01340	-0.01335
gf180mcu_osu_sc_9T_tbuf_8	(!EN * EN_BAR)	0.00653	0.00646	0.00646
	(!EN * !EN_BAR * !Y)	-0.01140	-0.01211	-0.01200
	(!EN * !EN_BAR * !Y)	0.00829	0.00719	0.00689

Passive power(pJ) for A falling (conditional):

Cell Name	W/h ove	Power(pJ)		
Cell Name	When	first	mid	last
	(EN * EN_BAR * Y)	0.01478	0.01394	0.01359
	(EN * EN_BAR * Y)	-0.00510	-0.00568	-0.00561
	(!EN * EN_BAR)	0.01350	0.01350	0.01335
gf180mcu_osu_sc_9T_tbuf_8	(!EN * EN_BAR)	-0.00639	-0.00646	-0.00646
	(!EN * !EN_BAR * !Y)	0.01212	0.01211	0.01200
	(!EN * !EN_BAR * !Y)	-0.00765	-0.00719	-0.00689

Passive power(pJ) for EN rising (conditional):

Cell Name	Whom			
Cen Name	When	first mid		last
	(EN_BAR * Y)	-0.00146	-0.00059	-0.00027
	(EN_BAR * Y)	0.00505	0.00509	0.00504
	(A * !EN_BAR * Y)	-0.00146	-0.00059	-0.00027
of 190 may ago at thus 9	(A * !EN_BAR * Y)	0.00505	0.00509	0.00504
gf180mcu_osu_sc_9T_tbuf_8	(!A * EN_BAR * !Y)	-0.00023	-0.00023	-0.00028
	(!A * EN_BAR * !Y)	0.00217	0.00216	0.00211
	(!A * !EN_BAR * !Y)	-0.00050	-0.00051	-0.00061
	(!A * !EN_BAR * !Y)	0.00190	0.00188	0.00178

Passive power(pJ) for EN falling (conditional):

Cell Name	¥¥71	Power(pJ)		
	When	first	mid	last
	(EN_BAR * Y)	0.00254	0.00059	0.00027
	(EN_BAR * Y)	-0.00395	-0.00509	-0.00504
	(A * !EN_BAR * Y)	0.00253	0.00059	0.00027
	(A * !EN_BAR * Y)	-0.00394	-0.00509	-0.00504
gf180mcu_osu_sc_9T_tbuf_8	(!A * EN_BAR * !Y)	0.00029	0.00029	0.00029
	(!A * EN_BAR * !Y)	-0.00213	-0.00209	-0.00208
	(!A * !EN_BAR * !Y)	0.00063	0.00063	0.00063
	(!A * !EN_BAR * !Y)	-0.00179	-0.00176	-0.00174

Passive power(pJ) for EN_BAR rising (conditional):

Cell Name	XX/I			
	When	first	mid	last
	(A * EN * Y)	-0.00458	-0.00454	-0.00451
	(A * EN * Y)	0.00129	0.00129	0.00129
	(A * !EN * Y)	-0.00564	-0.00559	-0.00556
of 100 men and a OT thruf 0	(A * !EN * Y)	0.00022	0.00022	0.00022
gf180mcu_osu_sc_9T_tbuf_8	(!EN * !Y)	-0.00735	-0.00732	-0.00732
	(!EN * !Y)	0.00505	0.00543	0.00554
	(!A * EN * !Y)	-0.00989	-0.01106	-0.01108
	(!A * EN * !Y)	0.00348	0.00107	0.00052

Passive power(pJ) for EN_BAR falling (conditional):

Cell Name	XX/I			
	When	first	mid	last
	(A * EN * Y)	0.00491	0.00484	0.00460
	(A * EN * Y)	-0.00100	-0.00102	-0.00129
	(A * !EN * Y)	0.00573	0.00568	0.00569
of 190 many control of the f	(A * !EN * Y)	-0.00017	-0.00017	-0.00021
gf180mcu_osu_sc_9T_tbuf_8	(!EN * !Y)	0.00735	0.00732	0.00732
	(!EN * !Y)	-0.00491	-0.00490	-0.00492
	(!A * EN * !Y)	0.01111	0.01106	0.01108
	(!A * EN * !Y)	-0.00241	-0.00107	-0.00052

GF180MCU_OSU_SC_9T_TIEHI

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_tiehi	0.00000

Pin Capacitance Information

Call Name	Max Cap(pf)
Cell Name	Y
gf180mcu_osu_sc_9T_tiehi	3.44214

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_tiehi	0.00000	0.00000	0.00000	

GF180MCU_OSU_SC_9T_TIELO

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_tielo	0.00000

Pin Capacitance Information

Call Name	Max Cap(pf)
Cell Name	Y
gf180mcu_osu_sc_9T_tielo	5.16285

Call Name	Leakage(nW)		
Cell Name	Min.	Avg	Max.
gf180mcu_osu_sc_9T_tielo	0.00000	0.00000	0.00000

GF180MCU_OSU_SC_9T_TINV_16

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

	IN	OUTPUT	
A	EN	EN_BAR	Y
0	x	0	0
0	x	1	1
1	X	X	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_tinv_16	0.00000

Pin Capacitance Information

Call Nama	Pin Cap(pf)			Max Cap(pf)
Cell Name	A	EN	EN_BAR	Y
gf180mcu_osu_sc_9T_tinv_16	0.00237	0.00117	0.00241	10.87854

Call Name	Leakage(nW)		
Cell Name	Min.	Avg	Max.
gf180mcu_osu_sc_9T_tinv_16	0.00000	4415470.00000	5510370.00000

Delay Information Delay(ns) to Y rising:

Cell Name	Timing	Delay(ns)		
Cen Name	Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_tinv_16	A->Y (-R)	0.04560	-0.27075	-1.03882
	EN->Y (RR)	0.03580	-0.32032	-1.45606
	EN_BAR->Y (RR)	9999999999999999635896294965248.00000	9999999999999999635896294965248.00000	9999999999999999635896294965248.00000

Delay(ns) to Y falling:

Cell Name	Timing	Delay(ns)		
Cen Name	Arc(Dir)	First	Mid	Last
	A->Y (-F)	2.25325	4.67119	105.91100
gf180mcu_osu_sc_9T_tinv_16	EN->Y (FF)	2.26061	4.77493	106.55800
	EN_BAR->Y (FF)	9999999999999999635896294965248.00000	9999999999999999635896294965248.00000	999999999999999635896294965248.00000

Internal switching power(pJ) to Y rising:

Cell Name	T4	Power(pJ)		
Cell Name	Input	first	mid	last
	A	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000
	A	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000
-F190 0T 4: 16	EN	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000
gf180mcu_osu_sc_9T_tinv_16	EN	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000
	EN_BAR	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000
	EN_BAR	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000

Internal switching power(pJ) to Y falling:

C II N		Power(p,J)		
Cell Name	Input	first	mid	last
	A	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000
	A	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000
-£190 OT 4' 16	EN	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000
gf180mcu_osu_sc_9T_tinv_16	EN	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000
	EN_BAR	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000
	EN_BAR	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000

GF180MCU_OSU_SC_9T_TINV_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

	IN	OUTPUT	
A	EN	EN_BAR	Y
0	X	0	1
0	X	1	HiZ
1	0	X	HiZ
1	1	X	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_tinv_1	0.00000

Pin Capacitance Information

Call Name		Max Cap(pf)		
Cell Name	A	EN	EN_BAR	Y
gf180mcu_osu_sc_9T_tinv_1	0.00413	0.00129	0.00267	0.76770

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_tinv_1	0.00000	0.00032	0.00090	

Delay Information Delay(ns) to Y rising:

Cell Name	Timing Ang(Din)			
	Timing Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_tinv_1	A->Y (FR)	0.06327	0.93640	9.57806
	A->Y (FR)	0.05111	0.94139	6.56566
	EN->Y (FR)	0.05111	0.94139	6.56566
	EN_BAR->Y (FR)	0.08089	0.65751	7.70910

Delay(ns) to Y falling:

Cell Name	Timin A (Div)		Delay(ns)	y(ns)	
	Timing Arc(Dir)	First	Mid	Last	
gf180mcu_osu_sc_9T_tinv_1	A->Y (RF)	0.05245	0.64777	7.14983	
	A->Y (FF)	0.05111	0.94139	6.56566	
	EN->Y (RF)	0.04490	0.39639	5.43990	
	EN_BAR->Y (FF)	0.05111	0.94139	6.56566	

Internal switching power(pJ) to Y rising:

Cell Name	T4			
	Input	first	mid	last
gf180mcu_osu_sc_9T_tinv_1	A	0.02169	0.05813	0.21371
	A	-0.00014	0.03627	0.19172
	EN_BAR	0.02886	0.02908	0.02983
	EN_BAR	0.00406	0.00406	0.00406

Internal switching power(pJ) to Y falling:

Call Name	Immud		Power(pJ)		
Cell Name	Input	first	mid	last	
gf180mcu_osu_sc_9T_tinv_1	A	-0.00004	0.03508	0.18263	
	A	0.02178	0.05699	0.20491	
	EN	0.00711	0.00711	0.00711	
	EN	0.02060	0.02064	0.02258	

Passive power(pJ) for A rising (conditional):

Cell Name	W/h or	Power(pJ)			
	When	first	mid	last	
gf180mcu_osu_sc_9T_tinv_1	(EN_BAR * !Y)	-0.00480	-0.00479	-0.00475	
	(EN_BAR * !Y)	0.00747	0.00750	0.00746	
	(!EN * Y)	-0.00868	-0.00873	-0.00871	
	(!EN * Y)	0.00287	0.00285	0.00279	

Passive power(pJ) for A falling (conditional):

Cell Name	Where		Power(pJ)		
	When	first	mid	last	
gf180mcu_osu_sc_9T_tinv_1	(EN_BAR * !Y)	0.00532	0.00500	0.00484	
	(EN_BAR * !Y)	-0.00683	-0.00727	-0.00746	
	(!EN * Y)	0.00868	0.00873	0.00871	
	(!EN * Y)	-0.00282	-0.00284	-0.00279	

Passive power(pJ) for EN rising (conditional):

Call Name	XVII ora	Power(pJ)		
Cell Name	When	first	mid	last
gf180mcu_osu_sc_9T_tinv_1	(A * !Y)	-0.00012	-0.00005	-0.00004
	(A * !Y)	0.00619	0.00623	0.00620
	(!A * EN_BAR) + (!A * !EN_BAR * Y)	0.00000	0.00000	0.00000
	(!A * EN_BAR) + (!A * !EN_BAR * Y)	0.00651	0.00656	0.00648

Passive power(pJ) for EN falling (conditional):

Coll Nama	XX/I	Power(pJ)			
Cell Name	When	first	mid	last	
gf180mcu_osu_sc_9T_tinv_1	(A * !Y)	0.00019	0.00005	0.00004	
	(A * !Y)	-0.00601	-0.00623	-0.00620	
	(!A * EN_BAR) + (!A * !EN_BAR * Y)	0.00000	0.00000	0.00000	
	(!A * EN_BAR) + (!A * !EN_BAR * Y)	-0.00637	-0.00652	-0.00647	

Passive power(pJ) for EN_BAR rising (conditional):

Cell Name	W/h ove	Power(pJ)			
	When	first	mid	last	
gf180mcu_osu_sc_9T_tinv_1	(A * EN * !Y) + (A * !EN)	-0.01308	-0.01344	-0.01339	
	(A * EN * !Y) + (A * !EN)	0.00004	-0.00000	-0.00000	
	(!A * Y)	-0.01226	-0.01289	-0.01288	
	(!A * Y)	0.00023	0.00007	0.00005	

Passive power(pJ) for EN_BAR falling (conditional):

Call Name	W/h ove	Power(pJ)		
Cell Name	When	first	mid	last
gf180mcu_osu_sc_9T_tinv_1	(A * EN * !Y) + (A * !EN)	0.01343	0.01344	0.01339
	(A * EN * !Y) + (A * !EN)	0.00000	0.00000	0.00000
	(!A * Y)	0.01297	0.01289	0.01288
	(!A * Y)	-0.00012	-0.00007	-0.00005

GF180MCU_OSU_SC_9T_TINV_2

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT		OUTPUT	
A	EN	EN_BAR	Y
0	x	0	0
0	X	1	1
1	X	X	1

Footprint

Cell Name	Area	
gf180mcu_osu_sc_9T_tinv_2	0.00000	

Pin Capacitance Information

Call Name	Pin Cap(pf)			Max Cap(pf)
Cell Name	A	EN	EN_BAR	Y
gf180mcu_osu_sc_9T_tinv_2	0.00239	0.00117	0.00241	1.38657

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_tinv_2	0.00000	927990.00000	972297.00000	

Delay Information Delay(ns) to Y rising:

Cell Name	Timing			
Cen Name	Arc(Dir)	First	Mid	Last
	A->Y (-R)	0.02773	-0.27365	-1.18187
gf180mcu_osu_sc_9T_tinv_2	EN->Y (RR)	0.01635	-0.31635	-1.57604
gr100incu_osu_sc_91_unv_2	EN_BAR->Y (RR)	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000

Delay(ns) to Y falling:

Call Name	Timing	Delay(ns)			
Cell Name Arc(I		First	Mid	Last	
	A->Y (-F)	0.68503	6.72005	106.94300	
gf180mcu_osu_sc_9T_tinv_2	EN->Y (FF)	0.75554	6.81965	107.63300	
grisonicu_osu_sc_91_unv_2	EN_BAR->Y (FF)	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	

Internal switching power(pJ) to Y rising:

Call Name	I4	Power(p,J)		
Cell Name Input		first	mid	last
	A	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000
	A	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000
-5190 OT 45 2	EN	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000
gf180mcu_osu_sc_9T_tinv_2	EN	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000
	EN_BAR	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000
	EN_BAR	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000

Internal switching power(pJ) to Y falling:

G HV		Power(pJ)				
Cell Name	Input	first	mid	last		
	A	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000		
	A	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000		
-£100 OT 4: 2	EN	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000		
gf180mcu_osu_sc_9T_tinv_2	EN	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000		
	EN_BAR	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000		
	EN_BAR	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000		

GF180MCU_OSU_SC_9T_TINV_4

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

	INPUT		OUTPUT
A	EN	EN_BAR	Y
0	x	0	0
0	x	1	1
1	X	X	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_tinv_4	0.00000

Pin Capacitance Information

Call Name	Pin Cap(pf)			Max Cap(pf)
Cell Name	A	EN	EN_BAR	Y
gf180mcu_osu_sc_9T_tinv_4	0.00237	0.00117	0.00241	2.76800

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_tinv_4	0.00000	1426200.00000	1620590.00000	

Delay Information Delay(ns) to Y rising:

Cell Name	Timing	Timing Delay(ns)		
Cen Name	Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_tinv_4	A->Y (-R)	0.03094	-0.29191	-1.16663
	EN->Y (RR)	0.01969	-0.33458	-1.55701
	EN_BAR->Y (RR)	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000

Delay(ns) to Y falling:

Call Name	Timing	Timing Delay(ns)		
Cell Name	Arc(Dir)	First	Mid	Last
	A->Y (-F)	0.89913	5.46740	106.89300
gf180mcu_osu_sc_9T_tinv_4	EN->Y (FF)	0.93897	5.55913	107.59100
	EN_BAR->Y (FF)	999999999999999635896294965248.00000	9999999999999999635896294965248.00000	999999999999999635896294965248.00000

Internal switching power(pJ) to Y rising:

Cell Name	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
	A	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	
	A	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	
-6180 OT 45 A	EN	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	
	EN	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	
	EN_BAR	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	
	EN_BAR	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	

Internal switching power(pJ) to Y falling:

G HV			Power(pJ)		
Cell Name	Input	first	mid	last	
	A	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	
	A	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	
	EN	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	
gf180mcu_osu_sc_9T_tinv_4	EN	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	
	EN_BAR	999999999999999635896294965248.00000	999999999999999635896294965248.00000	99999999999999635896294965248.00000	
	EN_BAR	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	

GF180MCU_OSU_SC_9T_TINV_8

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

	IN	OUTPUT	
A	EN	EN_BAR	Y
0	x	0	0
0	X	1	1
1	X	X	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_tinv_8	0.00000

Pin Capacitance Information

Call Name		Pin Cap(pf	Max Cap(pf)	
Cell Name	A	EN	EN_BAR	Y
gf180mcu_osu_sc_9T_tinv_8	0.00237	0.00117	0.00241	5.49376

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_tinv_8	0.00000	2422620.00000	2917180.00000	

Delay Information Delay(ns) to Y rising:

Cell Name	Timing	Delay(ns)			
Cen Name	Arc(Dir)	First	Mid	Last	
	A->Y (-R)	0.03637	-0.29225	-1.15570	
gf180mcu_osu_sc_9T_tinv_8	EN->Y (RR)	0.02575	-0.33718	-1.52531	
gr180mcu_osu_sc_91_unv_8	EN_BAR->Y (RR)	999999999999999635896294965248.00000	9999999999999999635896294965248.00000	9999999999999999635896294965248.00000	

Delay(ns) to Y falling:

Call Name	Timing	Timing Delay(ns)		
Cell Name	Arc(Dir)	First	Mid	Last
gf180mcu_osu_sc_9T_tinv_8	A->Y (-F)	1.34565	4.72254	106.38500
	EN->Y (FF)	1.36280	4.82278	107.05700
	EN_BAR->Y (FF)	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000

Internal switching power(pJ) to Y rising:

Cell Name	T4	Power(pJ)			
Cell Name	Input	first	mid	last	
	A	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	
	A	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	
-6100 OT 4: 0	EN	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	
gf180mcu_osu_sc_9T_tinv_8	EN	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	
	EN_BAR	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	
	EN_BAR	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000	

Internal switching power(pJ) to Y falling:

GHN		Power(pJ)				
Cell Name Inpu		first	mid	last		
	A	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000		
	A	999999999999999635896294965248.00000	999999999999999635896294965248.00000	99999999999999635896294965248.00000		
of 190man can so OT time 9	EN	999999999999999635896294965248.00000	999999999999999635896294965248.00000	99999999999999635896294965248.00000		
gf180mcu_osu_sc_9T_tinv_8	EN	999999999999999635896294965248.00000	999999999999999635896294965248.00000	99999999999999635896294965248.00000		
	EN_BAR	999999999999999635896294965248.00000	999999999999999635896294965248.00000	99999999999999635896294965248.00000		
	EN_BAR	999999999999999635896294965248.00000	999999999999999635896294965248.00000	999999999999999635896294965248.00000		

$GF180MCU_OSU_SC_9T_XNOR2_1$

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT		OUTPUT
A	В	Y
0	0	1
0	1	0
1	0	0
1	1	1

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_xnor2_1	0.00000

Pin Capacitance Information

C.II V	Pin C	ap(pf)	Max Cap(pf)	
Cell Name	A	В	Y	
gf180mcu_osu_sc_9T_xnor2_1	0.00806	0.00798	0.78925	

Call Name	Leakage(nW)			
Cell Name	Min.	Avg	Max.	
gf180mcu_osu_sc_9T_xnor2_1	0.00000	0.00288	0.00353	

Delay Information Delay(ns) to Y rising (conditional):

C.II V	T: A(D:)	***	Delay(ns)		
Cell Name	Timing Arc(Dir)	When	First	Mid	Last
gf180mcu_osu_sc_9T_xnor2_1	A->Y (RR)	В	0.15057	0.64067	6.49144
	A->Y (FR)	!B	0.11222	1.01224	9.84618
	B->Y (RR)	A	0.12126	0.62708	6.65943
	B->Y (FR)	!A	0.13276	0.86357	8.68525

Delay(ns) to Y falling (conditional):

Call Name	Timin A (Din)	****	Delay(ns)		
Cell Name	Timing Arc(Dir)	When	First	Mid	Last
gf180mcu_osu_sc_9T_xnor2_1	A->Y (FF)	В	0.16445	0.75328	6.42840
	A->Y (RF)	!B	0.07443	0.53805	6.11426
	B->Y (FF)	A	0.12382	0.70322	6.37809
	B->Y (RF)	!A	0.10564	0.59747	6.21650

Internal switching power(pJ) to Y rising (conditional):

C-II N	T4	When	Power(pJ)			
Cell Name	Input		first	mid	last	
	A	В	0.03150	0.11820	0.70846	
	A	В	0.06445	0.15105	0.74078	
	A	!B	0.06266	0.19071	0.94275	
-6100 OT 1	A	!B	0.01841	0.14620	0.89852	
gf180mcu_osu_sc_9T_xnor2_1	В	A	0.01355	0.10133	0.69052	
	В	A	0.05396	0.14182	0.73084	
	В	!A	0.07188	0.19987	0.99091	
	В	!A	0.01824	0.14604	0.93700	

Internal switching power(pJ) to Y falling (conditional):

C-II N	T4	When	Power(pJ)			
Cell Name	Input		first	mid	last	
	A	В	0.07882	0.16839	0.75300	
	A	В	0.04752	0.13712	0.72262	
	A	!B	0.02549	0.14696	0.89953	
26190man agu ga 0T man 1	A	!B	0.06906	0.19082	0.94320	
gf180mcu_osu_sc_9T_xnor2_1	В	A	0.06449	0.15440	0.74101	
	В	A	0.02375	0.11386	0.70118	
	В	!A	0.03665	0.16184	0.93352	
	В	!A	0.08960	0.21503	0.98716	

GF180MCU_OSU_SC_9T_XOR2_1

gf180mcu_9T_TT_3P3_25C.ccs Cell Library: Process , Voltage 3.30, Temp 25.00

Truth Table

INPUT		OUTPUT
A	В	Y
0	0	0
0	1	1
1	0	1
1	1	0

Footprint

Cell Name	Area
gf180mcu_osu_sc_9T_xor2_1	0.00000

Pin Capacitance Information

Cell Name	Pin C	ap(pf)	Max Cap(pf)	
Cen Name	A	В	Y	
gf180mcu_osu_sc_9T_xor2_1	0.00798	0.00801	0.79014	

Call Name	Leakage(nW)				
Cell Name	Min.	Avg	Max.		
gf180mcu_osu_sc_9T_xor2_1	0.00000	0.00288	0.00329		

Delay Information Delay(ns) to Y rising (conditional):

Cell Name	Timing Arc(Dir) W	When	Delay(ns)		
			First	Mid	Last
gf180mcu_osu_sc_9T_xor2_1	A->Y (RR)	!B	0.12136	0.62747	6.66700
	A->Y (FR)	В	0.13483	0.86447	8.69415
	B->Y (RR)	!A	0.16005	0.66627	6.70185
	B->Y (FR)	A	0.10455	0.81826	8.60272

Delay(ns) to Y falling (conditional):

Cell Name	Timing Arc(Dir) When	**/1	Delay(ns)		
		vvnen	First	Mid	Last
gf180mcu_osu_sc_9T_xor2_1	A->Y (FF)	!B	0.12378	0.70349	6.38493
	A->Y (RF)	В	0.10409	0.59731	6.22156
	B->Y (FF)	!A	0.13232	0.69281	6.17699
	B->Y (RF)	A	0.09892	0.74032	7.40536

Internal switching power(pJ) to Y rising (conditional):

Cell Name	T4	XX/I	Power(pJ)			
	Input	When	first	mid	last	
gf180mcu_osu_sc_9T_xor2_1	A	В	0.07710	0.20487	0.99711	
	A	В	0.02851	0.15619	0.94818	
	A	!B	0.01211	0.09999	0.68920	
	A	!B	0.05334	0.14119	0.73024	
	В	A	0.06408	0.18880	0.96462	
	В	A	0.02037	0.14493	0.92084	
	В	!A	0.02804	0.11392	0.70278	
	В	!A	0.06403	0.15010	0.73883	

Internal switching power(pJ) to Y falling (conditional):

Cell Name	T4	XX /1	Power(pJ)			
	Input	When	first	mid	last	
gf180mcu_osu_sc_9T_xor2_1	A	В	0.03064	0.15579	0.92722	
	A	В	0.07986	0.20538	0.97732	
	A	!B	0.06577	0.15569	0.74265	
	A	!B	0.02442	0.11450	0.70283	
	В	A	0.03117	0.15417	0.90318	
	В	A	0.07544	0.19883	0.94742	
	В	!A	0.07037	0.16051	0.74752	
	В	!A	0.03310	0.12339	0.71044	